

TECHNICAL DETAILS

Density : 1.18 +/- 0.05 g/cc

Relative Weight Strength : 75%

Relative Bulk Strength : 105%

Velocity of Detonation : 4000 +/- 400 m/s

**RWS and RBS are calculated relative to ANFO at a density of 0.8 g/cc.

KEY BENEFITS

- High-strength slurry formulation for medium to large diameter boreholes.
- Cross-linked gel matrix provides excellent stability and uniform explosive performance.
- High Velocity of Detonation (VOD) ensures effective rock fragmentation in medium to hard formations.
- Excellent water resistance for reliable performance in wet and water-filled boreholes.
- Suitable as a column explosive for surface mining, quarrying, and civil blasting applications.
- Low post-blast fumes contribute to improved working conditions in confined or underground environments.


NEO BASE SPECIAL

TECHNICAL DATASHEET

Neo Base Special is a non-cap-sensitive, water-resistant slurry explosive formulated for use in mining, quarrying, and civil construction blasting applications. It consists of an oxidizer-rich aqueous gel matrix containing ammonium nitrate, sodium nitrate, fuel components, sensitizers, and a cross-linked structure that provides a stable explosive composition suitable for a wide range of blasting conditions.

Being non-cap-sensitive, the explosive requires initiation through a suitable primer or booster. It is designed for use as a column charge in both dry and wet boreholes and is compatible with bulk and packaged blasting systems. It is intended for use in medium to large diameter boreholes where primer-assisted initiation of the explosive column is employed.





SAFETY & STORAGE

- Store in a cool, dry, well-ventilated, licensed magazine approved for Class-2 explosives.
- Avoid exposure to high temperatures, direct sunlight, or freezing conditions, as extreme temperatures may reduce shelf life or alter performance.
- Maintain proper inventory rotation: always use the oldest stock first.
- Shelf life is generally 5 months under recommended storage conditions; deterioration may occur sooner if exposed to heat, moisture, or rough handling.
- Protect cartridges from shock, friction, or mechanical impact to prevent accidental initiation.
- Dispose of deteriorated or damaged explosives as per local regulations and under supervision of authorized personnel.

RECOMMENDATIONS FOR USE

- Suitable for blasting in dry, wet, and water-filled boreholes.
- Must be initiated using a suitable primer or booster with an approved electric or non-electric initiation system.
- Recommended for use as a column explosive in medium to large diameter boreholes.
- Ensure continuous column loading and proper primer placement in accordance with the blast design.
- Use wooden or non-metallic loading/tamping tools where tamping is required.
- Ensure adequate ventilation before re-entry following underground blasting operations.
- Avoid excessive heat, impact, friction, or contamination during handling and charging.
- Suitable for ground temperatures ranging from -5°C to 50°C . For applications outside this range, consult the manufacturer or technical representative.

Transport Classification	Class	UN Number
Standard Packaging	1.1D	UN 0241

PRODUCT DISCLAIMER

© 2025 SBL Energy Ltd. All rights reserved. The details presented in this document ("Information") are intended to provide general technical guidance regarding the referenced products ("Products"). While reasonable care has been taken in compiling this Information, SBL Energy Ltd does not guarantee its accuracy, consistency, or applicability to every operational environment, and the Information may be updated or amended without prior notice. Explosive Products must only be handled, transported, and used by personnel who are properly trained, certified, and authorized to work with such materials. Users are responsible for assessing site-specific conditions, verifying regulatory requirements, and ensuring that all procedures align with applicable safety standards and legal obligations. To the extent permitted by law, SBL Energy Ltd rejects any form of warranty—statutory, express, or implied—relating to the Information or the Products, including but not limited to performance guarantees or suitability for a particular use. The company shall not be held liable for any loss, damage, injury, or operational consequence arising from reliance on this Information or from misuse or improper handling of the Products.

This document is provided solely for reference and shall not be interpreted as a contractual commitment, product guarantee, or legally binding representation by SBL Energy Ltd.

Diameter (mm)	Mass (g)	Units/box
83	2780	9
125	6250	4
200	12500	2



Office: 230, Hill Road, Da Rock Building, 2nd Floor,
Shivaji Nagar, Nagpur - 440010 (MH) India.



+91-8308810133



info@sblenergy.com



www.sblenergy.com