



NEO BLAST SPECIAL

TECHNICAL DATASHEET

Neo Blast Special is a cap-sensitive, water-resistant slurry explosive formulated for use in mining, quarrying, and civil construction blasting applications. It consists of an oxidizer-rich aqueous gel matrix containing ammonium nitrate, sodium nitrate, fuel components, sensitizers, and a cross-linked structure that provides a stable explosive composition suitable for a wide range of blasting conditions.

Being cap-sensitive, the explosive can be directly initiated using a No. 8 strength detonator, eliminating the need for a booster in many blasting applications and making it suitable for use as a primer charge. The product is intended for both dry and wet boreholes and can be used as a primer or as a column charge, depending on blast design requirements.

TECHNICAL DETAILS

Density : 1.15 +/- 0.05 g/cc

Relative Weight Strength : 88%

Relative Bulk Strength : 119%

Velocity of Detonation : 3900 +/- 300 m/s

**RWS and RBS are calculated relative to ANFO at a density of 0.8 g/cc.

KEY BENEFITS

- High-strength, cap-sensitive slurry for medium to large boreholes.
- Chemically gassed and cross-linked for a strong, rigid gel structure.
- High VOD delivers excellent fragmentation in medium to hard rock.
- Superior water resistance for use in wet boreholes.
- Safer handling due to reduced sensitivity to impact and friction.
- Low post-blast fumes for improved environmental conditions.





SAFETY & STORAGE

- Store in a cool, dry, well-ventilated, licensed magazine approved for Class-2 explosives.
- Avoid exposure to high temperatures, direct sunlight, or freezing conditions, as extreme temperatures may reduce shelf life or alter performance.
- Maintain proper inventory rotation: always use the oldest stock first.
- Shelf life is generally 5 months under recommended storage conditions; deterioration may occur sooner if exposed to heat, moisture, or rough handling.
- Protect cartridges from shock, friction, or mechanical impact to prevent accidental initiation.
- Dispose of deteriorated or damaged explosives as per local regulations and under supervision of authorized personnel.

RECOMMENDATIONS FOR USE

- Suitable for blasting in dry, wet, and watery holes..
- Can be initiated using electric or non-electric detonators (minimum No. 8 strength) or detonating cord of 5 g/m PETN or higher, as per product specification.
- Achieve maximum energy output by proper tamping using a wooden or non-metallic tamping rod.
- Do NOT tamp a primer cartridge containing a detonator.
- Post-blast fumes are generally suitable for surface and underground applications, but ensure adequate ventilation before re-entry.
- Avoid excessive shock, heat, friction, or mechanical impact to prevent premature initiation.
- Suitable for ground temperatures in range -5°C to 50°C. For operations outside this range, seek guidance from the manufacturer or technical representative.

Diameter (mm)	Length (mm)	Mass (g)	Units/box
83	500 +/- 5	2780	9
125	470 +/- 5	6250	4

Transport
Classification

Class

UN
Number

Standard
Packaging

1.1D

UN 0241

PRODUCT DISCLAIMER

© 2025 SBL Energy Ltd. All rights reserved. The details presented in this document ("Information") are intended to provide general technical guidance regarding the referenced products ("Products"). While reasonable care has been taken in compiling this Information, SBL Energy Ltd does not guarantee its accuracy, consistency, or applicability to every operational environment, and the Information may be updated or amended without prior notice. Explosive Products must only be handled, transported, and used by personnel who are properly trained, certified, and authorized to work with such materials. Users are responsible for assessing site-specific conditions, verifying regulatory requirements, and ensuring that all procedures align with applicable safety standards and legal obligations. To the extent permitted by law, SBL Energy Ltd rejects any form of warranty—statutory, express, or implied—relating to the Information or the Products, including but not limited to performance guarantees or suitability for a particular use. The company shall not be held liable for any loss, damage, injury, or operational consequence arising from reliance on this Information or from misuse or improper handling of the Products.

This document is provided solely for reference and shall not be interpreted as a contractual commitment, product guarantee, or legally binding representation by SBL Energy Ltd.



Office: 230, Hill Road, Da Rock Building, 2nd Floor,
Shivaji Nagar, Nagpur - 440010 (MH) India.



+91-8308810133



info@sblenergy.com



www.sblenergy.com