



NEO BOOST

TECHNICAL DATASHEET

Neo Boost is a high-strength emulsion booster manufactured using a high-energy emulsion explosive composition enclosed within a durable polymer shell. It is designed to deliver the high initiation energy required to reliably initiate bulk explosives, ANFO, watergels, packaged emulsions, and other non-cap-sensitive blasting agents.

The booster incorporates one or more longitudinal tunnels to accommodate a detonator or detonating cord, ensuring secure placement and efficient transfer of initiation energy. Its robust construction provides excellent water resistance and mechanical integrity, making it suitable for use in surface mining, underground mining, quarrying, tunnelling, and civil

TECHNICAL DETAILS

PARAMETER	VALUE
Classification	Class-3, Div.-2
Appearance	Yellowish Hard Solid Mass
Density	1.55 +0.05 gm/cc
VOD	7000 +/- 500 m/sec
Sensitivity	Cap Sensitive. Sensitive to No. 6 Detonator & Detonating Fuse
Water Resistance	Excellent
Weight per Cartridge	100gm/ 150gm/ 250gm/ 400gm
Package	25 Kgs. per box
Application	Initiation of non-cap sensitive charges in a bore, at any fixed point in a column of explosive charge Used with ANFO, cartridge and bulk explosives to prime the boreholes.

KEY BENEFITS

- High-energy emulsion composition for reliable initiation of bulk explosives and blasting agents.
- High detonation velocity and density for efficient transfer of initiation energy.
- Excellent water resistance, ensuring dependable performance in wet boreholes.
- Compatible with No. 8 strength detonators and approved detonating cord systems.
- The robust polymer shell provides good mechanical strength during handling and charging.
- Long shelf life with stable performance under





RECOMMENDATIONS FOR USE

1 Initiation with Detonating Cord

- Use Neo Boost boosters only with a detonating cord that meets the minimum PETN coreload requirement specified for the product (typically 10 g/m).
- Attach the cord securely by threading it through one tunnel, looping it around the curved path, and bringing it back through the second tunnel. Form a firm loop and ensure the cord is snug before lowering the assembly into the hole.
- Cut the downline from the reel and secure it properly at the collar so that tension is maintained during charging.
- When adding additional boosters on the same downline, loosen the cord tail, thread the cord through the straight tunnel of the next booster, re-secure at the collar, and lower the unit to the correct depth.

2 Initiation with Delay Detonators

- Insert the delay detonator through the booster tunnel designed for in-hole initiation.
- For angled or rough holes, tape the top/bottom of the booster after assembly to prevent the detonator from slipping out.
- Lower the complete primer carefully, ensuring the lead wires or shock tube remain undamaged—avoid stepping on them or dragging them through sharp edges.

STORAGE & HANDLING

- The boosters must be transported, stored and handled with care at all times.
- Avoid impact or collision with solid surfaces or other boosters, as this can cause damage leading to misfire or premature initiation.
- Use only detonators that can be fully fitted inside the booster. A partially exposed detonator may get damaged during charging and can cause untimely detonation.
- Suitable for use up to 60–65°C (depending on product specification). Seek technical advice for higher temperatures.
- Store in a cool, dry, licensed explosive magazine (Class 2).
- Follow FIFO (First-In-First-Out) inventory rotation to use the oldest stock first.
- Shelf life is typically up to 2 years under proper storage

PRODUCT DISCLAIMER

© 2025 SBL Energy Ltd. All rights reserved. The details presented in this document ("Information") are intended to provide general technical guidance regarding the referenced products ("Products"). While reasonable care has been taken in compiling this Information, SBL Energy Ltd does not guarantee its accuracy, consistency, or applicability to every operational environment, and the Information may be updated or amended without prior notice. Explosive Products must only be handled, transported, and used by personnel who are properly trained, certified, and authorized to work with such materials. Users are responsible for assessing site-specific conditions, verifying regulatory requirements, and ensuring that all procedures align with applicable safety standards and legal obligations. To the extent permitted by law, SBL Energy Ltd rejects any form of warranty—statutory, express, or implied—relating to the Information or the Products, including but not limited to performance guarantees or suitability for a particular use. The company shall not be held liable for any loss, damage, injury, or operational consequence arising from reliance on this Information or from misuse or improper handling of the Products.

This document is provided solely for reference and shall not be interpreted as a contractual commitment, product guarantee, or legally binding representation by SBL Energy Ltd.

Transport
Classification

Class

UN
Number

Standard
Packaging

1.1D

UN 0042



Office: 230, Hill Road, Da Rock Building, 2nd Floor,
Shivaji Nagar, Nagpur - 440010 (MH) India.



+91-8308810133



info@sblenergy.com



www.sblenergy.com