

DETONATORS

A detonator is an igniter or an initiating device used to activate an explosive. There are three ways to initiate a detonator: electrically, mechanically and chemically. Detonators initiate an explosive in controlled timing by transferring signal from one place to another using chemical, mechanical or electrical reactions. Initiation can be controlled by electrical timing systems or chemical delay elements.

ORDINARY DETONATOR

SBL is manufacturing Ordinary Detonators under the brand name NEO OD. The PESO ID of the Product is 1106 . The Aluminium Plain Ordinary Detonator, non-electric in nature, is commonly used with Safety fuse. These detonators are of No. 8 strength. The Detonators have 37 mm length and Diameter of Shell is 3.7 mm. These Detonators are manufactured in an extremely modern plant using highly sophisticated techniques. Detonator of No. 8 strength ensures effective initiation of Cap Sensitive Explosive. It is initiated when a piece of safety fuse is inserted into the cap.

APPLICATION

Detonators are more effective in Dry holes. They can be used for Boulder blasting, Secondary blasting, Safe initiation in quarry blasting and in non gassy underground, open cast mines, surface excavations, well sinking, road construction, civil works etc.

SAFETY

- Use Slandered quality of Crimper to ensure proper crimping of Detonator.
- Plain Detonators contain sensitive ingredients and must be handled with care and respect at all times.
- Use adequate length of Safety fuse to allow escape of shot firer to safe distance in sufficient time.
- Store at moderate temperatures and dry conditions.

PACKAGING

100 detonators are packed in a card board box which is further packed in wooden cases containing 1000 Detonators.

PRODUCTS	PESO BRAND ID	CATEGORY	PESO SIZE CODE	No of Detonators in Bunch/ inner box	No of Bunch/ Inner Box	TOTAL Detonators in a Box
NEO OD	1106	ORDINARY DETONATOR	DFQ	100	100	10000

