

Title : ATM Network Communication Architecture: Secure Connectivity using Leased Lines, VSAT, and IP Networks

Subject : Fundamentals of Telecommunication Systems

Experiment No. : 12

Class : SE

Division :S2

Batch :S21

Names and roll numbers of all group members:

Roll No.	Name of student	Group leader / Member
2401087	Nikhil Rajani	Group leader
2401088	Samyak Rajawat	Member
2401089	Janhvi R	Member
2401090	Arya Rane	Member

CASE STUDY

ATM Network Communication Architecture: Secure Connectivity using Leased Lines, VSAT, and IP Networks

INTRODUCTION:

Automated Teller Machines (ATMs) are a crucial component of modern banking systems, enabling customers to perform financial transactions such as cash withdrawal, deposits, balance inquiry, and fund transfers. These transactions require secure, reliable, and realtime communication between the ATM terminal and the bank's central servers. Earlier ATM systems relied heavily on dedicated leased lines, which ensured high reliability but were expensive and less flexible. With advancements in telecommunications, modern ATM networks now use a combination of:

- Leased Lines
- VSAT (Very Small Aperture Terminal)
- IP-based Networks (4G/5G, Broadband)

These technologies ensure continuous operation, even in remote or rural areas.


Telecommunication enables:

- Secure financial transactions
- Real-time account verification
- High availability and uptime
- Remote ATM monitoring and management
- Fraud detection and prevention

SYSTEM ARCHITECTURE:

(A) Block Diagram

The system follows the classical communication system structure:



ATM Communication Flow:

ATM Machine → Communication Network → Bank Switch → Core Banking Server → Response back to ATM

1. Source Customer inputs (card, PIN, transaction request) Financial data generated at ATM
2. Transmitter ATM terminal processes request Encrypts data using secure protocols Sends request via communication module
3. Channel Leased Line (wired) VSAT (satellite communication) IP Networks (4G/5G, broadband internet)
4. Receiver Bank's ATM switch or server receives request
5. Destination Core Banking System processes transaction Response sent back to ATM

(B) Technical Analysis

1. Network Types

ATM networks utilize various network architectures to ensure high availability. A Local Area Network (LAN) connects an on-site ATM directly to a bank branch's internal secure network. To connect offsite or remote ATMs to the bank's centralized data center, the data travels across a Wide Area Network

(WAN). Because WANs traverse public or third-party infrastructure, banks deploy Virtual Private Networks (VPNs) to create secure, encrypted tunnels

over IP networks, ensuring that financial data remains entirely isolated from public internet traffic.

2. Transmission Media

This system relies on highly specific transmission media based on the ATM's location.

- **Leased Lines:** Dedicated wired connections (often fiber optic) provide continuous, reliable, and highly secure pathways for ATMs located in bank branches or high-traffic urban centers.
- **VSAT (Very Small Aperture Terminal):** Uses satellite communication to connect ATMs in remote or rural areas where terrestrial cabling or cellular towers are unavailable. It operates via an antenna dish communicating with a satellite in orbit.
- **Cellular/IP Networks:** Modern standalone ATMs utilize wireless 4G/5G cellular modems. These transmit encrypted data via radio waves to cellular base stations, which then route the traffic through the provider's backbone to the bank's servers.

3. Devices and Standards

A complex chain of hardware handles ATM communication. The terminal relies on a specialized PC core and an Encrypting PIN Pad (EPP). An edge router or modem acts as the gateway. At the data center, a Hardware Security Module (HSM) is responsible for cryptographic processing. The entire system

adheres strictly to the ISO 8583 standard, which defines the format for electronic transactions made by cardholders, ensuring interoperability between different banks and network switches (like VISA or Mastercard).

4. Operational Details

The communication process begins when a customer inserts a card and enters a PIN. The EPP immediately encrypts the PIN block (usually using Triple DES or AES algorithms). The ATM software packages this encrypted PIN, along with card data and the transaction amount, into an ISO 8583 message. This message is encapsulated into TCP/IP packets. The router then pushes these packets over the VSAT, leased line, or IP VPN. To ensure data integrity across the channel, a Message Authentication Code (MAC) is attached. Once the bank's switch receives the packet, the HSM validates the MAC and translates the PIN block to verify it against the database.

5. Security

Financial data is incredibly sensitive, requiring banking-grade security at every OSI layer. At the physical and data-link layers, leased lines offer inherent isolation. Over IP and VSAT channels, IPsec (Internet Protocol Security) and TLS (Transport Layer Security) protocols are mandatory to establish encrypted tunnels. Furthermore, ATMs employ End-to-End Encryption (E2EE), meaning data is encrypted at the keypad and only decrypted inside the secure HSM at the bank's server. Strict compliance with

PCI DSS (Payment Card Industry Data Security Standard) ensures that firewalls, access controls, and network monitoring are continuously maintained to prevent interception or tampering.

ANALYSIS AND TRENDS

(A) Challenges

ATM network architecture faces unique operational challenges. Latency is a primary issue, specifically for VSAT connections; the physical distance signals must travel to space and back causes inherent propagation delays, which can slow down transaction times and risk timeouts. Network reliability is another concern; cellular dropouts or leased line fiber cuts lead to ATM downtime, directly impacting customer access to cash. Furthermore, security vulnerabilities persist; while the data transit is encrypted, physical network spoofing, malware introduced via USB, or network-level Distributed Denial of Service (DDoS) attacks targeting the banking switches remain significant threats.

(B) Future Scope

The future of ATM communication is moving toward highly integrated, smart network ecosystems. The rollout of 5G communication will provide ultra-low

latency and massive bandwidth, enabling a shift from standard cash dispensers to Interactive Teller Machines (ITMs) that support real-time HD video conferencing with remote bank tellers. The adoption of SoftwareDefined WAN (SD-WAN) will allow ATMs to dynamically switch between cellular, broadband, and satellite links in real-time if one network fails, achieving near 100% uptime. Additionally, advancements in biometric authentication (like retina or palm-vein scanning) integrated over high-speed networks may soon eliminate the need for physical cards and PINs entirely.

REFERENCES

- William Stallings - Data and Computer Communications.
- Behrouz A. Forouzan - Data Communications and Networking.
- ISO 8583 Financial Transaction Card Originated Messages Standard.
- PCI Security Standards Council - 1. William Stallings — Data and Computer Communications. 2. Behrouz A. Forouzan — Data Communications and Networking. 3. IEEE Official Website — <https://www.ieee.org> 4. 3GPP Specifications — <https://www.3gpp.org> 5. WHO Digital Health Resources — <https://www.who.int>
- IEEE Official Website - 1. William Stallings — Data and Computer Communications. 2. Behrouz A. Forouzan — Data Communications and Networking. 3. IEEE Official Website — <https://www.ieee.org> 4. 3GPP Specifications — <https://www.3gpp.org> 5. WHO Digital

Health Resources — <https://www.who.int>