

EXAMPLE PROGRAM TRACES

BFS:

```
$ ./Search_Graph bfs
vertices=275, edges=641
Enter starting node coords x,y:
1 1
Enter ending node coords x,y:
4 4
start=(1,1), goal=(4,4), vertices: 0 and 62
iter=1, frontier=1, popped=0 (1,1), depth=0, dist2goal=4.24264
pushed 1 (1,2)
pushed 20 (2,1)
pushed 21 (2,2)
iter=2, frontier=3, popped=1 (1,2), depth=1, dist2goal=3.60555
pushed 2 (1,3)
pushed 22 (2,3)
iter=3, frontier=4, popped=20 (2,1), depth=1, dist2goal=3.60555
pushed 40 (3,1)
pushed 41 (3,2)
iter=4, frontier=5, popped=21 (2,2), depth=1, dist2goal=2.82843
pushed 42 (3,3)
iter=5, frontier=5, popped=2 (1,3), depth=2, dist2goal=3.16228
pushed 3 (1,4)
pushed 23 (2,4)
iter=6, frontier=6, popped=22 (2,3), depth=2, dist2goal=2.23607
pushed 43 (3,4)
iter=7, frontier=6, popped=40 (3,1), depth=2, dist2goal=3.16228
pushed 59 (4,1)
pushed 60 (4,2)
iter=8, frontier=7, popped=41 (3,2), depth=2, dist2goal=2.23607
pushed 61 (4,3)
iter=9, frontier=7, popped=42 (3,3), depth=2, dist2goal=1.41421
pushed 62 (4,4)
iter=10, frontier=7, popped=3 (1,4), depth=3, dist2goal=3
pushed 4 (1,5)
pushed 24 (2,5)
iter=11, frontier=8, popped=23 (2,4), depth=3, dist2goal=2
pushed 44 (3,5)
iter=12, frontier=8, popped=43 (3,4), depth=3, dist2goal=1
pushed 63 (4,5)
iter=13, frontier=8, popped=59 (4,1), depth=3, dist2goal=3
pushed 75 (5,1)
```

```
pushed 76 (5,2)
iter=14, frontier=9, popped=60 (4,2), depth=3, dist2goal=2
pushed 77 (5,3)
iter=15, frontier=9, popped=61 (4,3), depth=3, dist2goal=1
iter=16, frontier=8, popped=62 (4,4), depth=3, dist2goal=0
```

=====

solution path:

vertex 0 (1,1)

vertex 21 (2,2)

vertex 42 (3,3)

vertex 62 (4,4)

search algorithm = BFS

total iterations = 16

max frontier size = 9

vertices visited = 23/275

path length = 3

DFS:

```
$ ./Search_Graph dfs
```

vertices=275, edges=641

Enter starting node coords x,y:

1 1

Enter ending node coords x,y:

4 4

start=(1,1), goal=(4,4), vertices: 0 and 62

iter=1, frontier=1, popped=0 (1,1), depth=0, dist2goal=4.24264

pushed 1 (1,2)

pushed 20 (2,1)

pushed 21 (2,2)

iter=2, frontier=3, popped=21 (2,2), depth=1, dist2goal=2.82843

pushed 22 (2,3)

pushed 41 (3,2)

pushed 42 (3,3)

iter=3, frontier=5, popped=42 (3,3), depth=2, dist2goal=1.41421

pushed 43 (3,4)

pushed 61 (4,3)

pushed 62 (4,4)

iter=4, frontier=7, popped=62 (4,4), depth=3, dist2goal=0

=====

solution path:

vertex 0 (1,1)

vertex 21 (2,2)

vertex 42 (3,3)
vertex 62 (4,4)
search algorithm = DFS
total iterations = 4
max frontier size = 7
vertices visited = 10/275
path length = 3

GBFS:

```
$ ./Search_Graph gbfs
vertices=275, edges=641
Enter starting node coords x,y:
1 1
Enter ending node coords x,y:
4 4
start=(1,1), goal=(4,4), vertices: 0 and 62
iter=1, frontier=1, popped=0 (1,1), depth=0, dist2goal=4.24264
pushed 1 (1,2)
pushed 20 (2,1)
pushed 21 (2,2)
iter=2, frontier=3, popped=21 (2,2), depth=1, dist2goal=2.82843
pushed 22 (2,3)
pushed 41 (3,2)
pushed 42 (3,3)
iter=3, frontier=5, popped=42 (3,3), depth=2, dist2goal=1.41421
pushed 43 (3,4)
pushed 61 (4,3)
pushed 62 (4,4)
iter=4, frontier=7, popped=62 (4,4), depth=3, dist2goal=0
```

=====

solution path:
vertex 0 (1,1)
vertex 21 (2,2)
vertex 42 (3,3)
vertex 62 (4,4)
search algorithm = GBFS
total iterations = 4
max frontier size = 7
vertices visited = 10/275
path length = 3