

```

% Lukas Chrostowski, curve fitting the MZI using findpeaks, 2015/08/14

% Enter the Dropbox URL here. Make sure it has a =1 at the end:

% TE
url = 'https://www.dropbox.com/s/1rvjfef4jqybc12/ZiheGao_MZI2_271_Scan1.mat?dl=1';
dL = 111.915; % [micron] Path length difference in the MZI

% TM:
%url = 'https://www.dropbox.com/s/onjwrarapf6dumv/ADCL_1_1153_Scan1_L2-L1%3D100um.mat?dl=1';
%dL = 100;

PORT=1; % Which Fibre array port is the output connected to?

a=websave('mzi.mat',url); % get data from Dropbox
load('mzi.mat');

% Data is stored in variable "scanResults".
% There are two columns - wavelength (1), and amplitude (2)
lambda=scanResults(1,PORT).Data(:,1)/1e9;
amplitude=scanResults(1,PORT).Data(:,2);

% Curve fit data to a polynomial for baseline correction
p=polyfit((lambda-mean(lambda))*1e6, amplitude, 4);
amplitude_baseline=polyval(p,(lambda-mean(lambda))*1e6);

% Perform baseline correction to flatten the spectrum
% Use the curve polynomial, and subtract from original data
amplitude_corrected = amplitude - amplitude_baseline;
amplitude_corrected = amplitude_corrected + max(amplitude_baseline) - max(amplitude);

% data only within the wavelength range of interest.
if not(exist('lambda_min'))
    lambda_min = min(lambda); % Can limit the analysis to a range of
wavelengths
end
if not(exist('lambda_max'))
    lambda_max = max(lambda); % if the data on the edges is noisy
end
lambda1=lambda_min:min(diff(lambda)):lambda_max;
amplitude=interp1(lambda, amplitude_corrected, lambda1,'linear');
lambda=lambda1;
amplitude(find(amplitude== -inf))=-50; % check if there are -infinity data
points


% plot baseline corrected spectrum
figure;

```

```

plot (lambda*1e6, amplitude);
xlabel ('Wavelength [\mu m]');
ylabel ('Transmission [dB]');
axis tight
title ('Experimental data (baseline corrected, wavelength range)');

```



```

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% Find peaks, extract FSR and ng, and neff
% as initial parameters
%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
% smooth (0.1% moving average filter)
windowSize = floor(1e-3*length(lambda)); b = (1/
windowSize)*ones(1,windowSize);
amplitude_smooth=filter(b,1,amplitude);
% FIND PEAKS
[pks,x_values,w,p]=findpeaks(-amplitude_smooth, lambda,
'minPeakProminence',4,'Annotate','extents');


% plot spectrum with peaks
figure;
plot (x_values*1e6, interp1(lambda, amplitude, x_values,'pchip'),
'ro','MarkerSize',10);
hold all;
plot (lambda*1e6, amplitude_smooth);

```

```

xlabel ('Wavelength [\mu m]');
ylabel ('Transmission [dB]');
axis tight
title ('Experimental data (with peaks)');

```



```

% Calculate and plot ng data points from FSR
lambda_ng = (x_values(1:end-1)+x_values(2:end))/2;
FSR=(x_values(2:end)-x_values(1:end-1));
ng = abs(lambda_ng.^2/1/(dL*1e-6)./FSR);
% find average ng from all reasonable ng values:
indexes = find(gt(ng,3)); ng=ng(indexes); lambda_ng = lambda_ng(indexes);
FSR = FSR(indexes);
indexes = find(lt(ng,5)); ng=ng(indexes); lambda_ng = lambda_ng(indexes);
FSR = FSR(indexes);
ng_av = mean(ng);
if eq(length(ng),0)
    disp ('No group index values found. Terminating script. ');
    return
end
disp (['(estimate) Group index: ' num2str(ng_av)])

```

```

(estimate) Group index: 4.1617

```

```


% plot FSR
figure;

```

```

plot (lambda_ng*1e6, FSR*1e9, '-o','LineWidth',1,'MarkerSize',7 );
xlabel ('Wavelength [\mu m]')
ylabel ('Free Spectral Range [nm]')
xlim([min(lambda), max(lambda)]*1e6);
title ('Free Spectral Range, from Experimental data');

```



```

% plot ng
figure
plot (lambda_ng*1e6, ng, '-o','LineWidth',1,'MarkerSize',7 )
xlabel ('Wavelength [\mu m]')
ylabel ('Group Index')
xlim([min(lambda), max(lambda)]*1e6);
title ('Waveguide Group Index, from Experimental data');

% find starting point for curve fitting MZI, using the ng data
% Part 1 - n1
% lambda0 is in microns.
lambda0 = x_values(floor(length(x_values)/2)) * 1e6;
n1_initial=2.4;
modeNumber = n1_initial * dL / lambda0 - 0.5;
n1 = (2*floor(modeNumber)+1)*lambda0/2/dL;
% Part 1 - n2 from ng_av
n2 = (n1-ng_av)/lambda0;
% Part 3 - n3 from slope of ng vs. lambda, to get the dispersion
f_line = @(x,xdata)x(2)*xdata+x(1);

```

```
[xfit,resnorm] = lsqcurvefit(f_line,[ng_av 0],lambda_ng*1e6,ng);
```

Local minimum found.


Optimization completed because the size of the gradient is less than the value of the optimality tolerance.

<stopping criteria details>

```
r=corrcoef(ng,f_line(xfit, lambda_ng*1e6));
r2_ng=r(1,2).^2;
disp(['Goodness of fit, r^2 value: ' num2str(r2_ng)] )
```

Goodness of fit, r^2 value: 0.0036376

```
hold all;
plot (lambda_ng*1e6, f_line(xfit, lambda_ng*1e6),'LineWidth',3)
```



```
n3 = -xfit(2)/2/lambda0;
Dispersion0 = -(lambda0*1e-6) / 299792458 * 2* (n3*1e12) * 1e12 /1e9 /
1e-3;
disp(['(estimate from ng slope) Dispersion [ps/nm/km]: '
num2str(Dispersion0) ])
```

(estimate from ng slope) Dispersion [ps/nm/km]: 773.89

```
if lt(r2_ng,0.01) % only use the result if the fit is good
    n3 = 0;
end
```


```

% Initial conditions for fitting:
nx_init = [n1 n2 n3];
alpha_init = 1e-3; % propagation loss [micron^-1]
x0=[nx_init, alpha_init, 0];

% Define the MZI transfer function
% - as a Taylor expansion around the central wavelength
% - Use units of [microns] - keeps the variables closer to 1.
% - These make the curve fitting easier.
% use Matlab anonymous functions
% effective index:
neff = @(nx, lambda) ...
    (nx(1) + nx(2).*(lambda-lambda0) + nx(3).*(lambda-lambda0).^2);
% neff([2.4, -1, 0], 1.56) % test it.
% alpha = 1e-3; % propagation loss [micron^-1]
% complex propagation constant
beta = @(nx, alpha, lambda) ...
    (2*pi*neff(nx, lambda)./lambda - 1i*alpha/2*ones(1,length(lambda)) );
% beta([2.4, -1, 0], 1e-3, [1.56, 1.57]) % test it.
% MZI transfer function
T_MZI = @(X, lambda) ...
    (10*log10( 0.25* abs(1+exp(-1i*beta(X(1:3), X(4), lambda)*dL)).^2)
+X(5) );
% T_MZI([2.4, -1, 0, 1e-3], [1.56, 1.57]) % test it.

figure;
plot (lambda*1e6, amplitude);
hold all;
plot (lambda0, -40, 's', 'MarkerSize',20);
plot(lambda*1e6, T_MZI(x0, lambda*1e6), '-', 'LineWidth',2);
xlabel ('Wavelength [\mu m]');
ylabel ('Transmission [dB]');
axis tight
title ('MZI model (initial parameters)');

```



% Curve fit:

```
[xfit,resnorm] = lsqcurvefit(T_MZI,x0,lambda*1e6,amplitude);
```

Local minimum possible.

lsqcurvefit stopped because the final change in the sum of squares relative to its initial value is less than the value of the function tolerance.

<stopping criteria details>

xfit


```
xfit = 1x5
      2.3916   -1.1468   -0.0112    0.0022    0.2992
```

```
r=corrcoef(amplitude,T_MZI(xfit, lambda*1e6));
r2=r(1,2).^2;
disp(['Goodness of fit, r^2 value: ' num2str(r2) ])
```

Goodness of fit, r^2 value: 0.99063

```
figure;
plot (lambda*1e6, amplitude);
hold all;
plot(lambda*1e6, T_MZI(xfit, lambda*1e6), 'LineWidth',3);
xlabel ('Wavelength [\μm]');
```

```
ylabel ('Transmission [dB]');
axis tight
title ('MZI model (fit parameters)');
```



```
% Check if the fit is good. If so, find ng
if (ge(r2,0.8))
    % plot ng curve
    figure;
    neff_fit = neff(xfit(1:3),lambda*1e6);
    dndlambda=diff(neff_fit)./diff(lambda); dndlambda=[dndlambda,
dndlambda(end)];
    ng=(neff_fit - lambda .* dndlambda);
    plot(lambda*1e6, ng, 'Linewidth',4);
    xlabel ('Wavelength [\μm]');
    ylabel ('Group index, n_g');
    axis tight
    title ('Group index (from MZI fit)');

    % waveguide parameters at lambda0
    disp (['Waveguide parameters at wavelength [um]: ' num2str(lambda0)])
    ng0 = xfit(1) - lambda0*xfit(2);
    disp (['Group index: ' num2str(ng0)])

    % Dispersion:
    c=299792458;
    Dispersion0 = -(lambda0*1e-6) / c * 2* (xfit(3)*1e12); % [s/m^2]
```




```

% [ps/nm/km]:
Dispersion0 = Dispersion0 * 1e12 /1e9 /1e-3;
disp(['Dispersion [ps/nm/km]: ' num2str(Dispersion0) ])

end

```



Waveguide parameters at wavelength [um]: 1.5429
 Group index: 4.1611
 Dispersion [ps/nm/km]: 115.1933