

Профилирование и оптимизация программ на Go

Олег Федосеев,
руководитель отдела backend-разработки
@olegfedoseev
o.fedoseev@office.ngs.ru



Кто я?


- Руководжу всей backend разработкой в **НГС**
- Пишу код более 8 лет
- Последние пару лет предпочитаю **Go**




А так же мы делаем

N1.RU **зарплата.ру**

Лирическое отступление





<https://habrahabr.ru/company/badoo/blog/301990/>

Краткий план

- Собираем данные
- Анализируем данные
- Примеры оптимизаций
- **Демо!**

Package pprof

```
import "runtime/pprof"
```

Overview

Index

Overview ▼

Package pprof writes runtime profiling data in the format expected by the pprof visualization tool. For more information about pprof, see <http://code.google.com/p/google-perftools/>.

Index ▼

func Profiles() []*Profile

func StartCPUProfile(w io.Writer) error

func StopCPUProfile()

func WriteHeapProfile(w io.Writer) error

type Profile

func Lookup(name string) *Profile

func NewProfile(name string) *Profile

func (p *Profile) Add(value interface{}, skip int)

func (p *Profile) Count() int

func (p *Profile) Name() string

func (p *Profile) Remove(value interface{})

func (p *Profile) WriteTo(w io.Writer, debug int) error

Bugs

import “runtime/pprof”

```
var cprofile = flag.String("cprofile", "", "write cpu profile to file")

func main() {
    flag.Parse()
    if *cprofile != "" {
        f, err := os.Create(*cprofile)
        if err != nil {
            log.Fatal(err)
        }
        pprof.StartCPUProfile(f)
        defer pprof.StopCPUProfile()
    }
    ...
}
```


Package pprof

```
import "net/http/pprof"
```

[Overview](#)

[Index](#)

Overview ▼

Package pprof serves via its HTTP server runtime profiling data in the format expected by the pprof visualization tool. For more information about pprof, see <http://code.google.com/p/google-perftools/>.

The package is typically only imported for the side effect of registering its HTTP handlers. The handled paths all begin with /debug/pprof/.

To use pprof, link this package into your program:

```
import _ "net/http/pprof"
```

If your application is not already running an http server, you need to start one. Add "net/http" and "log" to your imports and the following code to your main function:

```
go func() {  
    log.Println(http.ListenAndServe("localhost:6060", nil))  
}()
```

Then use the pprof tool to look at the heap profile:

```
go tool pprof http://localhost:6060/debug/pprof/heap
```


Benchmarks

Functions of the form

```
func BenchmarkXxx(*testing.B)
```

are considered benchmarks, and are executed by the "go test" command when its -bench flag is provided. Benchmarks are run sequentially.

For a description of the testing flags, see https://golang.org/cmd/go/#hdr-Description_of_testing_flags.

A sample benchmark function looks like this:

```
func BenchmarkHello(b *testing.B) {  
    for i := 0; i < b.N; i++ {  
        fmt.Sprintf("hello")  
    }  
}
```

The benchmark function must run the target code b.N times. During benchmark execution, b.N is adjusted until the benchmark function lasts long enough to be timed reliably. The output

```
BenchmarkHello    10000000    282 ns/op
```

means that the loop ran 10000000 times at a speed of 282 ns per loop.

Собираем данные

- Явный start-stop <https://golang.org/pkg/runtime/pprof/>
- Http-интерфейс <https://golang.org/pkg/net/http/pprof/>
- Бенчмарки <https://golang.org/pkg/testing/>

go tool pprof

(pprof) top10


Total: 2525 samples

298	11.8%	11.8%	345	13.7%	runtime.mapaccess1_fast64
268	10.6%	22.4%	2124	84.1%	main.FindLoops
251	9.9%	32.4%	451	17.9%	scanblock
178	7.0%	39.4%	351	13.9%	hash_insert
131	5.2%	44.6%	158	6.3%	sweepspan
119	4.7%	49.3%	350	13.9%	main.DFS
96	3.8%	53.1%	98	3.9%	flushptrbuf
95	3.8%	56.9%	95	3.8%	runtime.aeshash64
95	3.8%	60.6%	101	4.0%	runtime.settype_flush
88	3.5%	64.1%	988	39.1%	runtime.mallocgc


go tool pprof

```
(pprof) list main.handler
Total: 12.70s
ROUTINE ===== main.handler in profiling-demo/main.go
   0    4.11s (flat, cum) 32.36% of Total
   .      . 28:    })
   .      . 29:    log.Fatal(http.ListenAndServe(":8080", nil))
   .      . 30:}
   .      . 31:
   .      . 32:func handler(w http.ResponseWriter, r *http.Request) {
   . 4.01s   33: host, err := os.Hostname()
   .      . 34:    if err != nil {
   .      . 35:        log.Printf("Failed to get hostname: %v", err)
   .      . 36:        http.Error(w, err.Error(), http.StatusInternalServerError)
   .      . 37:    }
   .      . 38:
   .      . 39:    now := time.Now()
   .      . 40:
```

go tool pprof



go tool pprof



Спасибо!

Олег Федосеев
oleg.fedoseev@me.com
@olegfedoseev

Gopher designed by Renee French, original png created by
Takuya Ueda licensed under CC 3.0 Attribution