

DEVELOPER REFERENCE MANUAL — API Architecture & Base URLs

The DocuMind API follows RESTful architectural principles. Production endpoints are accessible at <https://api.documind.ai/v1>. All API payloads use UTF-8 JSON.

DEVELOPER REFERENCE MANUAL — Authentication & API Keys

All requests require a Bearer token passed in the Authorization header: 'Authorization: Bearer '. Keys start with prefix 'dm_live_' for production and 'dm_test_' for sandbox environments.

DEVELOPER REFERENCE MANUAL — Rate Limiting & Headers

Standard Tier rate limits allow 120 requests per minute and 10,000 requests per day. Response headers include X-RateLimit-Limit, X-RateLimit-Remaining, and X-RateLimit-Reset.

DEVELOPER REFERENCE MANUAL — Document Ingestion Endpoints

POST /v1/documents/signed-url requests pre-signed storage URLs. POST /v1/documents/register submits document metadata for asynchronous background ingestion.

DEVELOPER REFERENCE MANUAL — Semantic Search & Retrieval

POST /v1/search accepts query string, top_k integer (default 5, max 50), and score_threshold float (0.0 to 1.0). Returns list of chunk objects with similarity scores.

DEVELOPER REFERENCE MANUAL — Streaming Chat & SSE Protocol

POST /v1/chat/stream utilizes Server-Sent Events (SSE). Chunks are emitted in format 'data: {"content": "...", "provider": "..."}' terminating with '[DONE]'.

DEVELOPER REFERENCE MANUAL — Error Handling & Status Codes

The API returns standard RFC 7807 problem details. Status 400 = Bad Request, 401 = Unauthorized, 404 = Not Found, 422 = Validation Error, 429 = Rate Limit Exceeded, 503 = Service Unavailable.

DEVELOPER REFERENCE MANUAL — Webhooks & Event Subscriptions

Subscribers receive HMAC-SHA256 signed event notifications for events: 'document.processed', 'document.failed', and 'model.fallback_activated'.