

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 1

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 1). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 2

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 2). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 3

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 3). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 4

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 4). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 5

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 5). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 6

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 6). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 7

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 7). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 8

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 8). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 9

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 9). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 10

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 10). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 11

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 11). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 12

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 12). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 13

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 13). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 14

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 14). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 15

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 15). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 16

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 16). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 17

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 17). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.

GLOBAL SUSTAINABILITY & DECARBONIZATION ASSESSMENT 2026 — VOL 18

Detailed audit of Scope 1, Scope 2, and Scope 3 greenhouse gas emissions across data center supply chains (Module 18). By transitioning AI inference workloads to geothermal and wind-backed regions, carbon intensity was reduced from 420g CO₂e/kWh to 48g CO₂e/kWh. Water usage effectiveness (WUE) dropped to 0.18 liters per kilowatt-hour through closed-loop liquid dielectric immersion cooling.