

Utilitas A1 Utilitas A2

Ceiling Supply Unit (Anaesthesia Pendant)



Utilitas A1

Conforms to: IS / ISO 11197 : 2019, IS / ISO IEC 60601 - 1 : 2015 + A1 : 2020

IS / ISO 7396 - 1 : 2016 + A1 : 2017, IS / ISO 9170 - 1 : 2017

IS / ISO 19054: 2005 + A 1: 2016 (Medical Rail)

Certifications: ISO 13485:2016 – Medical devices – Quality Management Systems

ISO 9001:2015 – Quality Management Systems


Special Features

- 330° Utility console rotation
- 330° arm joint rotation
- · High Payload
- Configurable
- Flexible Solution
- True Versatility

- Bedside safety
- · Optimum functionality
- Effortless maneuverability
- Easy access to console facia
- User-friendly positioning of Medical Devices

Features

- All services integrated into the pendant system ensuring optimal safety
- Lateral arm Large effective field for convenient positioning
- Convenient positioning of gas, equipment, electrical and speciality services
- Service head ergonomics Shelves / Monitor mounting solutions
- Hose connection Gas specific NIST connectors
- Power supply Low smoke halogen cable through spiral conduit terminating at junction box
- Hygiene Minimum visible screws, combined with smooth surfaces for easier cleaning and disinfection
- Configuration can be customized within the limits of applicable standards



Technical Specifications

Description	Utilitas A1	Utilitas A2
Pendant Configuration	Stationary with 1 Arm Rotation - 330° + Utility Console 330°	Stationary with 2 Arms Rotation - 330° + 330° + Utility Console 330°
Length - Lateral Arm	810mm	810mm + 610mm
Functional Radius	636mm	636mm + 436mm = 1072mm combined
Rotation Utility Console	0 to 330°	0 to 330°
Utility Console Size (L x W x H)	170mm x 160mm x 1224mm	170mm x 160mm x 1224mm
Weight (Approx)	40 Kgs	50 Kgs
Payload (Max.)	150 Kgs	120 Kgs

Conforms to:	IS / ISO 11197 : 2019, IS / ISO IEC 60601 - 1 : 2015 + A1 : 2020 IS / ISO 7396 - 1 : 2016 + A1 : 2017, IS / ISO 9170 - 1 : 2017 IS / ISO 19054 : 2005 + A 1 : 2016 (Medical Rail)	
Gas & Vac. Terminals	6 Nos. Pre-piped & Customizable combinations	
Terminal type	DISS, BS, DIN, PB & Ohmeda (Any one type) (BS by default)	
220V AC Electrical sockets	Four shutter type multi-standard sockets compatible to 5-6-10-13A plugs and three 16A sockets will be provided	
Communication Ports	1 - RJ45 Data socket, 1 - RJ11 Telephone socket	
Support System - Medical Rail	Horizontal Medical Rail 320mm - 3 Nos. with clamps	
	Optional - Monitor stand with mounting bracket assembly and arm	
	Optional - Vertical round pole for Syringe Pump cum IV stand with clamps	
	Optional - Crimped medical gas tube to connect secondary devices, Table top, Pole, Holder extensions, Shelves, Catheter jar, Suction jar, Bottle holders, Utility basket, Rubbish bag holder, Clamps for medical rail, Wire basket etc	
Earthing	Protective Earth	
SEEB (Optional)	Plug and socket for Supplementary Equipotential Earth Bonding	
Protection	Class II, IP51	
Mounting	Complete mounting system with NIST connection for gas & vac services and terminals for power connection	
Vertical Boom	Alloy 6063 T6: Extruded round aluminium profile (T = not less than 3mm). To specify length i.e. Console 1224mm + Additional boom required	
Body (Pendant)	Alloy 6063 T6: Extruded aluminium profile (T = not less than 2.5mm)	
Suspension Assembly	Pre-engineered Rust-proof (passivate) Trivalent Zinc plated (8-10µm) steel	
Finish (Pendant)	Epoxy coating to RAL 7035 (Textured)	

Ordering Information

Utilitas A1 633A000 Utilitas A2 633B000

Add-Ons (Optional)

Medical Rail 320mm with 2 Mounting Clamps



Ordering Code: 635J100

Ordering Code: 635C100

shelf adjustment

Monitor shelf with 300 mm channel &

265 mm swivel arm with 15° Angular

Flowconnect LP Medical Gas anti-static Hose Assembly with Crimped End Connectors



NOTE: Request separate AKTIV Hoses brochure for ordering code

Autoclavable Semi-transparent Polycarbonate Basket Size - 260 x 130 x 70 mm

Tray size - 325 x 270 mm with fixed clamp

Ordering Code: 635I100



Ordering Code: 635F100

Mounting Block for Secondary Devices (In conjunction with Quick Claw Clamp)



Ordering Code: 635G100

Self Locking Quick Claw Clamp (QCC) for Rail mounting



Ordering Code: 635B100

Wire basket with rail mounting clamp Size: 300 x 200 x 140 mm




Ordering Code: 635F200

Autoclavable Semitransparent Polycarbonate Catheter Jar Ø90mm x 250mm "U" shaped bottom



Ordering Code:635K100

Wire basket for catheter



Ordering Code: 635KF200

SS Telescopic Drip Pole with fixed clamp & 120 mm swivel aluminium arm for Rail mount



Ordering Code: 635H100

Syringe Pump cum IV Pole with 45° angular clamps





Corporate Office: Plot No. 691, Sector 69, IMT, Faridabad, Haryana 121004, INDIA Tel: +91-7291838253

Email: aktivtechnologies@gmail.com, sanjay.aktiv@gmail.com

Website: www.aktivtechnologies.com



12/21

ЦТ / 633 Rev 02