

PulseEDU

Phase 1 — User Roles & Access Matrix

End-to-end developer reference

Generated: May 10, 2026

Scope: every user type that exists in the Phase 1 launch, every page they can reach, every action they can take, and every cross-feature dependency.

Source of truth: this document is generated from the live codebase — staff schema, capability flags, route guards (requireSchool / isCoreTeam / requireAdmin / parent token / signage token), nav predicates in App.tsx, and parent / signage entry points.

How to read this document

- Section 1 — Master role list: every identifier with its scope and how it is checked.
- Section 2 — Capability flags: granular per-user toggles layered on top of roles.
- Section 3 — Helper predicates: derived gates (Core Team, Safety Plan editor, etc.).
- Section 4 — Page × Role matrix (cross-reference grid for every page).
- Section 5 — Per-feature access detail: each feature, who can do what, and dependencies on other features.
- Section 6 — API surface by feature (route !' guard).
- Section 7 — Cross-feature dependency map (writes that touch other modules).

1. Master User Type List

PulseEDU has four authentication tiers: staff (with role flags), parents, kiosk/signage devices, and unauthenticated public displays. Roles are stored as boolean flags on the staff record (`lib/db/src/schema/staff.ts`) and resolved in the global auth middleware (`artifacts/api-server/src/app.ts`).

1a. Staff roles (privileged)

Identifier	Display name	Scope	Check / notes
isSuperUser	SuperUser	District	Top-level. Can act as any school in district via <code>active_school_override</code> . Grants/revokes any role. Manages tenancy and school plans.
isDistrictAdmin	District Admin	District	Manages all schools in their district (rosters, staff, imports). Cannot reach other districts. <code>canActAsDistrict()</code> in <code>lib/scope.ts</code> .
isAdmin	School Admin	School	Manages school settings, staff roles, all admin surfaces for one school.
isBehaviorSpecialist	Behavior Specialist	School	Core Team member. Receives Watchlist check-in notifications and pullout verifications.
isMtssCoordinator	MTSS Coordinator	School	Core Team. Owns Tier 2/3 plans and intervention reports.
isSchoolPsychologist	School Psychologist	School	Core Team. Full Safety Plan editing rights.
isGuidanceCounselor	Guidance Counselor	School	<code>canEditSafetyPlan</code> gate. Manages student safety plans and library.
isDean	Dean	School	Bundled with Admin/Core Team for displays and discipline visibility.
isEseCoordinator	ESE Coordinator	School	Manages school accommodations library; presets for ESE staff.
isPbisCoordinator	PBIS Coordinator	School	Owns PBIS settings, milestones, and store edit rights.

Identifier	Display name	Scope	Check / notes
isIssTeacher	ISS Teacher	School	Granted capIssDashboard by default. Runs the ISS room daily.
isCounselor	Counselor	School	Label/preset for non-guidance counseling staff.
isSocialWorker	Social Worker	School	Label/preset; access via capability flags.

1b. Non-staff user types

Identifier	Category	Scope	Auth mechanism
parentId	Parent Portal user	Linked students	parents table; email + password (or invite token). verifyParentAuthToken in lib/parentAuth.ts. Only sees students in parent_students join.
kioskActivation	Kiosk (active)	Room / school	kiosk_activations.tokenHash (32-byte). Can issue passes / add to queue for one room.
kioskViewer	Kiosk viewer (QR)	Room	kiosk_viewer_tokens. Read-only token for the waiting-queue display.
publicDisplay	Signage / TV	Playlist / school	None — /api/displays/public/* is open. Scoped by playlist or school id in URL.
anonymous	Public	n/a	Login pages, branding fetches, /api/healthz.

2. Capability Flags (cap_*)

Granular per-staff toggles defined in adminStaff.ts. Default values fall into two buckets: defaults-on (any signed-in staff member) and defaults-off (must be granted by an Admin or SuperUser).

Defaults ON — every staff account starts with these

Capability	What it unlocks
capHallPasses	Issue and end hall passes for own students.
capTardies	Log tardies, check-ins, check-outs.
capStudentActivity	View the live activity feed and student timelines.
capPbisAward	Award PBIS points.
capParentEmail	Send parent emails / log a parent contact.
capSupportNotes	Add staff support notes on a student profile.
capAccommodationLog	Log that an accommodation was provided.
capPulloutsRequest	Submit a pullout request for behavioral support.
capInterventionLog	Log a Tier 2/3 intervention contact.
capReports	Access teacher-level reports (own students).
capKioskActivate	Activate a kiosk device with their staff credentials.

Defaults OFF — must be granted

Capability	What it unlocks
capHallPassesViewAll	View hall pass log school-wide (not just own classes).
capPbisManage	Edit PBIS reasons, milestones, and run bulk awards.

Capability	What it unlocks
capAccommodationManage	Edit the school accommodations library.
capPulloutsVerify	Verify and triage pullout requests.
capPulloutsReview	Review pullout outcomes / behavior review board.
capInterventionManage	Manage intervention types and pullout reasons (school-wide).
capIssDashboard	Run the ISS dashboard and reporting.
capManageLocations	Edit rooms, locations, and bell schedules.
capStaffRoles	View the staff roles matrix.
capManageRoles	Edit other staff members' roles and capabilities.
capManageDisplays	Manage signage playlists and display content.

3. Helper Predicates

Derived gates used throughout the route layer and the client nav. These compose role flags + capability flags.

Predicate	Defined in	Logic
isCoreTeam	lib/coreTeam.ts	isSuperUser isDistrictAdmin isAdmin isBehaviorSpecialist isMtssCoordinator isSchoolPsychologist.
canEditSafetyPlan	routes/safetyPlans.ts	isCoreTeam isGuidanceCounselor.
canActAsDistrict	lib/scope.ts	isSuperUser isDistrictAdmin.
canManageDisplays	components/Displays guard	Core Team isDean capManageDisplays.
canManageStaffRoles	App.tsx nav	isAdmin isSuperUser capManageRoles.
canAccessMtssHub	App.tsx nav	isCoreTeam (drives all six insights dashboards).
canAccessPbisHub	App.tsx nav	isCoreTeam isPbisCoordinator.
canEditSchoolStore	App.tsx nav	isCoreTeam isPbisCoordinator.
canManageMtssPlans	App.tsx nav	isCoreTeam.
canManageBehaviorLists	App.tsx nav	isCoreTeam.
canViewIssDashboard	App.tsx nav	isAdmin isIssTeacher capIssDashboard.
canVerifyPullouts	App.tsx nav	isCoreTeam capPulloutsVerify.
canManageBellSchedules	App.tsx nav	isAdmin isSuperUser capManageLocations.
canManageSettings	App.tsx nav	isAdmin isSuperUser.

Predicate	Defined in	Logic
requireSchool	lib/scope.ts (server)	Resolves req.schoolId from session or active_school_override; rejects if absent.
requireAdmin	routes/kiosk.ts (server)	isAdmin isSuperUser.
requireSuperUser	server middleware	isSuperUser only.

4. Page x Role Matrix

R = read, W = write, A = admin (manage settings / others), — = no access. Capability-gated cells are marked 'cap'. The matrix is split into six tables to stay legible at letter-size.

4a. Hall Pass & Tardies

Page / Feature	SU	DA	Admin	BS/MTSS/ Psych	GC	Dean	PBIS coord	ESE coord	ISS Tch	Teach er	Pare nt	Sign ge
Hall Passes (issue/end)	W	W	W	W	W	W	W	W	W	W	—	R*
Hall Pass log (school-wide)	R	R	R	R	cap	R	cap	cap	cap	cap	—	—
Hall Pass mgmt (lists, limits, polarity)	A	A	A	A	—	—	—	—	—	—	—	—
Tardy Pass / check-in	W	W	W	W	W	W	W	W	W	W	R	—
Hall Pass reports (YTD / research)	R	R	R	R	—	R	—	R	—	—	—	—
Hall Pass Queue (kiosk)	A	A	A	—	—	—	—	—	—	W	—	R

[illegible]

Page / Feature	SU	DA	Admin	BS/MTSS/ Psych	GC	Dean	PBIS coord	ESE coord	ISS Tch	Teach er	Pare nt	Sign ge
School Store mgmt	A	A	A	A	—	—	A	—	—	—	—	—
Classroom Store	R	R	R	R	R	R	R	R	R	W	—	—
PBIS House standings (signage)	R	R	R	R	R	R	R	R	R	R	—	R

Page / Feature	SU	DA	Admin	BS/MTSS/ Psych	GC	Dean	PBIS coord	ESE coord	ISS Tch	Teach er	Pare nt	4c Sign ge
Request Pullout	W	W	W	W	W	W	W	W	W	W	—	—
Verify Pullouts	W	W	W	W	—	—	—	—	—	cap	—	—
Behavior Review (outcomes)	W	W	W	W	—	—	—	—	—	—	—	—
ISS Dashboard (live room)	W	W	W	—	—	—	—	—	W	cap	—	—
ISS Reporting (daily logs)	R	R	R	R	—	R	—	—	R	—	—	—
Log Intervention	W	W	W	W	W	W	W	W	W	W	—	—
My Interventions (history)	R	R	R	R	R	R	R	R	R	R	—	—
Interventions mgmt (types/ reasons)	A	A	A	A	—	—	—	—	—	—	—	—

Page / Feature	SU	DA	Admin	BS/MTSS/ Psych	GC	Dean	PBIS coord	ESE coord	ISS Tch	Teach er	Pare nt	4d Sign ge
MTSS Plans (T2/T3)	A	A	A	A	—	—	—	—	—	—	R†	—

Page / Feature	SU	DA	Admin	BS/MTSS/ Psych	GC	Dean	PBIS coord	ESE coord	ISS Tch	Teach er	Pare nt	Sign ge
MTSS Reports (fidelity, progress)	R	R	R	R	—	—	—	—	—	—	—	—
Safety Plans	A	A	A	A	A	—	—	—	—	R	—	—
Trusted Adults admin	W	W	W	W	—	—	—	—	—	—	—	—
Watchlist Hub (alerts, summary)	W	W	W	W	—	—	—	—	—	—	—	—
Watchlist Network (graph)	R	R	R	R	—	—	—	—	—	—	—	—
Watchlist Case detail (notes/players)	W	W	W	W	—	—	—	—	—	—	—	—
Witness Statements	W	W	W	W	W*	W*	W*	W*	W*	W*	—	—
Page / Feature	SU	DA	Admin	BS/MTSS/ Psych	GC	Dean	PBIS coord	ESE coord	ISS Tch	Teach er	Pare nt	† Par Sign ge
Insights Hub (launcher)	R	R	R	R	—	—	—	—	—	—	—	—
Engagement Dashboard	R	R	R	R	—	—	—	—	—	—	—	—
Behavior Dashboard	R	R	R	R	—	—	—	—	—	—	—	—
Academics Dashboard	R	R	R	R	—	—	—	—	—	—	—	—
Academics Trajectory	R	R	R	R	—	—	—	—	—	—	—	—
SEB-SEL Dashboard	R	R	R	R	—	—	—	—	—	—	—	—
Equity Dashboard	R	R	R	R	—	—	—	—	—	—	—	—

Page / Feature	SU	DA	Admin	BS/MTSS/ Psych	GC	Dean	PBIS coord	ESE coord	ISS Tch	Teach er	Pare nt	Sign ge
Early Warning Dashboard	R	R	R	R	—	—	—	—	—	—	—	—
Student Profile (deep dive)	R	R	R	R	R	R	R	R	R	R	—	—
My Watch List (personal)	W	W	W	W	W	W	W	W	W	W	—	—

Page / Feature	SU	DA	Admin	BS/MTSS/ Psych	GC	Dean	PBIS coord	ESE coord	ISS Tch	Teach er	Pare nt	4f. S Sign ge
Staff Roles matrix	A	A	A	—	—	—	—	—	—	—	—	—
Staff Directory	W	W	W	—	—	—	—	—	—	—	—	—
Teacher Roster (own)	R	R	R	R	R	R	R	R	R	R	—	—
Teacher Roster (any teacher)	R	R	R	R	—	—	—	—	—	—	—	—
Data Importer	A	A	A	—	—	—	—	—	—	—	—	—
Bell Schedules	A	A	A	—	—	—	—	—	—	cap	—	—
Kiosk Setup	A	A	A	—	—	—	—	—	—	—	—	—
Displays / Signage mgmt	A	A	A	A	—	A	—	—	—	cap	—	—
Branding (logo, colors, EKG)	A	A	A	—	—	—	—	—	—	—	—	—
Parent Portal (invites + sections)	A	A	A	—	—	—	—	—	—	—	—	—
Accommodations library	A	A	A	—	—	—	—	A	—	—	—	—

5. Per-Feature Access Detail

Each feature includes: who can see it, what they can do, the entry point in the UI, and any cross-feature dependencies that the developers must keep wired up.

Hall Pass system

Where: App.tsx !' activeSection 'hallPasses'; routes/hallPasses.ts; routes/hallPassQueue.ts

Who: Any staff with capHallPasses (default on). School-wide log requires capHallPassesViewAll. Mgmt requires Core Team.

Can do: Issue / end passes; tardy returns; student polarity pairs; daily limits; queue; YTD + research reports for Admin / Dean / ESE.

Dependencies: Bell Schedules — queue auto-resets on period change; falls back to 45-minute idle buckets if no default schedule. Signage pulls active passes when showActiveHallPasses is on. Parent Portal shows recent passes when section enabled.

PBIS Hub & Stores

Where: activeSection 'pbis' / 'pbisHub' / 'pbisLists' / 'schoolStore' / 'schoolStoreManage'

Who: Award: any staff (capPbisAward). Hub: Core Team or PBIS Coordinator. Store mgmt: Core Team / PBIS coord. Classroom store: each teacher edits own.

Can do: Award single + bulk; reasons & milestones; eligibility lists; school-wide store catalog; classroom store; house standings.

Dependencies: Watchlist alerts read PBIS counts. Parent Portal `recognition` section pulls from PBIS. Heartbeat & Houses signage stream PBIS events live (names masked to first + last initial).

MTSS Intervention Plans

Where: activeSection 'mtssPlans' / 'interventionReports'; routes/mtssPlans.ts

Who: Core Team only.

Can do: Create T2/T3 plans, weekly progress monitoring, strategy categories, completion reports; tier-aware launcher with bell-notification system.

Dependencies: Watchlist 'Schedule Check-in' creates a Tier 2 cico plan if absent and inserts today's tier2_intervention_entries row. Parent Portal `mtss` section reads active plans (when admin opts in).

Safety Plans

Where: activeSection 'safetyPlans'; routes/safetyPlans.ts

Who: Edit: Core Team or Guidance Counselor. View: any staff member.

Can do: Per-student behavioral / physical safety checklists; library items; audit log; integrated into student rosters and profiles.

Dependencies: Surfaced as a flag on Teacher Roster and Student Profile. Audit log retained per change.

Watchlist Hub / Network / Case Detail

Where: activeSection 'watchlistHub' / 'watchlistNetwork' / 'watchlistCase'; routes/watchlist.ts

Who: Core Team only (server enforces requireSchool plus client nav predicate).

Can do: Hub: alerts (5 rules), summary, orbit. Network: school-wide relationship graph with clickable case halos. Case Detail: notes timeline, players list, link/log incidents, request witness statements.

Dependencies: POST /alerts/check-in writes to MTSS (T2 cico plan) AND tier2_intervention_entries AND admin_notifications for BS + MTSS coord. Witness statements email staff via Resend (RESEND_FROM_ADDRESS, EMAIL_REMINDERS_ENABLED).

Insights Dashboards (Engagement, Behavior, Academics, SEB-SEL, Equity, Early Warning)

Where: activeSection ends with 'Dashboard'; insights/* components

Who: Core Team (canAccessMtssHub).

Can do: Aggregate data, trends, top-N lists; grade & window filters; demographic disaggregation; drill-down to Student Profile.

Dependencies: Reads PBIS, hall passes, tardies, FAST, accommodations, intervention logs. Drill-through respects student-level scoping.

ISS Dashboard & Reporting

Where: activeSection 'issDashboard' / 'issReporting'; routes/issRoster.ts; routes/issAttendance.ts

Who: ISS Teacher (default) or anyone with capIssDashboard or Admin.

Can do: Run live ISS room (per-period presence), daily attendance sheet, rollover absent students to next school day.

Dependencies: Admin Hub feed surfaces recent ISS assignments. Future work: edit / trim / delete with audit trail (see replit.md).

Teacher Roster

Where: activeSection 'teacherRoster'; routes/teacherRoster.ts

Who: Each teacher sees own; Core Team can view any teacher.

Can do: FAST scores, ESE/504/ELL flags, safety plan indicators.

Dependencies: Aggregates Safety Plans, accommodations, FAST academics — must stay live with importer.

Data Importer

Where: activeSection 'data-imports'; routes/dataImports.ts

Who: Admin / SuperUser / District Admin (canManageSettings).

Can do: CSV uploads with template mapping; preview, commit, rollback; assessments / rosters / behavior.

Dependencies: Feeds students, rosters, FAST, behavior — every dashboard depends on it.

Display Management & Signage

Where: activeSection 'displays'; routes/displays.ts; signage pages

Who: Mgmt: Core Team or Dean or capManageDisplays. Viewing: public via signed URLs.

Can do: Per-school playlists (image, video, audio, PDF, url); scheduling overrides; toggles for showActiveHallPasses, showHeartbeat, showPbisHousePage.

Dependencies: Heartbeat signage streams pulse events live. Houses signage reads PBIS standings. Active hall pass display reads hall pass system. Names masked (first + last initial) on public displays.

Parent Portal

Where: artifacts/client/src/parent/*; routes/parentSnapshot.ts; routes/parentInvites.ts

Who: Parents linked to a student via parent_students. Admin manages invites.

Can do: Snapshot dashboard (PBIS, hall passes, tardies, accommodations, staff notes), child switcher, PDF export, per-section visibility prefs.

Dependencies: Sections toggleable globally by admin and per-parent: recognition, hallPasses, attendance, accommodations, staffNotes, fastScores, interventions, mtss. Email invites use Resend.

Accommodations

Where: routes/accommodationsAdmin.ts; routes/accommodationLogs.ts

Who: Library mgmt: ESE Coordinator or Admin. Logging: any staff.

Can do: Define IEP/504 accommodations; teachers log when provided; appears in Parent Portal.

Dependencies: Surfaced on Student Profile, Teacher Roster, Parent Portal `accommodations` section.

6. API Surface (route !' guard)

Inventory of every endpoint and the guard that protects it, grouped by feature. Use this when wiring new clients or auditing.

Watchlist & Cases

Method	Path	Guard	Purpose
GET	/watchlist/summary	requireSchool + Core	Hub stats
GET	/watchlist/alerts	requireSchool + Core	5-rule alerts
POST	/watchlist/alerts/dismiss	requireSchool + Core	Snooze/dismiss
POST	/watchlist/alerts/check-in	requireSchool + Core	Cross-write to MTSS + BS
GET	/watchlist/orbit	requireSchool + Core	Bubble-chart
GET	/watchlist/network	requireSchool + Core	Graph nodes/edges
GET / POST	/watchlist/cases	requireSchool + Core	List / create
GET / PATCH	/watchlist/cases/:id	requireSchool + Core	Detail / update
POST	/watchlist/cases/:id/notes	requireSchool + Core	Add note
POST	/watchlist/cases/:id/players	requireSchool + Core	Add players
GET / POST	/watchlist/interactions	requireSchool + Core	List / log
POST	/watchlist/interactions/:id/witness-statements/request	requireSchool + Core	Request statement
POST	/watchlist/statements/:id/remind	requireSchool	Email reminder
POST	/watchlist/statements/:id/submit	requireSchool	Submit content

Hall Pass / Tardies / Kiosk

Method	Path	Guard	Purpose
GET / POST	/hall-passes	requireSchool	List / issue
PATCH	/hall-passes/:id/end	requireSchool	End pass
GET	/hall-pass-queue	requireStaff	Wait queue
POST	/kiosk/queue/:token/add	kiosk token	Kiosk add
POST	/kiosk/viewer-token	requireStaff	QR display token
GET / POST	/tardies	requireSchool	Tardy log

PBIS / Stores

Method	Path	Guard	Purpose
GET / POST	/pbis	requireSchool	Award / list
POST	/pbis/bulk	requireSchool + capPbisManage	Bulk awards
GET	/pbis-goals	requireStaff	Goals
GET / POST	/school-store	requireSchool (POST: Core/PBIS)	Catalog
GET	/classroom-store	requireSchool	Per-teacher rewards

MTSS / Safety / Interventions

Method	Path	Guard	Purpose
POST	/mtss-plans	requireSchool + Core	Create plan
GET	/mtss-plans/probe/:studentId	requireSchool + Core	Progress probe
GET	/mtss-reports/summary	requireSchool + Core	Effectiveness
GET / POST	/safety-plans/library	requireSchool (POST: Core/GC)	Library
GET	/safety-plans/student/:id	requireSchool	Per-student

ISS

Method	Path	Guard	Purpose
GET / POST	/iss-roster	requireRosterMW	Today's roster
GET	/iss-attendance	requireAttendanceMW	Attendance sheet
POST	/iss-attendance/rollover	requireAttendanceMW	Rollover absent
PUT	/iss-attendance/:id	requireAttendanceMW	Update presence

Displays / Signage

Method	Path	Guard	Purpose
GET	/displays/playlists	requireSchool	Manage playlists
GET	/displays/public/playlists/:id	public	Render on TV
GET	/displays/public/passes/:schoolId	public	Active passes

Method	Path	Guard	Purpose
POST	/displays/playlists/:id/overrides	requireSchool + canManageDisplays	Schedule override

Parent Portal

Method	Path	Guard	Purpose
GET	/parent/snapshot	parent token	Live snapshot
GET	/parent/snapshot.pdf	parent token	PDF export
POST	/parent-auth/login	public	Email + password
GET	/admin/parent-invites	requireAdmin	Invite list
POST	/admin/parent-invites/send	requireAdmin	Bulk send

Admin / Importer / Storage

Method	Path	Guard	Purpose
GET	/admin/staff	requireAdminOrSuper	Staff list
PATCH	/admin/staff/:id	requireAdminOrSuper	Update roles
POST	/custom-roles	requireSuperUser	Custom role
GET	/data-imports/jobs	requireImporter	Import history
POST	/data-imports/students	requireImporter	Trigger import
POST	/storage/uploads/request-url	signed-in staff	Presigned upload
GET	/storage/objects/*	requireSchool + ACL	Tenant-scoped fetch

Method	Path	Guard	Purpose
GET	/storage/public-objects/*	public	Branding etc.

Accommodations

Method	Path	Guard	Purpose
GET / POST	/accommodation-logs	requireStaff	Log + history
GET / POST	/school-accommodations	requireSchool (POST: ESE/Admin)	Library

7. Cross-Feature Dependency Map

Where one feature writes into or reads from another. Developers must keep these wired when refactoring.

Source feature	Action	Target feature(s)	Why
Watchlist Hub	POST /alerts/check-in	MTSS Plans + Tier 2 entries + Admin Notifications	Turns alert into a tracked CICO plan and notifies BS + MTSS coord.
Watchlist Cases	Witness statement request	Email (Resend) + statement inbox for staff	Collect statements from any staff who witnessed an event.
Hall Pass Queue	Bell schedule period change	Hall Pass Queue (auto-reset)	Each period gets a clean line; falls back to 45-min buckets without a default schedule.
Data Importer	Roster / FAST / behavior commit	Teacher Roster, Insights dashboards, Watchlist, Parent Portal	All downstream views read these tables; rollback supported.
PBIS awards	Insert pbis_entry	PBIS Hub, Houses signage, Heartbeat signage, Parent Portal recognition	Live propagation of recognition events.
Hall passes	Active pass / end pass	Active Hall Pass display, Parent Portal hallPasses, Insights Behavior	Operational visibility + parent transparency + analytics.
Tardies	Tardy logged	Parent Portal attendance, Insights Engagement, Watchlist alert rules	Tardy spikes trigger Watchlist alerts.

Source feature	Action	Target feature(s)	Why
Safety Plans	Plan added/edited	Teacher Roster (flag), Student Profile, Audit log	Teachers see indicator; auditors see history.
Accommodations log	Provided event	Parent Portal accommodations, Student Profile	Compliance and parent visibility.
Pullout request	Submit request	Verify Pullouts queue !' Behavior Review	Triage chain for behavioral intervention.
ISS roster	Daily entry	Admin Hub feed, Insights Behavior, Parent Portal attendance	Discipline visibility across surfaces.
Displays mgmt	Toggle showHeartbeat / showActiveHallPasses / showPbisHousePage	Public signage URLs	Per-playlist enablement of cross-feature widgets.
Parent invite	Admin sends invite	Parent Portal account creation via Resend email	Onboarding handshake.
Staff Preview	Admin starts session	All scoped routes (impersonation context)	QA and support — every read/write reflects the previewed role.
School plan (SU)	Assign tier	Feature flags across all artifacts	Drives which features the school sees.

Notes for the dev team

- Every server route MUST go through requireSchool unless explicitly public. Multi-tenant isolation depends on req.schoolId.

- studentId and displayName are NOT globally unique — always scope queries by schoolId. Composite indexes are (school_id, column).
- More-specific routes must be registered before broader dynamic routes (avoid path shadowing).
- Cron jobs are gated on NODE_ENV plus EMAIL_REMINDERS_ENABLED and RESEND_FROM_ADDRESS. Verify both before relying on emails.
- Drizzle-kit db push can block on rename prompts — additive schema changes use direct ALTER TABLE in seed.ts.
- Names on public signage are masked to `First L.` to keep privacy on hallway TVs.

