

Migration Report — 2026-07-06 → present

Audience: developer migrating these changes to the **live/production** environment. Scope: every schema, DB, and server-logic change since 2026-07-06. Purely client-side (UI) changes are listed for completeness but need no DB work.

Source commits (oldest → newest):

Commit	Summary	DB change?
d6ee390b	Allow teachers to send Family Messages to their own students	YES (1 new column)
5bc60d83	Sidebar navigation restructure (Family / Family (Admin) split, Pullout Notifications → Student Support)	No
f495d427	Behavior Specialists auto-included in pullout notifications	No

1. DATABASE CHANGES (action required)

1.1 New column — `school_settings.teacher_family_messaging_enabled`

- **Commit:** d6ee390b
- **Table:** `school_settings`
- **Column:** `teacher_family_messaging_enabled` `BOOLEAN NOT NULL DEFAULT FALSE`
- **Why:** Gates whether non-Core-Team classroom teachers may send Family Messages to families on their own roster. **OFF by default** — an admin must opt in per school. Existing behavior is unchanged until a school flips it on.

DDL to run against production:

```
ALTER TABLE school_settings
  ADD COLUMN IF NOT EXISTS teacher_family_messaging_enabled BOOLEAN NOT NULL DEFAULT FALSE
```

Auto-migration note (important): this project already applies additive `school_settings` flags at server boot. On startup the API server runs `ensureSchoolSettingsFeatureFlagsSchema()` (in `artifacts/api-server/src/seed.ts`), which executes the exact `ALTER TABLE ... ADD COLUMN IF NOT EXISTS ...` above. So if you deploy the new server build and let it boot against the live DB, the column is created automatically. The manual DDL is provided only if you prefer to run

migrations explicitly ahead of the deploy. The statement is idempotent (`IF NOT EXISTS`) and safe to run either way.

- **Drizzle source of truth:** `lib/db/src/schema/schoolSettings.ts` (`teacherFamilyMessagingEnabled` field).
- **No data backfill required** — the `DEFAULT FALSE` preserves current behavior for every existing school.
- **No indexes, constraints, enums, or FKs** were added or altered.

This is the **only** schema/DB change in the entire date range.

2. SERVER LOGIC CHANGES (deploy the API build)

These ship with the server bundle — no DB step, but they must be deployed.

2.1 Teacher-scoped Family Messages (commit d6ee390b)

- `artifacts/api-server/src/routes/parentMessages.ts` — teachers whose school has `teacher_family_messaging_enabled = true` may compose messages to families of **one of their own class periods** or **hand-picked students from their own roster**. The server **re-enforces** own-periods / own-students scope on every send; the flag only decides whether a teacher may send. Core Team broadcast behavior is unchanged and does not depend on the flag.
- `artifacts/api-server/src/routes/schoolSettings.ts` — GET/PUT now read/write the new flag (admin-gated).
- `artifacts/api-server/src/seed.ts` — registers the new column in the boot migration (see §1.1).

2.2 Behavior Specialists in pullout notifications (commit f495d427)

- `artifacts/api-server/src/lib/pulloutEmail.ts` — Behavior Specialists (`staff.is_behavior_specialist = true`) are now included in the **default** pullout dispatch recipient set (email + SMS), alongside Admins, Deans, MTSS Coordinators, and ISS Teachers. Recipients remain de-duped and school-scoped.
 - `artifacts/api-server/src/routes/pullouts.ts` — the notify-config UI now labels Behavior Specialists as auto-recipients so the displayed list matches who actually receives.
 - **No DB change** — relies on the existing `staff.is_behavior_specialist` column.
-

3. CLIENT-ONLY CHANGES (no DB / no server; deploy the web build)

3.1 Navigation restructure (commit 5bc60d83)

- `artifacts/client/src/App.tsx` — split the "Family" sidebar group into **Family** (Student, Family Messages) and **Family (Admin)** (PulseDNA Studio, Call Campaign, Data Chats, Parent Access, Parent Notifications); moved **Pullout Notifications** into the **Student Support** group.

3.2 Family Messages UI (commit d6ee390b, client portion)

- `artifacts/client/src/App.tsx` and `artifacts/client/src/components/FamilyMessagesHub.tsx` — teacher composer UI + the new admin toggle wiring for `teacherFamilyMessagingEnabled`. (UI gating is convenience only; §2.1 server checks are authoritative.)

4. Migration checklist for production

1. **Schema:** run the DDL in §1.1 (or rely on the boot auto-migration — the API server applies it on startup). Idempotent; safe to run first.
2. **Deploy API server** build (includes §1 + §2).
3. **Deploy web client** build (includes §3).
4. **Verify:**
5. `school_settings.teacher_family_messaging_enabled` exists and defaults to `FALSE` for all schools.
6. A Behavior-Specialist-only staffer appears as an auto-recipient on the Pullout Notifications config page and receives a dispatch on the next pullout.
7. No behavior change for teacher messaging until an admin opts a school in.
8. **Rollback:** all changes are additive. The new column can remain in place if you roll back code (it is simply unused). No destructive migration to undo.

Environment note: this workspace and the live host use separate databases. Confirm the DDL / boot migration ran against the **production** DB specifically — verifying it in the workspace does not confirm it in prod.