

PulseEDU — Developer Migration Handoff

Everything required to bring the LIVE site up to current dev — for a non-Replit deployment.

Last in-sync commit

5aaa9a80 · 2026-06-22

Code changed

113 files · +30,142 / -2,376

Window

2026-06-22 → 2026-06-28

Target (current dev HEAD)

fbd6847b · 2026-06-28

New runtime dependencies

None (no lockfile change)

Report date

2026-06-29

Companion file: pulseedu-dev-to-live-2026-06-29.patch

⚠ **The one thing that breaks live if skipped.** Six schema changes have **no automatic boot migration** (Section 2). They reach dev via `db push` but will be **missing on live** unless you apply them. Apply Section 2 against the live database **before** the app serves traffic. Everything else applies automatically when your api-server boots.

1 · What to move (code)

All application changes live in three workspace packages. The companion **patch file** contains the complete diff and applies cleanly on top of `5aaa9a80`:

```
# from the repo root, on a checkout at commit 5aaa9a80
git apply exports/pulseedu-dev-to-live-2026-06-29.patch
# or, if not a git tree:
patch -p1 < pulseedu-dev-to-live-2026-06-29.patch
```

Package	What changed	Notes
lib/db	7 new schema files + 9 modified	Source of truth for all tables/columns.
artifacts/api-server	13 new files (routes + lib) + ~28 modified	Express backend. Boot runs the auto-migrations.
artifacts/client	17 new components + ~24 modified	Staff app + parent + student portals (single Vite bundle).

Excluded from the patch (not part of the live staff app): the demo/marketing slide artifacts (`pulseedu-district-demo` , `-features` , `-pitch`), `attached_assets/` , `screenshots`, and `docs/` . Include them only if you also host the demo decks.

Key new modules this window

Feature	New files (representative)
School Store redemption engine + wallet	<code>lib/storeRedemptions.ts</code> , <code>routes/schoolStore.ts</code> , <code>routes/parentStore.ts</code> , <code>SchoolStoreFulfillmentView.tsx</code> , <code>StoreFulfillmentBell.tsx</code> , <code>parent/StoreTab.tsx</code> , <code>schema/schoolStoreRedemptions.ts</code>
Student ClassLink portal + self-redeem	<code>routes/studentAuth.ts</code> , <code>routes/studentPortal.ts</code> , <code>student/*</code> (App, Login, Dashboard, StoreTab, api)
Parent Notifications panel	<code>lib/parentNotify.ts</code> , <code>ParentNotificationsPanel.tsx</code>
Eligibility Hub	<code>lib/eligibility.ts</code> , <code>lib/eligibilityNotify.ts</code> , <code>routes/eligibility.ts</code> , <code>EligibilityHub.tsx</code>
Communication Log + Call Initiative	<code>routes/communications.ts</code> , <code>CallInitiativePanel.tsx</code> , <code>ContactRatePage.tsx</code> , <code>ContactFixesPage.tsx</code> , <code>schema/communicationLogs/communicationTypes/badNumberFlags/callInitiatives.ts</code>
PBIS color-fork + point import	<code>InterventionTypesAdmin.tsx</code> , <code>PulloutReasonsAdmin.tsx</code> , <code>schema/pbisPointMigrations.ts</code>
Insights drill-downs / FAST pills	<code>FastScorePill.tsx</code> , <code>BandStudentsDrawer.tsx</code> (mod)

2 · Database — manual steps (NO auto-migration)

Apply against the **live** database. Easiest is one command (derives exact DDL from the schema):

```
pnpm --filter @workspace/db run push # answer "create" to any rename prompt
```

...or run this idempotent SQL (safe to re-run):

```
-- 2.1 Confidential Secretary role – read by login/role code (#1 breaker)
ALTER TABLE staff
  ADD COLUMN IF NOT EXISTS is_confidential_secretary BOOLEAN NOT NULL DEFAULT FALSE;

-- 2.2 School Store redemption engine – NEW TABLE
CREATE TABLE IF NOT EXISTS school_store_redemptions (
  id SERIAL PRIMARY KEY,
  school_id INTEGER NOT NULL,
  item_id INTEGER NOT NULL,
  student_id TEXT NOT NULL,
  item_name TEXT NOT NULL,
  points_spent INTEGER NOT NULL,
  status TEXT NOT NULL DEFAULT 'pending',
  requested_by_type TEXT NOT NULL,
  requested_by_id INTEGER,
  approved_by_staff_id INTEGER, approved_at TEXT,
  fulfilled_by_staff_id INTEGER, fulfilled_at TEXT,
  deliver_teacher_name TEXT, deliver_period TEXT,
  cancelled_by_staff_id INTEGER, cancelled_at TEXT, cancel_reason TEXT,
  stock_held BOOLEAN NOT NULL DEFAULT FALSE,
  points_refunded BOOLEAN NOT NULL DEFAULT FALSE,
  created_at TEXT NOT NULL, updated_at TEXT
);
CREATE INDEX IF NOT EXISTS school_store_redemptions_school_status_idx ON school_store_redemptions (school_id, status);
CREATE INDEX IF NOT EXISTS school_store_redemptions_school_student_idx ON school_store_redemptions (school_id, student_id);
CREATE INDEX IF NOT EXISTS school_store_redemptions_school_item_idx ON school_store_redemptions (school_id, item_id);

-- 2.3 School Store item inventory/approval columns
ALTER TABLE school_store_items ADD COLUMN IF NOT EXISTS in_stock BOOLEAN NOT NULL DEFAULT TRUE;
ALTER TABLE school_store_items ADD COLUMN IF NOT EXISTS quantity_on_hand INTEGER;
ALTER TABLE school_store_items ADD COLUMN IF NOT EXISTS per_student_limit INTEGER;
ALTER TABLE school_store_items ADD COLUMN IF NOT EXISTS requires_approval BOOLEAN NOT NULL DEFAULT FALSE;

-- 2.4 School Store inventory mode ('simple' | 'quantity')
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS school_store_inventory_mode TEXT NOT NULL DEFAULT 'simple';

-- 2.5 Parent Notifications toggles (default TRUE = today's behavior preserved)
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS notify_parent_eligibility BOOLEAN NOT NULL DEFAULT TRUE;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS notify_parent_pbis_milestone BOOLEAN NOT NULL DEFAULT TRUE;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS notify_parent_tardy BOOLEAN NOT NULL DEFAULT TRUE;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS notify_parent_event_tickets BOOLEAN NOT NULL DEFAULT TRUE;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS notify_parent_esign BOOLEAN NOT NULL DEFAULT TRUE;
```

3 · Database — applied automatically on api-server boot

These run from the application code itself (idempotent `ensure*` migrations in `seed.ts` / `index.ts`), so they apply automatically when **your** api-server starts — Replit is not involved. No action needed; listed for verification.

New tables AUTO	Feature
<code>communication_types</code> , <code>communication_logs</code> , <code>bad_number_flags</code> , <code>call_initiatives</code>	Communication Log + Call Initiative
<code>eligibility_activities</code> , <code>eligibility_activity_members</code> , <code>eligibility_activity_coaches</code> , <code>eligibility_absences</code>	Eligibility Hub
<code>teacher_allowlist_import_batches</code> , <code>teacher_allowlist_zone_rules</code>	Hall-pass bulk destinations
<code>pbis_point_migrations</code>	PBIS point-balance import

app_one_shot_markers	One-shot job ledger (Section 4)
----------------------	---------------------------------

New columns AUTO	On table
cap_manage_contact_info , house_id , department , title , is_athletic_director	staff
sso_external_id , last_portal_login_at	students
behavior_reason	intervention_entries
import_job_id	pbis_entries , pbis_milestone_emails
restroom_area , gender , school_wide_default	locations
staff_id (+ unique index)	teacher_destination_allowlist
intervention_effectiveness_days , iready_apl_cuts , feature_eligibility , plan/feature flags	school_settings

Note the asymmetry: `staff.is_athletic_director` has a boot migration (auto), but `staff.is_confidential_secretary` does *not* (manual — Section 2.1).

4 · One-shot data jobs (auto, run once)

Guarded by `app_one_shot_markers` ; each runs exactly once per environment, then no-ops forever. No action needed: enterprise/licensing fold (re-applies plans to existing schools), room-location seed, demo-email normalization, SuperUser recovery. To re-run one, delete its marker row and reboot.

5 · Environment variables

Because this is off Replit: the Replit-injected vars (`REPLIT_DOMAINS` , `REPLIT_DEV_DOMAIN` , `REPL_IDENTITY` , `REPLIT_CONNECTORS_HOSTNAME`) will be unset. That makes **PUBLIC_APP_URL required** — it is the fallback used to build all external links and QR codes (e-sign, tours, kiosk, student/parent portals). Set it to your live HTTPS domain.

Variable	Required?	Purpose
DATABASE_URL	Yes	Your live Postgres connection string.
SESSION_SECRET	Yes	Session signing.
AUTH_TOKEN_SECRET	Yes	Bearer-token signing (iframe/portal auth).
PUBLIC_APP_URL	Yes (off Replit)	Live domain for all external links/QR codes.
RESEND_API_KEY	Yes (email)	Resend API key — all parent email.
RESEND_FROM_EMAIL	Yes (email)	Verified sender address.
EMAIL_REMINDERS_ENABLED	Yes (email)	Master switch for scheduled email crons.
PRIVATE_OBJECT_DIR , PUBLIC_OBJECT_SEARCH_PATHS , AWS_*	If using uploads	Object storage (item thumbnails, photos, flyers).
NODE_ENV =production, LOG_LEVEL , SCHEDULER_TZ	Recommended	Standard runtime config.
ELIGIBILITY_DIGEST_CRON / _TZ , WEEKLY_HEARTBEAT_CRON / _TZ , other *_CRON / *_TZ	Optional	Have safe defaults; override only to retime.

Security — must NOT be enabled in production: `STUDENT_DEMO_LOGIN` (=1 enables a password-less student login bypass) and `DEMO_MODE` . Leave both unset. Review `ALLOW_CROSS_DISTRICT_SUPERUSER` before enabling.

The `AI_INTEGRATIONS_ANTHROPIC_*` vars point at Replit's AI proxy and will not work off-Replit. Only relevant if you use the AI consistency-check feature; otherwise ignore.

6 • Dependencies, build & run

No runtime dependency or lockfile changes this window. A plain `pnpm install` after pulling is sufficient.

```
pnpm install
pnpm run build          # typecheck + build all packages

# run the API server (boot applies Section 3 auto-migrations)
pnpm --filter @workspace/api-server run start

# the client is a static Vite build – serve artifacts/client/dist behind your proxy;
# API is mounted at /api (path-based routing, same as today)
```

Node 24 · pnpm · PostgreSQL. The client and API are routed by path (`/api` → server, everything else → client bundle), so keep your reverse proxy mapping the same as the current live host.

7 • Deploy order & verification

1. **Back up the live database.**
2. Move code (Section 1 patch) and `pnpm install` + `pnpm run build`.
3. Apply **Section 2** SQL/push against the live DB.
4. Set/confirm env vars (Section 5), especially `PUBLIC_APP_URL`.
5. Start the api-server — confirm boot logs show no migration errors (Section 3/4 run here).
6. Verify:
 - `staff` has `is_confidential_secretary`; `school_store_redemptions` exists; `school_settings` has the 5 `notify_parent_*` cols + `school_store_inventory_mode`.
 - Admin → **Family** → **Parent Notifications** loads and a toggle saves (200).
 - A family/student can open the **School Store** and a redemption creates a row with correct wallet math.
 - Login works for a Confidential-Secretary user.
 - `STUDENT_DEMO_LOGIN` is unset; a test parent email sends.

8 • Rollback

Code rolls back by redeploying the prior build. All schema changes here are **purely additive** (new tables, new nullable/defaulted columns) and backward-compatible — the previous build keeps working against the new schema, so there is **nothing destructive to undo**. You generally do not drop anything on rollback.

Generated 2026-06-29 · Source of truth: `lib/db/src/schema/*.ts` and the companion patch `pulseedu-dev-to-live-2026-06-29.patch`. Full markdown version: `docs/migration-report-2026-06-29.md`.