

PulseEDU Developer's Guide

Pullout Notifications: Extra Recipients + SMS Toggle

Commit: 1543e9f5 | Branch: client-replit-sync-june2026
feat(pullouts): admin-managed extra recipients + SMS toggle for dispatch
8 files changed, 689 insertions(+), 27 deletions(-)

Two no-code-for-admin controls for Request Pullout dispatch notifications: (1) add EXTRA notification recipients - any staff regardless of role (e.g. a reading coach); (2) an SMS on/off toggle for pullout dispatch. Both are managed entirely from the admin UI (no code or DB editing). Below is every file changed, what changed and why, followed by what must be pushed to the live website.

Files Changed

1. Database schema - lib/db/src/schema/schoolSettings.ts

~14 lines added, after notifyParentEsign (around line 198)

Two new columns on school_settings (Drizzle source of truth):

- pulloutSmsEnabled -> boolean("pullout_sms_enabled"), NOT NULL DEFAULT false
- pulloutExtraRecipientStaffIds -> jsonb("pullout_extra_recipient_staff_ids").\$type<number[]>(), NOT NULL DEFAULT []

This does not itself alter the live DB - the boot migration below applies it.

2. Boot migration - artifacts/api-server/src/seed.ts

9 lines added inside ensureAdminHubSchema() (after the tour_sms_scope ALTER, ~line 2090)

```
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  pullout_sms_enabled BOOLEAN NOT NULL DEFAULT FALSE;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  pullout_extra_recipient_staff_ids JSONB NOT NULL DEFAULT '[]'::jsonb;
```

ensureAdminHubSchema() runs at boot (seed.ts:3864). It is idempotent (IF NOT EXISTS), so it self-applies on every api-server start, including off-Replit. This is how the live DB gets the columns - no manual SQL required.

3. Dispatch logic - artifacts/api-server/src/lib/pulloutEmail.ts

~95 lines changed in sendPulloutDispatchEmail()

- New imports: inArray (drizzle), sendSmsBatch (./sms).
- Settings loaded early (moved up): needed for the recipient union and the SMS toggle. The old duplicate settings load lower down was removed.
- Recipient union: recipients are now active staff who hold a dispatch role (Admin / Dean / MTSS Coordinator / ISS Teacher) OR are in pulloutExtraRecipientStaffIds. Emails de-duplicated via a Set.
- FLEID fix (security): the student label no longer interpolates p.studentId (the canonical FLEID). It now uses student.localSisId with a safe "Student" fallback - never the FLEID. Broadening recipients widens who sees the email body, so this came into scope.
- SMS send block (before the success return): only runs when settings.pulloutSmsEnabled. Texts the de-duplicated cell numbers of the active recipients. The SMS body carries NO student name and NO FLEID - recipients open PulseED for details. Best-effort: never fails the dispatch.

4. Admin API - artifacts/api-server/src/routes/pullouts.ts

~137 lines added

- New imports: schoolSettingsTable, or, asc.
- GET /pullouts/notify-config (admin/superuser gated via isPulloutNotifyAdmin): returns smsEnabled, extraRecipientStaffIds, and a staff list (id, displayName, roleLabels, isActive, isAutoRecipient, hasEmail, hasCell, isExtra). Returns active staff OR already-selected extras, so a staffer who later went inactive still

appears and can be removed.

- PUT /pullouts/notify-config (same gate): validates smsEnabled (boolean) and extraRecipientStaffIds (array), school-scopes the ids (drops any id not in req.schoolId), then upserts the row.
- Registered before the dynamic /pullouts/:id routes to avoid shadowing.

5. Client panel - artifacts/client/src/components/PulloutNotificationsPanel.tsx

New file, 423 lines

Mirrors ParentNotificationsPanel: an SMS on/off switch plus a staff picker for extra recipients, with role-based recipients shown read-only ("always notified"). Inactive selected extras render an "Inactive" tag so they can be toggled off. Instant-save on each change.

6. Client mount - artifacts/client/src/App.tsx

~14 lines across 5 spots

- Line ~21: import PulloutNotificationsPanel
- Line ~4007: added "pulloutNotifications" to the family nav group ownership
- Line ~5735: added "pulloutNotifications" to the activeSection union type
- Line ~12009: nav item "Pullout Notifications" under the canManageSettings gate
- Line ~23243: render block, gated on canManageSettings

7-8. Memory files (internal)

.agents/memory/MEMORY.md and .agents/memory/notify-recipient-broadening.md are internal agent notes only. Not needed on live; harmless if included.

What Needs To Be Pushed To Live

Note: the live site (pulseedu.pulsekinetics.us) is a separate host with its own database. "Push to live" means deploy this code to that host.

Step 1 - Deploy the code

Push/merge the commit and deploy these 6 functional files (memory files optional):

- lib/db/src/schema/schoolSettings.ts
- artifacts/api-server/src/seed.ts
- artifacts/api-server/src/lib/pulloutEmail.ts
- artifacts/api-server/src/routes/pullouts.ts
- artifacts/client/src/components/PulloutNotificationsPanel.tsx
- artifacts/client/src/App.tsx

Build steps on the live host: rebuild the api-server bundle (esbuild) and the client bundle (Vite), same as any deploy.

Step 2 - Database (automatic)

No manual SQL. When the live api-server boots, ensureAdminHubSchema() runs the two idempotent ALTER TABLE ... IF NOT EXISTS statements and adds the columns. Confirm your live boot sequence calls the seed/schema bootstrap (it does on this codebase).

If your live host does NOT run ensureAdminHubSchema() at boot, run these once by hand against the live DB:

```
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  pullout_sms_enabled BOOLEAN NOT NULL DEFAULT FALSE;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  pullout_extra_recipient_staff_ids JSONB NOT NULL DEFAULT '[]'::jsonb;
```

Step 3 - Verify on live

- Log in as an admin -> Family -> Pullout Notifications appears.

- Toggle SMS on, add an extra recipient (e.g. reading coach), confirm it saves.
- Submit and dispatch a test pullout -> the extra recipient receives the email; the email shows the local SIS id, never the FLEID.

Rollback

Code: revert commit 1543e9f5. The two DB columns are additive with safe defaults - they can be left in place (harmless) or dropped if you fully revert.

Generated for PulseEDU. Email + extra-recipients work with no environment changes; the SMS path follows your existing live configuration unchanged.