

Complete Manual Go-Live Runbook

All changes: July 5 (evening) through July 7, 2026

PulseEDU · School Operations App

Prepared: July 7, 2026

Method: changes promoted BY HAND (no full publish). This document SUPERSEDES the two earlier partial PDFs (2026-07-07-hall-pass-auto-end.pdf and 2026-07-06-go-live-runbook.pdf).

Commit range: bcde7df3 .. f817cbfa · 22 features across 3 work sessions

At a glance — database footprint

- 3 NEW TABLES: `section_support_staff`, `fast_bq_import_batches`, `app_one_shot_markers`.
- 8 NEW COLUMNS on `school_settings` (1 boolean opt-in flag, 4 Watch List thresholds, 2 year-flip, 1 hall-pass timeout).
- 1 DATA one-shot (L25 start-of-year baseline) + 1 stray-data cleanup — both idempotent at boot.
- No drops, no renames, no destructive migrations. Every column is additive with a safe default.

Impact legend

- [DB] database statement required (Section 3).
- [FLAG] per-school setting must be flipped to actually turn the feature ON (Section 4).
- [OPS] behavioral change external consumers/staff must be told about (Section 5).
- [CODE] source files only; live once deployed.

1. How to use this runbook

You are promoting changes by hand. Work top-down: run all DB statements in Section 3 first, deploy the source files in Section 6, restart the API server (this also runs the idempotent boot one-shots), then flip the flags in Section 4, then complete the operational hand-offs in Section 5, then verify with Section 7.

2. Feature inventory (22 items, by session)

Session A — July 5 evening: roster & insights tooling

Section Support Access (co-teachers) [DB] [CODE]

ESE Coordinator grants a support teacher period-scoped access to another teacher's whole section (see + log accommodations, not edit). New table `section_support_staff`.

Instructional Coverage Report [CODE]

New teacher coverage-monitoring dashboard; subject derived from teacher + content affinity; unified coverage bands.

Teacher selection / search unification [CODE]

Single shared teacher picker; removed a duplicate selector; search box matches other filters.

Print & download class rosters [CODE]

Server-rendered roster PDF (new lib `rosterPrintPdf.ts`).

Privacy gate back button [CODE]

Adds a back button to the privacy gate.

Sticky headers on data tables [CODE]

Sticky `<th>` on all data tables + insights trajectory drawer (later label-visibility fix in Session C).

Data-import selected-option visibility [CODE]

Improves visibility of selected options in the importer.

Bottom-quartile (L25) flagging + import consolidation [DB] [CODE]

New full-replace L25 importer with rollback ledger table `fast_bq_import_batches`.

Session B — July 6: family comms & navigation

Teacher Family Messaging [\[DB\]](#) [\[FLAG\]](#) [\[CODE\]](#)

Teachers may message families of their OWN period / OWN roster students. New column `teacher_family_messaging_enabled`, OFF by default.

Family admin navigation split [\[CODE\]](#)

Family-related admin tools moved into a new sidebar section.

Behavior specialists on pullout emails [\[CODE\]](#) [\[OPS\]](#)

Behavior Specialists are now default recipients of pullout-notification emails.

Close nav groups (incl. Special Programs) [\[CODE\]](#)

Fixes the sidebar group that would only open, never close, when it held the active page.

Data export uses local SIS ID, not FLEID [\[CODE\]](#) [\[OPS\]](#)

Export payloads + UI emit `local_sis_id` instead of `student_id` (FLEID).

Session C — July 7 overnight !' now: FAST history, watch list, year rollover, hall pass**Authenticated file download** [\[CODE\]](#)

Download endpoints now require auth + proper error handling.

Sticky header label visibility restore [\[CODE\]](#)

Fixes header labels hidden by the new sticky headers.

Historical FAST data view [\[CODE\]](#)

New `FastHistoryModal` to view prior-year FAST performance.

Stray school data cleanup [\[OPS\]](#)

One-off cleanup of stray demo/school rows.

Watch List "needs attention" gate [\[DB\]](#) [\[CODE\]](#)

Configurable thresholds: 4 new `school_settings` columns (`absence/behavior/ISS/tardy`).

L25 auto-baseline + current-year FAST fixes [\[DB\]](#) [\[CODE\]](#)

Start-of-year bottom-quartile baseline one-shot (uses `app_one_shot_markers`); current-year display + flagging fixes.

School-year rollover (school-controlled dates) [\[DB\]](#) [\[CODE\]](#)

2 new columns (`school_year_flip_date/active`); controls always visible to admins.

FAST History Drawer default view = Level [\[CODE\]](#)

Drawer defaults to Level instead of scale score.

Hall pass auto-end + admin edit fix [\[DB\]](#) [\[CODE\]](#) [\[OPS\]](#)

Auto-ends forgotten passes (new column `hall_pass_auto_end_minutes`, default 20); admins can now edit a pass (PATCH 403 fixed). New status value `"auto_ended"`.

3. Database changes [\[DB\]](#) — run first

All statements are idempotent (IF NOT EXISTS). Run them once per target database. The API server will also run equivalent statements on boot, but applying them by hand first is safe.

3.1 New tables

[section_support_staff](#)

```

CREATE TABLE IF NOT EXISTS section_support_staff (
  id                serial PRIMARY KEY,
  school_id         integer NOT NULL,
  teacher_staff_id  integer NOT NULL,
  period            integer NOT NULL,
  support_staff_id  integer NOT NULL,
  assigned_by_staff_id integer,
  assigned_by_name   text,
  assigned_at        timestampz NOT NULL DEFAULT now(),
  notes             text
);
CREATE UNIQUE INDEX IF NOT EXISTS section_support_staff_unique
  ON section_support_staff (school_id, teacher_staff_id, period, support_staff_id);
CREATE INDEX IF NOT EXISTS section_support_staff_support_idx
  ON section_support_staff (school_id, support_staff_id);
CREATE INDEX IF NOT EXISTS section_support_staff_section_idx
  ON section_support_staff (school_id, teacher_staff_id, period);

```

Keyed on the STABLE business identity (school, teacher_staff_id, period) — NOT class_sections.id, which is wiped on every roster re-import.

fast_bq_import_batches

```

CREATE TABLE IF NOT EXISTS fast_bq_import_batches (
  id                serial PRIMARY KEY,
  import_job_id     integer NOT NULL,
  school_id         integer NOT NULL,
  prior_json        jsonb NOT NULL,
  created_at        timestampz NOT NULL DEFAULT now()
);
CREATE INDEX IF NOT EXISTS fast_bq_import_batches_job_idx
  ON fast_bq_import_batches (import_job_id);
CREATE INDEX IF NOT EXISTS fast_bq_import_batches_school_idx
  ON fast_bq_import_batches (school_id);

```

Rollback ledger for the full-replace L25 importer. prior_json snapshots the pre-import bottom-quartile set per subject.

app_one_shot_markers

```

CREATE TABLE IF NOT EXISTS app_one_shot_markers (
  name    text PRIMARY KEY,
  ran_at  timestampz NOT NULL DEFAULT now()
);

```

Infra table: lets idempotent boot one-shots (e.g. the L25 start-of-year baseline) run exactly once per database.

3.2 New columns on school_settings

```

ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  teacher_family_messaging_enabled BOOLEAN NOT NULL DEFAULT FALSE;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  watchlist_absence_threshold INTEGER NOT NULL DEFAULT 10;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  watchlist_behavior_threshold INTEGER NOT NULL DEFAULT 3;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  watchlist_iss_threshold INTEGER NOT NULL DEFAULT 1;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  watchlist_tardy_threshold INTEGER NOT NULL DEFAULT 5;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  school_year_flip_date TEXT;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  school_year_flip_active TEXT;
ALTER TABLE school_settings ADD COLUMN IF NOT EXISTS
  hall_pass_auto_end_minutes INTEGER NOT NULL DEFAULT 20;

```

The Watch List thresholds and hall-pass timeout ship safe defaults, so those features work immediately with no flag flip. Only `teacher_family_messaging_enabled` is an opt-in (default FALSE) — see Section 4.

3.3 Data one-shots (run automatically on API-server boot)

- L25 start-of-year baseline — seeds prior-year bottom-quartile flags; guarded by `app_one_shot_markers` so it runs once per DB. Just restart the API server against the target DB; do NOT hand-write this data SQL.
- Stray school-data cleanup — one-off tidy of demo rows; also idempotent at boot.

3.4 Full rollback (only to fully revert everything)

```

DROP TABLE IF EXISTS section_support_staff;
DROP TABLE IF EXISTS fast_bq_import_batches;
-- keep app_one_shot_markers (harmless infra table);
-- dropping it would let one-shots re-run.
ALTER TABLE school_settings
  DROP COLUMN IF EXISTS teacher_family_messaging_enabled,
  DROP COLUMN IF EXISTS watchlist_absence_threshold,
  DROP COLUMN IF EXISTS watchlist_behavior_threshold,
  DROP COLUMN IF EXISTS watchlist_iss_threshold,
  DROP COLUMN IF EXISTS watchlist_tardy_threshold,
  DROP COLUMN IF EXISTS school_year_flip_date,
  DROP COLUMN IF EXISTS school_year_flip_active,
  DROP COLUMN IF EXISTS hall_pass_auto_end_minutes;

```

4. Feature flags to flip [FLAG]

4.1 Teacher Family Messaging (OFF by default)

Stays OFF until an admin opts in per school. Flip in School Settings -> Family, or by hand:

```

UPDATE school_settings SET teacher_family_messaging_enabled = TRUE
WHERE school_id = :school_id;

```

Prerequisite gates (must also be ON for teachers to send):

- `super_feature_family_comm` = TRUE (district master, default TRUE).
- `feature_family_comm` = TRUE (school-level Family Comm switch).
- `teacher_family_messaging_enabled` = TRUE (this new opt-in, default FALSE).

Scope is always re-enforced server-side (own periods / own roster only). Copy App.tsx whole — the flag is wired in 4 mapper spots or the toggle silently reverts after save.

4.2 Optional tuning (safe defaults already applied)

- Watch List thresholds (absence 10 / behavior 3 / ISS 1 / tardy 5) — adjust per school if desired.
- hall_pass_auto_end_minutes (default 20) — adjust per school if desired.
- School-year flip date/active — set when you want a school to roll to the next year; blank = no scheduled flip.

5. Operational hand-offs [OPS]

- Data export now emits local SIS ID instead of FLEID. Tell any downstream consumer/spreadsheet/SIS import that keyed on the FLEID column to switch BEFORE the next export is shared.
- Behavior Specialists now receive pullout-notification emails by default. Confirm the right staff hold that role; warn any who should not suddenly receive them.
- Hall passes gain a new status value "auto_ended". Any report that filters/groups pass status must treat it as a terminal (closed) state, like "ended".
- Admins can now edit an existing hall pass (the PATCH endpoint 403 was fixed) — the fix that let admins correct a pass that ran too long.

6. Source files to deploy

Every non-asset, non-doc file changed in the window. Deploy all of them; the DB/flag steps above cover the rest.

New files (added)

```
lib/db/src/schema/sectionSupportStaff.ts
lib/db/src/schema/fastBqImportBatches.ts
artifacts/api-server/src/lib/hallPassLifecycle.ts
artifacts/api-server/src/lib/rosterPrintPdf.ts
artifacts/api-server/src/lib/schoolYearFlip.ts
artifacts/api-server/src/routes/coverageReport.ts
artifacts/client/src/components/CoverageReportDashboard.tsx
artifacts/client/src/components/FastHistoryModal.tsx
artifacts/client/public/samples/pulseedu-bq-l25-sample.csv
```

Modified — schema & server

```
lib/db/src/schema/index.ts      lib/db/src/schema/schoolSettings.ts
artifacts/api-server/src/seed.ts artifacts/api-server/src/index.ts
routes/: schoolSettings, parentMessages, pullouts, dataImports, hallPasses,
  hallPassQueue, kiosk, insights, watchlist, teacherRoster, studentLookup,
  schedule, schoolGrade, coverageReport, fastBenchmarks, fastCoverage,
  intensiveGroups, mtssPlans, accommodationLogs, accommodationsAdmin,
  adminReseed, algebraPlacement, benchmarkDeliveries, reteachLog,
  pulseBrainLabDelivery, index
lib/: fastHistory, insightsFilters, onboardingSteps, pulloutEmail,
  schoolYear, scope
```

Modified — client

```
App.tsx  index.css
components/: TeacherRosterPage, InsightsHub, InsightsWatchlist,
  InstructionalCoverageDashboard, BandStudentsDrawer, DataChats,
  DataExportPanel, DataImports, FamilyMessagesHub, MtssPlansAdmin,
  PbisPointsHub, PrivacyGate, SafetyPlansAdminPage, SettingsHub,
  SchoolStoreFulfillmentView, StaffDirectoryPage, TicketingAdminPage,
  TourAdminPage
```

7. Order of operations & verification

1. Back up the target database.
2. Run all of Section 3.1 (tables) and 3.2 (columns).
3. Deploy all Section 6 files; restart the API server (runs boot one-shots: L25 baseline + cleanup).
4. Deploy the client build.
5. Flip teacher_family_messaging_enabled for pilot school(s) (Section 4.1); tune optional thresholds if desired.
6. Complete the Section 5 operational hand-offs.
7. Run the verification below.

Verification queries

```
SELECT to_regclass('section_support_staff'),
       to_regclass('fast_bq_import_batches'),
       to_regclass('app_one_shot_markers');
-- all three should be non-null

SELECT column_name FROM information_schema.columns
WHERE table_name='school_settings' AND column_name IN (
  'teacher_family_messaging_enabled', 'watchlist_absence_threshold',
  'watchlist_behavior_threshold', 'watchlist_iss_threshold',
  'watchlist_tardy_threshold', 'school_year_flip_date',
  'school_year_flip_active', 'hall_pass_auto_end_minutes');
-- expect 8 rows
```

Smoke tests

- Toggle teacher family messaging, save, reload — it stays ON (proves all 4 App.tsx mapper spots deployed).
- ESE Coordinator can grant Support Access; the support teacher then sees that section's students.
- Sticky headers stay visible (with labels) when scrolling a long roster.
- Special Programs sidebar group now opens AND closes.
- An admin can edit an existing (over-long) hall pass; a forgotten active pass auto-ends after the configured minutes.
- Data export shows local SIS ID; pullout email reaches Behavior Specialists.

Complete manual go-live runbook for all database, schema, server, client, flag, and operational changes from 2026-07-05 evening through 2026-07-07. Supersedes the two earlier partial migration PDFs.