

Manual Go-Live Runbook

All changes shipped on July 6, 2026

PulseEDU · School Operations App

Prepared: July 7, 2026

Method: changes are being promoted BY HAND (no full publish). Follow every step in order.

Commit range: d6ee390b~1 .. f1876f22 (8 functional commits)

0. How to use this runbook

Because you are moving changes by hand rather than publishing the whole workspace, this document lists (a) every source file to copy, (b) every SQL statement to run, and (c) every setting to flip — grouped by feature. Do the shared infrastructure steps in Section 2 FIRST, then apply each feature in Section 3, then run the verification in Section 5.

Impact legend

- **[DB]** — requires a database statement (Section 2).
- **[FLAG]** — requires flipping a per-school setting to actually turn the feature ON.
- **[CODE]** — source files only; no DB, no flag. Live as soon as the code is deployed.
- **[OPS]** — a behavioral change external consumers/staff must be told about.

1. What shipped yesterday (inventory)

Eight functional commits. Documentation-only commits (migration report, kiosk-activation docs) and screenshot/asset commits are intentionally excluded — they need no promotion.

Teacher Family Messaging d6ee390b

[DB] [FLAG] [CODE]

Lets classroom teachers send Family Messages to families of ONE of their own class periods or hand-picked students from their own roster. Adds a new school-settings column; OFF by default.

Family admin nav split 5bc60d83

[CODE]

Splits family-related admin tools into a new sidebar navigation section.

Behavior specialists on pullout emails f495d427

[CODE] [OPS]

Behavior Specialists are now default recipients of automatic pullout-notification emails.

Close nav group w/ active page c465ac92

[CODE]

Users can collapse a navigation group even when it contains the active page.

Data export uses local SIS ID a692a93d

[CODE] [OPS]

Data-export payloads and UI now emit local_sis_id instead of student_id (FLEID). Privacy improvement; changes exported column.

Excluded (no action): 7706d356 & 5db75b3e (migration report + PDF), 1c9bebf3 (kiosk-activation docs), f1876f22 (screenshots).

2. Database changes [DB]

There is exactly ONE schema change yesterday: a single new column on school_settings. It is additive, NOT NULL with a constant default, so existing rows backfill automatically. No new tables, no drops, no renames, no data migration.

2.1 Add the column (run once per database)

```
ALTER TABLE school_settings
  ADD COLUMN IF NOT EXISTS teacher_family_messaging_enabled
  BOOLEAN NOT NULL DEFAULT FALSE;
```

Column: teacher_family_messaging_enabled · type boolean · NOT NULL · DEFAULT FALSE (opt-in).

This matches the app boot ensure-block (ensureSchoolSettingsFeatureFlagsSchema, falseDefaultCols). If the API server boots against the target DB it will run this itself, but running it by hand is safe and idempotent.

2.2 ORM definition (already in the code you are copying)

lib/db/src/schema/schoolSettings.ts

```
teacherFamilyMessagingEnabled: boolean('teacher_family_messaging_enabled')
  .notNull()
  .default(false),
```

2.3 Rollback (only to fully revert)

```
ALTER TABLE school_settings
  DROP COLUMN IF EXISTS teacher_family_messaging_enabled;
```

Dropping discards each school's opt-in choice. Not needed for a normal promotion.

3. Per-feature promotion steps

3.1 Teacher Family Messaging [DB] [FLAG] [CODE]

Files to copy (this feature):

```
lib/db/src/schema/schoolSettings.ts      (schema: new column)
artifacts/api-server/src/seed.ts         (boot ensure-block)
artifacts/api-server/src/routes/schoolSettings.ts (read/write flag)
artifacts/api-server/src/routes/parentMessages.ts (teacher send + scope)
artifacts/client/src/App.tsx              (settings UI + 4 mapper spots)
artifacts/client/src/components/FamilyMessagesHub.tsx (teacher composer)
```

1. Run the DB statement in Section 2.1 on the target database.
2. Deploy the six files above (server + client).
3. Restart the API server so the new route + boot ensure-block load.
4. [FLAG] The feature is OFF until an admin opts in PER SCHOOL. Either flip it in the admin UI (School Settings !' Family) or by hand in SQL:

```
-- enable for ONE school (replace :school_id)
UPDATE school_settings
  SET teacher_family_messaging_enabled = TRUE
  WHERE school_id = :school_id;

-- verify which schools have it on
SELECT school_id, teacher_family_messaging_enabled
  FROM school_settings;
```

Prerequisite gates (must also be ON for teachers to send):

- super_feature_family_comm = TRUE (district-level Family Comm master switch; default TRUE).
- feature_family_comm = TRUE (school-level Family Comm switch).
- teacher_family_messaging_enabled = TRUE (this new per-school opt-in; default FALSE).

Scope is always re-enforced server-side: a teacher may only target their OWN periods / OWN roster students — the flag only decides IF a teacher may send, never widens scope. Core Team can broadcast regardless of this flag.

Note: the client flag is wired in FOUR App.tsx spots (type, defaults, load reducer, save reducer). Copy the whole App.tsx change — a partial copy makes the toggle silently revert to OFF after save.

3.2 Family admin navigation split [CODE]

```
artifacts/client/src/App.tsx
```

Client-only. Live as soon as App.tsx is deployed. No DB, no flag. (Shares App.tsx with 3.1 and 3.3 — copying the final App.tsx covers all three.)

3.3 Close nav group with active page [CODE]

```
artifacts/client/src/App.tsx
```

Client-only. Same App.tsx file as above.

3.4 Behavior specialists on pullout emails [CODE] [OPS]

```
artifacts/api-server/src/lib/pulloutEmail.ts  
artifacts/api-server/src/routes/pullouts.ts
```

1. Deploy the two files and restart the API server.
2. [OPS] No DB or flag. Behavior Specialists now receive automatic pullout-notification emails by default.

Confirm the staff you intend to notify actually hold the Behavior Specialist role, and warn any who should NOT suddenly receive these emails.

3.5 Data export uses local SIS ID instead of FLEID [CODE] [OPS]

```
artifacts/api-server/src/routes/dataImports.ts (export payload)  
artifacts/client/src/components/DataExportPanel.tsx (UI labels)
```

1. Deploy the two files and restart the API server.
2. [OPS] No DB change. Exported files now carry local_sis_id where they previously carried student_id

(FLEID). Tell any downstream consumer / spreadsheet / SIS import job that keyed on the FLEID column to switch to the local SIS ID column BEFORE the next export is shared.

4. Complete file manifest (copy checklist)

Every non-asset file touched yesterday. Docs are optional; code + schema are required.

Required — schema & server

```
M lib/db/src/schema/schoolSettings.ts  
M artifacts/api-server/src/seed.ts  
M artifacts/api-server/src/routes/schoolSettings.ts  
M artifacts/api-server/src/routes/parentMessages.ts  
M artifacts/api-server/src/routes/pullouts.ts  
M artifacts/api-server/src/lib/pulloutEmail.ts  
M artifacts/api-server/src/routes/dataImports.ts
```

Required — client

```
M artifacts/client/src/App.tsx  
M artifacts/client/src/components/FamilyMessagesHub.tsx  
M artifacts/client/src/components/DataExportPanel.tsx
```

Optional — docs / memory (no runtime effect)

```
A docs/developer-change-notes.md
A docs/kiosk-activation-architecture.md / .pdf
A docs/migration-report-2026-07-06.md / .pdf
M replit.md
M .agents/memory/*
```

5. Recommended order & verification

Order of operations

1. Back up the target database.
2. Run the ALTER in Section 2.1.
3. Deploy all Required server files; restart the API server.
4. Deploy all Required client files.
5. Flip teacher_family_messaging_enabled for the pilot school(s) (Section 3.1 step 4).
6. Run the verification checks below.
7. Notify data-export consumers (3.5) and behavior specialists (3.4).

Verification

Column exists with correct type/default:

```
SELECT column_name, data_type, column_default, is_nullable
FROM information_schema.columns
WHERE table_name='school_settings'
      AND column_name='teacher_family_messaging_enabled';
-- expect: boolean | false | NO
```

Functional smoke tests:

- As an admin, toggle "teacher family messaging" in School Settings !' save !' reload !' it stays ON (proves all 4 App.tsx mapper spots were copied).
- As a normal teacher in an enabled school, the teacher composer appears and can only target own-period/own-roster students.
- As a teacher in a NOT-enabled school, the composer stays hidden.
- Trigger a pullout notification; confirm Behavior Specialists receive it.
- Run a data export; confirm the ID column is local SIS ID, not FLEID.

Complete manual go-live runbook for all database, schema, server, client, flag, and operational changes made on 2026-07-06. The only database change is the single school_settings.teacher_family_messaging_enabled column; everything else is code or configuration.