

In-class Assignment 5

Andrew Shao

2024-10-02


5.8.5 Q1

```
library(r02pro)
```

```
## Warning: package 'r02pro' was built under R version 4.3.3
```

```
library(ggplot2)
ggplot(data = sahp) +
  geom_bar(mapping = aes(x = gar_car))
```


```
## Warning: Removed 1 rows containing non-finite values (`stat_count()`).
```



5.8.5 Q2

```
ggplot(data = sahp) +  
  geom_bar(mapping = aes(x = gar_car, fill = oa_qual > 5))
```


Warning: Removed 1 rows containing non-finite values (`stat_count()`).



5.8.5 Q3


```
ggplot(data = sahp) +  
  geom_bar(mapping = aes(x = gar_car, fill = oa_qual > 5),  
           position = 'dodge')
```

Warning: Removed 1 rows containing non-finite values (`stat_count()`).




5.8.5 Q4

```
tab <- table(sahp$gar_car)
ggplot(data.frame(gar_car = names(tab),
                  freq = as.vector(tab),
                  prop = as.vector(tab / nrow(sahp))),
       aes(x = '',
           y = prop,
           fill = gar_car)) +
  geom_bar(stat = 'identity') +
  geom_text(aes(label = round(100 * prop, 2)),
            position = position_stack(vjust = 0.5)) +
  coord_polar('y') +
  theme_void()
```




5.9.5. Q1


```
ggplot(sahp) +  
  geom_histogram(mapping = aes(x = liv_area),  
    bins = 10)
```



```
ggplot(sahp) +  
  geom_histogram(mapping = aes(x = liv_area),  
                 binwidth = 300)
```




```
ggplot(sahp) +  
  geom_histogram(mapping = aes(x = liv_area),  
                 breaks = seq(0, 3500, 500))
```



5.9.5 Q2

```
ggplot(sahp) +  
  geom_histogram(mapping = aes(x = liv_area,  
                               fill = kit_qual),  
                 bins = 5)
```



On houses with more living area have better kitchen quality (probably related to pricing).