02 / Experience

What interaction data does one episode generate, and how will we use them?

EX01 / ALOHA / ACT | Source analysis | C1 | P: paper; W: project; R: repository



1. Objective and start

Link the claim, episode start/reset and end rule. Label this episode planned, team-observed or externally reported.

Example episode: reset a cup, teleoperate opening, stop after outcome; this is a reconstructed episode type. [P V]

2. Input and action

Identify observations, timestamps, commands and executed actions where known. Distinguish command from response.

Four camera views and follower joint states accompany leader-derived action targets, recorded at 50 Hz. [P III,V]

3. Response and outcome

Record response, outcome rule, failures, timeouts and interventions. A selected success does not establish reliability.

Object opening is the outcome; commanded joint motion alone is insufficient. Keep failed stages and interventions. [P V]

4. Record and reuse

List the retained interaction data: observations, actions, responses, outcomes and context. State intended use and missing fields.

Most real tasks use 50 demonstrations; Thread Velcro uses 100. Evaluation attempts are a separate record. [P V]

Review: What could make the recorded outcome misleading? Mark missing measurements or an alternative explanation.

Example response: A selected success can hide repeated failed grasps or resets.

Worksheet 2 / Experience - evidence and team review

EX01 / ALOHA / ACT | SOURCE ANALYSIS EXAMPLE | Original review-page layout

Example ID: EX01 Project: ALOHA / ACT Claim ID: C1 Revision: draft 1

Mode: Source analysis Pages: canvas + this review; Decision also includes both A3 sides

Evidence scope: paper sections and public documentation; no dataset download or independent experiment.

Evidence ID	Artifact/source + location (clickable)	What it supports; limitation / access gap
P	arxiv.org/abs/2304.13705v1	Paper: method/results; reported evidence, not our measurement.
W	tonyzhaozh.github.io/aloha	Project: system/videos; selected examples do not establish reliability.
R	github.com/tonyzhaozh/act	Repository: documented route; code and data not executed or audited.

Next action / owner / verification:

A selected success can hide repeated failed grasps or resets. Reviewer: inspect the cited basis before adapting this answer.

Teaching example: no actual student team or signatures. Source analysis is not a reproduced result; blank signature fields are intentional.

1. Name / student ID: _____

Signature: _____ Date: _____

2. Name / student ID: _____

Signature: _____ Date: _____

3. Name / student ID: _____

Signature: _____ Date: _____

4. Name / student ID: _____

Signature: _____ Date: _____

5. Name / student ID: _____

Signature: _____ Date: _____

6. Name / student ID: _____

Signature: _____ Date: _____

7. Name / student ID: _____

Signature: _____ Date: _____

8. Name / student ID: _____

Signature: _____ Date: _____

P/W/R identify linked public sources above. NE: not examined in this brief example, not evidence of failure. Support/context labels are provisional, not grades.