

CLARUS Analysis Report

Document: rfc1034.txt
Analyzed: 2026-05-06T15:00:31.277034

1. Document Processing

Metric	Value
Total Segments	1344
Normative Segments	168
Informative Segments	719
Unknown Segments	457
High Confidence (≥ 0.7)	261
Low Confidence (< 0.4)	0
Text Length (chars)	129180

2. Semantic Extraction

Metric	Value
Total Profiles	21
Average Confidence	70.8%

Profiles (21)

#	Sentence	Subject	Object	Modality	Condition
1	- Where there tradeoffs between the cost of acquiring data and the speed of processing...	data	control the tradeoff	should	there tradeoffs between the cost of acquiring data and the speed of processing...
2	For example, when naming a mail domain, the user should satisfy both constraints.	user	followed	should	naming a mail domain
3	TTL which is the time to live of the RR. This field is used to indicate how long the data can be cached.	they	discarded	can	they cache RRs
4	The meaning of the TTL field is a time limit on how long an RR can be kept in a cache.	an RR	kept in a cache	can	the data originates
5	suggest that these times should be on the order of days for the top level of the hierarchy.	change	anticipated	should	a change can be anticipated
6	RR. If a CNAME RR is present at a node, no other data should be used to determine the canonical name for that node.	data	be	should	a CNAME RR is present at a node
7	rather than pointing at USC-ISIC.ARPA. Of course, by the time the software is written, the canonical name will have changed.	software	followed and CNAME	should	presented with CNAME chains or loops
8	Inverse queries may not return the proper TTL, and do not indicate the TTL of the identified RR.	inverse queries	return the proper TTL	may not	the identified RR is one of a set (for example)
9	technical constraints dealing with where in the tree this can be done.	tree	done	can	in the tree this can be done
10	The recursive mode occurs when a query with RD set arrives at a server which is willing to provide recursive service.	recursive service	recursive service	can	a query with RD set arrives at a server which is willing to provide recursive service
11	The method is that a name server may add an SOA RR to the additional section of the response.	that response	be	may	that response is authoritative

12	SERIAL field in the SOA of the zone is always advanced whenever any...	a simple increment	can	any change is made to the zone
13	This happens when the referenced name does not exist. example,...	Referenced name	have mistyped a host name	the referenced name does not exist
14	request to the same name for some other type of information if the... errors	slow the application	may	the two errors are combined
15	It is essential that this sort of condition should not be signalled...	the	should	mail systems use the
16	lost UDP packets and dead servers; the name server can't easily ov...	an answer	can	it interprets retransmissions as new requests
17	This structure keeps track of the resolver's current best guess...	desired information	can	arriving information changes the guess
18	SBELT a "safety belt" structure of the same size...	used when the resolver	should	the resolver
19	is not recommended as the default. If the resolver has direct acce...	authoritative data in	should	the resolver has direct access to a name server's zones
20	If the response shows a delegation, the resolver should check these...	ignored	should	the response shows a delegation
21	Since the class of all RRs in a zone must be the same, only the fir...	the same	must	a name server loads a zone

3. Terminology Analysis

Metric	Value
Defined Terms	1
Undefined Terms	49
Definition Coverage	2.0%

4. Contradiction Analysis

Total contradictions detected: **26**

#	Type	Conf.	Statement A	Statement B
1	semantic	100%	obtain new zone copies when changes have been made.	impossible to perform a serial check for the EXPIRE ...
2	semantic	100%	which happens to require a suffix toward the end of ...	cached due to direct SOA queries, and name servers a...
3	semantic	100%	limit on how fast a zone can be updated, basically t...	impossible to perform a serial check for the EXPIRE ...
4	semantic	100%	data or the cache. Go to step 4.	not the node with the "label. Go to st...
5	semantic	100%	cached due to direct SOA queries, and name servers a...	inevitable changes are made, they must be distribute...
6	semantic	100%	6.3.2. Get the host name for address 26.6.0.65	6.3.3. Get the host address of poneria.ISI.EDU
7	semantic	100%	obtain new zone copies when changes have been made.	limit on how fast a zone can be updated, basically t...
8	semantic	100%	servers in response to client requests. Resolvers m...	query using referrals to other name servers. A reso...
9	semantic	100%	inevitable changes are made, they must be distribute...	impossible to perform a serial check for the EXPIRE ...
10	semantic	100%	assume that the name does not exist during the TTL p...	cached due to direct SOA queries, and name servers a...
11	semantic	100%	load the new zone. The other non-master or secondar...	impossible to perform a serial check for the EXPIRE ...

12	semantic	99%	wish to use datagrams for queries and responses, and...	systems will use virtual circuits exclusively.
13	semantic	99%	MX data at X.COM and A.X.COM is required, and that n...	cached due to direct SOA queries, and name servers a...
14	semantic	99%	return an MX RR pointing at A.X.COM. Two wildcard R...	cached due to direct SOA queries, and name servers a...
15	semantic	99%	3. Start matching down, label by label, in the zone....	not the node with the "*" label. Go to st...
16	semantic	99%	This function will often follow the form of previous	matching RRs. This function will often use the DNS ...
17	semantic	99%	host which has a name in that domain. In many cases...	server "closer" to the answer. All name s...
18	semantic	99%	return an MX RR pointing at A.X.COM. Two wildcard R...	MX data at X.COM and A.X.COM is required, and that n...
19	semantic	97%	server "closer" to the answer. All name s...	bit specifies specifies whether the requester wants ...
20	semantic	96%	2. Search the available zones for the zone which is ...	data or the cache. Go to step 4.
21	semantic	93%	with local caching to improve performance. Approach...	wish to use datagrams for queries and responses, and...
22	semantic	91%	impossible to perform a serial check for the EXPIRE ...	Each secondary server is required to perform the fol...
23	modality	90%	cached due to direct SOA queries, and name servers a...	become part of the standard protocol in the future. ...
24	modality	90%	cached due to direct SOA queries, and name servers a...	All resolvers and recursive name servers are require...
25	modality	90%	become part of the standard protocol in the future. ...	All resolvers and recursive name servers are require...
26	semantic	82%	be the case that the addresses are not available. T...	to cycle around all of the addresses for all of the ...