

IPySlides 4.3.2 Documentation

Creating slides with IPySlides

Abdul Saboor¹

Jun 23, 2024



¹My University is somewhere in the middle of nowhere

Table of contents

1. | Introduction

2. Adding Slides and Content
3. Layout and **Theme** Settings
4. Useful Functions for **Rich Content**
5. Loading from File/Exporting to HTML
6. Advanced Functionality
7. Presentation Code

This is summary of current section

Oh we can use inline columns

Column A

Column B

here and what not!

Markdown

- ```
1 ````toc Table of contents
2 Extra content for current section which is on right
3 ````
```

# Main App

**Slides**(extensions=[], auto\_focus=True, \*\*settings)

Interactive Slides in IPython Notebook. Only one instance can exist. `auto_focus` can be reset from settings and enable jumping back to slides after a cell is executed. settings are passed to `Slides.settings.apply` if you like to set during initialization.

To suppress unwanted print from other libraries/functions, use:

```
1 with slides.suppress_stdout():
2 some_function_that_prints() # This will not be printed
3 print('This will not be printed either')
4 display('Something') # This will be printed
```



## Info

The methods under settings starting with `Slides.settings.set_` returns settings back to enable chaining without extra typing, like `Slides.settings.set_animation().set_layout()...`



## Tip

- Use `Slides.display` whenever possible instead of IPython's `display`, it automatically adds serializer metadata.
- Use `Slides.instance()` class method to keep older settings. `Slides()` apply default settings every time.
- Run `slides.demo()` to see a demo of some features.
- Run `slides.docs()` to see documentation.

# Adding Slides



## Note

Besides function below, you can add slides with `%%slide number [-m]` magic as well.

**Slides.build**(slide\_number, /, content=None, trusted=False)

Build slides with a single unified command in two ways:

1. `slides.build(number, str)` creates many slides with markdown content. Equivalent to `%%slide number -m` magic in case of one slide.
  - Frames separator is double dashes `--` and slides separator is triple dashes `---`. Same applies to `Slides.sync_with_file` too.
  - Use `%++` to join content of frames incrementally.
  - Markdown multicol before `--` creates incremental columns if `%++` is provided.
  - See `slides.xmd_syntax` for extended markdown usage.
  - Keyword argument `trusted` is used here if there are python run blocks in markdown.
  - To debug markdown content, use EOF on its own line to keep editing and clearing errors. Same applies to `Slides.sync_with_file` too.
2. with `slides.build(number)`: creates single slide. Equivalent to `%%slide number` magic.
  - Use `fsep()` from top import or `Slides.fsep()` to split content into frames.
  - Use for item in `fsep.loop(iterable)`: block to automatically add frame separator.
  - Use `fsep.join` to join content of frames incrementally.



## Tip

- In all cases, number could be used as `-1`.

Use `%%effectinteger` in py in markdown or `Slides.this.effect(integer)` to make all frames align vertically to avoid jumps

```
1 self.write(self.fmt("{self.version!r}``{self.xmd_syntax}``"))
```

'4.3.2'

## Extended Markdown

Extended syntax for markdown is constructed to support almost full presentation from Markdown.

**Following syntax works only under currently building slide:**

- `notes`This is slide notes`` to add notes to current slide
- `cite`key`` to add citation to current slide. citations are automatically added in suitable place and should be set once using `Slides.set_citations` function.
- With citations mode set as 'footnote', you can add `refs`ncol`` to add citations anywhere on slide. If ncol is not given, it will be picked from layout settings.
- `section`content`` to add a section that will appear in the table of contents.
- `toc`Table of content header text`` to add a table of contents. For block type toc, see below.
- `proxy`placeholder text`` to add a proxy that can be updated later with `Slides[slide_number,].proxies[index].capture` contextmanager or a shortcut `Slides.capture_proxy(slides_number, proxy_index)`. Useful to keep placeholders for plots/widgets in markdown.
- Triple dashes --- is used to split text in slides inside markdown content of `Slides.build` function or markdown file.
- Double dashes -- is used to split text in frames. Alongwith this `%++` can be used to increment text on framed slide.

Block table of contents with extra content can be added as follows:

# Adding Content



## Note

Besides functions below, you can add content to slides with `%%xmd,%xmd` as well.

**Slides.write**(\*objs, widths=None)

Write objs to slides in columns. To create rows in a column, wrap objects in a list or tuple. You can optionally specify widths as a list of percentages for each column.

Write any object that can be displayed in a cell with some additional features:

- Strings will be parsed as as extended markdown that can have citations/python code blocks/Javascript etc.
- Display another function in order by passing it to a lambda function like `lambda: func()`. Only body of the function will be displayed/printed. Return value will be ignored.
- Display IPython widgets such as `ipywidgets` or `ipyvolume` by passing them directly.
- Display Axes/Figure from libraries such as `matplotlib`, `plotly`, `altair`, `bokeh`, `ipyvolume` ect. by passing them directly.
- Display source code of functions/classes/modules or other languages by passing them directly or using `Slides.code` API.
- Use `Slides.alt` function to display obj/widget on slides and alternative content in exported slides.
- Use `Slides.alt_clip` function to display anything (without parsing) on slides and paste its screenshot for export. Screenshots are persistent and taken on slides.
- Use `Slides.image_clip` to add screenshots from clipboard while running the cell.
- `ipywidgets`.`[HTML, Output, Box]` and their subclasses will be displayed as `Slides.alt(html_converter_func, widget)`. The value of exported HTML will be most recent.
- Other options include but not limited to:
  - Output of functions in `ipyslides.utils` module that are also linked to `Slides` object.

# Adding Speaker Notes

→ Skip to Dynamic Content



## Note

You can use `notes`notes content`` in markdown.



## Danger

This is experimental feature, and may not work as expected.

`Slides.notes.display()`

`Slides.notes.insert(content)`

Add notes to current slide. Content could be any object except javascript and interactive widgets.



## Tip

In markdown, you can use `notes`notes content``.

# Displaying Source Code

`Slides.code.cast(obj, language='python', name=None, **kwargs)`

Create source code object from file, text or callable. kwargs are passed to `ipyslides.formatter.highlight`.

`Slides.code.context(returns=False, **kwargs)`

Execute and displays source code in the context manager. kwargs are passed to `ipyslides.formatter.highlight` function. Useful when source is written inside context manager itself. If `returns` is `False` (by default), then source is displayed before the output of code. Otherwise you can assign the source to a variable and display it later anywhere.

## Usage:

```
1 with source.context(returns = True) as s:
2 do_something()
3 write(s) # or s.display(), write(s)
4
5 #s.raw, s.value are accesible attributes.
6 #s.focus_lines, s.show_lines are methods that are used to show selective lines.
```

`Slides.code.from_callable(callable, **kwargs)`

Returns source object from a given callable [class,function,module,method etc.] with `show_lines` and `focus_lines` methods. kwargs are passed to `ipyslides.formatter.highlight`

`Slides.code.from_file(filename, language=None, name=None, **kwargs)`



# Contents

1. Introduction
2. Adding Slides and Content
- 3. Layout and Theme Settings**
4. Useful Functions for Rich Content
5. Loading from File/Exporting to HTML
6. Advanced Functionality
7. Presentation Code

# Layout and Theme Settings

`Slides.settings.apply(**settings)`

Apply multiple settings at once. Top level keys should be function names without 'set\_' and values should be dictionary of parameters to that function. For example:

```
1 Slides.settings.apply(
2 layout = {"aspect":1.6, "scroll":False},
3 footer = {0:"footer text", "numbering":True} # 0 key goes to first positional argument
4)
```

`Slides.settings.set_animation(main='slide_h', frame='appear')`

Set animation for slides and frames.

`Slides.settings.set_bg_image(src=None, opacity=0.25, filter='blur(2px)', contain=False)`

Adds glassmorphic effect to the background with image. src can be a url or a local image path. Overall background will not be exported, but on each slides will be. This is to keep exported file size minimal.

`Slides.settings.set_code_theme(style='default', color=None, background=None, hover_color='var(--alternate-bg)', lineno=True)`

Set code style CSS. Use background for better view of your choice. This is overwritten by theme change.

`Slides.settings.set_css(props: dict)`

# Useful Functions for Rich Content

Slides.**alt**(func\_or\_html, obj, /)

Display obj for slides and output of func\_or\_html will be and displayed only in exported formats as HTML.

- func\_or\_html should be a str, an obj with `_repr_html_` method or a callable to receive obj as its only argument.
- In case obj is an instance of `ipywidgets.DOMWidget`:
  - A callable func\_or\_html will give the latest representation of widget in exported slides.
  - In other cases, it will export the runtime representation of widget.
- For any other obj, representation is always computed at runtime.



Python

```
1 import ipywidgets as ipw
2 slides = get_slides_instance()
3 slides.alt(lambda w: f'<input type="range" min="{w.min}" max="{w.max}" value="{w.value}">', ipw.IntSlider()).display()
```

## Info

- If you happen to be using alt many times for same type, you can use `Slides.serializer.register` and then pass that type of widget without alt.
- ipywidgets's HTML, Box and Output widgets and their subclasses directly give html representation if used inside write command.
- Use `alt_clip` to paste images of widgets and other objects directly on slides.

# Citations and Sections

Use syntax `cite`key`` to add citations which should be already set by `Slides.set_citations(data, mode)` method. Citations are written on suitable place according to given mode. Number of columns in citations are determined by `Slides.settings.set_layout(..., ncol_refs = int)`.<sup>1</sup>

Add sections in slides to separate content by `section`text``. Corresponding table of contents can be added with `toc`title`/``toc title\n summary of current section \n```.

`Slides.set_citations(data, mode='footnote')`

Set citations from dictionary or file that should be a JSON file with citations keys and values, key should be cited in markdown as `cite`key``. mode for citations should be one of ['inline', 'footnote']. Number of columns in citations are determined by `Slides.settings.set_layout(..., ncol_refs=N)`.



## Note

- You should set citations in start if using voila or python script. Setting in start in notebook is useful as well.
- Citations are replaced with new ones, so latest use of this function represents available citations.

---

1. Citation A

# Dynamic Content

`Slides.on_refresh(func)`

Decorator for inserting dynamic content on slide, define a function with no arguments. Content updates when `slide.update_display` is called or when `Slides.refresh` is called.



Tip

You can use it to dynamically fetch a value from a database or API while presenting, without having to run the cell again.



Note

- No return value is required. If any, should be like `display('some value')`, otherwise it will be ignored.
- A slide with dynamic content enables a refresh button in bottom bar.
- All slides with dynamic content are updated when refresh button in top bar is clicked.

Python







```
1 import time
2 slides = get_slides_instance() # Get slides instance, this is to make doctring runnable
3 source.display() # Display source code of the block
4 @slides.on_refresh
5 def update_time():
6 print('Local Time: {3}:{4}:{5}'.format(*time.localtime())) # Print time in HH:MM:SS format
7 # Updates on update_display or refresh button click
```

Local Time: 17:56:30

# Content Styling

You can **style** or **colorize** your *content* and **text**. Provide **CSS** for that using `.format_css` or use some of the available styles. See these **styles** with `.css_styles` property as below:

Use any or combinations of these styles in `css_class` argument of writing functions:

| css_class       | Formatting Style                                                                                                            |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------|
| 'text-[value]'  | [value] should be one of tiny, small, big, large, huge.                                                                     |
| 'align-[value]' | [value] should be one of center, left, right.                                                                               |
| 'rtl'           | اردو عربی                                                                                                                   |
| 'info'          | Blue text. Icon  for note-info class.      |
| 'tip'           | Blue Text. Icon  for note-tip class.       |
| 'warning'       | Orange Text. Icon  for note-warning class. |
| 'success'       | Green text. Icon  for note-success class.  |
| 'error'         | Red Text. Icon  for note-error class.      |
| 'note'          |  Text with note icon.                      |
| 'export-only'   | Hidden on main slides, but will appear in exported slides.                                                                  |
| 'jupyter-only'  | Hidden on exported slides, but will appear on main slides.                                                                  |
| 'block'         | Block of text/objects                                                                                                       |
| 'block-[color]' | Block of text/objects with specific background color from red, green, blue, yellow, cyan, magenta and gray.                 |
| 'raw-text'      | Text will not be formatted and will be shown as it is.                                                                      |
| 'zoom-self'     | Zooms object on hover, when Zoom is enabled.                                                                                |
| 'zoom-child'    | Zooms child object on hover, when Zoom is enabled.                                                                          |
| 'no-zoom'       | Disables zoom on object when it is child of 'zoom-child'                                                                    |

# Highlighting Code

pygments is used for syntax highlighting <sup>1</sup>. You can **highlight** code using highlight function <sup>2</sup> or within markdown like this:

Python

```
1 import ipyslides as isd
```

Javascript

```
1 import React, { Component } from "react";
```

Markdown

```
1 ## Highlighting Code
2 [pygments](https://pygments.org/) is used for syntax highlighting cite`A`.
3 You can highlight{.error} code using `highlight` function cite`B` or within markdown like this:
4 ```python
5 import ipyslides as isd
6 ```
7 ```javascript
8 import React, { Component } from "react";
9 ```
10 proxy`source code of slide will be updated here later using slide_handle.proxies[0].capture contextmanager`
```

1. Citation A

2. Citation B

# Loading from File/Exporting to HTML



## Note

You can parse and view a markdown file. The output you can save by exporting notebook in other formats.

**Slides.sync\_with\_file**(start\_slide\_number, /, path, trusted=False, interval=500)

Auto update slides when content of markdown file changes. You can stop syncing using `Slides.unsync` function. interval is in milliseconds, 500 ms default. Read `Slides.build` docs about content of file.

The variables inserted in file content are used from top scope.



## Tip

To debug a linked file, use EOF on its own line to keep editing and clearing errors.

**Slides.demo()**

Demo slides with a variety of content.

**Slides.docs()**

Create presentation from docs of IPySlides.

**Slides.export\_html**(path='slides.html', overwrite=False)

Build beautiful html slides that you can print.

- Use 'overrides.css' file in some folder to override CSS styles



# Contents

1. Introduction
2. Adding Slides and Content
3. Layout and **Theme** Settings
4. Useful Functions for **Rich Content**
5. Loading from File/Exporting to HTML
- 6. Advanced Functionality**
7. Presentation Code

# Adding content on frames incrementally

Python

```
1 self.write("## Adding content on frames incrementally yoffset`0`")
2 self.display(widget := (code := s.get_source()).as_widget())
3 @self.on_load
4 def highlight_line(slide): # only oldest state in export with self.display above, latest with write
5 widget.value = code.focus_lines(range(slide.indexf + 1)).value
6
7 for ws, cols in self.fsep.loop(zip([None, (2,3),None], [(0,1),(2,3),(4,5,6,7)])):
8 cols = [self.html('h1', f'{c}', style="background:var(--alternate-bg);margin-block:0.05em !important;") for c in cols]
9 self.fsep.join() # incremental
10 self.write(*cols, widths=ws)
```

# Adding content on frames incrementally

Python

```
1 self.write("## Adding content on frames incrementally yoffset`0`")
2 self.display(widget := (code := s.get_source()).as_widget())
3 @self.on_load
4 def highlight_line(slide): # only oldest state in export with self.display above, latest with write
5 widget.value = code.focus_lines(range(slide.indexf + 1)).value
6
7 for ws, cols in self.fsep.loop(zip([None, (2,3),None], [(0,1),(2,3),(4,5,6,7)])):
8 cols = [self.html('h1', f'{c}', style="background:var(--alternate-bg);margin-block:0.05em !important;") for c in cols]
9 self.fsep.join() # incremental
10 self.write(*cols, widths=ws)
```

0

# Adding content on frames incrementally

Python

```
1 self.write("## Adding content on frames incrementally yoffset`0`")
2 self.display(widget := (code := s.get_source()).as_widget())
3 @self.on_load
4 def highlight_line(slide): # only oldest state in export with self.display above, latest with write
5 widget.value = code.focus_lines(range(slide.indexf + 1)).value
6
7 for ws, cols in self.fsep.loop(zip([None, (2,3),None], [(0,1),(2,3),(4,5,6,7)])):
8 cols = [self.html('h1', f'{c}', style="background:var(--alternate-bg);margin-block:0.05em !important;") for c in cols]
9 self.fsep.join() # incremental
10 self.write(*cols, widths=ws)
```

0

1

# Adding content on frames incrementally

Python

```
1 self.write("## Adding content on frames incrementally yoffset`0`")
2 self.display(widget := (code := s.get_source()).as_widget())
3 @self.on_load
4 def highlight_line(slide): # only oldest state in export with self.display above, latest with write
5 widget.value = code.focus_lines(range(slide.indexf + 1)).value
6
7 for ws, cols in self.fsep.loop(zip([None, (2,3),None], [(0,1),(2,3),(4,5,6,7)])):
8 cols = [self.html('h1', f'{c}', style="background:var(--alternate-bg);margin-block:0.05em !important;") for c in cols]
9 self.fsep.join() # incremental
10 self.write(*cols, widths=ws)
```

0

1

2

# Adding content on frames incrementally

Python

```
1 self.write("## Adding content on frames incrementally yoffset`0`")
2 self.display(widget := (code := s.get_source()).as_widget())
3 @self.on_load
4 def highlight_line(slide): # only oldest state in export with self.display above, latest with write
5 widget.value = code.focus_lines(range(slide.indexf + 1)).value
6
7 for ws, cols in self.fsep.loop(zip([None, (2,3),None], [(0,1),(2,3),(4,5,6,7)])):
8 cols = [self.html('h1', f'{c}', style="background:var(--alternate-bg);margin-block:0.05em !important;") for c in cols]
9 self.fsep.join() # incremental
10 self.write(*cols, widths=ws)
```

0

1

2

3

# Adding content on frames incrementally

Python

```
1 self.write("## Adding content on frames incrementally yoffset`0`")
2 self.display(widget := (code := s.get_source()).as_widget())
3 @self.on_load
4 def highlight_line(slide): # only oldest state in export with self.display above, latest with write
5 widget.value = code.focus_lines(range(slide.indexf + 1)).value
6
7 for ws, cols in self.fsep.loop(zip([None, (2,3),None], [(0,1),(2,3),(4,5,6,7)])):
8 cols = [self.html('h1', f'{c}', style="background:var(--alternate-bg);margin-block:0.05em !important;") for c in cols]
9 self.fsep.join() # incremental
10 self.write(*cols, widths=ws)
```

0

1

2

3

4

# Adding content on frames incrementally

Python

```
1 self.write("## Adding content on frames incrementally yoffset`0`")
2 self.display(widget := (code := s.get_source()).as_widget())
3 @self.on_load
4 def highlight_line(slide): # only oldest state in export with self.display above, latest with write
5 widget.value = code.focus_lines(range(slide.indexf + 1)).value
6
7 for ws, cols in self.fsep.loop(zip([None, (2,3),None], [(0,1),(2,3),(4,5,6,7)])):
8 cols = [self.html('h1', f'{c}', style="background:var(--alternate-bg);margin-block:0.05em !important;") for c in cols]
9 self.fsep.join() # incremental
10 self.write(*cols, widths=ws)
```

0

1

2

3

4

5



# Adding content on frames incrementally

Python

```
1 self.write("## Adding content on frames incrementally yoffset`0`")
2 self.display(widget := (code := s.get_source()).as_widget())
3 @self.on_load
4 def highlight_line(slide): # only oldest state in export with self.display above, latest with write
5 widget.value = code.focus_lines(range(slide.indexf + 1)).value
6
7 for ws, cols in self.fsep.loop(zip([None, (2,3),None], [(0,1),(2,3),(4,5,6,7)])):
8 cols = [self.html('h1', f"{c}",style="background:var(--alternate-bg);margin-block:0.05em !important;") for c in cols]
9 self.fsep.join() # incremental
10 self.write(*cols, widths=ws)
```

0

1

2

3

4

5

6

# Adding content on frames incrementally

Python

```
1 self.write("## Adding content on frames incrementally yoffset`0`")
2 self.display(widget := (code := s.get_source()).as_widget())
3 @self.on_load
4 def highlight_line(slide): # only oldest state in export with self.display above, latest with write
5 widget.value = code.focus_lines(range(slide.indexf + 1)).value
6
7 for ws, cols in self.fsep.loop(zip([None, (2,3),None], [(0,1),(2,3),(4,5,6,7)])):
8 cols = [self.html('h1', f'{c}', style="background:var(--alternate-bg);margin-block:0.05em !important;") for c in cols]
9 self.fsep.join() # incremental
10 self.write(*cols, widths=ws)
```

0

1

2

3

4

5

6

7

# Adding User defined Objects/Markdown Extensions

I will be on exported  
slides

Python

```
1 self.write('## Adding User defined Objects/Markdown Extensions')
2 self.write(
3 lambda: display(self.html('h3','I will be on main slides',css_class='warning'),
4 metadata = {'text/html': '<h3 class="warning">I will be on exported slides</h3>'}, # Can also c
5 s.get_source(), widths = [1,3]
6)
7 self.write('If you need to serialize your own or third party objects not serialized by this module, you can use
8 self.doc(self.serializer,'Slides.serializer', members = True, itself = False).display()
9 self.write('**You can also extend markdown syntax** using `markdown extensions`, ([See here](h
10 self.doc(self.extender,'Slides.extender', members = True, itself = False).display()
```



## Note

If you need to serialize your own or third party objects not serialized by this module, you can use `@Slides.serializer.register` to serialize them to html.

`Slides.serializer.display(obj)`

Display an object with metadata if a serializer available. Same as `display(obj, metadata = serializer.get_metadata(obj))`

`Slides.serializer.get_func(obj_type)`

Get serializer function for a type. Returns None if not found.

## Focus on what matters

- There is a zoom button on top bar which enables zooming of certain elements. This can be toggled by Z key.
- Most of supported elements are zoomable by default like images, matplotlib, bokeh, PIL image, altair plotly, dataframe, etc.
- You can also enable zooming for an object/widget by wrapping it inside Slide.

function conveniently. - You can also enable by manually adding

zoom-self, zoom-child classes to an element. To prevent zooming under as zoom-child class, use no-zoom class.

---

## Focus on Me 🕶️

- If zoom button is enabled, you can hover here to zoom in this part!
- You can also zoom in this part by pressing Z key while mouse is over this part.

## SVG Icons

Icons that appear on buttons inslides (and their rotations) available to use in your slides as well besides standard ipywidgets icons.

arrow: → arrowb: ↗ arrowbd: ↘ arrowbl: ↖ arrowbr: ↘ arrowbu: ↗ arrowd: ↓ arrowl: ← arrowr: → arrowu: ↑ bars: ≡  
camera: 📷 chevron: > chevrong: ∨ chevronl: < chevronr: > chevronu: ^ circle: ○ close: ✕ code: </> columns: 📄  
compress: ↗ dots: ⋮ edit: ✎ expand: ↗ info: ⓘ laser: 🎯 loading: 🔄 pause: ⏸ pencil: 🖋 play: ▶ refresh: 🔄 rows: 📄  
search: 🔍 settings: ⚙ stop: ■ win-maximize: 🖥 win-restore: 🖥 zoom-in: 🔍 zoom-out: 🔍

Python

```
1 import ipywidgets as ipw
2 btn = ipw.Button(description='Chevron-Down Icon',icon='chevrong')
3 self.write(btn)
```

# Auto Slide Numbering

Use **-1** as placeholder to update slide number automatically.

- In Jupyter notebook, this will be updated to current slide number.
- In python file, it stays same.
- You need to run cell twice if creating slides inside a for loop while using -1.
- Additionally, in python file, you can use `Slides.build_` instead of using -1.

# Presentation Code

Python

```
1 def docs(self):
2 "Create presentation from docs of IPySlides."
3 self.close_view() # Close any previous view to speed up loading 10x faster on average
4 self.clear() # Clear previous content
5 self.create(range(23)) # Create slides faster
6
7 from ..core import Slides
8
9 self.set_citations({'A': 'Citation A', 'B': 'Citation B'}, mode = 'footnote')
10 self.settings.set_footer('IPySlides Documentation', date=False)
11
12 with self.build(0): # Title page
13 self.this.set_bg_image(Path(__file__).parent.parent.parent / 'slide.png', 1, filter='blur(10px)', contain=True)
14 self.write(f'## IPySlides {self.version} Documentation\n### Creating slides with IPySlides')
15 self.center(self.fmt("""
16 alert`Abdul Saboor`sup`1`
17
18 today``
```