

IPySlides 4.2.0 Documentation

Creating slides with IPySlides

Abdul Saboor¹, Unknown Author²
Jun 08, 2024

¹My University is somewhere in the middle of nowhere

²Their University is somewhere in the middle of nowhere

Table of contents

1. **Introduction**
2. Adding Slides and Content
3. Layout and **Theme** Settings
4. Useful Functions for **Rich Content**
5. Loading from File/Exporting to HTML
6. Advanced Functionality
7. Presentation Code

This is summary of current
section

Oh we can use inline columns

Column A

Column B

here and what not!

Markdown

```
1  ```toc Table of contents
2  Extra content for current section which is on right
3  ```
```

Main App

Slides(extensions=[], auto_focus=True, **settings)

Interactive Slides in IPython Notebook. Only one instance can exist. `auto_focus` can be reset from settings and enable jumping back to slides after a cell is executed. settings are passed to `Slides.settings.apply` if you like to set during initialization.

To suppress unwanted print from other libraries/functions, use:

```
1 with slides.suppress_stdout():
2     some_function_that_prints() # This will not be printed
3     print('This will not be printed either')
4     display('Something') # This will be printed
```



The methods under settings starting with `Slides.settings.set_` returns settings back to enable chaining without extra typing, like `Slides.settings.set_animation().set_layout()...`



- Use `Slides.instance()` class method to keep older settings. `Slides()` apply default settings every time.
- Run `slides.demo()` to see a demo of some features.
- Run `slides.docs()` to see documentation.
- Instructions in left settings panel are always on your fingertips

Adding Slides



Note

Besides function below, you can add slides with `%%slide number [-m]` magic as well.

`Slides.build`(slide_number, /, content=None, *, repeat=False, trusted=False)

Build slides with a single unified command in three ways:

- `slides.build(number, str)` creates many slides with markdown content.
 - Equivalent to `%%slide number -m` magic in case of one slide.
 - Frames separator is double dashes `--` and slides separator is triple dashes `---`. Same applies to `Slides.sync_with_file` too.
 - Markdown before the first `--` (frame separator) is written on all frames.
 - Use `%++` in frames to add frames incrementally.
 - See `slides.xmd_syntax` for extended markdown usage.
 - Keyword argument `trusted` is used here if there are python run blocks in markdown.
- `with slides.build(number):` creates single slide. Equivalent to `%%slide number` magic.
- `@slides.build(number, iterable)` creates a slide with multiple frames.
 - `iterable` is a sequence other than a string.
 - Automatic call as `slides.build(number, iterable)()` will write objects from top to bottom.
 - Use decorated `func(frame_index, frame_content)` to write content flexibly.
 - `repeat` can be `False`, `True` or an indexing sequence over `iterable`. Top list-like creates frames, inner list-like items can be nested to two more levels for arranging items. `[]` can be used to have empty column/row.
 - If function has a docstring, it will be parsed and added on top of all frames.

```
1 slides.build(1 [a b c])() # content is a b c
```

```
1 self.write(self.fmt('{{self.version!r}}' '{self.xmd_syntax}'))
```

'4.2.0'

Extended Markdown

Extended syntax for markdown is constructed to support almost full presentation from Markdown.

Following syntax works only under currently building slide:

- `notes`This is slide notes`` to add notes to current slide
- `cite`key`` to add citation to current slide. citations are automatically added in suitable place and should be set once using `Slides.set_citations` function.
- With citations mode set as 'footnote', you can add `refs`ncol`` to add citations anywhere on slide. If `ncol` is not given, it will be picked from layout settings.
- `section`content`` to add a section that will appear in the table of contents.
- `toc`Table of content header text`` to add a table of contents. For block type toc, see below.
- `proxy`placeholder text`` to add a proxy that can be updated later with `Slides.get(slide_number).proxies[index].capture` contextmanager or a shortcut `Slides.capture_proxy(slides_number, proxy_index)`. Useful to keep placeholders for plots/widgets in markdown.
- Triple dashes `---` is used to split text in slides inside markdown content of `Slides.build` function or markdown file.
- Double dashes `--` is used to split text in frames.

Block table of contents with extra content can be added as follows:

Adding Content



Note

Besides functions below, you can add content to slides with `%%xmd,%xmd` as well.

Slides.**write**(*objs, widths=None)

Write `objs` to slides in columns. To create rows in a column, wrap objects in a list or tuple. You can optionally specify `widths` as a list of percentages for each column.

Write any object that can be displayed in a cell with some additional features:

- Strings will be parsed as extended markdown that can have citations/python code blocks/Javascript etc.
- Display another function in order by passing it to a lambda function like `lambda: func()`. Only body of the function will be displayed/printed. Return value will be ignored.
- Display IPython widgets such as `ipywidgets` or `ipyvolume` by passing them directly.
- Display Axes/Figure from libraries such as `matplotlib`, `plotly`, `altair`, `bokeh`, `ipyvolume` etc. by passing them directly.
- Display source code of functions/classes/modules or other languages by passing them directly or using `Slides.code` API.
- Use `Slides.alt(widget, func)` function to display widget on slides and alternative content in exported slides, function should return possible HTML representation of widget.
- `ipywidgets.HTML` and its subclasses will be displayed as `Slides.alt(widget, html_converter_func)`. The value of exported HTML will be most recent.
- Other options include but not limited to:
 - Output of functions in `ipyslides.utils` module that are also linked to `Slides` object.
 - PIL images, SVGs etc.

Adding Speaker Notes

[Skip to Dynamic Content](#)



Note

You can use `notes`notes content`` in markdown.



Danger

This is experimental feature, and may not work as expected.

`Slides.notes.display()`

`Slides.notes.insert(content)`

Add notes to current slide. Content could be any object except javascript and interactive widgets.



Tip

In markdown, you can use `notes`notes content``.

Displaying Source Code

`Slides.code.cast(obj, language='python', name=None, **kwargs)`

Create source code object from file, text or callable. kwargs are passed to `ipyslides.formatter.highlight`.

`Slides.code.context(returns=False, **kwargs)`

Execute and displays source code in the context manager. kwargs are passed to `ipyslides.formatter.highlight` function. Useful when source is written inside context manager itself. If `returns` is `False` (by default), then source is displayed before the output of code. Otherwise you can assign the source to a variable and display it later anywhere.

Usage:

```
1 with source.context(returns = True) as s:
2     do_something()
3     write(s) # or s.display(), write(s)
4
5 #s.raw, s.value are accesible attributes.
6 #s.focus_lines, s.show_lines are methods that are used to show selective lines.
```

`Slides.code.from_callable(callable, **kwargs)`

Returns source object from a given callable [class,function,module,method etc.] with `show_lines` and `focus_lines` methods. kwargs are passed to `ipyslides.formatter.highlight`

Contents

1. Introduction
2. Adding Slides and Content
- 3. Layout and Theme Settings**
4. Useful Functions for Rich Content
5. Loading from File/Exporting to HTML
6. Advanced Functionality
7. Presentation Code

Layout and Theme Settings

`Slides.settings.apply(**settings)`

Apply multiple settings at once. Top level keys should be function names without 'set_' and values should be dictionary of parameters to that function. For example:

```
1 Slides.settings.apply(  
2     layout = {"aspect":1.6, "scroll":False},  
3     footer = {0:"footer text", "numbering":True} # 0 key goes to first positional arg  
4 )
```

`Slides.settings.set_animation(main='slide_h', frame='appear')`

Set animation for slides and frames.

`Slides.settings.set_bg_image(src=None, opacity=0.25, filter='blur(2px)', contain=False)`

Adds glassmorphic effect to the background with image. src can be a url or a local image path.

`Slides.settings.set_code_theme(style='default', color=None, background=None, hover_color='var(--hover-bg)',
lineno=True)`

Set code style CSS. Use background for better view of your choice. This is overwritten by theme change.

`Slides.settings.set_css(props: dict)`

Set CSS for all slides. This loads on slides navigation, so you can include keyframes animations as well.

Useful Functions for Rich Content

Slides.alt(widget, func)

Display widget for slides and output of `func(widget)` will be and displayed only in exported formats as HTML. `func` should return possible HTML representation (provided by user) of widget as string.



Python

```
1 import ipywidgets as ipw
2 slides = get_slides_instance()
3 slides.alt(ipw.IntSlider(), lambda w: f'<input type="range" min="{w.min}" max="{w.max}"
```



Info

- If you happen to be using `alt` many times for same type, you can use `Slides.serializer.register` and then pass that type of widget without `alt`.
- `ipywidgets`'s HTML, Box and Output widgets and their subclasses directly give html representation if used inside `write` command.
- Use `alt_clip` to paste images of widgets and other objects directly on slides.

Slides.alt_clip(filename, obj=None, quality=95, **kwargs)

Save image from clipboard to file with a given quality when you paste in given area on slides. Pasting UI is automatically enabled and can be disabled in settings panel. On next run, it loads from saved file under `Slides.clips_dir`.

Citations and Sections

Use syntax `cite`key`` to add citations which should be already set by `Slides.set_citations(data, mode)` method. Citations are written on suitable place according to given mode. Number of columns in citations are determined by `Slides.settings.set_layout(..., ncol_refs = int)`.¹

Add sections in slides to separate content by `section`text``. Corresponding table of contents can be added with `toc`title`/``toc title\n summary of current section \n```.

`Slides.set_citations(data, mode='footnote')`

Set citations from dictionary or file that should be a JSON file with citations keys and values, key should be cited in markdown as `cite`key``. mode for citations should be one of ['inline', 'footnote']. Number of columns in citations are determined by `Slides.settings.set_layout(..., ncol_refs=N)`.



Note

- You should set citations in start if using voila or python script. Setting in start in notebook is useful as well.
- Citations are replaced with new ones, so latest use of this function represents available citations.

1. Citation A

Dynamic Content

`Slides.on_refresh(func)`

Decorator for inserting dynamic content on slide, define a function with no arguments. Content updates when `slide.update_display` is called or when `Slides.refresh` is called.



Tip

You can use it to dynamically fetch a value from a database or API while presenting, without having to run the cell again.



Note

- No return value is required. If any, should be like `display('some value')`, otherwise it will be ignored.
- A slide with dynamic content enables a refresh button in bottom bar.
- All slides with dynamic content are updated when refresh button in top bar is clicked.

Python

```
1 import time
2 slides = get_slides_instance() # Get slides instance, this is to make doctring running
3 source.display() # Display source code of the block
4 @slides.on_refresh
5 def update_time():
6     print('Local Time: {3}:{4}:{5}'.format(*time.localtime())) # Print time in HH:MM:SS
7 # Updates on update_display or refresh button click
```

Content Styling

You can **style** or **colorize** your *content* and *text*. Provide **CSS** for that using `.format_css` or use some of the available styles. See these **styles** with `.css_styles` property as below:

Use any or combinations of these styles in `className` argument of writing functions:

className	Formatting Style
-----------	------------------

'text-[value]'	[value] should be one of tiny, small, big, large, huge.
----------------	---

'align-[value]'	[value] should be one of center, left, right.
-----------------	---

'rtl'	---- اردو عربی
-------	----------------

'info'	Blue text. Icon ⓘ for note-info class.
--------	--

'tip'	Blue Text. Icon 💡 for note-tip class.
-------	---------------------------------------

'warning'	Orange Text. Icon ⚠ for note-warning class.
-----------	---

'success'	Green text. Icon ✅ for note-success class.
-----------	--

'error'	Red Text. Icon ⚡ for note-error class.
---------	--

'note'	📝 Text with note icon.
--------	------------------------

'export-only'	Hidden on main slides, but will appear in exported slides.
---------------	--

'jupyter-only'	Hidden on exported slides, but will appear on main slides.
----------------	--

'block'	Block of text/objects
---------	-----------------------

'block-[color]'	Block of text/objects with specific background color from red, green blue yellow cyan magenta and gray
-----------------	---

Python

```
1 self.write(('You can style{.error} or color[teal]'colorize' your *content*{:  
2         'Provide CSS{.info} for that using '.format_css' or use some of the avai  
3         'See these styles{.success} with '.css_styles' property as below:'))
```

Highlighting Code

pygments is used for syntax highlighting ¹. You can **highlight** code using highlight function ² or within markdown like this:

Python

```
1 import ipyslides as isd
```

Javascript

```
1 import React, { Component } from "react";
```

Markdown

```
1 ## Highlighting Code
2 [pygments](https://pygments.org/) is used for syntax highlighting cite`A`.
3 You can highlight{.error} code using `highlight` function cite`B` or within m
4 ```python
5 import ipyslides as isd
6 ```
7 ```javascript
8 import React, { Component } from "react";
9 ```
10 proxy`source code of slide will be updated here later using slide_handle.proxies
```

1. Citation A

2. Citation B

Loading from File/Exporting to HTML



Note

You can parse and view a markdown file. The output you can save by exporting notebook in other formats.

Slides.sync_with_file(start_slide_number, /, path, trusted=False, interval=500)

Auto update slides when content of markdown file changes. You can stop syncing using `Slides.unsync` function. interval is in milliseconds, 500 ms default. Read `Slides.build` docs about content of file.

The variables inserted in file content are used from top scope.

Slides.demo()

Demo slides with a variety of content.

Slides.docs()

Create presentation from docs of IPySlides.

Slides.export_html(path='slides.html', overwrite=False)

Build beautiful html slides that you can print. Widgets are supported via `Slides.alt(widget, func)`.

- Use 'overrides.css' file in same folder to override CSS styles.
- If a slide has only widgets or does not have single object with HTML representation, it will be skipped.
- You can take screenshot (using system's tool) of a widget and add it back to slide using

Contents

1. Introduction
2. Adding Slides and Content
3. Layout and **Theme** Settings
4. Useful Functions for **Rich Content**
5. Loading from File/Exporting to HTML
- 6. Advanced Functionality**
7. Presentation Code

Adding User defined Objects/Markdown Extensions

I will be on
exported slides

Python

```
1 self.write('## Adding User defined Objects/Markdown Extensions')
2 self.write(
3     lambda: display(self.html('h3', 'I will be on main slides')
4     metadata = {'text/html': '<h3 class="warning">I will be o
5     s.get_source(), widths = [1,3]
6 )
7 self.write('If you need to serialize your own or third party )
8 self.doc(self.serializer, 'Slides.serializer', members = True,
9 self.write('**You can also extend markdown syntax** using `ma
10 self.doc(self.extender, 'Slides.extender', members = True, its
```



Note

If you need to serialize your own or third party objects not serialized by this module, you can use `@Slides.serializer.register` to serialize them to html.

`Slides.serializer.display(obj)`

Display an object with metadata if a serializer available. Same as `display(obj, metadata = serializer.get_metadata(obj))`

`Slides.serializer.get_func(obj_type)`

Get serializer function for a type. Returns None if not found.

Focus on what matters

- There is a zoom button on top bar which enables zooming of certain elements. This can be toggled by Z key.
- Most of supported elements are zoomable by default like images, matplotlib, bokeh, PIL image, altair plotly, dataframe, etc.
- You can also enable zooming for an object/widget by wrapping it inside `Slide`.

function conveniently. - You can also enable by manually adding

`zoom-self`, `zoom-child` classes to an element. To prevent zooming under as `zoom-child` class, use `no-zoom` class.

Focus on Me 🕶️

- If zoom button is enabled, you can hover here to zoom in this part!
- You can also zoom in this part by pressing Z key while mouse is over this part.

SVG Icons

Icons that appear on buttons inslides (and their rotations) available to use in your slides as well besides standard ipywidgets icons.

arrow: → arrowb: ↗ arrowbd: ↘ arrowbl: ⬅ arrowbr: ↘ arrowbu: ↗ arrowd: ↓ arrowl: ← arrowr: → arrowu: ↑ bars: ≡ camera: 📷 chevron: > chevrong: ∨ chevronl: < chevronr: > chevronu: ^ circle: ○ close: ✕ code: </> columns: 📊 compress: ↗ dots: ⋮ edit: ✎ expand: ↗ info: ⓘ laser: 🎯 loading: ⌂ pause: ⏸ pencil: 🖋 play: ▶ refresh: ↻ rows: 📋 search: 🔍 settings: ⚙ stop: ■ win-maximize: 🖥 win-restore: 🖥 zoom-in: 🔍 zoom-out: 🔍

Python

```
1 import ipywidgets as ipw
2 btn = ipw.Button(description='Chevron-Down Icon', icon='chevrong')
3 self.write(btn)
```

Auto Slide Numbering

Use **-1** as placeholder to update slide number automatically.

- In Jupyter notebook, this will be updated to current slide number.
- In python file, it stays same.
- You need to run cell twice if creating slides inside a for loop while using -1.

Presentation Code

Python

```
1  def docs(self):
2      "Create presentation from docs of IPySlides."
3      self.close_view() # Close any previous view to speed up loading 10x faster on a
4      self.clear() # Clear previous content
5      self.create(range(22)) # Create slides faster
6
7      from ..core import Slides
8
9      self.set_citations({'A': 'Citation A', 'B': 'Citation B'}, mode = 'footnote')
10     self.settings.set_footer('IPySlides Documentation')
11
12     with self.build(0): # Title page
13         self.write(f'## IPySlides {self.version} Documentation\n### Creating slides
14         self.center(''
15             alert`Abdul Saboor`sup`1`, Unknown Authorsup`2`
```