

IPySlides 3.8.0 Documentation

Creating slides with IPySlides

Abdul Saboor¹, Unknown Author²

May 06, 2024

¹My University is somewhere in the middle of nowhere

²Their University is somewhere in the middle of nowhere

Table of contents

1. Introduction
2. Adding Slides and Content
3. Layout and Theme Settings
4. Useful Functions for Rich Content
5. Loading from File/Exporting to HTML
6. Advanced Functionality
7. Presentation Code

This is summary of current
section

Oh we can use inline columns

Column A

Column B

here and what not!

Markdown

```
1  ```toc Table of contents
2  Extra content for current section which is on right
3  ```
```

Main App

`Slides(extensions=[], auto_focus=True)`

Interactive Slides in IPython Notebook. Only one instance can exist. `auto_focus` can be reset from settings and enable jumping back to slides after a cell is executed.

To suppress unwanted print from other libraries/functions, use:

```
1 with slides.suppress_stdout():
2     some_function_that_prints() # This will not be printed
3     print('This will not be printed either')
4     display('Something') # This will be printed
```

✦ Info

The methods under settings starting with `Slides.settings.set_` returns settings back to enable chaining without extra typing, like
`Slides.settings.set_animation().set_layout()...`

💡 Tip

- Use `Slides.instance()` class method to keep older settings. `Slides()` apply default settings every time.
- Run `slides.demo()` to see a demo of some features.
- Run `slides.doc()` to see documentation.

Adding Slides



Note

Besides functions below, you can add slides with `%%title/%%slide` magics as well.

`Slides.title()`

Use this context manager to write title. It is equivalent to `%%title` magic.

`Slides.slide()`

`Slides.frames(slide_number, *objs, repeat=False)`

Decorator for inserting frames on slide, define a function with two arguments acting on each obj in objs and current frame index. You can also call it as a function, e.g. `.frames(1,*objs)()` because it can write by default.

```
1 @slides.frames(1,a,b,c) # slides 1.1, 1.2, 1.3 with content a,b,c
2 def f(obj, idx):
3     do_something(obj)
4     if idx == 0: # Main Slide
5         print('This is main slide')
6     else:
7         print('This is frame', idx)
8
9 slides.frames(1,a,b,c)() # Auto writes the frames with same content as above
```

```
1 self.write(self.fmt('{self.version!r}' '{self.xmd_syntax}'))
```

'3.8.0'

Extended Markdown

Extended syntax for markdown is constructed to support almost full presentation from Markdown.

Following syntax works only under currently building slide:

- **notes**`This is slide notes` to add notes to current slide
- **cite**`key` to add citation to current slide. citations are automatically added in suitable place and should be set once using `Slides.set_citations` function.
- With citations mode set as 'footnote', you can add **refs**`ncol` to add citations anywhere on slide. If ncol is not given, it will be picked from layout settings.
- **section**`content` to add a section that will appear in the table of contents.
- **toc**`Table of content header text` to add a table of contents. For block type toc, see below.
- **proxy**`placeholder text` to add a proxy that can be updated later with `Slides.proxies[index].capture contextmanager`. Useful to keep placeholders for plots in markdwon.
- **peoxy**`[Button Text]` to add a proxy that can be replaced by pasting image from clipboard later.
- Triple dashes `---` is used to split markdown text in slides inside `from_markdown(start, content)` function.
- Double dashes `--` is used to split markdown text in frames

Adding Content



Note

Besides functions below, you can add content to slides with `%%xmd,%xmd` as well.

Slides.write(*objs, widths=None)

Write objs to slides in columns. To create rows in a column, wrap objects in a list or tuple. You can optionally specify widths as a list of percentages for each column.

Write any object that can be displayed in a cell with some additional features:

- Strings will be parsed as extended markdown that can have citations/python code blocks/javascript etc.
- Display another function in order by passing it to a lambda function like `lambda: func()`. Only body of the function will be displayed/printed. Return value will be ignored.
- Display IPython widgets such as `ipywidgets` or `ipyvolume` by passing them directly.
- Display Axes/Figure from libraries such as `matplotlib`, `plotly`, `altair`, `bokeh`, `ipyvolume` etc. by passing them directly.
- Display source code of functions/classes/modules or other languages by passing them directly or using `Slides.code` API.
- Use `Slides.alt(widget, func)` function to display widget on slides and alternative content in exported slides, function should return possible HTML representation of widget.
- `ipywidgets.HTML` and its subclasses will be displayed as `Slides.alt(widget, html_converter_func)`. The value of exported HTML will be most recent.

Adding Speaker Notes

Skip to Dynamic Content

Note

You can use `notes`notes content`` in markdown.

Danger

This is experimental feature, and may not work as expected.

`Slides.notes.display()`

`Slides.notes.insert(content)`

Add notes to current slide. Content could be any object except javascript and interactive widgets.

Tip

In markdown, you can use `notes`notes content``.

Displaying Source Code

`Slides.code.cast(obj, language='python', name=None, **kwargs)`

Create source code object from file, text or callable. kwargs are passed to `ipyslides.formatter.highlight`.

`Slides.code.context(returns=False, **kwargs)`

Execute and displays source code in the context manager. kwargs are passed to `ipyslides.formatter.highlight` function. Useful when source is written inside context manager itself. If `returns` is `False` (by default), then source is displayed before the output of code. Otherwise you can assign the source to a variable and display it later anywhere.

Usage:

```
1 with source.context(returns = True) as s: #if not used as `s`, still it is stored `s`
2     do_something()
3     write(s) # or s.display(), write(s)
4
5 #s.raw, s.value are accesible attributes.
6 #s.focus_lines, s.show_lines are methods that are used to show selective lines.
```

`Slides.code.from_callable(callable, **kwargs)`

Returns source object from a given callable [class,function,module,method etc.] with `show_lines`

Contents

1. Introduction
2. Adding Slides and Content
3. Layout and **Theme** Settings
4. Useful Functions for Rich Content
5. Loading from File/Exporting to HTML
6. Advanced Functionality
7. Presentation Code

Layout and Theme Settings

`Slides.settings.get_footer(slide, update_widget=False)`

Get footer text. `slide` is a slide object.

`Slides.settings.set_animation(main='slide_h', frame='appear')`

Set animation for slides and frames.

`Slides.settings.set_bg_image(src=None, opacity=0.25, blur_radius=None)`

Adds glassmorphic effect to the background with image. `src` can be a url or a local image path.

`Slides.settings.set_code_theme(style='default', color=None, background=None, hover_color='var(--hover-bg)',
lineno=True)`

Set code style CSS. Use background for better view of your choice. This is overwritten by theme change.

`Slides.settings.set_css(css_dict={})`

Set CSS for all slides. This loads on slides navigation, so you can include keyframes animations as well. Individual slide's CSS set by `slides[index].set_css` will override this. `css_dict` is a nested dict of css selectors and properties. There are few special rules in `css_dict`:

- All nested selectors are joined with space, so `'.A': {'.B': ... }` becomes `'.A .B {...}'` in CSS.

Useful Functions for Rich Content

`Slides.clipboard_image(filename, quality=95, overwrite=False)`

Save image from clipboard to file with a given quality. On next run, it loads from saved file under `notebook-dir/.ipyslides-assets/clips`. Useful to add screenshots from system into IPython. You can use overwrite to overwrite existing file. You can add saved clips using a "clip:" prefix in path in `Slides.image("clip:filename.png")` function and also in markdown.

- Output can be directly used in write command.
- Converts to PIL image using `.to_pil()`.
- Convert to HTML representation using `.to_html()`.
- Convert to Numpy array using `.to_numpy()` in RGB format that you can plot later.

`Slides.alt(widget, func)`

Display widget for slides and output of `func(widget)` will be and displayed only in exported formats as HTML. `func` should return possible HTML representation (provided by user) of widget as string.



Python

```
1 import ipywidgets as ipw
2 slides = get_slides_instance()
3 slides.alt(ipw.IntSlider(), lambda w: f'<input type="range" min="{w.min}" max="{w.max}" value="{w.value}" />')
```

Citations and Sections

Use syntax `citekey`` to add citations which should be already set by `Slides.set_citations(data, mode)` method. Citations are written on suitable place according to given mode. Number of columns in citations are determined by `Slides.settings.set_layout(..., ncol_refs = int)`.¹

Add sections in slides to separate content by `sectiontext``. Corresponding table of contents can be added with `toctitle`/toc title\n summary of current section \n``.

`Slides.set_citations(data, mode='footnote')`

Set citations from dictionary or file that should be a JSON file with citations keys and values, key should be cited in markdown as `citekey``. mode for citations should be one of `['inline', 'footnote']`. Number of columns in citations are determined by `Slides.settings.set_layout(..., ncol_refs=N)`.



Note

- You should set citations in start if using voila or python script. Setting in start in notebook is useful as well.
- Citations are replaced with new ones, so latest use of this function represents available citations.

1. Citation A

Dynamic Content

`Slides.on_refresh(func)`

Decorator for inserting dynamic content on slide, define a function with no arguments. Content updates when `slide.update_display` is called or when `Slides.refresh` is called.



Tip

You can use it to dynamically fetch a value from a database or API while presenting, without having to run the cell again.



Note

- No return value is required. If any, should be like `display('some value')`, otherwise it will be ignored.
- A slide with dynamic content enables a refresh button in bottom bar.
- All slides with dynamic content are updated when refresh button in top bar is clicked.







Python

```
1 import time
2 slides = get_slides_instance() # Get slides instance, this is to make doctring running
3 source.display() # Display source code of the block
4 @slides.on_refresh
5 def update_time():
6     print('Local Time: {3}:{4}:{5}'.format(*time.localtime())) # Print time in HH:MM:SS
```

Content Styling

You can **style** or **colorize** your *content* and *text*. Provide **CSS** for that using `.format_css` or use some of the available styles. See these **styles** with `.css_styles` property as below:

Use any or combinations of these styles in `className` argument of writing functions:

className	Formatting Style
'text-[value]'	[value] should be one of tiny, small, big, large, huge.
'align-[value]'	[value] should be one of center, left, right.
'rtl'	اردو عربی
'info'	Blue text. Icon  for note-info class.
'tip'	Blue Text. Icon  for note-tip class.
'warning'	Orange Text. Icon  for note-warning class.
'success'	Green text. Icon  for note-success class.
'error'	Red Text. Icon  for note-error class.
'note'	 Text with note icon.
'export-only'	Hidden on main slides, but will appear in exported slides.
'jupyter-only'	Hidden on exported slides, but will appear on main slides.
'block'	Block of text/objects
'block-[color]'	Block of text/objects with specific background color from red, green, blue, yellow, cyan, magenta and gray.
..

Python

```
1 self.write(('You can style{.error} or color[teal]'colorize' your content{:  
2         'Provide CSS{.info} for that using .format_css or use some of the avai  
3         'See these styles{.success} with .css_styles property as below:'))
```

Highlighting Code

pygments is used for syntax highlighting ¹. You can **highlight** code using `highlight` function ² or within markdown like this:

Python

```
1 import ipyslides as isd
```

Javascript

```
1 import React, { Component } from "react";
```

Markdown

```
1 ## Highlighting Code
2 [pygments](https://pygments.org/) is used for syntax highlighting cite`A`.
3 You can highlight{.error} code using 'highlight' function cite`B` or within m
4 ```python
5 import ipyslides as isd
6 ```
7 ```javascript
8 import React, { Component } from "react";
9 ```
10 proxy`source code of slide will be updated here later using slide_handle.proxies
```

1. Citation A

2. Citation B

Loading from File/Exporting to HTML



Note

You can parse and view a markdown file. The output you can save by exporting notebook in other formats.

`Slides.sync_with_file(start, path, trusted=False, interval=500)`

Auto update slides when content of markdown file changes. You can stop syncing using `Slides.unsync` function. interval is in milliseconds, 500 ms default. Read `Slides.from_markdown` docs about content of file.

The variables inserted in file content are used from top scope.

`Slides.from_markdown(start, content, trusted=False)`

You can create slides from a markdown tex block as well. It creates slides `start + (0,1,2,3...)` in order. You should add more slides by higher number than the number of slides in the file/text, or it will overwrite.

- Slides separator should be `---` (three dashes) in start of line.
- Frames separator should be `--` (two dashes) in start of line. All markdown before first `--` will be written on all frames.
- In case of frames, you can add `%++` (percent plus plus) in the content to add frames incrementally.
- You can use frames separator `--` inside `multicol` to make columns span multiple frames with

Contents

1. Introduction
2. Adding Slides and Content
3. Layout and **Theme** Settings
4. Useful Functions for **Rich Content**
5. Loading from File/Exporting to HTML
- 6. Advanced Functionality**
7. Presentation Code

Adding User defined Objects/Markdown Extensions

I will be on
exported slides

Python

```
1 self.write('## Adding User defined Objects/Markdown Extension:
2 self.write(
3     lambda: display(self.html('h3','I will be on main slides'
4     metadata = {'text/html': '<h3 class="warning">I will be o
5     s.get_source(), widths = [1,3]
6 )
7 self.write('If you need to serialize your own or third party (
8 self.doc(self.serializer,'Slides.serializer', members = True,
9 self.write('**You can also extend markdown syntax** using `ma
10 self.doc(self.extender,'Slides.extender', members = True, its
```



Note

If you need to serialize your own or third party objects not serialized by this module, you can use `@Slides.serializer.register` to serialize them to html.

`Slides.serializer.display(obj)`


















Display an object with metadata if a serializer available. Same as `display(obj, metadata = serializer.get_metadata(obj))`

`Slides.serializer.get_func(obj_type)`

Get serializer function for a type. Returns None if not found

Keys and Shortcuts

- You can use `Slides.current` to access a slide currently in view.
- You can use `Slides.running` to access the slide currently being built, so you can set CSS, animations etc.

Shortcut	Button	Action
<code>_</code> / <code>▶</code>	 , 	Move to next slide
<code>Ctrl</code> + <code>_</code> / <code>◀</code>	 , 	Move to previous slide
<code>Ctrl</code> + <code>0</code> / <code>0</code>	 / 	Jump to Star/End of slides
<code>Ctrl</code> + <code>[1-9]</code> / <code>[1-9]</code>		Shift <code>[1-9]</code> slides left/right
<code>Z</code>	 , 	Toggle objects zoom mode
<code>S</code>		Take screenshot
<code>F</code>	 , 	Toggle fullscreen
<code>Esc</code>		Exit fullscreen
<code>V</code>	 , 	Toggle fit to viewport [voila only]
<code>G</code>	 , 	Toggle settings panel
<code>E</code>	<code></></code>	Edit Source Cell of Current Slide
<code>L</code>	 , 	Toggle LASER pointer
<code>K</code>		Show keyboard shortcuts

Focus on what matters




























- There is a zoom button on top bar which enables zooming of certain elements. This can be toggled by Z key.
- Most of supported elements are zoomable by default like images, matplotlib, bokeh, PIL image, altair plotly, dataframe, etc.
- You can also enable zooming for an object/widget by wrapping it inside `Slide.enable_zoom` function conveniently.
- You can also enable by manually adding `zoom-self`, `zoom-child` classes to an element. To prevent zooming under as `zoom-child` class, use `no-zoom` class.

Focus on Me 🕶️

- If zoom button is enabled, you can hover here to zoom in this part!
- You can also zoom in this part by pressing Z key while mouse is over this part.

SVG Icons

Icons that appear on buttons inslides (and their rotations) available to use in your slides as well.

chevron:  pencil:  bars:  arrow:  arrow-bar:  close:  dots:  expand:  compress: 
camera:  play:  pause:  stop:  loading:  circle:  info:  refresh:  laser:  zoom-in:  zoom-out:  search:  code:  win-maximize:  win-restore:  rows:  columns: 
settings: 

Python

```
1 import ipywidgets as ipw
2 btn = ipw.Button(description='Chevron-Down', icon='plus').add_class('MyIcon') # Any
3 self.write(btn)
4 self.format_css({'MyIcon .fa.fa-plus': self.icon('chevron', color='crimson', size=':')}
```

Auto Slide Numbering in Python Scripts

`Slides.AutoSlides()`

Returns a named tuple `AutoSlides(get_next_number, title, slide, frames, from_markdown)` if run from inside a python script. Functions inside this tuple replace main functions while removing the 'slide_number' parameter. Useful to handle auto numbering of slides inside a sequentially running script. Call at top of script before adding slides.

Alert

Returns `None` in Jupyter's context and it is not useful there due to lack of sequence.

```
1 import ipyslides as isd
2 slides = isd.Slides()
3 auto = slides.AutoSlides() # Call at top of script
4
5 with auto.slide() as s:
6     slides.write(f'This is slide {s.number}')
```

Use `auto.title`, `auto.slide` contextmanagers, `auto.frames` decorator and `auto.from_markdown` function without thinking about what should be slide number.

Presentation Code

Python

```
1 def docs(self):
2     "Create presentation from docs of IPySlides."
3     self.close_view() # Close any previous view to speed up loading 10x faster on a
4     self.clear() # Clear previous content
5     self.create(*range(23)) # Create slides faster
6
7     from ..core import Slides
8
9     self.set_citations({'A': 'Citation A', 'B': 'Citation B'}, mode = 'footnote')
10    self.settings.set_footer('IPySlides Documentation')
11
12    auto = self.AutoSlides() # Does not work inside notebook (should not as well)
13
14    with auto.title(): # Title
15        self.write(f'## IPySlides {self.version} Documentation\n### Creating slides
```

Interact Demo!

Only output is exported, not control widgets. Latest state is exported!

10

Python

```
1 import ipywidgets as ipw
2 @ipw.interact(x = 5)
3 def f(x):
4     print("Interact Demo!\nOnly output is exported, not control widgets. Latest state is exported!")
5     print(x)
6
7 slides.running.get_source()
```