

# IPySlides 3.9.7 Documentation

## Creating slides with IPySlides

Abdul Saboor<sup>1</sup>, Unknown Author<sup>2</sup>

May 29, 2024

<sup>1</sup>My University is somewhere in the middle of nowhere

<sup>2</sup>Their University is somewhere in the middle of nowhere

# Table of contents

1. Introduction
2. Adding Slides and Content
3. Layout and Theme Settings
4. Useful Functions for Rich Content
5. Loading from File/Exporting to HTML
6. Advanced Functionality
7. Presentation Code

This is summary of current  
section

Oh we can use inline columns

Column A

Column B

here and what not!

## Markdown

```
1  ```toc Table of contents
2  Extra content for current section which is on right
3  ```
```

# Main App

**Slides**(extensions=[], auto\_focus=True, \*\*settings)

Interactive Slides in IPython Notebook. Only one instance can exist. `auto_focus` can be reset from settings and enable jumping back to slides after a cell is executed. settings are passed to `Slides.settings.apply` if you like to set during initialization.

To suppress unwanted print from other libraries/functions, use:

```
1 with slides.suppress_stdout():
2     some_function_that_prints() # This will not be printed
3     print('This will not be printed either')
4     display('Something') # This will be printed
```

## Info

The methods under settings starting with `Slides.settings.set_` returns settings back to enable chaining without extra typing, like `Slides.settings.set_animation().set_layout()...`

## Tip

- Use `Slides.instance()` class method to keep older settings. `Slides()` apply default settings every time.
- Run `slides_demo()` to see a demo of some features

# Adding Slides



## Note

Besides functions below, you can add slides with `%%title`/`%%slide` magics as well.

### `Slides.title()`

Use this context manager to write title. It is equivalent to `%%title` magic.

### `Slides.slide(slide_number)`

Use this context manager to generate any number of slides from a cell. It is equivalent to `%%slide` magic.



## Info

Use this function with `'next_'` prefix to enable auto numbeing of slides inside python file.

### `Slides.frames(slide_number, *objs, repeat=False)`

Decorator for inserting frames on slide, define a function with two arguments (`frame_index`, `frame_content`). You can also call it as a function, e.g. `.frames(1,*objs)(<optional function>)`.

```
1 @slides.frames(1,a,b,c) # slides 1.1, 1.2, 1.3 with content a,b,c
2 def f(frame_index, frame_content):
3     do_something(frame_content)
4     if frame_index == 0: # Main Slide
```

```
1 self.write(self.fmt('{self.version!r}' '{self.xmd_syntax}'))
```

'3.9.7'

## Extended Markdown

Extended syntax for markdown is constructed to support almost full presentation from Markdown.

Following syntax works only under currently building slide:

- **notes**`This is slide notes` to add notes to current slide
- **cite**`key` to add citation to current slide. citations are automatically added in suitable place and should be set once using `Slides.set_citations` function.
- With citations mode set as 'footnote', you can add **refs**`ncol` to add citations anywhere on slide. If ncol is not given, it will be picked from layout settings.
- **section**`content` to add a section that will appear in the table of contents.
- **toc**`Table of content header text` to add a table of contents. For block type toc, see below.
- **proxy**`placeholder text` to add a proxy that can be updated later with `Slides.proxies[index].capture contextmanager`. Useful to keep placeholders for plots in markdwon.
- **peoxy**`[Button Text]` to add a proxy that can be replaced by pasting image from clipboard later.
- Triple dashes `---` is used to split markdown text in slides inside `from_markdown(start, content)` function.
- Double dashes `--` is used to split markdown text in frames

# Adding Content



## Note

Besides functions below, you can add content to slides with `%%xmd,%xmd` as well.

**Slides.write**(\*objs, widths=None)

Write objs to slides in columns. To create rows in a column, wrap objects in a list or tuple. You can optionally specify widths as a list of percentages for each column.

Write any object that can be displayed in a cell with some additional features:

- Strings will be parsed as extended markdown that can have citations/python code blocks/javascript etc.
- Display another function in order by passing it to a lambda function like `lambda: func()`. Only body of the function will be displayed/printed. Return value will be ignored.
- Display IPython widgets such as `ipywidgets` or `ipyvolume` by passing them directly.
- Display Axes/Figure from libraries such as `matplotlib`, `plotly`, `altair`, `bokeh`, `ipyvolume` etc. by passing them directly.
- Display source code of functions/classes/modules or other languages by passing them directly or using `Slides.code` API.
- Use `Slides.alt(widget, func)` function to display widget on slides and alternative content in exported slides, function should return possible HTML representation of widget.
- `ipywidgets.HTML` and its subclasses will be displayed as `Slides.alt(widget, html_converter_func)`. The value of exported HTML will be most recent.

# Adding Speaker Notes

Skip to Dynamic Content

## Note

You can use `notes`notes content`` in markdown.

## Danger

This is experimental feature, and may not work as expected.

`Slides.notes.display()`

`Slides.notes.insert(content)`

Add notes to current slide. Content could be any object except javascript and interactive widgets.

## Tip

In markdown, you can use `notes`notes content``.

# Displaying Source Code

`Slides.code.cast(obj, language='python', name=None, **kwargs)`

Create source code object from file, text or callable. kwargs are passed to `ipyslides.formatter.highlight`.

`Slides.code.context(returns=False, **kwargs)`

Execute and displays source code in the context manager. kwargs are passed to `ipyslides.formatter.highlight` function. Useful when source is written inside context manager itself. If `returns` is `False` (by default), then source is displayed before the output of code. Otherwise you can assign the source to a variable and display it later anywhere.

## Usage:

```
1 with source.context(returns = True) as s: #if not used as `s`, still it is stored `s`
2     do_something()
3     write(s) # or s.display(), write(s)
4
5 #s.raw, s.value are accesible attributes.
6 #s.focus_lines, s.show_lines are methods that are used to show selective lines.
```

`Slides.code.from_callable(callable, **kwargs)`

Returns source object from a given callable [class,function,module,method etc.] with `show_lines`



# Contents

1. Introduction
2. Adding Slides and Content
3. Layout and **Theme** Settings
4. Useful Functions for Rich Content
5. Loading from File/Exporting to HTML
6. Advanced Functionality
7. Presentation Code

# Layout and Theme Settings

`Slides.settings.apply(**settings)`

Apply multiple settings at once. Top level keys should be function names without 'set\_' and values should be dictionary of parameters to that function. For example:

```
1 Slides.settings.apply(  
2     layout = {"aspect":1.6, "scroll":False},  
3     footer = {0:"footer text", "numbering":True} # 0 key goes to first positional arg  
4 )
```

`Slides.settings.set_animation(main='slide_h', frame='appear')`

Set animation for slides and frames.

`Slides.settings.set_bg_image(src=None, opacity=0.25, blur_radius=None)`

Adds glassmorphic effect to the background with image. src can be a url or a local image path.

`Slides.settings.set_code_theme(style='default', color=None, background=None, hover_color='var(--hover-bg)',  
lineno=True)`

Set code style CSS. Use background for better view of your choice. This is overwritten by theme change.

# Useful Functions for Rich Content

**Slides.clipboard\_image**(filename, quality=95, overwrite=False)

Save image from clipboard to file with a given quality. On next run, it loads from saved file under `notebook-dir/.ipyslides-assets/clips`. Useful to add screenshots from system into IPython. You can use overwrite to overwrite existing file. You can add saved clips using a "clip:" prefix in path in `Slides.image("clip:filename.png")` function and also in markdown.

- Output can be directly used in write command.
- Converts to PIL image using `.to_pil()`.
- Convert to HTML representation using `.to_html()`.
- Convert to Numpy array using `.to_numpy()` in RGB format that you can plot later.

**Slides.alt**(widget, func)

Display widget for slides and output of `func(widget)` will be and displayed only in exported formats as HTML. `func` should return possible HTML representation (provided by user) of widget as string.



Python

```
1 import ipywidgets as ipw
2 slides = get_slides_instance()
3 slides.alt(ipw.IntSlider(), lambda w: f'<input type="range" min="{w.min}" max="{w.max}" value="{w.value}" />')
```

# Citations and Sections

Use syntax `citekey`` to add citations which should be already set by `Slides.set_citations(data, mode)` method. Citations are written on suitable place according to given mode. Number of columns in citations are determined by `Slides.settings.set_layout(..., ncol_refs = int)`.<sup>1</sup>

Add sections in slides to separate content by `sectiontext``. Corresponding table of contents can be added with `toctitle`/toc title\n summary of current section \n``.

`Slides.set_citations(data, mode='footnote')`

Set citations from dictionary or file that should be a JSON file with citations keys and values, key should be cited in markdown as `citekey``. mode for citations should be one of `['inline', 'footnote']`. Number of columns in citations are determined by `Slides.settings.set_layout(..., ncol_refs=N)`.



## Note

- You should set citations in start if using voila or python script. Setting in start in notebook is useful as well.
- Citations are replaced with new ones, so latest use of this function represents available citations.

---

1. Citation A

# Dynamic Content

## `Slides.on_refresh(func)`

Decorator for inserting dynamic content on slide, define a function with no arguments. Content updates when `slide.update_display` is called or when `Slides.refresh` is called.



### Tip

You can use it to dynamically fetch a value from a database or API while presenting, without having to run the cell again.



### Note

- No return value is required. If any, should be like `display('some value')`, otherwise it will be ignored.
- A slide with dynamic content enables a refresh button in bottom bar.
- All slides with dynamic content are updated when refresh button in top bar is clicked.







## Python

```
1 import time
2 slides = get_slides_instance() # Get slides instance, this is to make doctring running
3 source.display() # Display source code of the block
4 @slides.on_refresh
5 def update_time():
6     print('Local Time: {3}:{4}:{5}'.format(*time.localtime())) # Print time in HH:MM:SS
```

# Content Styling

You can **style** or **colorize** your *content* and *text*. Provide **CSS** for that using `.format_css` or use some of the available styles. See these **styles** with `.css_styles` property as below:

Use any or combinations of these styles in `className` argument of writing functions:

className	Formatting Style
'text-[value]'	[value] should be one of tiny, small, big, large, huge.
'align-[value]'	[value] should be one of center, left, right.
'rtl'	اردو عربی
'info'	Blue text. Icon  for note-info class.
'tip'	Blue Text. Icon  for note-tip class.
'warning'	Orange Text. Icon  for note-warning class.
'success'	Green text. Icon  for note-success class.
'error'	Red Text. Icon  for note-error class.
'note'	 Text with note icon.
'export-only'	Hidden on main slides, but will appear in exported slides.
'jupyter-only'	Hidden on exported slides, but will appear on main slides.
'block'	Block of text/objects
'block-[color]'	Block of text/objects with specific background color from red, green, blue, yellow, cyan, magenta and gray.
.. ..	.. ..

Python

```
1 self.write(('You can style{.error} or color[teal]'colorize' your content{:  
2         'Provide CSS{.info} for that using '.format_css' or use some of the avai  
3         'See these styles{.success} with '.css_styles' property as below:'))
```

# Highlighting Code

pygments is used for syntax highlighting <sup>1</sup>. You can **highlight** code using `highlight` function <sup>2</sup> or within markdown like this:

Python

```
1 import ipyslides as isd
```

Javascript

```
1 import React, { Component } from "react";
```

Markdown

```
1 ## Highlighting Code
2 [pygments](https://pygments.org/) is used for syntax highlighting cite`A`.
3 You can highlight{.error} code using 'highlight' function cite`B` or within m
4 ```python
5 import ipyslides as isd
6 ```
7 ```javascript
8 import React, { Component } from "react";
9 ```
10 proxy`source code of slide will be updated here later using slide_handle.proxies
```

1. Citation A

2. Citation B

# Loading from File/Exporting to HTML



## Note

You can parse and view a markdown file. The output you can save by exporting notebook in other formats.

`Slides.sync_with_file(start, path, trusted=False, interval=500)`

Auto update slides when content of markdown file changes. You can stop syncing using `Slides.unsync` function. interval is in milliseconds, 500 ms default. Read `Slides.from_markdown` docs about content of file.

The variables inserted in file content are used from top scope.

`Slides.from_markdown(start, content, trusted=False)`

You can create slides from a markdown tex block as well. It creates slides `start + (0,1,2,3...)` in order. You should add more slides by higher number than the number of slides in the file/text, or it will overwrite.

- Slides separator should be `---` (three dashes) in start of line.
- Frames separator should be `--` (two dashes) in start of line. All markdown before first `--` will be written on all frames.
- In case of frames, you can add `%++` (percent plus plus) in the content to add frames incrementally.
- You can use frames separator `--` inside `multicol` to make columns span multiple frames with



# Contents

1. Introduction
2. Adding Slides and Content
3. Layout and **Theme** Settings
4. Useful Functions for **Rich Content**
5. Loading from File/Exporting to HTML
- 6. Advanced Functionality**
7. Presentation Code

# Adding User defined Objects/Markdown Extensions

I will be on  
exported slides

Python

```
1 self.write('## Adding User defined Objects/Markdown Extension:
2 self.write(
3     lambda: display(self.html('h3','I will be on main slides'
4     metadata = {'text/html': '<h3 class="warning">I will be o
5     s.get_source(), widths = [1,3]
6 )
7 self.write('If you need to serialize your own or third party (
8 self.doc(self.serializer,'Slides.serializer', members = True,
9 self.write('**You can also extend markdown syntax** using `ma
10 self.doc(self.extender,'Slides.extender', members = True, its
```



## Note

If you need to serialize your own or third party objects not serialized by this module, you can use `@Slides.serializer.register` to serialize them to html.

`Slides.serializer.display(obj)`


















Display an object with metadata if a serializer available. Same as `display(obj, metadata = serializer.get_metadata(obj))`

`Slides.serializer.get_func(obj_type)`

Get serializer function for a type Returns None if not found

# Keys and Shortcuts

- You can use `Slides.current` to access a slide currently in view.
- You can use `Slides.running` to access the slide currently being built, so you can set CSS, animations etc.

Shortcut	Button	Action
<code>_</code> / <code>▶</code>	 , 	Move to next slide
<code>Ctrl</code> + <code>_</code> / <code>◀</code>	 , 	Move to previous slide
<code>Ctrl</code> + <code>0</code> / <code>0</code>	 / 	Jump to Star/End of slides
<code>Ctrl</code> + <code>[1-9]</code> / <code>[1-9]</code>		Shift <code>[1-9]</code> slides left/right
<code>Z</code>	 , 	Toggle objects zoom mode
<code>S</code>		Take screenshot
<code>F</code>	 , 	Toggle fullscreen
<code>Esc</code>		Exit fullscreen
<code>V</code>	 , 	Toggle fit to viewport [voila only]
<code>G</code>	 , 	Toggle settings panel
<code>E</code>	<code>&lt;/&gt;</code>	Edit Source Cell of Current Slide
<code>L</code>	 , 	Toggle LASER pointer
<code>K</code>		Show keyboard shortcuts

## Focus on what matters




























- There is a zoom button on top bar which enables zooming of certain elements. This can be toggled by Z key.
- Most of supported elements are zoomable by default like images, matplotlib, bokeh, PIL image, altair plotly, dataframe, etc.
- You can also enable zooming for an object/widget by wrapping it inside `Slide.enable_zoom` function conveniently.
- You can also enable by manually adding `zoom-self`, `zoom-child` classes to an element. To prevent zooming under as `zoom-child` class, use `no-zoom` class.

### Focus on Me 🕶️

- If zoom button is enabled, you can hover here to zoom in this part!
- You can also zoom in this part by pressing Z key while mouse is over this part.

# SVG Icons

Icons that appear on buttons inslides (and their rotations) available to use in your slides as well.

chevron:  pencil:  bars:  arrow:  arrow-bar:  close:  dots:  expand:  compress:   
camera:  play:  pause:  stop:  loading:  circle:  info:  refresh:  laser:  zoom-in:  zoom-out:  search:  code:  win-maximize:  win-restore:  rows:  columns:   
settings: 

## Python

```
1 import ipywidgets as ipw
2 btn = ipw.Button(description='Chevron-Down', icon='plus').add_class('MyIcon') # Any
3 self.write(btn)
4 self.format_css({'MyIcon .fa.fa-plus': self.icon('chevron', color='crimson', size=':')}
```

# Auto Slide Numbering in Python Scripts

`Slides.next_slide()`

See docs of `slide` excpet need of a slide number.

`Slides.next_frames(*objs, repeat=False)`

See docs of `frames` excpet need of a slide number.

`Slides.next_from_markdown(content, trusted=False)`

See docs of `from_markdown` excpet need of a slide number.

`Slides.next_number()`

Get next slide number if need inside a `.py` file, e.g. in slide magic or explicit numbering.

# Presentation Code

Python

```
1 def docs(self):
2     "Create presentation from docs of IPySlides."
3     self.close_view() # Close any previous view to speed up loading 10x faster on a
4     self.clear() # Clear previous content
5     self.create(*range(23)) # Create slides faster
6
7     from ..core import Slides
8
9     self.set_citations({'A': 'Citation A', 'B': 'Citation B'}, mode = 'footnote')
10    self.settings.set_footer('IPySlides Documentation')
11
12    with self.title(): # Title
13        self.write(f'## IPySlides {self.version} Documentation\n### Creating slides
14        self.center(''
15            alert`Abdul Saboor`sup`1`, Unknown Authorsup`2`
```