

MAY 2024



GSURE Denoising enables training of higher quality generative priors for accelerated Multi-Coil MRI Reconstruction

Authors: **Asad Aali¹**, Marius Arvinte², Sidharth Kumar¹, Yamin Arefeen¹, Jon Tamir¹

¹The University of Texas at Austin


²Intel Labs



Motivation

- Deep learning based accelerated MRI reconstruction with Generative Models
 - ✓ Develops a prior with large training databases
 - ✓ Decouples from the forward model



Training Dataset



Motivation

- Generative models are powerful image generators


Sample from Gaussian Distribution





Motivation

- Generative models are powerful image generators

Sample from Gaussian Distribution




Sample from Image Distribution





Motivation

- Generative models are powerful image generators

Sample from Gaussian Distribution





Sample from Image Distribution




Motivation

- Generative models are powerful image generators

Sample from Gaussian Distribution



Sample from Image Distribution



Motivation

- Generative models are powerful image generators

Sample from Gaussian Distribution


$$\sim \mathcal{N}(z)$$

Image Prior

Sample from Image Distribution

$$\sim p(x)$$



Image Prior



Motivation

- Using Generative Models to guide accelerated MRI reconstructions.


"High
Probability
Images"




Motivation

- Using Generative Models to guide accelerated MRI reconstructions.

"High
Probability
Images"




Images that
match data



Motivation

- Using Generative Models to guide accelerated MRI reconstructions.


"High
Probability
Images"



Motivation

- Generative Models rely on large amounts of *high-quality data*.

Training Dataset




¹FastMRI (<https://fastmri.med.nyu.edu/>), ²Wang, MRM (2024)

Motivation

- Generative Models rely on large amounts of *high-quality data*.
- MRI data are *inherently noisy*^{1,2}.

Training Dataset




¹FastMRI (<https://fastmri.med.nyu.edu/>), ²Wang, MRM (2024)

Motivation

- Generative Models rely on large amounts of *high-quality data*.
- MRI data are *inherently noisy*^{1,2}.

Training Dataset




¹FastMRI (<https://fastmri.med.nyu.edu/>), ²Wang, MRM (2024)

Motivation

- Generative Models rely on large amounts of *high-quality data*.
- MRI data are *inherently noisy*^{1,2}.

Training Dataset




¹FastMRI (<https://fastmri.med.nyu.edu/>), ²Wang, MRM (2024)

Motivation

- Generative Models rely on large amounts of *high-quality data*.
- MRI data are *inherently noisy*^{1,2}.

Training Dataset




¹FastMRI (<https://fastmri.med.nyu.edu/>), ²Wang, MRM (2024)

Motivation

- Generative Models rely on large amounts of *high-quality data*.
- MRI data are *inherently noisy*^{1,2}.


Training Dataset



¹FastMRI (<https://fastmri.med.nyu.edu/>), ²Wang, MRM (2024)

Motivation



- Training generative models with noisy datasets leads to a poor prior.




Motivation

- Training generative models with noisy datasets leads to a poor prior.

Sample from Gaussian Distribution




Sample from Image Distribution




Motivation

- Training generative models with noisy datasets leads to a poor prior.

Sample from Gaussian Distribution




Sample from Image Distribution




Motivation

- Training generative models with noisy datasets leads to a poor prior.
- **Reconstruction performance depends on accuracy of priors**

Sample from Gaussian Distribution



Sample from Image Distribution



Motivation Application in real world datasets: low field neo-natal MRI

- Training generative models with noisy datasets leads to a poor prior.
- **Reconstruction performance depends on accuracy of priors**

Training Dataset




training

...


Generative
Model

Sample from Image Distribution




Purpose

- Use a learned denoiser to denoise the training dataset before training the generative model



Purpose

Training a learned denoiser without access clean training samples?



Purpose

Investigate the **feasibility** and **effectiveness** of self-supervised
denoising MRI samples as a pre-processing step to learning
generative priors for accelerated MRI reconstruction

Problem Formulation

Problem Formulation


Goal is to learn the **clean distribution** using *noisy* data (i.i.d Gaussian, with known power σ_w^2).

$$y = Ax + \text{noise}$$

Problem Formulation

Goal is to learn the **clean distribution** using *noisy* data (i.i.d Gaussian, with known power σ_w^2).

$$y = Ax + \text{noise}$$




Original K-Space

Problem Formulation

Goal is to learn the **clean distribution** using *noisy* data (i.i.d Gaussian, with known power σ_w^2).


$$y = Ax + \text{noise}$$



Problem Formulation

Goal is to learn the **clean distribution** using *noisy* data (i.i.d Gaussian, with known power σ_w^2).


$$y = Ax + \text{noise}$$




Proposed Methods

Proposed Methods


\hat{x}_{noisy}




Proposed Methods



Proposed Methods



Proposed Methods



Self-Supervised Denoising

Goal is to learn the **clean distribution** using *noisy* data (i.i.d Gaussian, with known power σ_w^2).

A is a Linear Forward Operator (Fully-Sampled) -> **GSURE**^{1,2,3}

$$y = FSx + \text{noise}$$

¹Soltanayev, NeurIPS, 2018, ²Eldar, IEEE Transactions on Signal Processing, 2008, ³Kawar, TMLR, 2023

Generalized SURE (GSURE) Basics

- GSURE¹: Self-supervised denoising technique, only need access to:
 - $\hat{x}_{noisy} \rightarrow \text{Noisy Samples}$
 - Noise **Covariance Matrix**
- An unbiased estimate of the MSE

$$E[\text{L}_{GSURE}] = E\|g_\phi(\hat{x}_{noisy}) - x\|$$


¹Yonina, *IEEE Transactions on Signal Processing*, 2008

Pre-Processing Noisy Dataset

- GSURE loss requires the **noise covariance** matrix
- **Pre-whitening** (noise covariance = I) makes computation relatively straight-forward


Pre-Processing Noisy Dataset

- GSURE loss requires the **noise covariance** matrix
- **Pre-whitening** (noise covariance = I) makes computation relatively straight-forward




Pre-Processing Noisy Dataset

- GSURE loss requires the **noise covariance** matrix
- **Pre-whitening** (noise covariance = I) makes computation relatively straight-forward




Pre-Processing Noisy Dataset

- GSURE loss requires the **noise covariance** matrix
- **Pre-whitening** (noise covariance = I) makes computation relatively straight-forward




Pre-Processing Noisy Dataset

- GSURE loss requires the **noise covariance** matrix
- **Pre-whitening** (noise covariance = I) makes computation relatively straight-forward




Pre-Processing Noisy Dataset

- GSURE loss requires the **noise covariance** matrix
- **Pre-whitening** (noise covariance = I) makes computation relatively straight-forward




GSURE Denoising - Summary



$$L_{GSURE} = \|g_\phi(u)\|^2 + 2 \left(Tr \left(\frac{\partial g_\phi(u)}{\partial u} \right) + g_\phi^T(u) \frac{\partial \ln q(u)}{\partial u} \right)$$

GSURE Training


Proposed Methods



Score-based generative models



Score-based generative models




Experiments

1. Evaluation of **Self-Supervised Denoising** (GSURE)
2. **Prior sampling** performance of score models trained on Noisy vs. GSURE Denoised data
3. **Posterior Reconstruction** performance of score models trained on Noisy vs. GSURE Denoised data


T2 Brain Scans

Original FastMRI




T2 Brain Scans

Original FastMRI



T2 Brain Scans

Original FastMRI




T2 Brain Scans

Original FastMRI

Original FastMRI

+

Additive Gaussian Noise




T2 Brain Scans

Original FastMRI

Original FastMRI

+

Additive Gaussian Noise




Knee Scans

Original FastMRI

Original FastMRI

+

Additive Gaussian Noise




Results

1. Evaluation of **Self-Supervised Denoising** (GSURE)
2. **Prior sampling** performance of score models trained on Noisy vs. GSURE Denoised data
3. **Posterior Reconstruction** performance of score models trained on Noisy vs. GSURE Denoised data

Prior Sampling

$p(x)$


Naive Score
~ 32dB




Prior Sampling

$p(x)$

Naive Score
~ 32dB




Naive Score
~ 22dB




Prior Sampling

$p(x)$


Naive Score
~ 32dB




Naive Score
~ 22dB



GSURE-Score
~ 32dB



GSURE-Score
~ 22dB




Results


1. Evaluation of **Self-Supervised Denoising** (GSURE)
2. **Prior sampling** performance of score models trained on Noisy vs. GSURE Denoised data
3. **Posterior Reconstruction** performance of score models trained on Noisy vs. GSURE Denoised data

Posterior Sampling $x \sim p(x|y)$

Fully-Sampled



R=5



Naive Score @ 22dB


GSURE-Score @ 22dB

Naive Score @ 32dB


GSURE-Score @ 32dB

Posterior Sampling $x \sim p(x|y)$


Fully-Sampled



Naive Score @ 22dB






GSURE-Score @ 22dB



Naive Score @ 32dB


GSURE-Score @ 32dB

R=5




Posterior Sampling $x \sim p(x|y)$


Fully-Sampled




Naive Score @ 22dB




GSURE-Score @ 22dB








Naive Score @ 32dB




GSURE-Score @ 32dB



R=5



Posterior Sampling $x \sim p(x|y)$



Discussion and Conclusion

1. Self-supervised denoising techniques can successfully **remove noise**
2. Denoising as a pre-processing step helps train more **accurate priors**
3. The benefit of denoising is more visible in **lower SNR** settings
4. Priors trained on denoised FastMRI are **better inverse problem solvers** than naive training
5. We see application in the low-field setting (neo-natal MRI)

Future Works

A is a Linear Forward Operator (**Fully-Sampled**) -> GSURE^{1,2,3}

$$y = FSx + \text{noise}$$

Assume A is a **Low-Rank** Forward Operator⁴

$$y = PFSx + \text{noise}$$

¹Soltanayev, *NeurIPS*, 2018, ²Eldar, *IEEE Transactions on Signal Processing*, 2008, ³Kawar, *TMLR*, 2023, ⁴Aali, AmbientDPS, *Arxiv*, 2024

Thank you!

Asad Aali

Email: asad.aali@utexas.edu

Website: <https://asad-aali.github.io/>

MS ECE Student, UT Austin



Source Code: <https://github.com/utcsilab/GsureScore-Diffusion.git>