

হাবিজাবি হিজিবিজবিজ

yet another হ জ ব র ল programming blog

- [প্রথম পাতা](#)
- [আমি](#)
- [কোড লাইব্রেরি](#)
- [অন্যান্য লিঙ্ক](#)
-

Type text to search here...

কোড লাইব্রেরি

আমার কনটেস্ট কোড লাইব্রেরি – কমন কিছু অ্যালগরিদমের স্কেলিটন কোড। অ্যালগরিদম সম্পর্কে কারো পর্যাপ্ত ধারণা না থাকলে তাকে এই কোড লাইব্রেরি এর কোড কপি করার ক্ষেত্রে নিরুৎসাহিত করা যাচ্ছে, কারণ সেক্ষেত্রে অধিকাংশ কোডই ঠিক মত কাজ করবে না। কোড গুলোর উপরে কমেন্ট সেকশন গুরুত্ব দিয়ে পড়ার জন্যও অনুরোধ থাকল, পরে প্রবলেমে পেনাল্টি খেলে আবার বলতে আসবেন না যে আমার এই কোড ভুয়া। এগুলা সবই অনেকবার টেস্ট করা কোড (টাইপিং মিসটেক থাকলে সেটা অন্য কথা, যদিও থাকার চাঞ্চ খুবই কম), ধন্যবাদ।

ইনডেক্সঃ

1. বিবিধ কোড
 - [কন্টেস্ট টেমপ্লেট](#)
 - [ফাস্ট রিডার](#)
 - [টাইম ট্র্যাকার](#)
 - [পপ কাউন্ট](#)
 - [হিস্টোগ্রাম প্রবলেম](#)
 - [ইনফাইনাইট চেসবোর্ডে নাইট ডিস্ট্যান্স](#)
2. স্ট্রিং
 - [টাই \(প্রিফিক্স ট্রি\)](#)
 - [টাই \(স্ট্যাটিক অ্যারে\)](#)
 - [সাফিক্স অ্যারে \(স্লো\)](#)
 - [সাফিক্স অ্যারে \(\$n \log n\$ \)](#)
 - [মিনিমাম এক্সপ্রেশন \(বো-জয়ান\)](#)
 - [কে.এম.পি](#)
 - [ম্যানাক্যার আলগোরিদম](#)
3. ম্যাথ
 - [জোসেফাস রিকারেন্স](#)
 - [শ্যাক্স'স বেবি স্টেপ জায়ান্ট স্টেপ](#)
 - [সেগমেন্টেড সিভ](#)
 - [এক্সটেন্ডেড ইউক্লিড ও মডুলার ইনভার্স](#)
4. জিওমেট্রি

- o [কনভেক্স হাল \(গ্রাহাম'স স্ক্যান\)](#)
- o [পয়েন্ট ইন কনভেক্স পলিগন](#)
- o [পলিগন এরিয়া \(2D\)](#)
- o [ক্লোজেস্ট পেয়ার](#)
- o [সার্কেল ইন্টারসেকশন এরিয়া](#)
- o [সেগমেন্ট ইন্টারসেকশন \(2D\)](#)
- o [টেটোহেড্রন ফরমুলা](#)

5. গ্রাফ

- o [স্ট্রিংলি কানেকটেড কম্পোনেন্ট \(টারজান\)](#)
- o [আটোকুলেশন পয়েন্ট](#)
- o [ব্রিজ](#)
- o [বাই কানেকটেড কম্পোনেন্ট](#)
- o [স্টেবল ম্যারিজ](#)
- o [ম্যাক্স ফ্লো \(ডিনিক\)](#)
- o [মিন কস্ট ম্যাক্স ফ্লো \(বেলম্যান ফোর্ড\)](#)
- o [ম্যাক্সিমাম বাইপারটাইট ম্যাচিং \(ডি.এফ.এস.\)](#)
- o [ম্যাক্সিমাম বাইপারটাইট ম্যাচিং \(হেপ্তক্রফট কার্প\)](#)
- o [হেভী লাইট ডিকম্পজিশন](#)
- o [টারজান'স অফলাইন এল.সি.এ](#)

6. ডাটা স্ট্রাকচার

- o [বাইনারি সার্চ](#)
- o [ডিসজেন্ট সেট](#)
- o [2D বি.আই.টি](#)

7. হ্যাশিং

- o [ডাবল হ্যাশিং](#)
- o [ম্যাপের সাহায্যে স্ট্রিং হ্যাশিং](#)
- o [বার্নস্টাইন স্ট্রিং হ্যাশিং](#)

কন্টেস্ট টেমপ্লেট [ইনডেক্স]

```

1  /*
2  USER: zobayer
3  TASK:
4  ALGO:
5  */
6
7  // #pragma warning (disable: 4786)
8  // #pragma comment (linker, "/STACK:0x8000000")
9  // #define _CRT_SECURE_NO_WARNINGS 1
10
11 #include <cassert>
12 #include <cctype>
13 #include <climits>
14 #include <cmath>
15 #include <cstdio>
16 #include <cstdlib>
17 #include <cstring>
18 #include <iostream>
19 #include <sstream>
```

Follow

Follow “হাবিজাবি
ইজিবিজিভিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

Sign me up

```

20 #include <iomanip>
21 #include <string>
22 #include <vector>
23 #include <list>
24 #include <set>
25 #include <map>
26 #include <stack>
27 #include <queue>
28 #include <algorithm>
29 #include <iterator>
30 #include <utility>
31 using namespace std;
32
33 template< class T > T _abs(T n) { return (n < 0 ? -n : n); }
34 template< class T > T _max(T a, T b) { return (!(a < b) ? a : b); }
35 template< class T > T _min(T a, T b) { return (a < b ? a : b); }
36 template< class T > T sq(T x) { return x * x; }
37
38 #define ALL(p) p.begin(),p.end()
39 #define MP(x, y) make_pair(x, y)
40 #define SET(p) memset(p, -1, sizeof(p))
41 #define CLR(p) memset(p, 0, sizeof(p))
42 #define MEM(p, v) memset(p, v, sizeof(p))
43 #define CPY(d, s) memcpy(d, s, sizeof(s))
44 #define READ(f) freopen(f, "r", stdin)
45 #define WRITE(f) freopen(f, "w", stdout)
46 #define SZ(c) (int)c.size()
47 #define PB(x) push_back(x)
48 #define ff first
49 #define ss second
50 #define i64 long long
51 #define ld long double
52 #define pii pair< int, int >
53 #define psi pair< string, int >
54
55 const double EPS = 1e-9;
56 const int INF = 0x7f7f7f7f;
57
58 int main() {
59     //READ("in.txt");
60     //WRITE("out.txt");
61     return 0;
62 }
```

ফাস্ট রিডার [ইনডেক্স]

```

1 /*
2 In gcc/g++ fread_unlocked() is even faster.
3 Can be made faster in non-object-oriented fashion
4 In contest, who cares dynamic allocation?
5 */
6
7 struct FastRead {
8     char *buff, *ptr;
9     FastRead(int size) {
10         buff = new char[size];
11     }
12     ~FastRead() {
13         delete [] buff;
14     }
15     char operator<<(char c) {
16         if (ptr == buff + size) {
17             fread(buff, 1, size, file);
18             ptr = buff;
19         }
20         return *ptr++;
21     }
22 };
23
24 int main() {
25     FastRead in("input.txt");
26     char c;
27     while ((c = in << c) != '\0') {
28         cout << c;
29     }
30 }
```

Follow “শাবিজাবি
হিজিবিজবিজ”

Get every new post delivered to
your inbox.

Join 67 other followers

Sign me up

```

11     ptr = buff;
12     fread(buff, 1, size, stdin);
13 }
14 ~FastRead() {
15     delete[] buff;
16 }
17 int nextInt() {
18     int ret = 0;
19     while(*ptr < '0' || *ptr > '9') ptr++;
20     do { ret = ret * 10 + *ptr++ - '0';
21     } while(*ptr >= '0' && *ptr <= '9');
22     return ret;
23 }
24 };

```

টাইম ট্র্যাকার [ইনডেক্স]

```

1 /*
2 Usage: Just create an instance of it at the start of the block of
3 which you want to measure running time. Reliable up to millisecond
4 scale. You don't need to do anything else, even works with freopen.
5 */
6
7 class TimeTracker {
8     clock_t start, end;
9 public:
10    TimeTracker() {
11        start = clock();
12    }
13 ~TimeTracker() {
14     end = clock();
15     fprintf(stderr, "%.3lf s\n", (double)(end - start) / CLOCKS_PER_SEC);
16 }
17 };

```

পপ কাউন্ট [ইনডেক্স]

```

1 /*
2 Counts number of set bits in an integer.
3 For 32 bit integer, delete 8 hex from const value
4 */
5
6 typedef __int64 INT;
7
8 const INT b1 = 0x5555555555555555;
9 const INT b2 = 0x3333333333333333;
10 const INT b4 = 0x0f0f0f0f0f0f0f0f;
11 const INT b8 = 0x00ff00ff00ff00ff;
12 const INT b16 = 0x0000ffff0000ffff;
13 const INT b32 = 0x00000000ffffffff;
14
15 int popcount(INT x) {
16     x = (x & b1) + ((x >> 1) & b1); // 2 bit

```

[Follow](#)

Follow “**শাবিজাবি**
হিজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

```

17     x = (x & b2 ) + (( x >> 2 ) & b2 ); // 4 bit
18     x = (x & b4 ) + (( x >> 4 ) & b4 ); // 8 bits
19     x = (x & b8 ) + (( x >> 8 ) & b8 ); //16 bits
20     x = (x & b16) + (( x >> 16 ) & b16); //32 bits
21     x = (x & b32) + (( x >> 32 ) & b32); //64 bits
22
23 }
```

হিস্টোগ্রাম প্রবলেম [ইনডেক্স]

```

1 /*
2 Finds largest rectangular area in a histogram in O(n)
3 */
4
5 i64 calc(int *ht, int n) {
6     i64 ret = 0;
7     int top = 1, st[MAX], i;
8     ht[0] = st[0] = ht[++n] = 0;
9     for(i = 1; i <= n; i++) {
10         while(top > 1 && ht[st[top-1]] >= ht[i]) {
11             ret = _max(ret, (i64)ht[st[top-1]]*(i64)(i - st[top-2]-1));
12             top--;
13         }
14         st[top++] = i;
15     }
16     return ret;
17 }
```

ইনফাইনাইট চেসবোর্ডে নাইট ডিস্ট্যান্স [ইনডেক্স]

```

1 /*
2 NK is the size of grid you want to precalculate
3 NK/2,NK/2 will be considered origin
4 Calculates minimum knight distance from 0,0 to x,y
5 */
6
7 const int KN = 101;
8
9 i64 dk[KN][KN];
10 int dx[] = {-1, -1, 1, 1, -2, -2, 2, 2};
11 int dy[] = {-2, 2, -2, 2, -1, 1, -1, 1};
12
13 void precalc() {
14     int x, y, x1, y1, i;
15     queue< int > Q;
16     memset(dk, 0x3f, sizeof dk);
17     x = y = (KN >> 1);
18     dk[x][y] = 0;
19     Q.push(x); Q.push(y);
20     while(!Q.empty()) {
21         x = Q.front(); Q.pop();
22         y = Q.front(); Q.pop();
23         for(i = 0; i < 8; i++) {
24             x1 = x + dx[i], y1 = y + dy[i];
25             if(x1 < 0 || y1 < 0 || x1 > KN || y1 > KN) continue;
26             if(dk[x1][y1] >= dk[x][y] + 1) {
27                 dk[x1][y1] = dk[x][y] + 1;
28                 Q.push(x1); Q.push(y1);
29             }
30         }
31     }
32 }
```

[Follow](#)

Follow “শাবিজাবি
ইজিবিজিবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

Enter your email address

Sign me up

```

25         if(0 <= x1 && x1 < KN && 0 <= y1 && y1 < KN) {
26             if(dk[x1][y1] > dk[x][y] + 1) {
27                 dk[x1][y1] = dk[x][y] + 1;
28                 Q.push(x1); Q.push(y1);
29             }
30         }
31     }
32 }
33
34
35 i64 knight(i64 x, i64 y) {
36     i64 step, res = 0;
37     if(x < y) swap(x, y);
38     while((x<<1) > KN) {
39         step = x / 2 / 2; res += step;
40         x -= step * 2; y -= step;
41         if(y < 0) y = ((y % 2) + 2) % 2;
42         if(x < y) swap(x, y);
43     }
44     res += dk[x+(KN>>1)][y+(KN>>1)];
45     return res;
46 }
```

ট্ৰাই (প্ৰিফৰ্ক্স ট্ৰি) [ইনডেক্স]

```

1  /*
2   Basic trie, don't use it with large alphabet set or long length.
3   All operation has complexity O(length).
4   MAX is number of different items.
5 */
6
7  struct trie {
8      trie *next[MAX+1];
9      trie() { for(int i=0; i<=MAX; i++) next[i] = NULL; }
10 }
11
12 void insert(trie *root, int *seq, int len) {
13     trie *curr = root;
14     for(int i = 0; i < len; i++) {
15         if(!curr->next[seq[i]]) curr->next[seq[i]] = new trie;
16         curr = curr->next[seq[i]];
17     }
18     if(!curr->next[MAX]) curr->next[MAX] = new trie;
19 }
20
21 bool found(trie *root, int *seq, int len) {
22     trie *curr = root;
23     for(int i = 0; i < len; i++) {
24         if(!curr->next[seq[i]]) return false;
25         curr = curr->next[seq[i]];
26     }
27     if(!curr->next[MAX]) return false;
28     return true;
29 }
```

Follow “শাবিজাবি
হিজিবিজবিজ”

Get every new post delivered to
your inbox.

Join 67 other followers

[Sign me up](#)

ট্রাই (স্ট্যাটিক অ্যারে) [ইনডেক্স]

```

1  /*
2   Trie implementation using array, faster and takes less memory.
3   Each node can contain arbitrary data as needed for solving the problem.
4   The ALPHABET, MAX and scale() may need tuning as necessary.
5  */
6
7  const int ALPHABET = 26;
8  const int MAX = 100000;
9
10 // for mapping items from 0 to ALPHABET-1
11 #define scale(x) (x-'a')
12
13
14 struct TrieTree {
15     int n, root;
16     int next[MAX][ALPHABET];
17     char data[MAX]; // there can be more data fields
18
19     void init() {
20         root = 0, n = 1; data[root] = 0;
21         memset(next[root], -1, sizeof(next[root]));
22     }
23
24     void insert(char *s) {
25         int curr = root, i, k;
26         for(i = 0; s[i]; i++) {
27             k = scale(s[i]);
28             if(next[curr][k] == -1) {
29                 next[curr][k] = n;
30                 data[n] = s[i]; // optional
31                 memset(next[n], -1, sizeof(next[n]));
32                 n++;
33             }
34             curr = next[curr][k];
35         }
36         data[curr] = 0; // sentinel, optional
37     }
38
39     bool find(char *s) {
40         int curr = root, i, k;
41         for(i = 0; s[i]; i++) {
42             k = scale(s[i]);
43             if(next[curr][k] == -1) return false;
44             curr = next[curr][k];
45         }
46         return (data[curr] == 0);
47     }
48
49 } trieTree;

```

সাফিক্স অ্যারে (ম্লো) [ইনডেক্স]

1 /*

[Follow](#)

Follow “**শাবিজাবি**
হিজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

Enter your email address

[Sign me up](#)

```

2 Generates suffix array in O(n (lg n)^2). Finds LC
3 A[] is the target string with N length. base is the lowest character in A[]
4 S[i] holds the index of ith suffix when sorted lexicographically.
5 Change base as necessary and MAXLOG = log2(MAXLEN).
6 */
7
8 int N, stp, P[MAXLOG][MAXLEN], S[MAXLEN];
9 char A[MAXLEN], base = 'a';
10 struct entry { int nr[2], p; } L[MAXLEN];
11
12 inline bool cmp(const entry &a, const entry &b) {
13     return a.nr[0] == b.nr[0] ? (a.nr[1] < b.nr[1] ? 1 : 0) : (a.nr[0] < b.nr[0] ? -1 : 1);
14 }
15
16 void generateSuffix() {
17     register int i, cnt;
18     for(i=0; i<N; i++) P[0][i] = A[i]-base;
19     for(stp = cnt = 1; cnt>>1 < N; stp++, cnt<<=1) {
20         for(i=0; i<N; i++) {
21             L[i].nr[0] = P[stp-1][i];
22             L[i].nr[1] = i+cnt<N ? P[stp-1][i+cnt] : -1;
23             L[i].p = i;
24         }
25         sort(L, L+N, cmp);
26         for(i=0; i<N; i++) {
27             if(i > 0 && L[i].nr[0] == L[i - 1].nr[0] && L[i].nr[1] == L[i - 1].nr[1])
28                 else P[stp][L[i].p] = i;
29         }
30     }
31     for(i=0; i<N; i++) S[P[stp-1][i]] = i;
32 }
33
34 int lcp(int x, int y) {
35     int k, ret = 0;
36     if(x == y) return N - x;
37     for(k = stp - 1; k >= 0 && x < N && y < N; k --)
38         if(P[k][x] == P[k][y])
39             x += 1 << k, y += 1 << k, ret += 1 << k;
40     return ret;
41 }
```

[View original post](#)

সাফিক্স অ্যারে (n lg n) [ইনডেক্স]

```

1 /*
2 Suffix array implementation using bucket sorting
3 Complexity O(n log n), str[] is the target string
4 n is its length and suffix[i] contains i'th sorted suffix
5 */
6
7 const int MAXN = 1 << 16;
8 const int MAXL = 16;
9
10 int n, stp, mv, suffix[MAXN], tmp[MAXN];
11 int sum[MAXN], cnt[MAXN], rank[MAXL][MAXN];
12 char str[MAXN];
```

Follow

Follow “শাবিজাবি হিজিবিজবিজ”

Get every new post delivered to your inbox.

Join 67 other followers

```

13
14 inline bool equal(const int &u, const int &v){
15     if(!stp) return str[u] == str[v];
16     if(rank[stp-1][u] != rank[stp-1][v]) return false;
17     int a = u + mv < n ? rank[stp-1][u+mv] : -1;
18     int b = v + mv < n ? rank[stp-1][v+mv] : -1;
19     return a == b;
20 }
21
22 void update(){
23     int i, rnk;
24     for(i = 0; i < n; i++) sum[i] = 0;
25     for(i = rnk = 0; i < n; i++) {
26         suffix[i] = tmp[i];
27         if(i && !equal(suffix[i], suffix[i-1])) {
28             rank[stp][suffix[i]] = ++rnk;
29             sum[rnk+1] = sum[rnk];
30         }
31         else rank[stp][suffix[i]] = rnk;
32         sum[rnk+1]++;
33     }
34 }
35
36 void Sort() {
37     int i;
38     for(i = 0; i < n; i++) cnt[i] = 0;
39     memset(tmp, -1, sizeof tmp);
40     for(i = 0; i < mv; i++){
41         int idx = rank[stp - 1][n - i - 1];
42         int x = sum[idx];
43         tmp[x + cnt[idx]] = n - i - 1;
44         cnt[idx]++;
45     }
46     for(i = 0; i < n; i++){
47         int idx = suffix[i] - mv;
48         if(idx < 0)continue;
49         idx = rank[stp-1][idx];
50         int x = sum[idx];
51         tmp[x + cnt[idx]] = suffix[i] - mv;
52         cnt[idx]++;
53     }
54     update();
55     return;
56 }
57
58 inline bool cmp(const int &a, const int &b){
59     if(str[a]!=str[b]) return str[a]<str[b];
60     return false;
61 }
62
63 void SortSuffix() {
64     int i;
65     for(i = 0; i < n; i++) tmp[i] = i;
66     sort(tmp, tmp + n, cmp);
67     stp = 0;
68     update();
69     ++stp;

```

[Follow](#)

Follow “শাবিজাবি হিজিবিজবিজ”

Get every new post delivered to your Inbox.

Join 67 other followers

```

70     for(mv = 1; mv < n; mv <= 1) {
71         Sort();
72         stp++;
73     }
74     stp--;
75     for(i = 0; i <= stp; i++) rank[i][n] = -1;
76 }
77
78 inline int lcp(int u, int v) {
79     if(u == v) return n - u;
80     int ret, i;
81     for(ret = 0, i = stp; i >= 0; i--) {
82         if(rank[i][u] == rank[i][v]) {
83             ret += 1<<i;
84             u += 1<<i;
85             v += 1<<i;
86         }
87     }
88     return ret;
89 }
```

মিনিমাম এক্সপ্রেশন (ঝো-জুয়ান) [ইনডেক্স]

```

1 /*
2 Finds alphabetically first representation of a cyclic string in O(length)
3 */
4
5 inline int minimumExpression(char *s) {
6     int i, j, k, n, len, p, q;
7     len = n = strlen(s), n <= 1, i = 0, j = 1, k = 0;
8     while(i + k < n && j + k < n) {
9         p = i+k >= len ? s[i+k-len] : s[i+k];
10        q = j+k >= len ? s[j+k-len] : s[j+k];
11        if(p == q) k++;
12        else if(p > q) { i = i+k+1; if(i <= j) i = j+1; k = 0; }
13        else if(p < q) { j = j+k+1; if(j <= i) j = i+1; k = 0; }
14    }
15    return i < j ? i : j;
16 }
```

কে.এম.পি [ইনডেক্স]

```

1 /*
2 finds all occurrence of pattern in buffer
3 buffer can be online
4 */
5
6 char buffer[MAX], pattern[MAX];
7 int overlap[MAX];
8
9 void computeOverlap() {
10     overlap[0] = -1;
11     for(int i=0; pattern[i]; i++) {
12         overlap[i+1] = overlap[i] + 1;
13         while(overlap[i+1] > 0 && pattern[i] != p
```

[Follow](#)

Follow “শাবিজাবি
হিজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

```

14         overlap[i+1] = overlap[overlap[i+1]-1]
15     }
16 }
17
18
19 vector< int > kmpMatcher(int m) {
20     vector< int > V;
21     for(int i = 0, j = 0; buffer[i]; i++) {
22         while(true) {
23             if(buffer[i] == pattern[j]) {
24                 j++;
25                 if(j == m) {
26                     V.push_back(i-m+1);
27                     j = overlap[j];
28                 }
29                 break;
30             }
31             else if(j == 0) break;
32             else j = overlap[j];
33         }
34     }
35     return V;
36 }
```

ম্যানাক্যার আলগোরিদম [ইনডেক্স]

```

1 /*
2 Manacher algorithm implementation.
3 Application, largest palindromic substring, largest palindromic suffix
4 */
5
6 int lengths[MAX<<1];
7
8 int manacher(char *buff, int len) {
9     int i, k, pallen, found, d, j, s, e;
10    k = pallen = 0;
11    for(i = 0; i < len; ) {
12        if(i > pallen && buff[i-pallen-1] == buff[i]) {
13            pallen += 2, i++;
14            continue;
15        }
16        lengths[k++] = pallen;
17        s = k - 2, e = s - pallen, found = 0;
18        for(j = s; j > e; j--) {
19            d = j - e - 1;
20            if(lengths[j] == d) {
21                pallen = d;
22                found = 1;
23                break;
24            }
25            lengths[k++] = (d < lengths[j]? d : 1
26        }
27        if(!found) { pallen = 1; i++; }
28    }
29    lengths[k++] = pallen;
```

[Follow](#)

Follow “**শাবিজাবি**
হিজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

```

30     return lengths[k-1];
31 }
```

জোসেফাস রিকারেন্স [ইনডেক্স]

```

1  /*
2  The first one is for K = 2 and the second one is general.
3  Note: first function returns 1 based index while second one is 0 based.
4  */
5
6  int f(int n) {
7      if(n == 1) return 1;
8      return (f((n-(n&1))>>1)<<1) + ((n&1)?1:-1);
9  }
10
11 int f(int n, int k) {
12     if(n == 1) return 0;
13     return (f(n-1, k) + k)%n;
14 }
```

শ্যান্ক'স বেবি স্টেপ জায়ান্ট স্টেপ [ইনডেক্স]

```

1  /*
2  Shanks baby step giant step - discrete logarithm algorithm
3  for the equation: b = a^x % p where a, b, p known, finds x
4  works only when p is an odd prime
5  */
6
7  int shank(int a, int b, int p) {
8      int i, j, m;
9      long long c, aj, ami;
10     map< long long, int > M;
11     map< long long, int > :: iterator it;
12     m = (int)ceil(sqrt(double)(p));
13     M.insert(make_pair(1, 0));
14     for(j = 1, aj = 1; j < m; j++) {
15         aj = (aj * a) % p;
16         M.insert(make_pair(aj, j));
17     }
18     ami = modexp(modinv(a, p), m, p);
19     for(c = b, i = 0; i < m; i++) {
20         it = M.find(c);
21         if(it != M.end()) return i * m + it->second;
22         c = (c * ami) % p;
23     }
24     return 0;
25 }
```

সেগমেন্টেড সিভ [ইনডেক্স]

```

1  /*
2  Generates primes within interval [a, b] when b -
3  and 1 <= a <= b <= 2147483647
```

[Follow](#)

Follow “হাবিজাবি
ইজিবিজিবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

```

4  */
5 int base[MAX>>6], segment[RNG>>6], primes[LEN], prlen;
6
7 #define chkC(x,n) (x[n>>6]&(1<<((n>>1)&31)))
8 #define setC(x,n) (x[n>>6]|=(1<<((n>>1)&31)))
9
10 void sieve() {
11     int i, j, k;
12     for(i=3; i<LMT; i+=2) if(!chkC(base, i)) for(j=i*i, k=i<<1; j<MAX; j+=k)
13         for(i=3, prlen=0; i<MAX; i+=2) if(!chkC(base, i)) primes[prlen++] = i;
14 }
15
16 int segmented_sieve(int a, int b) {
17     int rt, i, k, cnt = (a<=2 && 2<=b)? 1 : 0;
18     if(b<2) return 0;
19     if(a<3) a = 3;
20     if(a%2==0) a++;
21     memset(segment, 0, sizeof segment);
22     for(i=0, rt=(int)sqrt((double)b); i < prlen && primes[i] <= rt; i++) {
23         unsigned j = primes[i] * ( (a+primes[i]-1) / primes[i] );
24         if(j%2==0) j += primes[i];
25         for(k=primes[i]<<1; j<=b; j+=k) if(j!=primes[i]) setC(segment, (j-a));
26     }
27     for(i=0; i<=b-a; i+=2) if(!chkC(segment, i)) cnt++;
28 }
29 }
```

এক্সটেন্ডেড ইউক্লিড ও মডুলার ইনভার্স [ইনডেক্স]

```

1 /*
2 Implementation of extended euclid algorithm.
3 Modular inverse requires gcd(a, n) = 1.
4 */
5
6 class Euclid {
7 public:
8     i64 x, y, d;
9     Euclid() {}
10    Euclid(i64 _x, i64 _y, i64 _d) : x(_x), y(_y), d(_d) {}
11 };
12
13 Euclid egcd(i64 a, i64 b) {
14     if(!b) return Euclid(1, 0, a);
15     Euclid r = egcd(b, a % b);
16     return Euclid(r.y, r.x - a / b * r.y, r.d);
17 }
18
19 i64 modinv(i64 a, i64 n) {
20     Euclid t = egcd(a, n);
21     if(t.d > 1) return 0;
22     i64 r = t.x % n;
23     return (r < 0 ? r + n : r);
24 }
```

[Follow](#)

Follow “শাবিজাবি
হিজিবিজবিজ”

Get every new post delivered to
your inbox.

Join 67 other followers

[Sign me up](#)

কনভেক্স হাল (গ্রাহাম'স স্ক্যান) [ইনডেক্স]

```

1  /*
2  ConvexHull : Graham's Scan O(n lg n), integer implementation
3  P[]: holds all the points, C[]: holds points on the hull
4  np: number of points in P[], nc: number of points in C[]
5  to handle duplicate, call makeUnique() before calling convexHull()
6  call convexHull() if you have np >= 3
7  to remove co-linear points on hull, call compress() after convexHull()
8  */
9
10 point P[MAX], C[MAX], P0;
11
12 inline int triArea2(const point &a, const point &b, const point &c) {
13     return (a.x*(b.y-c.y) + b.x*(c.y-a.y) + c.x*(a.y-b.y));
14 }
15
16 inline int sqDist(const point &a, const point &b) {
17     return ((a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-b.y));
18 }
19
20 inline bool comp(const point &a, const point &b) {
21     int d = triArea2(P0, a, b);
22     if(d < 0) return false;
23     if(!d && sqDist(P0, a) > sqDist(P0, b)) return false;
24     return true;
25 }
26
27 inline bool normal(const point &a, const point &b) {
28     return ((a.x==b.x) ? a.y < b.y : a.x < b.x);
29 }
30
31 inline bool issame(const point &a, const point &b) {
32     return (a.x == b.x && a.y == b.y);
33 }
34
35 inline void makeUnique(int &np) {
36     sort(&P[0], &P[np], normal);
37     np = unique(&P[0], &P[np], issame) - P;
38 }
39
40 void convexHull(int &np, int &nc) {
41     int i, j, pos = 0;
42     for(i = 1; i < np; i++) {
43         if(P[i].y < P[pos].y || (P[i].y == P[pos].y &
44             pos = i;
45         swap(P[0], P[pos]);
46         P0 = P[0];
47         sort(&P[1], &P[np], comp);
48         for(i = 0; i < 3; i++) C[i] = P[i];
49         for(i = j = 3; i < np; i++) {
50             while(triArea2(C[j-2], C[j-1], P[i]) < 0)
51                 C[j++] = P[i];
52         }
53         nc = j;
54     }
}

```

Follow

Follow “শাবিজাবি
ইজিবিজিবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

```

55
56 void compress(int &nc) {
57     int i, j, d;
58     C[nc] = C[0];
59     for(i=j=1; i < nc; i++) {
60         d = triArea2(C[j-1], C[i], C[i+1]);
61         if(d || (!d && issame(C[j-1], C[i+1]))) C[j++] = C[i];
62     }
63     nc = j;
64 }
```

পয়েন্ট ইন কনভেক্স পলিগন [ইনডেক্স]

```

1 /*
2 C[] array of points of convex polygon in ccw order,
3 nc number of points in C, p target points.
4 returns true if p is inside C (including edge) or false otherwise.
5 complexity O(lg n)
6 */
7
8 inline bool inConvexPoly(point *C, int nc, const point &p) {
9     int st = 1, en = nc - 1, mid;
10    while(en - st > 1) {
11        mid = (st + en)>>1;
12        if(triArea2(C[0], C[mid], p) < 0) en = mid;
13        else st = mid;
14    }
15    if(triArea2(C[0], C[st], p) < 0) return false;
16    if(triArea2(C[st], C[en], p) < 0) return false;
17    if(triArea2(C[en], C[0], p) < 0) return false;
18    return true;
19 }
```

পলিগন এরিয়া (2D) [ইনডেক্স]

```

1 /*
2 P[] holds the points, must be either in cw or ccw
3 function returns double of the area.
4 */
5
6 inline int dArea(int np) {
7     int area = 0;
8     for(int i = 0; i < np; i++) {
9         area += p[i].x*p[i+1].y - p[i].y*p[i+1].x
10    }
11    return abs(area);
12 }
```

ক্লোজেস্ট পেয়ার [ইনডেক্স]

```

1 /*
2 closestPair(Point *X, Point *Y, int n);
3 X contains the points sorted by x co-ordinate,
```

[Follow](#)

Follow “হাবিজাবি
ইজিবিজবিজ”

Get every new post delivered to
your inbox.

Join 67 other followers

[Sign me up](#)

```

4 Y contains the points sorted by y co-ordinate,
5 One additional item in Point structure is needed, the original index.
6 */
7
8 typedef long long i64;
9 typedef struct { int x, y, i; } Point;
10
11 int flag[MAX];
12
13 inline i64 sq(const i64 &x) {
14     return x*x;
15 }
16
17 inline i64 sqdist(const Point &a, const Point &b) {
18     return sq(a.x-b.x) + sq(a.y-b.y);
19 }
20
21 inline i64 closestPair(Point *X, Point *Y, int n) {
22     if(n == 1) return INF;
23     if(n == 2) return sqdist(X[0], X[1]);
24
25     int i, j, k, n1, n2, ns, m = n >> 1;
26     Point Xm = X[m-1], *XL, *XR, *YL, *YR, *YS;
27     i64 lt, rt, dd, tmp;
28
29     XL = new Point[m], YL = new Point[m];
30     XR = new Point[m+1], YR = new Point[m+1];
31     YS = new Point[n];
32
33     for(i = 0; i < m; i++) XL[i] = X[i], flag[X[i].i] = 0;
34     for(; i < n; i++) XR[i - m] = X[i], flag[X[i].i] = 1;
35     for(i = n2 = n1 = 0; i < n; i++) {
36         if(!flag[Y[i].i]) YL[n1++] = Y[i];
37         else YR[n2++] = Y[i];
38     }
39
40     lt = closestPair(XL, YL, n1);
41     rt = closestPair(XR, YR, n2);
42     dd = min(lt, rt);
43
44     for(i = ns = 0; i < n; i++)
45         if(sq(Y[i].x - Xm.x) < dd)
46             YS[ns++] = Y[i];
47     for(j = 0; j < ns; j++)
48         for(k = j + 1; k < ns && sq(YS[k].y - YS[j].y) < dd)
49             dd = min(dd, sqdist(YS[j], YS[k]));
50
51     delete[] XL; delete[] XR;
52     delete[] YL; delete[] YR;
53     delete[] YS;
54
55     return dd;
56 }
```

[Follow](#)

Follow “**শাবিজাবি**
হিজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

সার্কেল ইন্টারসেকশন এরিয়া [ইনডেক্স]

```

1  /*
2   This code assumes the circle center and radius to be integer.
3   Change this when necessary.
4  */
5
6  inline double commonArea(const Circle &a, const Circle &b) {
7      int dsq = sqDist(a.c, b.c);
8      double d = sqrt((double)dsq);
9      if(sq(a.r + b.r) <= dsq) return 0;
10     if(a.r >= b.r && sq(a.r-b.r) >= dsq) return pi * b.r * b.r;
11     if(a.r <= b.r && sq(b.r-a.r) >= dsq) return pi * a.r * a.r;
12     double angleA = 2.0 * acos((a.r * a.r + dsq - b.r * b.r) / (2.0 * a.r * a.r));
13     double angleB = 2.0 * acos((b.r * b.r + dsq - a.r * a.r) / (2.0 * b.r * b.r));
14     return 0.5 * (a.r * a.r * (angleA - sin(angleA)) + b.r * b.r * (angleB - sin(angleB)));
15 }

```

সেগমেন্ট ইন্টারসেকশন (2D) [ইনডেক্স]

```

1  /*
2   Segment intersection in 2D integer space.
3   P1, p2 makes first segment, p3, p4 makes the second segment
4  */
5
6  inline bool intersect(const Point &p1, const Point &p2, const Point &p3, const Point &p4,
7      i64 d1, d2, d3, d4;
8      d1 = direction(p3, p4, p1);
9      d2 = direction(p3, p4, p2);
10     d3 = direction(p1, p2, p3);
11     d4 = direction(p1, p2, p4);
12     if((d1 < 0 && d2 > 0) || (d1 > 0 && d2 < 0)) && ((d3 < 0 && d4 > 0) || (d3 > 0 && d4 < 0))
13     if(!d3 && onsegment(p1, p2, p3)) return true;
14     if(!d4 && onsegment(p1, p2, p4)) return true;
15     if(!d1 && onsegment(p3, p4, p1)) return true;
16     if(!d2 && onsegment(p3, p4, p2)) return true;
17     return false;
18 }

```

টেট্রাহেড্রন ফরমুলা [ইনডেক্স]

```

1  /*
2   Some tetrahedron formulas
3  */
4
5  inline double volume(double u, double v, double w
6      double u1,v1,w1;
7      u1 = v * v + w * w - U * U;
8      v1 = w * w + u * u - V * V;
9      w1 = u * u + v * v - W * W;
10     return sqrt(4.0*u*u*v*v*w*w - u*u*u1*u1 - v*v*v1*w*w);
11 }
12
13 inline double surface(double a, double b, double c
14     return sqrt((a + b + c) * (-a + b + c) * (a - b) * (a - c));

```

Follow “শাবিজাবি
হিজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

Enter your email address

Sign me up

```

15 }
16
17 inline double insphere(double WX, double WY, double WZ, double XY, double X:
18     double sur, rad;
19     sur = surface(WX, WY, XY) + surface(WX, XZ, WZ) + surface(WY, YZ, WZ) +
20     rad = volume(WX, WY, WZ, YZ, XZ, XY) * 3.0 / sur;
21     return rad;
22 }
```

স্ট্রংলি কানেকটেড কম্পোনেন্ট (টারজান) [ইনডেক্স]

```

1 /*
2 SCC (Tarjan) in O(|v| + |e|)
3 Input:
4 G[] is a input directed graph with n nodes in range [1,n]
5 Output:
6 Component[i] holds the component id to which node i belongs
7 components: total number of components in the graph
8 */
9
10 int Stack[MAX], top;
11 int Index[MAX], Lowlink[MAX], Onstack[MAX];
12 int Component[MAX];
13 int idx, components;
14 vector< int > G[MAX];
15
16 void tarjan(int u) {
17     int v, i;
18     Index[u] = Lowlink[u] = idx++;
19     Stack[top++] = u;
20     Onstack[u] = 1;
21     for(i = 0; i < SZ(G[u]); i++) {
22         v = G[u][i];
23         if(Index[v]==-1) {
24             tarjan(v);
25             Lowlink[u] = min(Lowlink[u], Lowlink[v]);
26         }
27         else if(Onstack[v]) Lowlink[u] = min(Lowlink[u], Index[v]);
28     }
29     if(Lowlink[u] == Index[u]) {
30         components++;
31         do {
32             v = Stack[--top];
33             Onstack[v] = 0;
34             Component[v] = components;
35         } while(u != v);
36     }
37 }
38
39 void findSCC(int n) {
40     components = top = idx = 0;
41     SET(Index); CLR(Onstack); MEM(Lowlink, 0x3f);
42     for(int i = 1; i <= n; i++) if(Index[i]==-1)
43 }
```

[Follow](#)

Follow “হাবিজাবি
ইজিবিজিবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

আটিকুলেশন পয়েন্ট [ইনডেক্স]

```

1  /*
2   G[][]: undirected graph
3   cut[v] is true if node v is an articulation point / cut-vertex
4  */
5
6  vector< int > G[MAX];
7  int low[MAX], vis[MAX], used[MAX], cut[MAX], dfstime;
8
9  void dfs(int u, int par = -1) {
10    int i, v, child = 0;
11    used[u] = 1;
12    vis[u] = low[u] = ++dfstime;
13    for(i = 0; i < G[u].size(); i++) {
14      v = G[u][i];
15      if(v == par) continue;
16      if(used[v]) low[u] = min(low[u], vis[v]);
17      else {
18        child++;
19        dfs(v, u);
20        low[u] = min(low[u], low[v]);
21        if(low[v] >= vis[u]) cut[u] = 1;
22      }
23    }
24    if(par == -1) cut[u] = (child > 1);
25  }

```

ব্ৰিজ [ইনডেক্স]

```

1  /*
2   G[][]: undirected graph
3   finds all the bridges in a connected graph and
4   adds those edges to the Bridges[] vector
5  */
6
7  vector< int > G[MAX];
8  vector< pair< int, int > > Bridges;
9  int low[MAX], vis[MAX], used[MAX], dfstime;
10
11 void dfs(int u, int par) {
12   int i, v;
13   used[u] = 1;
14   vis[u] = low[u] = ++dfstime;
15   for(i = 0; i < G[u].size(); i++) {
16     v = G[u][i];
17     if(v == par) continue;
18     if(used[v]) low[u] = min(low[u], vis[v]);
19     else {
20       dfs(v, u);
21       low[u] = min(low[u], low[v]);
22       if(low[v] > vis[u]) Bridges.push_back
23     }
24   }
25 }

```

[Follow](#)

Follow “হাবিজাৰি
ইজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

বাই কানেকটেড কম্পোনেন্ট [ইনডেক্স]

```

1  /*
2   G[][]: undirected graph
3   Separates bi-connected component by edges.
4  */
5
6  vector< int > G[MAX];
7  stack< pii > S;
8  int dfstime;
9  int low[MAX], vis[MAX], used[MAX];
10
11 void dfs(int u, int par) {
12     int v, i, sz = G[u].size();
13     pii e, curr;
14     used[u] = 1;
15     vis[u] = low[u] = ++dfstime;
16     for(i = 0; i < sz; i++) {
17         v = G[u][i];
18         if(v == par) continue;
19         if(!used[v]) {
20             S.push(pii(u, v));
21             dfs(v, u);
22             if(low[v] >= vis[u]) {
23                 // new component
24                 curr = pii(u, v);
25                 do {
26                     e = S.top(); S.pop();
27                     // e is an edge in current bcc
28                 } while(e != curr);
29             }
30             low[u] = min(low[u], low[v]);
31         }
32         else if(vis[v] < vis[u]) {
33             S.push(pii(u, v));
34             low[u] = min(low[u], vis[v]);
35         }
36     }
37 }

```

স্টেবল ম্যারিজ [ইনডেক্স]

```

1  /*
2   INPUT:
3   m: number of man, n: number of woman (must be at
4   L[i][]: the list of women in order of decreasing
5   R[j][i]: the attractiveness of i to j.
6   OUTPUTS:
7   L2R[]: the mate of man i (always between 0 and n-
8   R2L[]: the mate of woman j (or -1 if single)
9   man priority
10  */
11
12  int m, n, L[MAXM][MAXW], R[MAXW][MAXM], L2R[MAXM]

```

[Follow](#)

Follow “শাবিজাবি
হিজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

```

14 void stableMarriage() {
15     int i, man, wom, hubby;
16     SET(R2L); CLR(p);
17     for(i = 0; i < m; i++ ) {
18         man = i;
19         while(man >= 0) {
20             while(true) {
21                 wom = L[man][p[man]++;
22                 if(R2L[wom] < 0 || R[wom][man] > R[wom][R2L[wom]]) break;
23             }
24             hubby = R2L[wom];
25             R2L[L2R[man] = wom] = man;
26             man = hubby;
27         }
28     }
29 }
```

ম্যাক্স ফ্লো (ডিনিক) [ইনডেক্স]

```

1 /*
2 max flow (dinitz algorithm)
3 works on undirected graph
4 can have loops, multiple edges, cycles
5 */
6
7 int src, snk, nNode, nEdge;
8 int Q[MAXN], fin[MAXN], pro[MAXN], dist[MAXN];
9 int flow[MAXE], cap[MAXE], next[MAXE], to[MAXE];
10
11 inline void init(int _src, int _snk, int _n) {
12     src = _src, snk = _snk, nNode = _n, nEdge = 0;
13     SET(fin);
14 }
15
16 inline void add(int u, int v, int _cap) {
17     to[nEdge] = v, cap[nEdge] = _cap, flow[nEdge] = 0;
18     next[nEdge] = fin[u], fin[u] = nEdge++;
19     to[nEdge] = u, cap[nEdge] = _cap, flow[nEdge] = 0;
20     next[nEdge] = fin[v], fin[v] = nEdge++;
21 }
22
23 bool bfs() {
24     int st, en, i, u, v;
25     SET(dist);
26     dist[src] = st = en = 0;
27     Q[en++] = src;
28     while(st < en) {
29         u = Q[st++];
30         for(i=fin[u]; i>=0; i=next[i]) {
31             v = to[i];
32             if(flow[i] < cap[i] && dist[v]==-1) {
33                 dist[v] = dist[u]+1;
34                 Q[en++] = v;
35             }
36         }
37     }
38 }
```

[Follow](#)

Follow “শাবিজাবি
হিজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

```

38     return dist[snk]!=-1;
39 }
40
41 int dfs(int u, int fl) {
42     if(u==snk) return fl;
43     for(int &e=pro[u], v, df; e>=0; e=next[e]) {
44         v = to[e];
45         if(flow[e] < cap[e] && dist[v]==dist[u]+1) {
46             df = dfs(v, min(cap[e]-flow[e], fl));
47             if(df>0) {
48                 flow[e] += df;
49                 flow[e^1] -= df;
50                 return df;
51             }
52         }
53     }
54     return 0;
55 }
56
57 i64 dinitz() {
58     i64 ret = 0;
59     int df;
60     while(bfs()) {
61         for(int i=1; i<=nNode; i++) pro[i] = fin[i];
62         while(true) {
63             df = dfs(src, INF);
64             if(df) ret += (i64)df;
65             else break;
66         }
67     }
68     return ret;
69 }
```

মিন কস্ট ম্যাক্স ফ্লো (বেলম্যান ফোর্ড) [ইনডেক্স]

```

1 /*
2  min cost flow (bellman ford)
3  works only on directed graphs
4  handles multiple edges, cycles, loops
5 */
6
7 int src, snk, nNode, nEdge;
8 int fin[MAXN], pre[MAXN], dist[MAXN];
9 int cap[MAXE], cost[MAXE], next[MAXE], to[MAXE],
10
11 inline void init(int _src, int _snk, int nodes) {
12     SET(fin);
13     nNode = nodes, nEdge = 0;
14     src = _src, snk = _snk;
15 }
16
17 inline void addEdge(int u, int v, int _cap, int _cost) {
18     from[nEdge] = u, to[nEdge] = v, cap[nEdge] =
19     next[nEdge] = fin[u], fin[u] = nEdge++;
20     from[nEdge] = v, to[nEdge] = u, cap[nEdge] =
21     next[nEdge] = fin[v], fin[v] = nEdge++;
```

[Follow](#)

Follow “শাবিজাবি
হিজিবিজবিজ”

Get every new post delivered to
your inbox.

Join 67 other followers

```

22 }
23
24 bool bellman() {
25     int iter, u, v, i;
26     bool flag = true;
27     MEM(dist, 0x7f);
28     SET(pre);
29     dist[src] = 0;
30     for(iter = 1; iter < nNode && flag; iter++) {
31         flag = false;
32         for(u = 0; u < nNode; u++) {
33             for(i = fin[u]; i >= 0; i = next[i]) {
34                 v = to[i];
35                 if(cap[i] && dist[v] > dist[u] + cost[i]) {
36                     dist[v] = dist[u] + cost[i];
37                     pre[v] = i;
38                     flag = true;
39                 }
40             }
41         }
42     }
43     return (dist[snk] < INF);
44 }
45
46 int mcmf(int &fcost) {
47     int netflow, i, bot, u;
48     netflow = fcost = 0;
49     while(bellman()) {
50         bot = INF;
51         for(u = pre[snk]; u >= 0; u = pre[from[u]]) bot = min(bot, cap[u]);
52         for(u = pre[snk]; u >= 0; u = pre[from[u]]) {
53             cap[u] -= bot;
54             cap[u^1] += bot;
55             fcost += bot * cost[u];
56         }
57         netflow += bot;
58     }
59     return netflow;
60 }
```

ম্যাক্সিমাম বাইপারটাইট ম্যাচিং (ডি.এফ.এস.) টেনডেকা

[Follow](#)

```

1 /*
2 G[] is the left-side graph, must be bipartite
3 match(n): n is the number of nodes in left-side s
4 and returns the maximum possible matching.
5 Left[] and Right[] are assigned with corresponding
6 */
7
8 vector < int > G[MAX];
9 bool visited[MAX];
10 int Left[MAX], Right[MAX];
11
12 bool dfs(int u) {
13     if(visited[u]) return false;
```

Follow “হাবিজাবি
ইজিবিজবিজ”

Get every new post delivered to
your inbox.

Join 67 other followers

[Sign me up](#)

```

14     visited[u] = true;
15     int len = G[u].size(), i, v;
16     for(i=0; i<len; i++) {
17         v = G[u][i];
18         if(Right[v]==-1) {
19             Right[v] = u, Left[u] = v;
20             return true;
21         }
22     }
23     for(i=0; i<len; i++) {
24         v = G[u][i];
25         if(dfs(Right[v])) {
26             Right[v] = u, Left[u] = v;
27             return true;
28         }
29     }
30     return false;
31 }
32
33 int match(int n) {
34     int i, ret = 0;
35     bool done;
36     SET(Left); SET(Right);
37     do {
38         done = true; CLR(visited);
39         for(i=0; i<n; i++) {
40             if(Left[i]==-1 && dfs(i)) {
41                 done = false;
42             }
43         }
44     } while(!done);
45     for(i=0; i<n; i++) ret += (Left[i]!=-1);
46     return ret;
47 }
```

ম্যাক্সিমাম বাইপারটাইট ম্যাচিং (হপক্রফট কার্প) [ইনডেক্স]

```

1 /*
2  n: number of nodes on left side, nodes are numbered 1 to n
3  m: number of nodes on right side, nodes are numbered n+1 to n+m
4  G = NIL[0] ? G1[G[1---n]] ? G2[G[n+1---n+m]]
5 */
6
7 bool bfs() {
8     int i, u, v, len;
9     queue<int> Q;
10    for(i=1; i<=n; i++) {
11        if(match[i]==NIL) {
12            dist[i] = 0;
13            Q.push(i);
14        }
15        else dist[i] = INF;
16    }
17    dist[NIL] = INF;
18    while(!Q.empty()) {
19        u = Q.front(); Q.pop();
```

Follow

Follow “হাবিজাবি
ইজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

```

20     if(u!=NIL) {
21         len = G[u].size();
22         for(i=0; i<len; i++) {
23             v = G[u][i];
24             if(dist[match[v]]==INF) {
25                 dist[match[v]] = dist[u] + 1;
26                 Q.push(match[v]);
27             }
28         }
29     }
30 }
31     return (dist[NIL]!=INF);
32 }
33
34 bool dfs(int u) {
35     int i, v, len;
36     if(u!=NIL) {
37         len = G[u].size();
38         for(i=0; i<len; i++) {
39             v = G[u][i];
40             if(dist[match[v]]==dist[u]+1) {
41                 if(dfs(match[v])) {
42                     match[v] = u;
43                     match[u] = v;
44                     return true;
45                 }
46             }
47         }
48         dist[u] = INF;
49         return false;
50     }
51     return true;
52 }
53
54 int hopcroft_karp() {
55     int matching = 0, i;
56     CLR(match);
57     while(bfs())
58         for(i=1; i<=n; i++)
59             if(match[i]==NIL && dfs(i))
60                 matching++;
61     return matching;
62 }
```

হেভী লাইট ডিকম্পজিশন [ইনডেক্স]

```

1 /*
2 Rough code for heavy light decomposition. Input g
3 Also includes the LCA method.
4 What to do with the chain is problem dependent.
5 */
6
7 vector< int > G[MAX];
8 int cost[MAX], lvl[MAX], parent[MAX];
9 int head[MAX], cnext[MAX], chainid[MAX], chainpos
10 int nchain, temp[MAX];
```

[Follow](#)

Follow “হাবিজাবি
ইজিবিজবিজ”

Get every new post delivered to
your inbox.

Join 67 other followers

[Sign me up](#)

```

11
12 int dfs(int u, int p, int d) {
13     int i, v, sz = G[u].size(), tmp, mx, id, tot, hd, k;
14     lvl[u] = d, mx = 0, id = u, tot = 1;
15     for(i = 0; i < sz; i++) {
16         v = G[u][i];
17         if(v != p) {
18             parent[v] = u;
19             tmp = dfs(v, u, d + 1);
20             tot += tmp;
21             if(tmp > mx) {
22                 mx = tmp;
23                 id = v;
24             }
25         }
26     }
27     if(tot == 1) cnext[u] = -1;
28     else cnext[u] = id;
29     for(i = 0; i < sz; i++) {
30         v = G[u][i];
31         if(v != p && v != id) {
32             for(hd = v, k = 0; v != -1; v = cnext[v], k++) {
33                 head[v] = hd;
34                 temp[k] = cost[v];
35                 chainpos[v] = k;
36                 chainid[v] = nchain;
37             }
38             // buff is the current chain of size k
39             nchain++;
40         }
41     }
42     return tot;
43 }
44
45 void hld(int v) {
46     int hd, k;
47     nchain = 0; lvl[0] = -1;
48     dfs(v, 0, 0);
49     for(hd = v, k = 0; v != -1; v = cnext[v], k++) {
50         head[v] = hd;
51         temp[k] = cost[v];
52         chainpos[v] = k;
53         chainid[v] = nchain;
54     }
55     // buff is the current chain of size k
56     nchain++;
57 }
58
59 int lca(int a, int b) {
60     while(chainid[a] != chainid[b]) {
61         if(lvl[head[a]] < lvl[head[b]]) b = parent[head[b]];
62         else a = parent[head[a]];
63     }
64     return (lvl[a] < lvl[b]) ? a : b;
65 }

```

[Follow](#)

Follow “শাবিজাবি হিজিবিজবিজ”

Get every new post delivered to your Inbox.

Join 67 other followers

[Sign me up](#)

টারজান'স অফলাইন এল.সি.এ [ইনডেক্স]

```

1  /*
2   Tarjan's offline LCA algorithm. For each pair of node's in P {u, v, qid},
3   it finds the LCA of the nodes in the rooted tree G (no edge to back to the |
4   The array ans holds the result for queries in orders defined by qid.
5  */
6
7  void lca(int u) {
8      int v, i, sz;
9      make_set(u);
10     ancestor[find_set(u)] = u;
11     sz = G[u].size();
12     for(i = 0; i < sz; i++) {
13         v = G[u][i];
14         lca(v);
15         union_set(u, v);
16         ancestor[find_set(u)] = u;
17     }
18     color[u] = 1;
19     sz = P[u].size();
20     for(i = 0; i < sz; i++) {
21         v = P[u][i].first;
22         if(color[v]) ans[P[u][i].second] = ancestor[find_set(v)];
23     }
24 }
```

বাইনারি সার্চ [ইনডেক্স]

```

1  /*
2   st and en defines the range [st, en) in a[]
3   in every range, start is inclusive and end is exclusive
4  */
5
6  // returns index of first element not less than val
7  int lowerbound(int *a, int st, int en, int val) {
8      int idx, cnt, stp;
9      cnt = en - st;
10     while(cnt > 0) {
11         stp = cnt >> 1; idx = st + stp;
12         if(a[idx] < val) st = ++idx, cnt -= stp+1
13         else cnt = stp;
14     }
15     return st;
16 }
17
18 // returns index of first element greater than val
19 int upperbound(int *a, int st, int en, int val) {
20     int idx, cnt, stp;
21     cnt = en - st;
22     while(cnt > 0) {
23         stp = cnt >> 1; idx = st + stp;
24         if(a[idx] <= val) st = ++idx, cnt -= stp+
25         else cnt = stp;
```

Follow

Follow “শাবিজাবি
ইজিবিজিবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

```

26     }
27     return st;
28 }
29
30 // returns true if items is found, otherwise false
31 bool binarysearch(int *a, int st, int en, int val) {
32     int lb = lowerbound(a, st, en, val);
33     return (lb != en && a[lb] == val);
34 }
35
36 // returns the interval where each element is equal to val
37 pair< int, int > equalrange(int *a, int st, int en, int val) {
38     int ub = upperbound(a, st, en, val);
39     int lb = lowerbound(a, st, en, val);
40     return pair< int, int >(lb, ub);
41 }
```

ডিসজয়েন্ট সেট [ইনডেক্স]

```

1 /*
2 disjoint set data-structure
3 implements union by rank and path compression
4 */
5
6 struct DisjointSet {
7     int *root, *rank, n;
8     DisjointSet(int sz) {
9         root = new int[sz+1];
10    rank = new int[sz+1];
11    n = sz;
12 }
13 ~DisjointSet() {
14     delete[] root;
15     delete[] rank;
16 }
17 void init() {
18     for(int i = 1; i <= n; i++) {
19         root[i] = i;
20         rank[i] = 0;
21     }
22 }
23 int find(int u) {
24     if(u != root[u]) root[u] = find(root[u]);
25     return root[u];
26 }
27 void merge(int u, int v) {
28     int pu = find(u);
29     int pv = find(v);
30     if(rank[pu] > rank[pv]) root[pv] = pu;
31     else root[pu] = pv;
32     if(rank[pu]==rank[pv]) rank[pv]++;
33 }
34 };
```

[Follow](#)

Follow “শাবিজাবি
হিজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

Enter your email address

[Sign me up](#)

2D বি.আই.টি [ইনডেক্স]

```

1  /*
2   update and query function for 2D bit.
3   MAX is the maximum possible value.
4   bit[][] holds the 2D binary indexed tree
5  */
6
7  void update(int x, int y, int v) {
8      int y1;
9      while(x <= MAX) {
10         y1 = y;
11         while(y1 <= MAX) {
12             bit[x][y1] += v;
13             y1 += (y1 & -y1);
14         }
15         x += (x & -x);
16     }
17 }
18
19 int readsum(int x, int y) {
20     int v = 0, y1;
21     while(x > 0) {
22         y1 = y;
23         while(y1 > 0) {
24             v += bit[x][y1];
25             y1 -= (y1 & -y1);
26         }
27         x -= (x & -x);
28     }
29     return v;
30 }
```

ডাবল হ্যাশিং [ইনডেক্স]

```

1  /*
2   M > N and should be close, better both be primes.
3   M should be as much large as possible, not exceeding array size.
4   HKEY is the Hash function, change it if necessary.
5  */
6
7 #define NIL -1
8 #define M 1021
9 #define N 1019
10 #define HKEY(x,i) ((x)%M+(i)*(1+(x)%N))%M
11
12 int a[M+1];
13
14 inline int hash(int key) {
15     int i = 0, j;
16     do {
17         j = HKEY(key, i);
18         if(a[j]==NIL) { a[j] = key; return j; }
19         i++;
20     } while(i < M);
21     return -1;
22 }
```

[Follow](#)

Follow “**শাবিজাবি**
হিজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

[Sign me up](#)

```

24  inline int find(int key) {
25      int i = 0, j;
26      do {
27          j = HKEY(key, i);
28          if(a[j]==key) return j;
29          i++;
30      } while(a[j]!=NIL && i < M);
31      return -1;
32  }

```

ম্যাপের সাহায্যে স্ট্রিং হ্যাশিং [ইনডেক্স]

```

1  /*
2  hash() takes the string and next free index as parameter.
3  if string is found in map, it returns its index.
4  else, it inserts in current free index and updates the free index.
5  */
6
7  inline int hash(char *s, int &n) {
8      int ret; it = M.find(s);
9      if(it == M.end()) M.insert(pair< string, int > (s, ret = n++));
10     else ret = it->second;
11     return ret;
12 }

```

বার্নস্টাইন স্ট্রিং হ্যাশিং [ইনডেক্স]

```

1  /*
2  u64 stands for unsigned long long type. Must use unsigned type.
3  hash = hash * 33 ^ c, reliable hash
4  */
5  u64 hash(const char* s) {
6      u64 hash = 0, c;
7      while((c = *s++)) hash = ((hash << 5) + hash) ^ c;
8      return hash;
9  }

```

Share this:



Like



6 bloggers like this.

[মন্তব্য \(0\)](#)

1. কোন মন্তব্য নেই এখনও

1. মার্চ 16, 2011; 11:04 পুর্বাহ্ন এ
[programing learning « LOVE FOR ALL](#)

মন্তব্যসমূহ বন্ধ করা হয়েছে।

[RSS feed](#)

Follow

Follow “হাবিজাবি
ইজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

Enter your email address

Sign me up

Email Subscription

Enter your email address to subscribe to this blog and receive notifications of new posts by email.

Join 67 other followers

[Sign me up!](#)

Calender

জুলাই 2016

S S M T W T F

					1	
2	3	4	5	6	7	8
9	10	11	12	13	14	15
16	17	18	19	20	21	22
23	24	25	26	27	28	29
30	31					

[« Feb](#)

Archives

- [ফেব্রুয়ারি 2011](#) (1)
- [অক্টোবর 2010](#) (1)
- [অগাষ্ট 2010](#) (1)
- [জুলাই 2010](#) (2)
- [নভেম্বর 2009](#) (1)

[Follow](#)

Tags

[avro](#) [bangla](#) [c++](#) [data structure](#) pair priority queue [programmir](#)

Blog Stats

- 29,209 hits

Top Posts

Get every new post delivered to your Inbox.

Join 67 other followers

[Sign me up](#)

- [কোড লাইব্রেরি](#)
- [আমি](#)
- [অন্যান্য লিঙ্ক](#)
- [C++ STL :: pair](#)

Meta

- [রেজিষ্টার](#)
- [লগ ইন](#)
- [আরএসএস](#)
- [মন্তব্য RSS](#)
- [Create a free website or blog at WordPress.com.](#)

[Top](#)

[Create a free website or blog at WordPress.com. The INove Theme.](#)

[Follow](#)

Follow “**শাবিজাবি**
হিজিবিজবিজ”

Get every new post delivered to
your Inbox.

Join 67 other followers

Enter your email address

Sign me up