ACE – System Architecture

Last updated: Oct 18, 2026

Team

The document refers to members as M1–M5. The full split of work is in Per-member work plan, schedule and risks.

Code	Member	Main area
M1	Singh Multani Gurinder	Data agents (job ads, profiles), orchestrator, Skill Taxonomy
M2	Ullah Asad	Kafka, Cassandra, sink, deployment, monitoring; team coordinator
M3	Bailey Kelen	Batch forecasting, Skills Gap, LLM module
M4	Roomi Babar Ali	API, web app and Europe map, threat agent
M5	Richartz Lena	Education, workforce and platform analysis agents

Overview

ACE is an agentic, event-driven platform that collects cybersecurity job ads, professional profiles, education programmes, workforce reports and threat data, then shows skill Demand, skill Supply, the Skills Gap and threats per country on maps and dashboards. It is a European counterpart to CyberSeek.

Key terms: Demand is how often job ads ask for a Skill. **Supply** is how many profiles in a country show a Skill over the last 365 days. The **Skills Gap** is Demand ÷ Supply. A **Skill**, **Certification** or **Role** is always an entry in the Skill Taxonomy. A **Country** is an ISO two-letter code; `EU` is a **Region**, used only in forecasts.

The system has six layers. Each layer is a separate containerized service, and the layers connect only through Kafka topics, Cassandra tables or the REST API:

1. **Agent layer**: separate AI agents collect raw data, extract normalized skills and analyse similar platforms.
2. **Ingestion layer**: Kafka carries all events. Every agent publishes to Kafka; there are no exceptions.
3. **Stream layer**: stream-mining pipelines compute Top 10 lists, frequency counts, emerging skills, hiring companies, and drift and burst alerts per country.
4. **Storage layer**: Cassandra stores raw records, aggregates and forecasts.
5. **Batch layer**: a forecasting model predicts skill Demand per country and for Europe, and a gap job compares Demand with Supply.
6. **Serving layer**: an API and a web app with a CyberSeek-style Europe map, a role explorer, per-member dashboards and a world threat map with scroll-back.


Mandatory constraints from the brief: Kafka for real-time ingest, Cassandra for storage, Docker Swarm or Kubernetes for deployment, and no Apache Spark for analysis.

Course requirements coverage

Requirement (from the brief)	ACE design
Agentic solution, separate AI agents per sub-task	6 agents (job ads, profiles, education, workforce, threats, platform analysis) + skill extraction, directed by a planning orchestrator that decides what to collect

Requirement (from the brief)	ACE design
Dataset from online sources (e.g. LinkedIn job ads and professional user profiles, CYBERHEAD database, ISC2 annual reports)	European job APIs and a job-ads dataset for Demand, the Stack Overflow Developer Survey for Supply, CYBERHEAD for education, ISC2 reports for workforce figures, plus public threat-intelligence feeds for the threat map. Public LinkedIn data is almost all from the US, so it is not used (see Risks)
Skills needed vs skills offered	Demand (job ads) vs Supply (profiles), compared through one shared Skill Taxonomy
Kafka, Cassandra, Docker Swarm/Kubernetes, no Spark	Kafka (KRaft), Cassandra, Kubernetes with Swarm fallback, Python stream processing
Batch 1: per-country and European skills-need forecasting	Forecasting job on Demand history (Prophet / ARIMA, LightGBM challenger)
Pipeline 1: Top 10 skills per country	S3 (Space-Saving)
Pipeline 2: skills-need frequency on a choropleth	S4 (Count-Min Sketch)
Pipeline 3: skills-offered frequency on a choropleth	S5 (exponential histograms)
World threat choropleth with scroll-back	S7 + S8 + Threat landscape dashboard
Additional dashboards	5 member dashboards + shared Europe map
Something similar to CyberSeek	Europe map with metric switch, Top 10 skills and certifications, Skills Gap, role explorer (career pathway)
Higher grade: analyse similar platforms	Platform analysis agent compares CyberSeek, ENISA ECSF tools and the ISC2 Workforce Study
Higher grade: research papers	Space-Saving, Count-Min Sketch, MinHash LSH, exponential histograms, ADWIN, Half-Space Trees, Lossy Counting, HyperLogLog

Architecture at a glance



The numbers follow the data: online sources (1) are collected by the AI agents (2) and published to Kafka (3). The live pipelines (4) read from Kafka, find the skills, count them and publish their results back. A sink saves the records and results in Cassandra (5), the batch jobs (6) read the history and write forecasts and the Skills Gap back, and the FastAPI service and React web app (7) show the results; the API also takes live alerts straight from Kafka, and Prometheus and Grafana track pipeline health. Each box names its owner (M1–M5); boxes marked AI use the AI model to read text. The AI model server itself is shown in the deployment diagram.

CyberSeek comparison

ACE mirrors CyberSeek's two main tools for Europe:

CyberSeek	ACE equivalent
Heat map coloured by job openings, workforce or supply/demand ratio	**Europe map** with a metric switch: job ads, Demand, Supply, Skills Gap, education programmes, threats
Top skills, certifications and job titles per state	Top 10 Skills and Top 10 Certifications per Country (S3)
Supply/demand ratio	Skills Gap per Skill and Country
Career pathway (roles, skills, certifications, feeder roles)	**Role explorer** built on the 12 ECSF role profiles: top Skills and Certifications, Demand per Country, education programmes and related roles

Data sources and agent layer

Each sub-task runs as its own AI agent in its own container, owned by the member who uses its data. Kubernetes keeps every agent running (starts, restarts and scales the containers); the orchestrator (M1) decides what the agents collect. Every agent publishes to Kafka and never writes to Cassandra directly.

Agent	Owner	Input source	Output topic	What it does
Job ads agent	M1	Live: Adzuna API (AT, BE, CH, DE, ES, FR, GB, IT, NL, PL), Bundesagentur für Arbeit job search API (DE). History: German job postings dataset (Hugging Face, 2015–2026)	`raw.jobs`	Replays the history dataset in `posted_date` order, fetches live ads when the orchestrator asks, and tags country, date, company and title
Profile agent	M1	Stack Overflow Developer Survey (yearly public CSVs), filtered to security roles and skills	`raw.profiles`	Replays survey answers as anonymous profiles, with the survey date as `profile_date`, and strips any identifying details
Education agent	M5	ENISA CYBERHEAD database	`raw.programmes`	Collects cybersecurity higher-education programmes per country and maps each to ECSF roles with an LLM
Workforce agent	M5	ISC2 annual workforce reports	`raw.workforce`	Parses report PDFs and tables into workforce figures per country and year
Threat agent	M4	Public threat-intelligence feeds (AlienVault OTX, AbuseIPDB)	`threats.events`	Collects live threat events and geolocates them to a country
Skill extraction agent (S2)	M1	`jobs.clean`, `raw.profiles`	`skills.demand`, `skills.supply`	LLM reads the text and returns Skills, Certifications and an ECSF role, all mapped to the Skill Taxonomy

Agent	Owner	Input source	Output topic	What it does
Platform analysis agent	M5	CyberSeek, ENISA ECSF tools, ISC2 Workforce Study	`analysis.platforms`	LLM compares platform features and publishes a structured comparison

Skill Taxonomy: every Skill, Certification and role is an entry in a closed, versioned list in `shared/taxonomy/`, derived from the European Cybersecurity Skills Framework (ECSF) with NICE cross-references. Mentions that match no entry are counted as Unmapped Skills for pipeline health and never shown on maps; S9 lists the most frequent ones as candidates for the next taxonomy version. The whole team builds the first version together: each member adds the Skills and Certifications for their own area, and M1 reviews and merges them. After that, M1 maintains it and changes are agreed by the whole team.

Replay in event time: job-ad history and profiles come from static datasets, so their agents replay them into Kafka in date order, and every window uses event time, not arrival time. Live job ads from the APIs and threat events use their own posting or observation date in the same way.

Geography: Demand and Supply are measured for the Skills Scope (EU27, EEA, UK and Switzerland); threats are measured worldwide. Countries are always ISO 3166-1 alpha-2 codes (`GR`, `GB`, never `EL`, `UK`). `EU` is a Region used only in forecasts, never in a `country` field.

Orchestration: the orchestrator is the planning agent, built with LangGraph or CrewAI in Python. Every 6 hours it reads coverage from Kafka (job ads per country from `agg.demand_daily`, programmes from `raw.programmes`, threats from `agg.threats_daily`, rejected messages from `errors.invalid`), finds gaps such as "few Job Ads for PL", and uses the LLM module to choose from a fixed list of actions that live sources can perform:

Action	Agent	Limit per task
Fetch job ads for a country from a job API (Adzuna or Bundesagentur für Arbeit)	Job ads agent	10 pages
Refresh education programmes for a country	Education agent	1 country
Refresh threat events for a country	Threat agent	24 hours of events
Rerun the platform comparison	Platform analysis agent	1 run per week

It publishes at most 5 tasks per run to `tasks.collect`, each with a one-sentence reason. Agents refuse any action not on the list. The replayed datasets are fixed files, so the orchestrator never asks the replay for more data. If the LLM is unavailable or over budget, fixed rules choose the same actions. Every task and its reason is stored in `orchestrator_decisions` and shown on a "What the orchestrator decided" panel next to pipeline health. Each agent is a separate process, so it can be scaled and restarted on its own.

Ingestion layer (Kafka)

Kafka is the only path into the system. Messages are JSON, validated against schemas in `shared/schemas/`. Topics are keyed by country code, so all events for one country land in the same partition and stay in order. The list of topics, with each topic's schema and key, is kept in one file, `shared/schemas/topics.csv`, which both the Python code and the topic setup script read.

Topic	Producer	Consumers	Key	Schema
`raw.jobs`	Job ads agent	S1	country	`raw_job`
`raw.profiles`	Profile agent	S2, sink	country	`raw_profile`
`raw.programmes`	Education agent	Sink, orchestrator	country	`raw_programme`
`raw.workforce`	Workforce agent	Sink	country	`raw_workforce`

Topic	Producer	Consumers	Key	Schema
`jobs.clean`	S1	S2, sink	country	`raw_job`
`skills.demand`	S2	S3, S4	country	`skills_demand`
`skills.supply`	S2	S5	country	`skills_supply`
`threats.events`	Threat agent	S7	country	`threat_event`
`agg.top10_demand`	S3	Sink, S6	country	`agg_top10`
`agg.demand_daily`	S4	Sink, S6, orchestrator	country	`agg_count`
`agg.supply_daily`	S5	Sink	country	`agg_count`
`agg.threats_hourly`	S7	Sink, S8	country	`agg_threats`
`agg.threats_daily`	S7	Sink, orchestrator	country	`agg_threats`
`agg.emerging_skills`	S9	Sink	country	`agg_emerging`
`agg.companies_daily`	S10	Sink	country	`agg_companies`
`alerts.drift`	S6	Sink, API live feed	country	`alert`
`alerts.threats`	S8	Sink, API live feed	country	`alert`
`analysis.platforms`	Platform analysis agent	Sink	platform	`platform_analysis`
`errors.invalid`	Shared `ace` package (any producer)	Pipeline-health panels, orchestrator	topic	`invalid_message`
`tasks.collect`	Orchestrator	Job ads, education, threat and platform analysis agents, sink	agent	`collect_task`

Example `skills.demand` message:

```
{
  "event_id": "uuid",
  "source": "adzuna",
  "country": "HU",
  "posted_date": "2026-10-01",
  "job_title": "SOC Analyst",
  "ecsf_role": "Cyber Incident Responder",
  "skills": ["SIEM", "Incident response", "Python"],
  "certifications": ["CompTIA Security+"],
  "unmapped": ["Splunk dashboards"]
}
```

Shared code

Everything except the React app is Python, so the code every member needs lives in one package, `shared/python/ace/`, installed in every container. It is a shared contract: its owners fix bugs freely, but changes to how it is used are agreed by the whole team.

Part	What it does	Used by	Owner
Stage base (`ace.stage`)	Runs a stream stage: consumes, checks message formats, applies event time and the grace period, emits once per window, publishes, and counts late and invalid records. Supports windowed stages (S3, S4, S5, S7, S9, S10) and per-record stages (S1, S2, S6, S8). Each stage supplies only its algorithm.	All 10 stages	M2

Part	What it does	Used by	Owner
Contracts (`ace.contracts`)	Reads `shared/schemas/topics.csv` (topic, schema, key), validates every message before it is published, and gives every module the topic names.	All agents and stages	M2
Skill matcher (`ace.taxonomy`)	Loads the Skill Taxonomy and maps a mention to a Skill, Certification or Role by exact name or listed alias, ignoring case; anything else is Unmapped.	S2, S3, S4, S5, gap job, education agent, role explorer	M1
LLM module (`ace.llm`)	The only path to an LLM. Switches between a local open-source model (Qwen via Ollama) and a hosted model (Claude Haiku 5.5) with one setting, caches answers in the `llm_cache` table so nothing is paid for twice, retries when the provider is busy, checks that answers are valid JSON, and stops at a daily budget (`LLM_DAILY_BUDGET_EUR`).	S2, education agent, platform analysis agent	M3
Replay module (`ace.replay`)	Replays a static dataset into Kafka in event-time order at a set speed (`REPLAY_SECONDS_PER_DAY`), and resumes from the position saved in `replay_position` after a restart. Each agent supplies only how to turn one dataset row into a message.	Job ads agent, profile agent	M1

- **Invalid messages** are not dropped: the contracts part publishes them to `errors.invalid` with the reason, and they are counted on the pipeline-health panels.
- **Testing:** the stage base runs either on Kafka or on an in-memory list of records, so every stage is tested with plain lists of fake records and no running Kafka. Every stage ships at least one such test. The LLM module replays recorded answers in tests, so tests never pay for LLM calls.
- **Test data:** a small fake dataset (about 200 job ads and 200 profiles across several countries, one JSON message per line) lives in `shared/testdata/` from **Oct 22**. The replay module plays it like the real datasets, so the whole pipeline runs from the first week.
- **Timeline:** the package and one example stage (S4) are ready by **Oct 27**, so all stages start from the same base on Nov 2.
- **LLM choice:** Qwen, an open-source model run locally through Ollama, is the default: it is free, handles German and French job ads well, and keeps all data on our own machines. Claude Haiku 5.5 is the hosted fallback. Both are compared on a hand-labelled sample of about 50 job ads (including German and French ones); if Qwen is clearly less accurate, the final run switches to Claude Haiku 5.5 with one setting.

Stream processing

Ten stream stages, two per member, consume from Kafka and publish their results back to Kafka. Each stage runs in its own container, built with Quix Streams and the River library for the stream-mining algorithms, with no Spark.

Stage	Member	Input → output	Algorithm	Purpose
S1 Near-duplicate filter	M1	`raw.jobs` → `jobs.clean`	MinHash + LSH	Drop job ads reposted on several sites
S2 Skill extraction	M1	`jobs.clean`, `raw.profiles` → `skills.demand`, `skills.supply`	LLM agent + Skill Taxonomy mapping	Turn free text into Skills, Certifications and an ECSF role
S3 Top 10	M2	`skills.demand` → `agg.top10_demand`	Space-Saving (top-k), mergeable daily summaries	Pipeline 1: Top 10 Skills and Top 10 Certifications per Country over the last 30 days, snapshotted daily
S4 Demand frequency	M2	`skills.demand` → `agg.demand_daily`	Count-Min Sketch, daily tumbling windows	Pipeline 2: Demand heat map, plus job ads per Country per day
S5 Supply frequency	M3	`skills.supply` → `agg.supply_daily`	Exponential histograms (DGIM), 365-day sliding window	Pipeline 3: Supply heat map

Stage	Member	Input → output	Algorithm	Purpose
S6 Demand drift detection	M3	`agg.demand_daily`, `agg.top10_demand` → `alerts.drift`	ADWIN	Flag Skills whose Demand shifts, which triggers forecast retraining
S7 Threat frequency	M4	`threats.events` → `agg.threats_hourly`, `agg.threats_daily`	Hourly and daily tumbling windows	World threat map with scroll-back
S8 Threat burst detection	M4	`agg.threats_hourly` → `alerts.threats`	Half-Space Trees, one model per Country	Mark unusual threat spikes per country
S9 Emerging skills	M5	`skills.demand` → `agg.emerging_skills`	Lossy Counting over Unmapped Skills, 30-day window	Find new skills employers ask for that the Skill Taxonomy does not have yet
S10 Hiring companies	M5	`jobs.clean` → `agg.companies_daily`	HyperLogLog, mergeable daily sketches	Count distinct companies hiring per Country for the Europe map

Rules for every stage

- **Event time:** windows use the record's own date (`posted_date`, profile date, `observed_at`), never arrival time.
- **Grace period:** a window stays open 1 hour of event time after it ends for job ads and profiles, and 15 minutes for threats. Records arriving later are dropped and counted in a `late_records_total` metric for the pipeline-health panels.
- **Emit once:** a window's result is published once, when it closes (`.final()` in Quix Streams). Sink writes are idempotent upserts, so a replay never creates duplicate rows.
- **State:** stage state is kept in Kafka changelog topics, so a restarted stage continues where it stopped.

Stage notes

- **S3:** Space-Saving keeps one summary per (Country, day); summaries are mergeable, so the 30-day Top 10 is the merge of the last 30 daily summaries. It runs separately for Skills and for Certifications.
- **S4:** one Count-Min Sketch per (Country, day) window. When the window closes, the stage queries the sketch for every Skill Taxonomy entry, so the taxonomy is the key set. It also emits the plain count of job ads per Country per day for the Europe map.
- **S5:** Supply is a stock, not a flow: a profile has no posting date, so counting profiles per day would only show when the dataset was collected. It counts Profiles per (Country, Skill) over the last 365 days of profile dates, using exponential histograms to keep memory bounded, and emits the count as of each day.
- **S6:** one ADWIN detector per (Country, Skill) for Skills that have appeared in that Country's Top 10 at least once, plus one per Skill for the EU-wide sum. EU-level drift triggers early forecast retraining; Country-level drift shows as alerts.
- **S8:** features are log-scaled hourly counts per threat type plus hour-of-day. Each Country has its own model, so "unusual" means unusual for that Country.
- **S9:** Lossy Counting keeps every Unmapped mention whose count may be above a support threshold, with a known maximum error, in bounded memory. Each day it emits the most frequent mentions per Country over the last 30 days. M1 reviews them when updating the Skill Taxonomy; they are never shown on maps.
- **S10:** one HyperLogLog sketch of company names per (Country, day). Sketches are mergeable, so the 30-day count is the merge of the last 30 daily sketches. Job ads with no company are counted separately, so missing data stays visible.

Storage (Cassandra)

One **sink service** (owned by M2) consumes the topics listed below and writes them to Cassandra. For each topic it has one small function that turns a message into rows for each target table, so the row-splitting rules are tested like any other code; a ConfigMap only switches topics on and off. It is the only writer for stream data. Tables are designed query-first, one table per screen or question, and each query reads a single partition where possible. When two screens need the same data in different shapes, the sink writes it to both tables. Everything lives in keyspace `ace`, with replication factor 3 in the cluster. The schema is in `storage/cql/schema.cql`.

Counts use `kind` (`skill`, `certification` or `role`) and `item` (the taxonomy entry), so one set of tables serves Skills, Certifications and ECSF roles.

Table	Written from	Partition key	Clustering key	Answers
`job_ads_raw`	`jobs.clean`	(country, month)	posted_date, event_id	Raw de-duplicated job ads, used for retraining
`profiles_raw`	`raw.profiles`	(country, month)	event_id	Raw anonymized profiles
`education_programmes`	`raw.programmes`	country	programme_id	Programmes per country and the ECSF roles they teach
`workforce_baseline`	`raw.workforce`	country	year	Workforce figures per country
`job_ads_by_day`	`agg.demand_daily`	day	country	Europe map: job ads per country
`demand_by_day`	`agg.demand_daily`	(country, day)	kind, item	Country panel: Demand for every item on one day
`demand_map`	`agg.demand_daily`	(kind, item, day)	country	Europe map: Demand for one item across countries
`demand_trend`	`agg.demand_daily`	(country, kind, item)	day	Time series for one item, input to forecasting and the role explorer
`supply_by_day`	`agg.supply_daily`	(country, day)	kind, item	Country panel: Supply as of one day
`supply_map`	`agg.supply_daily`	(kind, item, day)	country	Europe map: Supply for one item across countries
`top10`	`agg.top10_demand`	(country, day, kind)	rank	Top 10 Skills or Certifications for a country, with scroll-back
`threats_by_day`	`agg.threats_daily`	day	country, threat_type	World threat map for one day (scroll-back)
`threats_by_hour`	`agg.threats_hourly`	(country, day)	hour, threat_type	Threat line chart for one country
`emerging_skills`	`agg.emerging_skills`	(country, day)	mention	Emerging skills list on the Education and workforce dashboard
`companies_by_day`	`agg.companies_daily`	day	country	Europe map: hiring companies per country
`alerts`	`alerts.*`	(country, day)	created_at, alert_type, subject	Drift (S6) and burst (S8) alerts
`platform_analysis`	`analysis.platforms`	platform	feature	Feature comparison of similar platforms

Table	Written from	Partition key	Clustering key	Answers
`forecasts`	Forecast job	(region, skill)	target_month	Forecast values and confidence band
`skills_gap`	Gap job	(country, month)	skill	Demand vs Supply per Skill
`role_relations`	Gap job	role	related_role	Related ECSF roles for the role explorer
`llm_cache`	LLM module	(task, input_hash)	–	Cached LLM answers, so nothing is paid for twice
`replay_position`	Replay module	dataset	–	Where each dataset replay stopped, so a restart resumes
`orchestrator_decisions`	`tasks.collect`	day	created_at, task_id	What the orchestrator decided and why

Raw tables use a time-to-live (TTL) of 2 years. Aggregate tables are kept with no expiry.

Batch processing

Batch jobs run as scheduled containers (Kubernetes CronJobs), read from Cassandra, and write their results back to Cassandra. They use pandas and scikit-learn, not Spark.

Batch 1: Skill Demand forecasting

- Input: `demand_trend` for `kind = skill`, summed to monthly counts per Country. The `EU` Region forecast is trained on the sum across EU countries.
- Models: Prophet or ARIMA/ETS (statsmodels) per Country and Skill, with LightGBM over lag features as a challenger.
- Evaluation: a time-based train/test split (last 3 months held out), scored by MAE and MAPE.
- Output: `forecasts` with a 6–12 month horizon and confidence bands.
- Schedule: retrained weekly, and early when S6 flags EU-level drift.

Skills Gap job (monthly): computes Demand ÷ Supply per Skill and Country and writes it to `skills_gap`. The ratio is only computed when Supply is at least `GAP_MIN_SUPPLY` (default 20, set in a ConfigMap); below that, `gap_ratio` is left empty and the dashboard shows "not enough supply data". The same job computes `role_relations`: two ECSF roles are related when their top Skills overlap most.

Serving and visualization

A FastAPI service is the only reader of Cassandra for the web app. M4 sets up the service and the React app shell; each member writes the endpoints and the page for their own dashboard, so every dashboard is one member's work end to end. A React app calls it over REST, and a WebSocket pushes new alerts. The maps use Leaflet or ECharts with GeoJSON country borders.

Endpoint	Returns	Used by
`GET /map?metric=&date=&item=`	One value per country for a metric (`job_ads`, `demand`, `supply`, `gap`, `programmes`, `companies`, `threats`)	Europe map, world threat map
`GET /top10?country=&kind=&date=`	Top 10 Skills or Certifications	Country panel, Skills demand dashboard
`GET /forecast?region=&skill=`	Forecast series with bands	Forecast dashboard

Endpoint	Returns	Used by
`GET /gap?country=&month=`	Demand vs Supply per Skill	Gap dashboard
`GET /threats/hourly?country=&from=&to=`	Hourly threat counts with burst alerts	Threat landscape dashboard
`GET /roles` and `GET /roles/{role}?country=`	ECSF roles; for one role its top Skills and Certifications, Demand per country, programmes and related roles	Role explorer
`GET /platforms`	Platform feature comparison	Education and workforce dashboard
`GET /education?country=`	Programmes per ECSF role and workforce figures for a country	Education and workforce dashboard
`GET /emerging?country=&date=`	Most frequent Unmapped Skills over the last 30 days	Education and workforce dashboard
`WS /live`	New drift and burst alerts as they arrive	Live feed

Europe map (home page, M4): CyberSeek's main screen for Europe. A choropleth with a metric switch (job ads, Demand, Supply, Skills Gap, education programmes, hiring companies) and an optional Skill filter. Clicking a country opens a panel with its Top 10 Skills and Certifications, workforce figures and alerts.


Dashboards: each member builds one dashboard with at least 2 graphs, all in the same React app.

Dashboard	Member	Graphs
Role explorer (career pathway)	M1	One card per ECSF role; top Skills and Certifications for a role (bar); Demand for the role per country (choropleth); education programmes teaching it; related roles
Skills demand	M2	Choropleth of Demand with a Skill filter; Top 10 Skills per country (bar); Top 10 Certifications per country (bar)
Supply, gap and forecast	M3	Choropleth of Supply; Demand vs Supply per Skill (grouped bar); forecast with confidence band (line); drift alerts
Threat landscape	M4	World threat choropleth with a time slider for scroll-back; threats per hour or day with S8 burst markers (line); threat types (bar)
Education and workforce	M5	Education programmes per country next to Demand (choropleth + bar); workforce figures per country (bar); emerging skills (ranked list); hiring companies per country (choropleth); platform comparison table

Pipeline health (records ingested per source, duplicates removed by S1, extraction success rate, Unmapped Skills, late records, daily LLM spend) is shown as Grafana panels built by M2 as part of monitoring. Next to it, a "What the orchestrator decided" panel (M1) lists recent collection tasks and their reasons.

Deployment

Every component ships as a Docker image. Development runs on Docker Compose, and the final system runs on Kubernetes, with Docker Swarm as a fallback.



Every box is one Docker container. Arrows point from the container that opens a connection to the one it calls, and the numbers are the ports (Kafka 9092, Cassandra 9042, the AI model server 11434). Kafka and Cassandra run as 3-node StatefulSets, each stream stage runs as its own pod so it can scale with its topic partitions, and the browser loads the page from the web app and calls the API, both through the ingress.

Component	Kubernetes object	Replicas
Kafka brokers (KRaft mode)	StatefulSet	3
Cassandra nodes	StatefulSet	3
Agents	Deployment, one per agent	1–2 each
LLM server (Ollama with Qwen)	Deployment + Service	1
Stream stages	Deployment, one per stage	1–3 (up to the partition count)
Sink	Deployment	2
Forecast and gap jobs	CronJob	Runs on schedule
API	Deployment + Service	2
Web app	Deployment + Ingress	2

- **Configuration:** ConfigMaps hold the topics the sink writes, schedules, `GAP_MIN_SUPPLY`, `LLM_PROVIDER`, `LLM_DAILY_BUDGET_EUR` and `REPLAY_SECONDS_PER_DAY`. Secrets hold API keys: Adzuna, the threat feeds and the hosted LLM fallback.
- **Monitoring:** Kafka UI to inspect topics, Prometheus and Grafana for service health and pipeline health.
- **CI:** GitHub Actions builds the images and runs tests on every pull request.

Technology stack

Layer	Technology	Why
Agents	Python, LangGraph or CrewAI, Qwen via Ollama (local, open source), Claude Haiku 5.5 as hosted fallback	Separate agents per sub-task, as the brief requires
Ingestion	Apache Kafka (KRaft)	Required by the brief; real-time and replayable
Stream processing	Quix Streams, River	Python stream processing on Kafka without Spark; maintained, with event-time windows
Storage	Apache Cassandra	Required by the brief; fast time-series writes
Batch / ML	pandas, Prophet, statsmodels, LightGBM	Light forecasting stack, no Spark
API	FastAPI	Async Python, auto-generated OpenAPI docs
Frontend	React, Leaflet or ECharts	Choropleth maps and dashboards
Deployment	Docker, Kubernetes or Docker Swarm	Required by the brief
CI / monitoring	GitHub Actions, Prometheus, Grafana	Automated builds and service health


Per-member work plan, schedule and risks

Each member is responsible for one component, two stream stages, one dashboard and one report section, so each person can be graded on their own work. The shared contracts (Skill Taxonomy, Kafka schemas, Cassandra tables and API endpoints) belong to the whole team, and changes to them are agreed together. A coordinator settles contract changes and runs integration; each member still owns, and is graded on, their own component.

Member	Component	Stream stages	Dashboard	Report and slides
M1 – Singh Multani Gurinder	Job ads and profile agents, orchestrator, Skill Taxonomy (review and merge), skill matcher, replay module, fake test data, dataset selection	S1 near-duplicate filter, S2 skill extraction	Role explorer	Datasets section
M2 – Ullah Asad	Kafka, Cassandra, sink, Docker/Kubernetes, CI, monitoring and pipeline-health panels, stage base and contracts	S3 Top 10 (Space-Saving), S4 Demand frequency (Count-Min)	Skills demand	System architecture section
M3 – Bailey Kelen	Batch forecasting, Skills Gap job, LLM module	S5 Supply frequency (exponential histograms), S6 drift detection (ADWIN)	Supply, gap and forecast	Testing and experiments section
M4 – Roomi Babar Ali	FastAPI service and React app shell, Europe map, map components, threat agent	S7 threat frequency, S8 burst detection (Half-Space Trees)	Threat landscape	Abstract, introduction, slide deck
M5 – Richartz Lena	Education (CYBERHEAD), workforce (ISC2) and platform analysis agents; proposes the S9 and S10 topics and tables	S9 emerging skills (Lossy Counting), S10 hiring companies (HyperLogLog)	Education and workforce	Related work (similar platforms)

Every member writes the agents, API endpoints and dashboard page for their own area, adds the Skills and Certifications for their area to the Skill Taxonomy, contributes 2–4 references for their own algorithms, and proofreads the report.

Schedule



The plan aims for the Nov 26 (12:00 CET) early submission. Dec 6 is the fallback.

Risks

- **European data coverage:** public LinkedIn job-ad datasets are almost all from the US (under 1% of rows in the Skills Scope), LinkedIn has no public API for reading job ads, and scraping breaks its terms. Mitigation: European job APIs, a German job-ads dataset and the Stack Overflow survey instead. If coverage is still thin (target: about 100 cybersecurity job ads per country per month), the Skills Scope is narrowed to the countries with enough data.
- **Short live history:** the job APIs only return ads that are open now, so by Nov 26 we hold about 6 weeks of live data. Mitigation: forecasts train on the replayed history; live data feeds the 30-day stages (S3, S9, S10).
- **Personal data in profiles:** names and identifiers are removed at the profile agent, and only skills, country and date are stored.
- **LLM cost and accuracy:** all LLM calls go through one module that caches answers, enforces a daily budget and can switch to a free local model. Extraction results are spot-checked against a hand-labelled sample, and the Unmapped Skills rate and daily LLM spend are tracked.

Platforms and data sources

Platforms analysed

- CyberSeek: cybersecurity supply and demand heat map and career pathway (US).
- ENISA ECSF: European role profiles.
- ENISA CYBERHEAD: European cybersecurity higher-education database.

Data sources

- Adzuna API: job ads for 10 countries in the Skills Scope, including France (free developer key).
- Bundesagentur für Arbeit job search API: German job ads (open, unofficial documentation).
- German job postings dataset: German job ads 2015–2026 with ESCO skills, used as job-ad history.
- Stack Overflow Developer Survey: yearly survey of IT professionals with country, role and skills (ODbL), used for Supply.
- Cedefop Skills-OVATE: EU online job-ad statistics by country, occupation and skill, used to check our Demand numbers.