

1. BOX CONTENTS

- AquaPearl 500 Pro main unit
- Under-sink mounting bracket
- Inlet and outlet tubing (2m each)
- Dedicated faucet with mounting hardware
- Power adapter
- Quick start guide
- Sediment, carbon, and RO membrane filter cartridges (pre-installed)

2. TECHNICAL SPECIFICATIONS

Flow rate: 2.5 litres per minute

Tank capacity: 4 litres (integrated storage tank)

Dimensions: 38cm (H) x 30cm (W) x 15cm (D)

Power: 24V DC, 0.5A (via included adapter)

Filter stages: 3 (sediment, carbon, RO membrane)

Input water pressure range: 20-80 psi

Input water temperature range: 4-38 degrees Celsius

3. CONTROL PANEL AND INDICATOR LIGHTS

The unit has a single status LED on the front panel.

- Solid blue: normal operation
- Slow blinking blue: filter due for replacement soon
- Solid red: fault detected, check audible alert code
- Blinking red: active fault, see Troubleshooting Guide
- Off: no power

4. OPERATING INSTRUCTIONS

Press and hold the front panel button for 2 seconds to dispense water. Release to stop. The unit will automatically shut off after 5 minutes of continuous dispensing as a safety measure.

5. FILTER REPLACEMENT INTERVALS

Sediment pre-filter: every 3 months, or when alert E-03 sounds

Carbon filter: every 6 months, or when alert E-04 sounds

RO membrane: every 12 months, or when alert E-05 sounds (see Product Changelog for firmware-dependent meaning of E-05)

6. CLEANING AND DESCALING SCHEDULE

Wipe the exterior with a damp cloth monthly. Descale the internal tank every 6 months using the descaling solution available from Pearlz, following the instructions included with that product.

7. SAFETY WARNINGS

Do not use with water from an unregulated or untested source. Do not attempt to open the unit while connected to power. Do not use if the power adapter or tubing shows visible damage.

8. AUDIBLE ALERT CODES

See the Troubleshooting Guide for the full table of alert codes E-01 through E-08.