

LAMP-Merge: Long-tail-Aware Medical Prototype Merging for One-shot Asynchronous Clinical Models

Anonymous submission

Abstract

Model merging aims to integrate multiple independently trained local checkpoints into a unified global model, typically through general-purpose paradigms such as parameter interpolation, task-vector composition, or update-direction alignment. These methods implicitly assume that client models share relatively complete and comparable global discriminative structures. We argue that this assumption does not hold in medical settings, giving rise to two diagnostic-structure anomalies: (1) Aggregation-induced prediction collapse after merging: When clients have incomplete diagnostic-class coverage, multiple locally effective models can be merged into a globally collapsed model whose predictive distribution concentrates on a small number of dominant classes. (2) Long-tailed medical prevalence cannot be ignored. Majority classes in medical data often reflect genuine clinical prevalence rather than merely data noise. To address these challenges, we propose LAMP-Merge, which recasts medical model merging from global parameter interpolation as class-level diagnostic-evidence reconstruction. Through diagnostic prototype reconstruction (DPR) and long-tail prevalence calibration (LPC), LAMP-Merge constructs a global diagnostic model without exposing raw medical images or requiring multi-round federated communication. Experiments on the Blood, Derma, Organ-C, Organ-S, and Ultrasound medical imaging datasets show that LAMP-Merge outperforms existing model-merging methods in most client-averaged settings while substantially mitigating prediction collapse.

Introduction

Federated learning (McMahan et al. 2017; Li et al. 2020; Karimireddy et al. 2020; Kairouz et al. 2021) and model merging (Izmailov et al. 2018; Wortsman et al. 2022; Ilharco et al. 2023; Yadav et al. 2023) provide two important collaboration routes for privacy-sensitive multi-center medical intelligence. Federated learning enables hospitals to train collaboratively without sharing raw data (Sheller et al. 2020; Rieke et al. 2020), while model merging further reduces communication and optimization costs by integrating independently trained local models after training (Ainsworth, Hayase, and Srinivasa 2023; Stoica et al. 2024; Wu et al. 2025). These

paradigms are particularly attractive for medical imaging, because a single hospital rarely covers the full disease spectrum, while privacy regulations and device heterogeneity make centralizing raw medical images difficult (Kaissis et al. 2020a; Bonawitz et al. 2019; Abadi et al. 2016).

Despite their success on natural images and general visual tasks (Izmailov et al. 2018; Wortsman et al. 2022; Ilharco et al. 2023; Entezari et al. 2022; Ainsworth, Hayase, and Srinivasa 2023), transferring these paradigms to medical data remains challenging. A key reason is that general-purpose model merging implicitly assumes that different client checkpoints contain relatively complete and comparable global discriminative structures; local models are expected to align through parameter space, task-vector space, update signs, or curvature statistics (Yadav et al. 2023; Yu et al. 2024; Wu et al. 2025; Jin et al. 2025). This assumption does not hold in medical scenarios. Medical centers differ not only in device domains but also in diagnostic-class availability: some centers may mainly cover common diseases or specific examination types, while having few rare-disease samples (Guan and Liu 2022; Zech et al. 2018; Li et al. 2021). The resulting local models are not complete replicas of the global task, but partial diagnostic experts supported by locally observed diseases.

As illustrated in Fig. 1, we summarize these challenges as two diagnostic-structure abnormalities in medical model merging:

- Diagnostic evidence fragmented across isolated medical clients. Each client has reliable supervision only for observed classes; thus, a local model may be locally discriminative but still lack evidence for the full global diagnostic space (Guan and Liu 2022; Li et al. 2021).
- Long-tailed Medical Image Prevalence. Medical image datasets naturally follow a long-tailed distribution: a few common diagnostic classes dominate the samples, while rare classes are underrepresented (Buda, Maki, and Mazurowski 2018; Brodersen et al. 2010). Under this imbalanced class prior, a merged model collapsed to the majority class can still obtain high Accuracy despite lacking complete




Figure 1: In multicenter healthcare settings, individual clients typically observe only a subset of the global diagnostic space. Conventional parameter-level model-merging methods can therefore cause the merged global model’s predictions to concentrate on a small number of dominant classes.

multi-class discrimination.

To address these issues, we propose LAMP-Merge, a long-tail-aware medical prototype-merging method for single-shot asynchronous medical image model merging. LAMP-Merge shifts the merge target from global parameter interpolation to class-level diagnostic-evidence reconstruction. The key idea is to use client-uploaded class-level statistics as a synchronization signal for the global diagnostic space, allowing the server to reconstruct a global diagnostic classifier without accessing raw medical images, using a server-side validation set, or conducting multi-round federated communication. Specifically, LAMP-Merge consists of two mechanisms: diagnostic prototype reconstruction aggregates reliable class-level evidence through prototypes in a shared reference feature space, and long-tail prevalence calibration injects a bounded prior bias from client-uploaded class counts, thereby mitigating prediction collapse while preserving clinically meaningful majority-class prevalence.

Our main contributions are summarized as follows:

- **Medical Merging Diagnosis.** We revisit model merging under single-shot asynchronous medical collaboration and identify limited local diagnostic coverage and aggregation-induced prediction collapse as two key abnormalities caused by medical class availability and long-tailed prevalence.
- **LAMP-Merge.** We propose a long-tail-aware medical prototype-merging method that reconstructs a global diagnostic classifier from client-side class prototypes and prevalence statistics without exposing raw images or requiring multi-round federated optimization.
- **Empirical Validation.** We conduct full-scope experiments on five medical image datasets, four vision-model families, three client-population sizes, and three non-IID skew levels, showing that LAMP-

Merge consistently outperforms strong model-merging baselines and improves prediction-collapse diagnostics.

Related Works

Model Merging

Model-merging methods integrate independently trained checkpoints in parameter, task-vector, or geometric spaces. Weight averaging (Izmailov et al. 2018) and Model Soups (Wortsman et al. 2022) directly interpolate parameters; permutation-aware matching (Entezari et al. 2022; Ainsworth, Hayase, and Srinivasa 2023) aligns hidden-unit symmetries; ZipIt (Stoica et al. 2024) performs feature-level zipping; Task Arithmetic (Ilharco et al. 2023), TIES-Merging (Yadav et al. 2023), and DARE (Yu et al. 2024) manipulate task deltas and sign conflicts; Fisher merging (Wu et al. 2025), RegMean (Jin et al. 2025), Model Stock (Jang, Yun, and Han 2025), Bread-crumbs (Davari and Belilovsky 2024), Iso-C (Marczak et al. 2025), FreeMerge (Zheng and Wang 2025), and RobustMerge (Zeng et al. 2025) introduce curvature, mean-statistic, subspace, frequency-domain, or robustness assumptions.

However, these methods share a class-agnostic merging interface: their variables are global parameters, task vectors, update signs, or geometric statistics rather than class-level diagnostic evidence. They do not encode whether a client has reliable supervision for a specific medical class. Under incomplete local class coverage and long-tailed prevalence, reliable class directions can be mixed with absent or conflicting directions from other clients, resulting in aggregation-induced prediction collapse (Buda, Maki, and Mazurowski 2018; Zech et al. 2018).

Medical Model Merging

Medical fusion studies exploit domain structures such as irregular clinical time series, physiological sensor graphs, and image-EHR fusion. mTAN (Shukla and Marlin 2021), Raindrop (Zhang et al. 2022), and MedFuse (Hayat, Geras, and Shamout 2023) show that medical tasks benefit from modeling clinical sampling mechanisms, modality heterogeneity, and patient-level temporal relations.

However, their fusion objects are usually patient-level inputs, multimodal records, or clinical representations rather than independently trained image-classifier checkpoints. They often require patient samples, timestamps, electronic health records, or server-side validation feedback, which conflicts with common privacy constraints (Kaissis et al. 2020a; Sheller et al. 2020; Bonawitz et al. 2019). MedMerge (Wei et al. 2026) is a relevant training-free medical knowledge-transfer framework, but it targets cross-modal adaptation for medical vision-language models rather than asynchronous checkpoint merging for the same classification task. Thus, existing medical fusion routes are




Figure 2: Local models from multicenter hospitals typically contain only partial diagnostic knowledge, while raw medical images cannot be centrally shared. LAMP-Merge reconstructs a privacy-friendly global medical classifier through DPR and LPC, without accessing raw data or requiring multi-round federated optimization.

mismatched with our privacy and single-upload protocol constraints. LAMP-Merge keeps the medical structure uploadable by using only locally computed class prototypes and prevalence counts.

Federated Learning

Federated and decentralized learning perform collaborative training through communication protocols. FedAvg (McMahan et al. 2017) and its variants or medical deployments (Li et al. 2020; Karimireddy et al. 2020; Li et al. 2021; Kaissis et al. 2020b; Sheller et al. 2020; Rieke et al. 2020; Kairouz et al. 2021) rely on repeated server-client updates; Swarm Learning (Warnat-Herresthal et al. 2021) and Gossip Learning (Heged\Hus, Danner, and Jelasity 2019) reduce centralization but still require participants to continue training, exchanging models, and optimizing from intermediate states.

However, our setting begins after local training has finished. Hospitals may not remain online, receive global checkpoints repeatedly, or run additional optimization rounds. The bottleneck is therefore communication feasibility in addition to privacy. LAMP-Merge requires one upload of a local model interface and class-level statistics, enabling the server to construct a unified diagnostic model without a multi-round feedback loop.

Method

In this section, we first formulate the diagnostic-structure pathologies exposed when generic model merging is applied to medical data, namely limited local diagnostic coverage and aggregation-induced prediction collapse. To correct these intrinsic mismatches, we pro-

pose LAMP-Merge, a two-stage framework composed of DPR and LPC, as shown in Fig. 2.

Preliminaries

Problem Formulation. Assume K medical clients. Client i owns a private labeled dataset $D_i = \{(x, y)\}$ drawn from a class-skewed medical distribution over C diagnosis classes. Let $D_{i,c}$ denote the subset of client i belonging to diagnosis class c . In medical partitions, $D_{i,c}$ can be empty for many classes; therefore, client i has reliable supervision only for its observed classes. The goal is to construct a global diagnostic model under this partial and heterogeneous diagnostic-label coverage.

Upload and Server Constraints. We study single-shot asynchronous merging: after local training, each client uploads only once, while the server cannot access raw medical images, per-sample features, per-sample predictions, or a server-side validation set, and does not issue multi-round updates to clients. Clients are allowed to upload class-level statistics. Specifically, $n_{i,c}$ denotes the class-support count, $m_{i,c}$ denotes the class-prevalence count, and $\mu_{i,c}$ denotes the class prototype computed in a shared reference feature space. The server performs one merge using only the local checkpoint interfaces and these class-level statistics. This setting differs from federated learning because clients do not continue optimization from server feedback; it also differs from standard model merging because the presence of class-level diagnostic evidence becomes an explicit merging variable.

Motivation

Although generic model merging is training-free and parameter-efficient, we find that its diagnostic structure can severely degenerate in medical model merging. Prediction-distribution diagnosis and class-support analysis reveal two key abnormalities:

(1) Aggregation-induced prediction collapse. Under partial diagnostic coverage, parameter-level merging can turn several locally useful predictors into a globally collapsed predictor. The merged model tends to allocate most test images to a few dominant classes, indicating that global class-discriminative structure has not been reconstructed.

(2) Prevalence prior cannot be ignored. Medical datasets often exhibit clinically meaningful long-tailed prevalence. Therefore, completely suppressing majority-class dominance is also inappropriate: a collapsed predictor is undesirable, but a merger should still preserve calibrated disease prevalence when the dominant class reflects the true clinical prior.

Diagnostic Prototype Reconstruction Module

To mitigate the fragmented diagnostic evidence across isolated medical clients caused by heterogeneous diagnostic coverage and conflicting class evidence, the diagnostic prototype reconstruction module shifts the merging target from parameter averaging to class-conditional evidence reconstruction. Instead of directly averaging local classifiers, it first collects reliable evidence for each diagnosis class in a shared reference space and then synthesizes a global diagnostic head over the full label space.

(1) Reference-space Class Prototype Extraction. First, all clients extract class prototypes with the same frozen reference backbone. Let ϕ_0 be the reference backbone instantiated from the shared model configuration before local training, and let $T(\cdot)$ be the evaluation transform. For each diagnosis class c , client i locally computes a reference-space class prototype

$$\mu_{i,c} = \frac{1}{n_{i,c}} \sum_{(x,y) \in D_i} \mathbf{1}[y=c] \phi_0(T(x)), \quad (1)$$

where $n_{i,c} = |D_{i,c}|$ is the class support count. If $n_{i,c} = 0$, the client uploads zero support for that class and contributes no prototype evidence.

(2) Support-aware Evidence Aggregation. Second, the server converts class-support counts into evidence weights to characterize the reliability of each client for a given class:

$$e_{i,c} = (n_{i,c} + 1)^\gamma \mathbf{1}[n_{i,c} > 0], \quad (2)$$

where $\gamma = 0.55$ is the default evidence exponent. This weight gives larger class-specific contribution to clients with more supervised samples of class c , while excluding

clients that never observe this class. The normalized reliability is

$$\alpha_{i,c} = \frac{e_{i,c}}{\sum_{j=1}^K e_{j,c}}. \quad (3)$$

The global diagnosis prototype is obtained by class-wise reliability-weighted aggregation:

$$p_c = \sum_{i=1}^K \alpha_{i,c} \mu_{i,c}. \quad (4)$$

This step aggregates evidence only from clients that have actually observed class c , preventing absent-class classifiers from diluting valid diagnostic signals.

(3) Prototype-induced Diagnostic Head. Finally, LAMP-Merge maps global diagnosis prototypes into a cosine prototype classifier:

$$w_c = s \frac{p_c}{\|p_c\|_2}, \quad (5)$$

where $s = 18.75$ is the default head scale. The resulting head is not an average of local classifier parameters; it is induced by class evidence in the shared reference space, thereby restoring multiclass diagnostic directions over the global label space.

Long-tail Prevalence Calibration

To address the fact that prevalence prior cannot be ignored in real medical tasks, the long-tail prevalence calibration module introduces a bounded class prior after prototype reconstruction. This module does not push the model back to single-class collapse; instead, it calibrates the clinical prevalence reflected by client statistics after multiclass diagnostic directions have been restored.

(1) Client-reported Prevalence Prior. First, each client uploads class-prevalence counts $m_{i,c}$. The server estimates the global class prior

$$\pi_c = \frac{\sum_{i=1}^K m_{i,c}}{\sum_{k=1}^C \sum_{i=1}^K m_{i,k}}. \quad (6)$$

This prior is computed only from class-level counts, not from raw images, per-sample features, or per-sample predictions.

(2) Long-tail Activation Criterion. Second, to avoid unnecessary calibration in non-long-tailed cases, the server measures dominant-class imbalance by

$$r = C \max_c \pi_c. \quad (7)$$

The calibration module is activated only when $r > \tau$, where $\tau = 2.5$ by default.

(3) Centered Log-prior Calibration. Finally, when the module is activated, LAMP-Merge constructs a centered log-prior bias

$$b_c = \lambda \left(\log \pi_c - \frac{1}{C} \sum_{k=1}^C \log \pi_k \right), \quad (8)$$

with default maximum calibration strength $\lambda = 4.25$. The centering term prevents a uniform shift of all class logits, so the bias only changes the relative class prior. This module calibrates prevalence without replacing the diagnostic directions reconstructed by the first module.

Optimization Objective and Algorithm

The final scoring function of LAMP-Merge integrates the diagnostic prototype reconstruction term and the long-tail prevalence calibration term:

$$\ell_c(x) = w_c^\top \phi_0(T(x)) + \mathbf{1}[r > \tau] b_c. \quad (9)$$

Experiments

Experimental Settings

(1) Evaluation Datasets: We evaluate the merged models on five representative MedMNIST v2 benchmarks (Yang, Shi, and Ni 2023): Blood, Derma, Organ-C, Organ-S, and Ultrasound. They cover blood-cell microscopy, dermoscopy, abdominal CT, and ultrasound image classification (detailed dataset descriptions are provided in the Appendix).

(2) Baselines: We compare LAMP-Merge with twelve model-merging baselines covering the main technical routes of current model merging: avg, ties (Yadav et al. 2023), dare_linear (Yu et al. 2024), dare_ties (Yu et al. 2024), regmean (Jin et al. 2025), fisher (Wu et al. 2025), breadcrumbs (Davari and Belilovsky 2024), model_stock (Jang, Yun, and Han 2025), from (Ilharco et al. 2023), iso_c (Marczak et al. 2025), free_merge (Zheng and Wang 2025), and robust-merge (Zeng et al. 2025). These baselines include weight averaging, task-vector pruning, sign-conflict resolution, curvature or mean-statistic correction, stock-style model interpolation, isotropic subspace merging, Fourier-domain fusion, and direction-robust merging.

(3) Merging Settings: We evaluate four vision-model families: ResNet, ConvNeXt, ViT-Tiny, and Swin-Tiny (He et al. 2016; Liu et al. 2022; Dosovitskiy et al. 2021; Liu et al. 2021). For each dataset-model pair, we construct non-IID client partitions with $K \in \{3, 5, 7\}$ clients and Dirichlet skew parameter $\beta \in \{0, 0.01, 0.1\}$, using seed 42 (Hsu, Qi, and Brown 2019). A client-average result fixes the dataset, model, and K , and then averages over the three β values. And the experiments follow a single-shot asynchronous model-merging protocol.

Comparison With the State of the Arts

Tables 1–4 report the full client-average results for all four backbones. Across the 60 client-average cells, LAMP-Merge wins or ties the strongest non-LAMP baseline in 57 cells (95.0%).

Ablation Study

Module-level ablations use exactly the same experimental setup as the main experiments. We report the




Figure 3: Internal ablations of the Diagnostic Prototype Reconstruction Module (DPR) and Long-tail Prevalence Calibration (LPC).

Weight-Averaging Baseline, Baseline + DPR, and full LAMP-Merge (Baseline + DPR + LPC), forming the incremental comparison used in Fig. 4.

1) Effectiveness of Diagnostic Prototype Reconstruction To further identify which information within diagnostic prototype reconstruction is necessary, we conduct controlled substitutions across the full setting. All configurations retain long-tail prevalence calibration and vary only the prototype semantics or support-count weighting.

Fig. 4 and Table 5 show that neither an arbitrary head nor a class-agnostic statistic explains the gain. Replacing reference-space prototypes or class-specific support weights consistently reduces ACC, confirming that diagnostic semantics and class-level reliability are jointly necessary.

2) Effectiveness of Long-tail Prevalence Calibration We further replace the prior term inside long-tail prevalence calibration. Table 6 shows that removing prevalence calibration or replacing the real prior with a uniform prior reduces mean ACC, confirming that long-tailed prevalence is part of the full method.

New-metric Diagnostic Experiment

Although the main experiments use ACC for direct comparison, long-tailed medical distributions can allow single-class or few-class predictors to achieve high ACC (Buda, Maki, and Mazurowski 2018; Brodersen et al. 2010). We therefore report collapse ratio, effective predicted classes, and predicted–true total variation.

Table 7 compares LAMP-Merge with the best-performing baseline for each metric. LAMP-Merge consistently and substantially outperforms the existing methods.

Visualization Experiment

To visualize the prediction-distribution changes measured by the new diagnostic metrics, we compare the predicted class allocation induced by LAMP-Merge with those of representative generic merges. These generic merges concentrate predictions on a few classes, whereas LAMP-Merge recovers a broader class allocation aligned with the test distribution.

Table 1: Client-average test accuracy (%) on ResNet. Each entry averages the three Dirichlet settings for a fixed client number; Avg denotes the mean over $K = 3, 5, 7$ within the corresponding dataset.

Method	Blood				Derma				Organ-C				Organ-S				Ultrasound			
	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg
Weight Avg.	33.45	24.67	28.22	28.78	62.91	47.00	62.44	57.45	22.61	17.72	13.96	18.10	28.64	17.94	24.75	23.78	24.35	15.81	15.42	18.53
TIES[NeurIPS 2023]	26.01	18.72	17.87	20.87	59.95	48.41	64.84	57.73	26.50	16.84	21.18	21.51	19.81	19.15	18.74	19.23	34.77	19.89	18.54	24.40
DARE-Linear[ICML 2024]	28.32	28.56	23.92	26.93	63.57	48.41	62.88	58.29	20.18	25.88	16.50	20.85	25.45	22.45	25.37	24.42	21.62	17.28	16.08	18.33
DARE-TIES[ICML 2024]	31.94	19.35	17.80	23.03	53.75	48.25	55.58	52.53	18.51	15.15	18.59	17.42	17.90	13.52	17.30	16.24	29.32	16.35	18.90	21.52
RegMean[ICLR 2023]	34.60	23.69	34.07	30.79	58.12	28.43	50.22	45.59	24.05	13.40	13.88	17.11	25.04	16.23	14.93	18.73	22.76	16.95	13.18	17.63
Fisher[NeurIPS 2022]	31.96	22.37	26.08	26.80	67.07	67.02	66.90	67.00	29.73	17.41	18.12	21.75	20.10	29.56	19.63	23.10	23.33	18.60	25.13	22.35
Breadcrumbs[ECCV 2024]	8.54	14.17	14.60	12.44	4.95	29.13	17.21	17.10	7.66	6.76	6.85	7.09	8.02	9.48	6.03	7.84	12.25	12.73	10.21	11.73
Model Stock[ECCV 2024]	24.20	18.24	19.75	20.73	62.16	43.11	57.21	54.16	12.25	12.74	11.85	12.28	27.42	15.78	20.12	21.11	17.91	13.21	15.78	15.63
Iso-C[ICML 2025]	32.78	27.48	30.23	30.16	50.49	44.22	64.16	52.96	23.31	16.29	13.83	17.81	27.36	21.18	24.53	24.36	26.15	16.98	15.54	19.56
Free-Merging[ICCV 2025]	33.45	24.67	28.22	28.78	62.91	47.00	62.46	57.46	22.61	17.71	13.96	18.09	28.63	17.93	24.75	23.77	24.35	15.81	15.45	18.54
RobustMerge[NeurIPS 2025]	34.01	24.30	22.56	26.96	29.56	20.85	39.42	29.94	24.58	17.64	16.53	19.58	26.80	22.27	23.01	24.03	21.89	22.31	17.07	20.42
FROM[AAAI 2026]	29.89	23.06	20.52	24.49	67.13	43.69	65.80	58.87	23.50	15.60	15.20	18.10	22.07	20.87	24.76	22.57	23.09	15.06	20.63	19.59
LAMP-Merge	80.01	79.94	79.92	79.95	67.55	67.63	67.63	67.60	60.05	59.94	60.07	60.02	52.98	52.79	52.81	52.86	48.07	46.75	47.35	47.39

Table 2: Client-average test accuracy (%) on ConvNeXt. Each entry averages the three Dirichlet settings for a fixed client number; Avg denotes the mean over $K = 3, 5, 7$ within the corresponding dataset.

Method	Blood				Derma				Organ-C				Organ-S				Ultrasound			
	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg
Weight Avg.	15.65	11.22	13.84	13.57	29.66	48.30	66.88	48.28	10.37	12.18	9.44	10.66	13.08	10.35	14.16	12.53	15.06	15.06	12.52	14.21
TIES[NeurIPS 2023]	17.15	12.14	15.24	14.84	29.66	17.97	27.13	24.92	12.17	7.86	7.16	9.06	11.23	7.61	7.96	8.93	15.18	14.56	12.91	14.22
DARE-Linear[ICML 2024]	17.56	11.22	13.45	14.08	27.05	48.30	48.30	41.22	10.35	6.99	10.85	9.40	12.82	10.35	7.97	10.38	15.75	15.75	12.64	14.71
DARE-TIES[ICML 2024]	10.96	15.19	14.97	13.71	9.08	27.98	24.51	20.52	13.05	13.46	7.70	11.40	10.96	9.46	7.09	9.17	14.56	12.97	15.00	14.18
RegMean[ICLR 2023]	15.65	8.17	18.56	14.13	26.33	7.73	27.20	20.42	11.43	10.17	7.68	9.76	10.14	12.59	10.38	11.04	15.75	15.39	15.00	15.38
Fisher[NeurIPS 2022]	15.65	9.99	11.89	12.51	48.25	26.38	29.71	34.78	10.03	9.74	9.15	9.64	6.04	5.17	8.43	6.55	16.95	13.60	14.56	15.04
Breadcrumbs[ECCV 2024]	15.16	13.66	11.63	13.48	5.24	27.66	46.30	26.40	10.31	14.44	15.74	13.50	15.16	15.54	20.77	17.16	13.84	13.63	13.63	13.70
Model Stock[ECCV 2024]	17.56	11.44	17.78	15.59	29.66	48.30	66.88	48.28	12.76	12.18	13.85	12.93	13.08	10.35	19.35	14.26	15.75	12.91	14.79	14.48
Iso-C[ICML 2025]	19.47	18.65	14.80	17.64	29.71	48.30	66.88	48.30	9.91	6.99	9.45	8.78	7.89	14.77	8.67	10.44	15.18	12.91	16.05	14.71
Free-Merging[ICCV 2025]	15.75	11.90	13.84	13.83	29.71	48.30	66.88	48.30	9.06	12.18	13.85	11.70	13.08	10.35	14.16	12.53	15.06	12.91	16.95	14.97
RobustMerge[NeurIPS 2025]	14.10	14.05	7.52	11.89	9.08	45.07	48.30	34.15	13.94	12.18	17.93	14.68	23.54	9.61	20.77	17.97	13.00	11.35	13.63	12.66
FROM[AAAI 2026]	15.65	10.83	16.71	14.40	29.66	34.06	45.69	36.47	12.32	12.24	6.50	10.35	13.24	11.05	8.97	11.09	15.75	15.78	10.87	14.13
LAMP-Merge	84.85	84.87	84.98	84.90	59.68	58.77	59.42	59.29	65.41	65.33	65.51	65.42	60.55	60.50	60.66	60.57	43.07	42.80	42.41	42.76

Hyperparameter Analysis Experiment

Fig. 6 evaluates the prototype-head scale s and calibration strength λ over 180 raw cells and 60 client-average cells. The fixed method uses $\gamma = 0.55$, $s = 18.75$, $\tau = 2.5$, and $\lambda = 4.25$; these values lie in broad stable regions, indicating that the gain is not produced by narrow hyperparameter tuning.

t-SNE Visualization Experiment

Fig. 7 uses t-SNE(van der Maaten and Hinton 2008) only for analysis on Blood with ResNet, $K = 3$, and $\beta = 0.01$. LAMP-Merge retains separated output-probability groups, while generic merges exhibit compressed or entangled predictive representations.

Conclusion

We studied one-shot asynchronous medical model merging, where independently trained hospital models must be fused without federated optimization rounds and

without exposing raw medical images to the server. Our empirical analysis shows that generic model-merging methods suffer from aggregation-induced predictive collapse under incomplete local diagnostic coverage. We further show that, on long-tailed medical datasets, such collapse can be masked by raw accuracy. We therefore introduce the Long-tail Prevalence Calibration module and perform secondary evaluation using macro recall, macro-F1, and predictive-distribution diagnostics(Buda, Maki, and Mazurowski 2018; Brodersen et al. 2010).

Taken together, the full-scope comparisons, module ablations, and prediction-distribution diagnostics establish a consistent mechanism: class-level support-weighted evidence reconstructs discriminative directions for locally absent diagnoses, while bounded prevalence calibration retains clinically meaningful imbalance without reintroducing majority-class collapse.

LAMP-Merge addresses these two properties through a concise two-module design. Future work will extend

Table 3: Client-average test accuracy (%) on ViT-Tiny. Each entry averages the three Dirichlet settings for a fixed client number; Avg denotes the mean over $K = 3, 5, 7$ within the corresponding dataset.

Method	Blood				Derma				Organ-C				Organ-S				Ultrasound			
	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg
Weight Avg.	13.43	10.82	11.60	11.95	46.38	43.69	36.96	42.34	16.57	10.43	9.52	12.17	8.44	8.52	17.10	11.35	14.50	13.27	18.84	15.54
TIES[NeurIPS 2023]	7.96	14.21	12.85	11.67	47.80	34.98	46.15	42.98	13.41	12.23	9.53	11.72	11.92	10.02	15.97	12.64	20.01	13.06	10.18	14.42
DARE-Linear[ICML 2024]	23.97	11.29	13.87	16.38	28.50	10.02	12.04	16.85	15.34	9.46	7.04	10.61	7.48	5.49	16.11	9.69	13.66	10.51	14.35	12.84
DARE-TIES[ICML 2024]	7.35	11.89	11.46	10.23	27.35	45.02	35.28	35.88	12.52	9.03	10.33	10.63	5.41	8.74	5.91	6.69	14.47	11.20	10.42	12.03
RegMean[ICLR 2023]	17.48	14.17	12.90	14.85	51.14	36.67	66.58	51.46	12.50	9.64	9.83	10.66	12.63	7.17	10.68	10.16	14.91	13.84	11.44	13.40
Fisher[NeurIPS 2022]	11.66	15.12	19.44	15.41	47.80	20.42	48.20	38.81	7.99	10.72	14.24	10.98	8.56	12.18	12.22	10.99	16.11	13.15	14.20	14.49
Breadcrumbs[ECCV 2024]	13.63	10.39	13.00	12.34	4.89	25.72	6.07	12.23	7.73	10.00	16.44	11.39	12.37	4.83	12.19	9.80	13.60	11.41	15.24	13.42
Model Stock[ECCV 2024]	19.40	11.20	11.34	13.98	38.05	30.79	27.35	32.06	14.88	12.27	12.15	13.10	8.93	8.59	18.67	12.06	15.99	18.09	16.41	16.83
Iso-C[ICML 2025]	12.34	14.83	10.18	12.45	57.09	45.29	23.06	41.81	10.84	5.67	8.97	8.49	6.11	5.31	10.81	7.41	14.17	15.27	18.69	16.04
Free-Merging[ICCV 2025]	19.89	14.57	13.92	16.13	46.30	47.70	38.55	44.18	14.25	9.80	7.59	10.55	7.27	9.14	16.43	10.95	14.05	15.93	16.47	15.48
RobustMerge[NeurIPS 2025]	14.82	10.70	14.25	13.26	3.47	27.68	17.24	16.13	9.54	6.17	14.38	10.03	12.60	7.07	12.17	10.61	16.98	18.54	15.63	17.05
FROM[AAAI 2026]	18.02	7.81	14.05	13.29	46.95	51.21	66.88	55.01	21.48	13.01	9.72	14.74	7.72	7.98	14.85	10.18	18.36	17.43	17.76	17.85
LAMP-Merge	85.21	85.06	84.98	85.09	59.45	59.32	59.83	59.53	58.78	58.40	58.29	58.49	54.39	54.51	54.65	54.52	46.12	45.97	45.94	46.01

Table 4: Client-average test accuracy (%) on Swin-Tiny. Each entry averages the three Dirichlet settings for a fixed client number; Avg denotes the mean over $K = 3, 5, 7$ within the corresponding dataset.

Method	Blood				Derma				Organ-C				Organ-S				Ultrasound			
	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg	$K = 3$	$K = 5$	$K = 7$	Avg
Weight Avg.	15.65	11.86	15.24	14.25	45.69	48.30	66.88	53.62	10.68	12.94	7.87	10.50	6.82	6.04	13.81	8.89	15.27	12.94	14.65	14.29
TIES[NeurIPS 2023]	9.72	11.90	13.84	11.82	8.41	7.80	66.88	27.70	11.60	7.02	9.34	9.32	7.34	6.07	11.07	8.16	16.95	13.03	12.61	14.20
DARE-Linear[ICML 2024]	15.65	11.61	18.25	15.17	45.69	27.71	46.30	39.90	11.55	12.72	7.76	10.68	6.40	7.20	13.81	9.14	17.43	15.36	14.97	15.92
DARE-TIES[ICML 2024]	13.84	11.62	13.84	13.10	29.61	26.38	66.88	40.96	12.76	7.74	11.16	10.55	11.94	4.34	12.30	9.53	17.91	13.51	13.00	14.81
RegMean[ICLR 2023]	13.74	17.15	15.78	15.56	27.05	46.30	45.69	39.68	14.11	7.73	8.11	9.98	12.15	8.21	9.26	9.87	14.65	11.05	17.79	14.50
Fisher[NeurIPS 2022]	16.33	17.56	15.65	16.51	45.82	6.52	47.18	33.17	8.14	8.99	9.78	8.97	6.51	6.50	10.92	7.98	17.46	11.65	17.55	15.55
Breadcrumbs[ECCV 2024]	15.00	13.65	15.37	14.67	6.47	27.71	7.15	13.78	14.45	17.83	16.60	16.29	23.54	20.77	21.11	21.81	14.50	13.12	16.53	14.72
Model Stock[ECCV 2024]	13.74	14.40	17.15	15.10	45.69	27.71	48.25	40.55	11.10	7.71	14.04	10.95	6.71	11.06	17.14	11.64	15.39	12.73	18.69	15.60
Iso-C[ICML 2025]	14.30	17.22	17.00	16.17	30.99	28.40	51.74	37.04	13.02	13.27	14.69	13.66	15.45	17.27	18.80	17.17	17.55	17.31	17.91	17.59
Free-Merging[ICCV 2025]	11.54	8.61	18.40	12.85	45.69	48.30	66.88	53.62	9.59	13.77	8.90	10.75	6.82	4.97	10.62	7.47	15.18	15.75	15.99	15.64
RobustMerge[NeurIPS 2025]	13.74	14.09	16.70	14.84	23.77	27.71	5.04	18.84	16.01	14.42	19.60	16.68	16.73	11.51	20.77	16.34	17.61	13.15	16.29	15.68
FROM[AAAI 2026]	15.65	14.95	16.71	15.77	45.69	29.71	66.88	47.43	11.74	12.20	10.51	11.48	11.33	10.16	13.80	11.76	15.39	12.52	14.76	14.22
LAMP-Merge	77.38	77.34	77.17	77.30	63.24	63.18	63.09	63.17	68.49	68.17	68.12	68.26	62.58	62.80	62.84	62.74	47.71	48.70	48.40	48.27

its applicability in two directions: first, from medical image classification to segmentation, detection, and multimodal diagnostic tasks; and second, toward stronger privacy-preserving mechanisms, such as differential privacy and secure aggregation, to further reduce potential privacy risks associated with class-level statistics (Kaissis et al. 2020a; Geyer, Klein, and Nabi 2017; Abadi et al. 2016). We will also explore deployment and validation in larger-scale real-world multicenter healthcare settings.

References

Abadi, M.; Chu, A.; Goodfellow, I.; McMahan, H. B.; Mironov, I.; Talwar, K.; and Zhang, L. 2016. Deep Learning with Differential Privacy. In Proceedings of the 2016 ACM SIGSAC Conference on Computer and Communications Security, 308–318.

Ainsworth, S. K.; Hayase, J.; and Srinivasa, S. 2023. Git Re-Basin: Merging Models modulo Permutation Symmetries. arXiv:2209.04836.

Bonawitz, K.; et al. 2019. Towards Federated Learning at Scale: System Design. In Proceedings of Machine Learning and Systems, volume 1, 374–388.

Brodersen, K. H.; Ong, C. S.; Stephan, K. E.; and Buhmann, J. M. 2010. The Balanced Accuracy and Its Posterior Distribution. In 2010 20th International Conference on Pattern Recognition, 3121–3124.

Buda, M.; Maki, A.; and Mazurowski, M. A. 2018. A systematic study of the class imbalance problem in convolutional neural networks. Neural Networks, 106: 249–259.

Davari, M.; and Belilovsky, E. 2024. Model Breadcrumbs: Scaling Multi-Task Model Merging with Sparse Masks. arXiv:2312.06795.

Dosovitskiy, A.; et al. 2021. An Image Is Worth 16x16 Words: Transformers for Image Recognition at Scale. In International Conference on Learning Representations.

Entezari, R.; Sedghi, H.; Saukh, O.; and Neyshabur, B. 2022. The Role of Permutation Invariance in Linear




Figure 4: Dataset-level client-average accuracy in the module ablation. Each dataset contains 12 cells from four vision-model families and three client counts; each cell is averaged over three Dirichlet skew levels.

Table 5: DPR internal ablation by dataset. Each entry averages all backbones, client counts, and Dirichlet settings; Avg averages the five datasets.

Setting	Blood	Derma	Organ-C	Organ-S	US	Avg
Cls-head agg.	18.95	56.14	17.74	18.88	16.43	25.63
Global feat. mean	8.88	66.88	22.33	23.54	10.87	26.50
Support-only	11.62	17.29	7.08	7.74	10.69	10.89
Shuffled proto.	24.46	28.73	14.18	16.25	14.25	19.57
Uniform client	78.03	59.61	58.36	53.86	41.79	58.33
Binary support	78.03	44.96	57.86	53.24	41.79	55.18
Client-size weight	78.45	62.48	59.11	53.79	43.13	59.39
LAMP-Merge	81.81	62.40	63.05	57.67	46.11	62.21

Mode Connectivity of Neural Networks. In International Conference on Learning Representations.

Geyer, R. C.; Klein, T.; and Nabi, M. 2017. Differentially Private Federated Learning: A Client Level Perspective. arXiv:1712.07557.

Guan, H.; and Liu, M. 2022. Domain Adaptation for Medical Image Analysis: A Survey. IEEE Transactions on Biomedical Engineering, 69(3): 1173–1185.

Hayat, N.; Geras, K. J.; and Shamout, F. E. 2023. Med-Fuse: Multi-modal fusion with clinical time-series data and chest X-ray images. arXiv:2207.07027.

He, K.; Zhang, X.; Ren, S.; and Sun, J. 2016. Deep Residual Learning for Image Recognition. In Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, 770–778.

Heged\Hus, I.; Danner, G.; and Jelasity, M. 2019. Gos-

Table 6: LPC internal ablation by dataset. Each entry averages all backbones, client counts, and Dirichlet settings; Avg averages the five datasets.

Setting	Blood	Derma	Organ-C	Organ-S	US	Avg
No LPC	81.81	46.58	62.57	57.50	46.11	58.91
Uniform prior	81.81	46.58	62.57	57.50	46.11	58.91
LAMP-Merge	81.81	62.40	63.05	57.67	46.11	62.21

Table 7: Prediction-collapse diagnostics by dataset. Best ref. is selected separately for each metric and dataset. Ratio metrics use percentage scale; Avg averages the five datasets.

Metric	Series	Blood	Derma	Organ-C	Organ-S	US	Avg
Collapse ↓	LAMP	19.58	68.05	20.72	24.36	20.45	30.63
	Best ref.	80.20	85.18	72.38	71.12	80.31	79.02
Eff. classes ↑	LAMP	7.48	3.10	9.55	8.44	7.44	7.20
	Best ref.	1.81	1.65	2.49	2.53	1.98	2.05
Pred-true TV ↓	LAMP	3.97	17.09	12.38	13.17	15.51	12.42
	Best ref.	73.48	46.03	75.42	73.85	72.73	69.44

sip Learning as a Decentralized Alternative to Federated Learning. In Pereira, J.; and Ricci, L., eds., Distributed Applications and Interoperable Systems, 74–90. Cham: Springer International Publishing. ISBN 978-3-030-22496-7.

Hsu, T.-M. H.; Qi, H.; and Brown, M. 2019. Measuring the Effects of Non-Identical Data Distribution for Federated Visual Classification. arXiv:1909.06335.

Ilharco, G.; Ribeiro, M. T.; Wortsman, M.; Guru-




Figure 5: Predicted class distributions on Ultrasound, averaged over the four visual backbones, $K \in \{3, 5, 7\}$, and the three Dirichlet skew levels. Generic merges concentrate predictions on a few classes, while LAMP-Merge recovers a broader class allocation aligned with the test distribution.

rangan, S.; Schmidt, L.; Hajishirzi, H.; and Farhadi, A. 2023. Editing Models with Task Arithmetic. arXiv:2212.04089.

Izmailov, P.; Podoprikin, D.; Garipov, T.; Vetrov, D. P.; and Wilson, A. G. 2018. Averaging Weights Leads to Wider Optima and Better Generalization. In Proceedings of the 34th Conference on Uncertainty in Artificial Intelligence, 876–885.

Jang, D.-H.; Yun, S.; and Han, D. 2025. Model Stock: All we need is just a few fine-tuned models. arXiv:2403.19522.

Jin, X.; Ren, X.; Preotiuc-Pietro, D.; and Cheng, P. 2025. Dataless Knowledge Fusion by Merging Weights of Language Models. arXiv:2212.09849.

Kairouz, P.; McMahan, H. B.; Avent, B.; et al. 2021. Advances and Open Problems in Federated Learning. Foundations and Trends in Machine Learning, 14(1–2): 1–210.

Kaissis, G. A.; Makowski, M. R.; Rückert, D.; and Braren, R. F. 2020a. Secure, privacy-preserving and federated machine learning in medical imaging. Nature Machine Intelligence, 2(6): 305–311.

Kaissis, G. A.; Makowski, M. R.; Rückert, D.; and Braren, R. F. 2020b. Secure, privacy-preserving and federated machine learning in medical imaging. Nature Machine Intelligence, 2(6): 305–311.

Karimireddy, S. P.; Kale, S.; Mohri, M.; Reddi, S.; Stich, S.; and Suresh, A. T. 2020. SCAFFOLD: Stochastic Controlled Averaging for Federated Learning. In Proceedings of the 37th International Conference on Machine Learning, 5132–5143.

Li, T.; Sahu, A. K.; Talwalkar, A.; and Smith, V. 2020. Federated Optimization in Heterogeneous Networks. In Proceedings of Machine Learning and Systems, volume 2, 429–450.

Li, X.; Jiang, M.; Zhang, X.; Kamp, M.; and Dou, Q. 2021. Federated Learning on Non-IID Features via Lo-

cal Batch Normalization. In International Conference on Learning Representations.

Liu, Z.; Mao, H.; Wu, C.-Y.; Feichtenhofer, C.; Darrell, T.; and Xie, S. 2022. A ConvNet for the 2020s. In Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition, 11976–11986.

Liu, Z.; et al. 2021. Swin Transformer: Hierarchical Vision Transformer Using Shifted Windows. In Proceedings of the IEEE/CVF International Conference on Computer Vision, 10012–10022.

Marczak, D.; Magistri, S.; Cygert, S.; Twardowski, B.; Bagdanov, A. D.; and van de Weijer, J. 2025. No Task Left Behind: Isotropic Model Merging with Common and Task-Specific Subspaces. arXiv:2502.04959.

McMahan, B.; Moore, E.; Ramage, D.; Hampson, S.; and Arcas, B. A. y. 2017. Communication-Efficient Learning of Deep Networks from Decentralized Data. In Singh, A.; and Zhu, J., eds., Proceedings of the 20th International Conference on Artificial Intelligence and Statistics, volume 54 of Proceedings of Machine Learning Research, 1273–1282. PMLR.

Rieke, N.; Hancox, J.; Li, W.; Milletari, F.; Roth, H. R.; Albarqouni, S.; Bakas, S.; Galtier, M. N.; Landman, B. A.; Maier-Hein, K.; Ourselin, S.; Sheller, M.; Summers, R. M.; Trask, A.; Xu, D.; Baust, M.; and Cardoso, M. J. 2020. The future of digital health with federated learning. npj Digital Medicine, 3(1): 171.

Sheller, M. J.; Edwards, B.; Reina, G. A.; Martin, J.; Pati, S.; Kotrotsou, A.; Milchenko, M.; Xu, W.; Marcus, D.; Colen, R. R.; and Bakas, S. 2020. Federated learning in medicine: Facilitating multi-institutional collaborations without sharing patient data. Scientific Reports, 10(1): 10933.

Shukla, S. N.; and Marlin, B. M. 2021. Multi-Time Attention Networks for Irregularly Sampled Time Series. arXiv:2101.10318.

Stoica, G.; Bolya, D.; Bjorner, J.; Ramesh, P.; Hearn, T.; and Hoffman, J. 2024. ZipIt! Merging Models from Different Tasks without Training. In International Conference on Learning Representations.

van der Maaten, L.; and Hinton, G. 2008. Visualizing Data Using t-SNE. Journal of Machine Learning Research, 9(86): 2579–2605.

Wernat-Herresthal, S.; Schultze, H.; Shastry; and so on. 2021. Swarm Learning for decentralized and confidential clinical machine learning. Nature, 594(7862): 265–270.

Wei, Y.; Zhu, Q.; Xia, Z.; Wang, L.; Zou, Y.; Li, Y.; Luo, Y.; and Du, B. 2026. MedMerge: A Training-Free Model Merging Framework for Medical Knowledge Transfer into Vision–Language Models. IEEE Transactions on Radiation and Plasma Medical Sciences, 1–1.

Wortsman, M.; Ilharco, G.; Gadre, S. Y.; Roelofs, R.; Gontijo-Lopes, R.; Morcos, A. S.; Namkoong, H.; Farhadi, A.; Carmon, Y.; Kornblith, S.; and Schmidt, L. 2022. Model soups: averaging weights of multiple




Figure 6: Full-scope hyperparameter sensitivity for DPR and LPC. The expanded vertical ranges emphasize that accuracy remains stable across broad parameter intervals.




Figure 7: Joint t-SNE of test-image output-probability representations on Blood; from left to right, LAMP-Merge, weight averaging, TIES-Merging, and DARE-Linear.

fine-tuned models improves accuracy without increasing inference time. In Chaudhuri, K.; Jegelka, S.; Song, L.; Szepesvari, C.; Niu, G.; and Sabato, S., eds., Proceedings of the 39th International Conference on Machine Learning, volume 162 of Proceedings of Machine Learning Research, 23965–23998. PMLR.

Wu, J.; Yang, J.; Wang, H.; Wen, J.; and Yu, Z. 2025. From Parameter to Representation: A Closed-Form Approach for Controllable Model Merging. ArXiv:2511.10943 [cs].

Yadav, P.; Tam, D.; Choshen, L.; Raffel, C.; and Bansal, M. 2023. TIES-Merging: Resolving Interference When Merging Models. arXiv:2306.01708.

Yang, J.; Shi, R.; and Ni, B. 2023. MedMNIST v2: A Large-Scale Lightweight Benchmark for 2D and 3D Biomedical Image Classification. Scientific Data, 10(1): 41.

Yu, L.; Yu, B.; Yu, H.; Huang, F.; and Li, Y. 2024. Language Models are Super Mario: Absorbing Abilities from Homologous Models as a Free Lunch. arXiv:2311.03099.

Zech, J. R.; Badgeley, M. A.; Liu, M.; Costa, A. B.; Titano, J. J.; and Oermann, E. K. 2018. Variable generalization performance of a deep learning model to detect pneumonia in chest radiographs: A cross-sectional study. PLOS Medicine, 15(11): 1–17.

Zeng, F.; Guo, H.; Zhu, F.; Shen, L.; and Tang, H. 2025. RobustMerge: Parameter-Efficient Model Merging for MLLMs with Direction Robustness. arXiv:2502.17159.

Zhang, X.; Zeman, M.; Tsiligkaridis, T.; and Zitnik, M. 2022. Graph-Guided Network for Irregularly Sampled Multivariate Time Series. arXiv:2110.05357.

Zheng, S.; and Wang, H. 2025. FREE-Merging: Fourier Transform for Efficient Model Merging. arXiv:2411.16815.

Supplementary Results and Analysis

Evaluation Datasets

The five MedMNIST v2 benchmarks(Yang, Shi, and Ni 2023) cover blood-cell microscopy, dermoscopy, abdominal CT organ slices, and ultrasound images. They involve cell morphology recognition, skin-lesion diagnosis,

Table 8: Dataset statistics and representative samples for the five medical image benchmarks. Counts are taken from the exact NPZ files used in our experiments.

Dataset	Classes	Train	Val	Test	Total	Sample
Blood	8	11,959	1,712	3,421	17,092	
Derma	7	7,007	1,003	2,005	10,015	
Organ-C	11	12,975	2,392	8,216	23,583	
Organ-S	11	13,932	2,452	8,827	25,211	
Ultrasound	8	3,869	549	1,113	5,531	

organ-structure recognition, and ultrasound-structure discrimination:

- Blood: an eight-class blood-cell microscopy dataset for hematological morphology classification, focusing on fine-grained cellular appearance and inter-class morphological similarity.
- Derma: a seven-class dermoscopic skin-lesion dataset, characterized by strong long-tailed prevalence and visually subtle lesion categories.
- Organ-C: an 11-class abdominal CT dataset in the coronal view, evaluating organ-category recognition under grayscale cross-sectional imaging.
- Organ-S: an 11-class abdominal CT dataset in the sagittal view, complementing Organ-C with a different anatomical imaging plane.
- Ultrasound: an eight-class ultrasound image dataset, covering structure recognition under modality-specific speckle noise and low-contrast boundaries.

Together, these benchmarks provide a systematic testbed for evaluating cross-modality robustness, class-discriminative capability, and task generalization under different medical image types and class-distribution conditions.

Detailed Ablation Configurations

All diagnostic-prototype substitutions retain long-tail prevalence calibration and vary only prototype semantics or support-count weighting:

- LAMP-Merge uses $p_c = \sum_i \alpha_{i,c} \mu_{i,c}$, where $e_{i,c} = (n_{i,c} + 1)^\gamma \mathbf{1}[n_{i,c} > 0]$ determines the class-support reliability.
- Classifier-head aggregation replaces the reference-space class prototype by the local classifier-head direction, i.e., $\mu_{i,c} \leftarrow h_{i,c}$.
- Global-feature mean removes class conditioning by setting $\mu_{i,c} \leftarrow g$ for all c , where g is the class-agnostic global reference-feature mean.
- Support-only synthetic head removes image evidence by replacing each prototype with a fixed random unit direction u_c , i.e., $p_c \leftarrow u_c$, $\|u_c\|_2 = 1$.

- Shuffled-label prototype preserves prototype magnitudes but permutes diagnostic semantics, i.e., $p_c \leftarrow p_{\sigma(c)}$, where σ is a random permutation over diagnosis labels.
- Uniform client weight replaces support-weighted aggregation with equal weights among clients containing class c , i.e., $\alpha_{i,c} \leftarrow \mathbf{1}[n_{i,c} > 0] / \sum_j \mathbf{1}[n_{j,c} > 0]$.
- Binary support only replaces fine-grained support and prevalence counts with class-presence indicators, i.e., $n_{i,c}, m_{i,c} \leftarrow \mathbf{1}[n_{i,c} > 0]$.
- Global client-size weight uses the total client support $N_i = \sum_k n_{i,k}$ rather than class-specific support, i.e., $e_{i,c} \leftarrow (N_i + 1)^\gamma \mathbf{1}[n_{i,c} > 0]$.

The long-tail prevalence substitutions vary only the class prior used by the calibration bias:

- LAMP-Merge estimates the empirical class prior as $\pi_c = \sum_i m_{i,c} / \sum_k \sum_i m_{i,k}$.
- No prevalence calibration removes the calibration bias by setting $b_c \leftarrow 0$.
- Uniform prevalence prior removes long-tail prevalence by setting $\pi_c \leftarrow 1/C$, where C is the number of diagnosis classes.

2) Additional Theoretical Analysis Let μ_c^* denote the true class mean in the shared reference space. If client class features have bounded second moments, the prototype estimation error satisfies

$$\mathbb{E} \|p_c - \mu_c^*\|_2^2 \leq \sum_i \alpha_{i,c}^2 \frac{\sigma_c^2}{n_{i,c}} + \text{Bias}_c^2. \quad (10)$$

This upper bound shows that support counts directly control the variance of class-prototype estimation. A client that does not observe class c should not contribute evidence for that class, and a client with more samples should contribute more, but only sublinearly.

Let the true margin between classes c and d for sample x be

$$\Delta_{c,d}(x) = (\mu_c^*)^\top z - (\mu_d^*)^\top z. \quad (11)$$

When the prototype error satisfies

$$\|p_c - \mu_c^*\|_2 + \|p_d - \mu_d^*\|_2 < \frac{\Delta_{c,d}(x)}{\|z\|_2}, \quad (12)$$

the estimated prototypes preserve the class order between c and d .

The role of long-tail prevalence calibration is to introduce long-tail priors in a bounded manner. For prevalence counts $m_{i,c}$, the class prior is

$$\pi_c = \frac{\sum_i m_{i,c}}{\sum_k \sum_i m_{i,k}}, \quad (13)$$

and the centered log-prior bias is

$$b_c = \lambda \left(\log \pi_c - \frac{1}{C} \sum_k \log \pi_k \right). \quad (14)$$

As long as λ is bounded, long-tail prevalence calibration does not replace the discriminative directions reconstructed by diagnostic prototype reconstruction; it

only calibrates the output toward the real class prevalence. This explains why using long-tail prevalence calibration alone is insufficient, while full LAMP-Merge remains both non-collapsed and prevalence-aware.

Metric Definitions

Let y_n and $\hat{y}_n$ denote the true and predicted labels of the n -th test sample. Let $q_c = N^{-1} \sum_n \mathbf{1}[\hat{y}_n = c]$ be the predicted-class distribution, $p_c = N^{-1} \sum_n \mathbf{1}[y_n = c]$ the true class distribution, and $\mathcal{C}_{\text{test}} = \{c \mid \sum_n \mathbf{1}[y_n = c] > 0\}$ the set of classes observed in the test set. We use:

- $\text{BA} = |\mathcal{C}_{\text{test}}|^{-1} \sum_{c \in \mathcal{C}_{\text{test}}} \text{Recall}_c$, balanced accuracy or macro recall, which measures whether all observed diagnosis classes are recalled.
- $\text{MacroF1} = |\mathcal{C}_{\text{test}}|^{-1} \sum_{c \in \mathcal{C}_{\text{test}}} \text{F1}_c$, class-balanced precision-recall quality that penalizes majority-only predictions.
- $\rho = \max_c q_c$, the prediction-collapse ratio, which measures concentration on a single diagnosis class.
- $C_{\text{eff}} = \exp(-\sum_c q_c \log q_c)$, the effective number of predicted classes.
- $\text{TV}(q, p) = \frac{1}{2} \sum_c |q_c - p_c|$, the total variation distance between predicted and true class distributions.