

# Patria Backend — API Documentation

## Base Info

|              |                                                              |
|--------------|--------------------------------------------------------------|
|              |                                                              |
| Base URL     | https://api.patriacoffeebeans.com/api                        |
| Content-Type | application/json (except file uploads → multipart/form-data) |
| Auth Header  | Authorization: Bearer {accessToken}                          |

## Authentication Flow

1. Call `POST /api/auth/login` → get `accessToken` (expires in 15 min) + `refreshToken` (expires in 7 days)
2. Attach `accessToken` to every request header
3. When `accessToken` expires → call `POST /api/auth/refresh` with `refreshToken` to get a new one

## Standard Response Format

Every response follows this structure:

```
{
  "statusCode": 200,
  "success": true,
  "message": "Success",
  "data": { }
}
```

### Error example:

```
{
  "statusCode": 400,
  "success": false,
  "message": "Validation error: email is required",
  "data": null
}
```

## Roles & Permissions

| Role        | Access Level                                         |
|-------------|------------------------------------------------------|
| SUPER_ADMIN | Full access — no restrictions                        |
| ADMIN       | Full management except some SUPER_ADMIN-only actions |
| MANAGER     | Daily operations, reports, staff management          |

|         |                          |
|---------|--------------------------|
| CASHIER | Orders, shifts, dispatch |
| KITCHEN | Kitchen orders only      |
| STAFF   | Limited read access      |

---

## 1. Authentication — `/api/auth`

---

### POST `/api/auth/register`

*Register a new admin user*

**No auth required**

```
// Request Body
{
  "name": "Ahmed",
  "email": "ahmed@example.com",
  "password": "123456"
}
```

```
// Response
{
  "data": {
    "user": { "_id": "...", "name": "Ahmed", "email": "...", "role": "ADMIN" },
    "accessToken": "eyJ...",
    "refreshToken": "eyJ..."
  }
}
```

---

### POST `/api/auth/login`

*Login with email and password*

**No auth required**

```
// Request Body
{
  "email": "ahmed@example.com",
  "password": "123456"
}
```

```
// Response
{
  "data": {
    "user": { "_id": "...", "name": "Ahmed", "role": "ADMIN" },
    "accessToken": "eyJ...",
  }
}
```

```
    "refreshToken": "eyJ..."
  }
}
```

---

### POST /api/auth/refresh

Get a new accessToken using refreshToken

No auth required

```
// Request Body
{
  "refreshToken": "eyJ..."
}
```

```
// Response
{
  "data": { "accessToken": "eyJ..." }
}
```

---

### POST /api/auth/logout

Logout current user

Auth required

```
// No body
// Response: { "message": "Logged out successfully" }
```

---

### GET /api/auth/me

Get current logged-in user info

Auth required

```
// Response
{
  "data": {
    "_id": "...",
    "name": "Ahmed",
    "email": "ahmed@example.com",
    "role": "ADMIN",
    "locationId": "..."
  }
}
```

---

### POST /api/auth/forgot-password

Send a password reset email

No auth required

```
// Request Body
{
  "email": "ahmed@example.com"
}
```

## 2. Users — /api/users

Manage staff accounts

Auth required — Role: ADMIN or SUPER\_ADMIN

### GET /api/users

Get all staff users

```
// Response
{
  "data": [
    { "_id": "...", "name": "...", "email": "...", "role": "CASHIER", "locationId":
    "..."}
  ]
}
```

### POST /api/users

Create a new staff user

```
// Request Body
{
  "name": "Mohammed",
  "email": "mo@example.com",
  "password": "123456",
  "role": "CASHIER",          // SUPER_ADMIN | ADMIN | MANAGER | CASHIER | KITCHEN |
  STAFF
  "locationId": "abc123"    // optional
}
```

### PUT /api/users/:id

Update a staff user

```
// Request Body (all fields optional)
{
```

```
"name": "...",
"email": "...",
"password": "...",
"role": "...",
"phone": "..."
}
```

---

#### DELETE /api/users/:id

Delete a staff user

---

### 3. Tables — /api/tables

---

#### GET /api/tables

Get all tables

Auth required

Query Params:

locationId (optional)  
status (optional) → available | occupied | reserved | cleaning

```
// Response
{
  "data": [
    { "_id": "...", "number": 5, "capacity": 4, "status": "available", "section":
"outdoor" }
  ]
}
```

---

#### POST /api/tables

Create a new table

Role: ADMIN | MANAGER

```
{
  "number": 5,
  "capacity": 4,
  "locationId": "abc123",
  "section": "outdoor", // optional
  "notes": "..." // optional
}
```

---

#### PUT /api/tables/:id

Update table details or status

Role: ADMIN | MANAGER | CASHIER

```
// All fields optional
{
  "status": "occupied", // available | occupied | reserved | cleaning
  "capacity": 6,
  "section": "...",
  "notes": "..."
}
```

---

### DELETE /api/tables/:id

Delete a table

Role: ADMIN | MANAGER

---

## 4. Reservations — /api/reservations

---

### GET /api/reservations

Get all reservations

Auth required

Query Params:

- page (default: 1)
- limit (default: 10)
- date → e.g. 2026-06-22
- status → pending | confirmed | cancelled | completed

---

### POST /api/reservations

Create a new reservation

Auth required

```
{
  "customerName": "Ali",
  "date": "2026-06-25",
  "time": "19:00",
  "guestCount": 4,
  "customerPhone": "01012345678", // optional
  "customerEmail": "...",         // optional
  "tableId": "abc123",            // optional
  "notes": "..."                // optional
}
```

---

### PUT /api/reservations/:id

Update reservation status

Role: ADMIN | MANAGER

```
{
  "status": "confirmed", // pending | confirmed | cancelled | completed
  "notes": "..."      // optional
}
```

---

### DELETE /api/reservations/:id

Delete a reservation

Role: ADMIN | MANAGER

---

## 5. Orders — /api/orders

---

### GET /api/orders

Get all orders

Auth required

Query Params:

```
page    (default: 1)
limit   (default: 10)
status  → pending | confirmed | preparing | ready | delivered | cancelled
type    → dine-in | takeaway | delivery
```

---

### GET /api/orders/:id

Get a single order by ID

Auth required

---

### POST /api/orders

Create a new order

Role: CASHIER | STAFF | ADMIN | MANAGER

```
{
  "items": [
    {
      "productId": "abc123",
      "quantity": 2,
```

```
    "notes": "no sugar"    // optional
  }
},
"type": "dine-in",        // dine-in | takeaway | delivery
"tableId": "abc123",      // optional – required for dine-in
"customerId": "abc123",   // optional
"couponCode": "SAVE10",   // optional
"notes": "...",           // optional
"locationId": "abc123"    // optional
}
```

---

### PUT /api/orders/:id

Update order status

Auth required

```
{
  "status": "confirmed",  // pending | confirmed | preparing | ready | delivered |
  cancelled
  "notes": "..."        // optional
}
```

---

### DELETE /api/orders/:id

Delete an order

Role: ADMIN | MANAGER

---

## 6. Products — /api/products

---

### GET /api/products

Get all products

Auth required

Query Params:

|            |                               |
|------------|-------------------------------|
| page       | (default: 1)                  |
| limit      | (default: 10)                 |
| categoryId | (optional)                    |
| search     | (optional) – searches by name |
| isActive   | (optional) → true   false     |

---

### POST /api/products

Create a new product

Role: ADMIN | MANAGER Content-Type: multipart/form-data

```
name          (required)
price          (required, number)
categoryId     (required)
description    (optional)
cost           (optional, number)
isActive       (optional, boolean – default: true)
images         (optional, up to 5 image files)
```

---

### PUT /api/products/:id

*Update a product*

Role: ADMIN | MANAGER Content-Type: multipart/form-data

Same fields as POST — all optional

---

### DELETE /api/products/:id

*Delete a product*

Role: ADMIN | MANAGER

---

## 7. Categories — /api/categories

---

### GET /api/categories

*Get all categories*

Auth required

```
// Response
{
  "data": [
    { "_id": "...", "name": "Hot Drinks", "icon": "...", "order": 1, "isActive": true }
  ]
}
```

---

### POST /api/categories

*Create a new category*

Role: ADMIN | MANAGER

```
{
  "name": "Hot Drinks",
  "description": "...", // optional
}
```

```
"icon": "🍷",           // optional
"order": 1             // optional – for sorting
}
```

---

### PUT /api/categories/:id

*Update a category*

Role: ADMIN | MANAGER

```
// All fields optional
{
  "name": "...",
  "description": "...",
  "icon": "...",
  "order": 2,
  "isActive": false
}
```

---

### DELETE /api/categories/:id

*Delete a category*

Role: ADMIN | MANAGER

---

## 8. Offers — /api/offers

---

### GET /api/offers

*Get all promotional offers*

Auth required

Query Params:

|          |                |
|----------|----------------|
| page     | (default: 1)   |
| limit    | (default: 10)  |
| isActive | → true   false |

---

### POST /api/offers

*Create a new offer*

Role: ADMIN | MANAGER Content-Type: multipart/form-data

|               |                                 |
|---------------|---------------------------------|
| title         | (required)                      |
| discountType  | (required) → percentage   fixed |
| discountValue | (required, number)              |
| description   | (optional)                      |

```
startDate    (optional)
endDate      (optional)
bannerImage  (optional, image file)
```

---

### PUT /api/offers/:id

*Update an offer*

Role: ADMIN | MANAGER Content-Type: multipart/form-data

Same fields as POST — all optional

---

### PATCH /api/offers/:id/toggle

*Toggle offer active/inactive*

Role: ADMIN | MANAGER

```
// No body needed
```

---

### DELETE /api/offers/:id

*Delete an offer*

Role: ADMIN | MANAGER

---

---

## 9. Coupons — /api/coupons

---

### GET /api/coupons

*Get all coupons*

Auth required

---

### POST /api/coupons

*Create a new coupon*

Role: ADMIN | MANAGER

```
{
  "code": "SAVE10",
  "discountType": "percentage", // percentage | fixed
  "discountValue": 10,
  "minOrderAmount": 50,         // optional
  "maxUses": 100,               // optional
  "expiresAt": "2026-12-31"    // optional
}
```

---

### PUT /api/coupons/:id

Update a coupon

Role: ADMIN | MANAGER

```
// All fields optional
{
  "code": "...",
  "discountType": "...",
  "discountValue": 0,
  "minOrderAmount": 0,
  "maxUses": 0,
  "expiresAt": "...",
  "isActive": true
}
```

### DELETE /api/coupons/:id

Delete a coupon

Role: ADMIN | MANAGER

## 10. Customers — /api/customers

### GET /api/customers

Get all customers

Auth required

Query Params:

|        |                                      |
|--------|--------------------------------------|
| page   | (default: 1)                         |
| limit  | (default: 10)                        |
| search | (optional) – search by name or phone |

### GET /api/customers/stats

Get customer statistics

Auth required

```
// Response example
{
  "data": {
    "totalCustomers": 320,
    "newThisMonth": 40,
    "loyaltyStats": { ... }
  }
}
```

```
}  
}
```

---

### PUT /api/customers/:id

*Update a customer*

Role: ADMIN | MANAGER

```
// All fields optional (at least 1 required)  
{  
  "name": "...",  
  "phone": "...",  
  "email": "...",  
  "loyaltyPoints": 100,  
  "notes": "..."  
}
```

---

### DELETE /api/customers/:id

*Delete a customer*

Role: ADMIN | MANAGER

---

## 11. Subscriptions — /api/subscriptions

---

### GET /api/subscriptions

*Get all subscriptions*

Auth required

Query Params:

```
page    (default: 1)  
limit   (default: 10)  
status  → active | paused | cancelled
```

---

### GET /api/subscriptions/stats

*Get subscription statistics*

Auth required

---

### POST /api/subscriptions

*Create a new subscription*

Role: ADMIN | MANAGER

```
{
  "customerId": "abc123",
  "items": [
    { "productId": "xyz", "quantity": 2 }
  ],
  "frequency": "weekly",          // daily | weekly | biweekly | monthly
  "startDate": "2026-07-01",     // optional
  "deliveryAddress": "..."     // optional
}
```

---

### PUT /api/subscriptions/:id

*Update a subscription*

Role: ADMIN | MANAGER

```
// All fields optional
{
  "items": [...],
  "frequency": "monthly",
  "status": "paused",           // active | paused
  "deliveryAddress": "..."
}
```

---

### DELETE /api/subscriptions/:id

*Cancel a subscription*

Role: ADMIN | MANAGER

---

## 12. Kitchen — /api/kitchen

---

### GET /api/kitchen/orders

*Get all active kitchen orders*

Role: KITCHEN | ADMIN | MANAGER

```
// Response
{
  "data": [
    {
      "_id": "...",
      "type": "dine-in",
      "tableId": "...",
      "status": "preparing",
      "items": [
```

```
    { "productId": "...", "name": "Espresso", "quantity": 2, "status": "pending"
  }
  ],
  "createdAt": "..."
}
]
```

---

#### PUT /api/kitchen/orders/:id

Update kitchen order status

Role: KITCHEN | ADMIN | MANAGER

```
{
  "status": "preparing", // pending | preparing | ready | served
  "itemIndex": 0         // optional – update a specific item by its index in the
items array
}
```

---

## 13. POS Shifts — /api/pos/shifts

---

#### POST /api/pos/shifts/open

Open a new cashier shift

Role: CASHIER | ADMIN | MANAGER

```
{
  "openingCash": 500,
  "notes": "..." // optional
}
```

---

#### PUT /api/pos/shifts/close

Close the current open shift

Role: CASHIER | ADMIN | MANAGER

```
{
  "closingCash": 1200,
  "notes": "..." // optional
}
```

```
// Response includes shift summary
{
```

```
"data": {
  "shift": { ... },
  "totalOrders": 45,
  "totalRevenue": 3200,
  "difference": 700
}
```

---

#### GET /api/pos/shifts/current

*Get the currently open shift*

Auth required

---

#### GET /api/pos/shifts/:shiftId

*Get a specific shift summary*

Auth required

---

## 14. Financial — /api/financial

---

#### GET /api/financial/overview

*Get financial summary*

Auth required

Query Params:

- startDate (optional) → e.g. 2026-01-01
- endDate (optional) → e.g. 2026-06-30

```
// Response
{
  "data": {
    "totalRevenue": 50000,
    "totalExpenses": 20000,
    "netProfit": 30000
  }
}
```

---

#### GET /api/financial/transactions

*Get all financial transactions*

Auth required

Query Params:

page (default: 1)  
limit (default: 10)  
type → income | expense

---

## POST /api/financial/transactions

*Record a new financial transaction*

Role: ADMIN | MANAGER

```
{
  "type": "expense",          // income | expense
  "amount": 500,
  "description": "...",      // optional
  "category": "...",         // optional
  "date": "2026-06-22"      // optional
}
```

---

# 15. Reports — /api/reports

Role: ADMIN | MANAGER | SUPER\_ADMIN

---

## GET /api/reports/overview

*General business overview*

Query Params:

startDate (optional)  
endDate (optional)

---

## GET /api/reports/employees

*Employee performance report*

Query Params:

startDate (optional)  
endDate (optional)  
locationId (optional)

---

## GET /api/reports/branches

*Branch performance report*

Query Params:

startDate (optional)  
endDate (optional)

---

## GET /api/reports/analytics

*Detailed analytics*

Query Params:

type → sales | orders | customers | products  
startDate (optional)  
endDate (optional)

## GET /api/reports/export

*Export report as a file*

Query Params:

type (required) → orders | customers | products | financial  
format (optional) → csv | xlsx | pdf  
startDate (optional)  
endDate (optional)

*Returns a downloadable file*

# 16. Locations — /api/locations

## GET /api/locations

*Get all branches/locations*

**Auth required**

```
// Response
{
  "data": [
    { "_id": "...", "name": "Main Branch", "address": "...", "isActive": true }
  ]
}
```

## POST /api/locations

*Create a new location*

**Role:** ADMIN | SUPER\_ADMIN | MANAGER

```
{
  "name": "New Branch",
  "address": "123 Main St...",
  "phone": "...", // optional
}
```

```
"email": "...", // optional
}
```

---

### PUT /api/locations/:id

*Update a location*

Role: ADMIN | SUPER\_ADMIN | MANAGER

```
// All fields optional
{
  "name": "...",
  "address": "...",
  "phone": "...",
  "email": "...",
}
```

---

### PATCH /api/locations/:id/toggle

*Toggle location active/inactive*

Role: ADMIN | SUPER\_ADMIN | MANAGER

```
// No body needed
```

---

### DELETE /api/locations/:id

*Delete a location*

Role: ADMIN | SUPER\_ADMIN

---

## 17. Suppliers — /api/suppliers

---

### GET /api/suppliers

*Get all suppliers*

Auth required

```
Query Params:
page      (default: 1)
limit     (default: 10)
search    (optional) – search by name
```

---

### POST /api/suppliers

*Create a new supplier*

Role: ADMIN | MANAGER

```
{
  "name": "Coffee Supplier Co.",
  "contactPerson": "Mohammed",
  "phone": "01012345678",
  "email": "...",           // optional
  "address": "...",        // optional
  "taxNumber": "...",      // optional
  "paymentTerms": "...",   // optional
  "notes": "..."         // optional
}
```

---

### PUT /api/suppliers/:id

*Update a supplier*

Role: ADMIN | MANAGER

Same fields as POST — all optional + "isActive": true

---

### DELETE /api/suppliers/:id

*Delete a supplier*

Role: ADMIN | MANAGER

---

## 18. Inventory — /api/inventory

---

### GET /api/inventory

*Get all inventory items*

Auth required — ?page=1&limit=10

---

### GET /api/inventory/shortages

*Get low-stock alerts*

Auth required

```
// Response
{
  "data": [
    { "productName": "Coffee Beans", "currentStock": 5, "minRequired": 20 }
  ]
}
```

---

### POST /api/inventory/synchronize

Sync inventory with current stock levels

Role: ADMIN | MANAGER

```
// No body needed
```

### PUT /api/inventory/:id/stock

Update stock for a single inventory item

Role: ADMIN | MANAGER

```
{
  "quantity": 50,
  "reason": "...", // optional
}
```

### PUT /api/inventory/bulk-update

Update stock for multiple items at once

Role: ADMIN | MANAGER

```
{
  "items": [
    { "id": "abc", "quantity": 20 },
    { "id": "xyz", "quantity": 10 }
  ]
}
```

## 19. Notifications — /api/notifications

### GET /api/notifications

Get notifications for the logged-in user

Auth required

Query Params:

|        |                           |
|--------|---------------------------|
| page   | (default: 1)              |
| limit  | (default: 10)             |
| unread | (optional) → true   false |

### PUT /api/notifications/:id/read

Mark a notification as read

Auth required

```
// No body needed
```

---

## 20. Reviews — /api/reviews

---

### GET /api/reviews

Get all customer reviews

Auth required

Query Params:

```
page      (default: 1)
limit     (default: 10)
rating    (optional) → 1 | 2 | 3 | 4 | 5
isVisible (optional) → true | false
```

---

### POST /api/reviews

Submit a customer review

No auth required — Public endpoint

```
{
  "rating": 5,
  "comment": "Excellent service!",
  "customerName": "...", // optional
  "customerPhone": "...", // optional
  "orderId": "..."      // optional
}
```

---

### PATCH /api/reviews/:id/visibility

Show or hide a review

Role: ADMIN | MANAGER

```
// No body needed – toggles visibility
```

---

### DELETE /api/reviews/:id

Delete a review

Role: ADMIN | MANAGER

---

---

## 21. Warehouses — `/api/warehouses`

---

### GET `/api/warehouses`

*Get all warehouses*

Auth required — `?page=1&limit=10`

---

### POST `/api/warehouses`

*Create a new warehouse*

Role: ADMIN | MANAGER

```
{
  "name": "Main Warehouse",
  "address": "...",
  "phone": "...",    // optional
  "capacity": 1000,  // optional
  "notes": "..."   // optional
}
```

---

### PUT `/api/warehouses/:id`

*Update a warehouse*

Role: ADMIN | MANAGER

Same fields as POST — all optional + `"isActive": true`

---

### DELETE `/api/warehouses/:id`

*Delete a warehouse*

Role: ADMIN | MANAGER

---

### GET `/api/warehouses/transfers`

*Get all stock transfers*

Auth required

```
Query Params:
  page    (default: 1)
  limit    (default: 10)
  status   → pending | in-transit | completed | cancelled
```

---

### POST `/api/warehouses/transfers`

Create a stock transfer between warehouses

Role: ADMIN | MANAGER

```
{
  "fromWarehouseId": "abc",
  "toWarehouseId": "xyz",
  "items": [
    { "productId": "...", "quantity": 10 }
  ],
  "scheduledDate": "2026-07-01", // optional
  "notes": "..."               // optional
}
```

---

#### PATCH /api/warehouses/transfers/:id/status

Update transfer status

Role: ADMIN | MANAGER

```
{
  "status": "completed", // pending | in-transit | completed | cancelled
  "notes": "..."       // optional
}
```

---

## 22. Purchasing — /api/purchasing

---

#### GET /api/purchasing

Get all purchase orders

Auth required — ?page=1&limit=10&status=...

---

#### POST /api/purchasing

Create a new purchase order

Role: ADMIN | MANAGER

```
{
  "supplierId": "abc123",
  "items": [
    {
      "productId": "...",
      "productName": "Coffee Beans",
      "quantity": 100,
      "unitCost": 25
    }
  ]
}
```

```
],
"warehouseId": "...",           // optional
"expectedDeliveryDate": "...",  // optional
"notes": "..."                 // optional
}
```

---

### POST /api/purchasing/:id/submit

*Submit purchase order to supplier*

Role: ADMIN | MANAGER

// No body needed

---

### POST /api/purchasing/:id/payment

*Record a payment for a purchase order*

Role: ADMIN | MANAGER

```
{
  "amount": 5000,
  "paymentMethod": "cash",           // cash | bank_transfer | credit
  "referenceNumber": "...",          // optional
  "notes": "..."                   // optional
}
```

---

### POST /api/purchasing/:id/receive

*Mark a purchase order as received*

Role: ADMIN | MANAGER

```
{
  "receivedDate": "2026-06-22",     // optional
  "notes": "..."                   // optional
}
```

---

### POST /api/purchasing/:id/cancel

*Cancel a purchase order*

Role: ADMIN | MANAGER

```
{
  "reason": "..."                 // optional
}
```

---

---

## 23. Pricing — /api/pricing

---

### GET /api/pricing

Get all pricing rules

Auth required

---

### POST /api/pricing/rules

Create a new pricing rule

Role: ADMIN | MANAGER

```
{
  "name": "Bulk Discount",
  "type": "bulk_discount",           // bulk_discount | surcharge |
  loyalty_discount | seasonal
  "value": 15,
  "adjustmentType": "percentage",   // percentage | fixed
  "minQuantity": 10,                // optional
  "applicableProductIds": ["..."],  // optional – empty means applies to all
  "startDate": "...",               // optional
  "endDate": "...",                 // optional
}
```

---

### PUT /api/pricing/rules/:id

Update a pricing rule

Role: ADMIN | MANAGER

Same fields as POST — all optional + "isActive": true

---

### DELETE /api/pricing/rules/:id

Delete a pricing rule

Role: ADMIN | MANAGER

---

### GET /api/pricing/pricelists

Get all price lists

Auth required

---

### POST /api/pricing/pricelists

Create a new price list

Role: ADMIN | MANAGER

```
{
  "name": "Wholesale Price List",
  "description": "...", // optional
  "items": [
    { "productId": "...", "price": 45 }
  ]
}
```

---

### PUT /api/pricing/pricelists/:id

*Update a price list*

Role: ADMIN | MANAGER

Same fields as POST — all optional

---

### DELETE /api/pricing/pricelists/:id

*Delete a price list*

Role: ADMIN | MANAGER

---

## 24. Production — /api/production

---

### GET /api/production/batches

*Get all production batches*

Auth required — ?page=1&limit=10&status=...

---

### POST /api/production/batches

*Create a new production batch*

Role: ADMIN | MANAGER

```
{
  "productName": "Ethiopian Coffee",
  "roastingDegree": "medium", // light | medium | dark
  "weightBefore": 100, // optional, in kg
  "weightAfter": 85, // optional, in kg
  "date": "2026-06-22", // optional
  "ingredients": [
    { "name": "Green Beans", "quantity": 100, "unit": "kg" }
  ],
}
```

```
  "notes": "...", // optional
}
```

---

### POST /api/production/batches/:id/quality-check

Run quality check on a batch

Role: ADMIN | MANAGER

```
{
  "passed": true,
  "notes": "...", // optional
  "checkedBy": "..." // optional
}
```

---

### PATCH /api/production/batches/:id/status

Update batch status

Role: ADMIN | MANAGER

```
{
  "status": "in-progress" // planned | in-progress | completed | cancelled
}
```

---

### GET /api/production/equipment

Get all production equipment

Auth required

---

### POST /api/production/equipment

Add new equipment

Role: ADMIN | MANAGER

```
{
  "name": "Coffee Roaster",
  "type": "roaster",
  "serialNumber": "...", // optional
  "purchaseDate": "...", // optional
  "nextServiceDate": "..." // optional
}
```

---

### PUT /api/production/equipment/:id

Update equipment details

Role: ADMIN | MANAGER

```
// All fields optional
{
  "name": "...",
  "status": "maintenance",    // active | maintenance | retired
  "nextServiceDate": "..."
}
```

---

#### POST /api/production/equipment/:id/service-log

Log a service entry for equipment

Role: ADMIN | MANAGER

```
{
  "description": "Routine maintenance",
  "serviceDate": "2026-06-22",
  "technician": "...",        // optional
  "cost": 500,                 // optional
  "nextServiceDate": "..."   // optional
}
```

---

#### GET /api/production/equipment/:id/service-logs

Get all service logs for a piece of equipment

Auth required

---

## 25. Logistics — /api/logistics

---

#### GET /api/logistics/drivers

Get all delivery drivers

Auth required

```
// Response
{
  "data": [
    { "_id": "...", "name": "...", "whatsappPhone": "...", "vehicleType":
"motorcycle", "status": "active" }
  ]
}
```

---

#### POST /api/logistics/drivers

Create a new delivery driver

Role: ADMIN | MANAGER

```
{
  "name": "Driver Name",
  "whatsappPhone": "01012345678",
  "vehicleType": "motorcycle",      // motorcycle | car | bicycle
  "zones": ["Zone A", "Zone B"],    // optional
  "status": "active"                // active | offline
}
```

---

### PUT /api/logistics/drivers/:id

Update a driver

Role: ADMIN | MANAGER

Same fields as POST — all optional + "isActive": true

---

### DELETE /api/logistics/drivers/:id

Delete a driver

Role: ADMIN | MANAGER

---

### POST /api/logistics/dispatch

Dispatch a driver for delivery

Role: ADMIN | MANAGER | CASHIER

```
{
  "driverId": "abc123",
  "orderId": "xyz789",
  "zone": "Zone A"    // optional
}
```

---

### POST /api/logistics/drivers/:id/complete

Mark a delivery as completed

Role: ADMIN | MANAGER

```
{
  "orderId": "...",    // optional
  "notes": "..."     // optional
}
```

---

## GET /api/logistics/zones/:zone/orders

Get all orders in a delivery zone

Auth required

URL Param: zone – e.g. /api/logistics/zones/zone-a/orders

## WebSocket — Real-time Events

Connect:

```
import { io } from 'socket.io-client';

const socket = io('https://api.patriacoffeebeans.com', {
  auth: { token: 'Bearer eyJ...' }
});
```

Events:

| Event                       | Direction       | Payload                         | Description                                  |
|-----------------------------|-----------------|---------------------------------|----------------------------------------------|
| kitchen:join                | Client → Server | {}                              | Join the kitchen room to receive live orders |
| kitchen:new-order           | Server → Client | { order }                       | Fired when a new order comes in              |
| kitchen:order-status-update | Client → Server | { orderId, status, itemIndex? } | Update order or item status from kitchen     |

## Quick Reference

### All Endpoints Summary

| Module       | Endpoints |
|--------------|-----------|
| Auth         | 6         |
| Users        | 4         |
| Tables       | 4         |
| Reservations | 4         |
| Orders       | 5         |
| Products     | 4         |

|               |            |
|---------------|------------|
| Categories    | 4          |
| Offers        | 5          |
| Coupons       | 4          |
| Customers     | 4          |
| Subscriptions | 5          |
| Kitchen       | 2          |
| POS Shifts    | 4          |
| Financial     | 3          |
| Reports       | 5          |
| Locations     | 5          |
| Suppliers     | 4          |
| Inventory     | 5          |
| Notifications | 2          |
| Reviews       | 4          |
| Warehouses    | 7          |
| Purchasing    | 6          |
| Pricing       | 8          |
| Production    | 9          |
| Logistics     | 7          |
| <b>Total</b>  | <b>116</b> |

## HTTP Methods

| Method | Count | Usage                   |
|--------|-------|-------------------------|
| GET    | 43    | Fetch data              |
| POST   | 45    | Create / actions        |
| PUT    | 20    | Full update             |
| PATCH  | 2     | Partial update / toggle |
| DELETE | 6     | Delete                  |

## Public Endpoints (No Auth)

| Endpoint                       | Description     |
|--------------------------------|-----------------|
| POST /api/auth/register        | Register admin  |
| POST /api/auth/login           | Login           |
| POST /api/auth/refresh         | Refresh token   |
| POST /api/auth/forgot-password | Reset password  |
| POST /api/reviews              | Submit a review |