

Ex.No. 2: Implementing TDMA Slot Allocation in GSM.

AIM: To implement TDMA (Time Division Multiple Access) slot allocation in GSM using MATLAB and analyze system performance in terms of time slot duration, frame utilization, and number of allocated slots.

Objective: 1. To calculate the Time Slot Duration in a GSM TDMA frame by dividing the total frame time into equal time slots. This helps in understanding the time structure of GSM communication.

2. To determine the Frame Utilization (%) based on the number of allocated time slots compared to total available slots. This evaluates the efficiency of TDMA resource usage.

3. To compute the Number of Allocated Time Slots for multiple users in the GSM system. This ensures proper scheduling and interference-free communication.

Procedure: 1. Define GSM frame parameters such as total frame duration and number of time slots.

2. Compute time slot duration by dividing frame duration by number of slots.

3. Assign time slots to multiple users based on availability.

4. Calculate frame utilization percentage using allocated slots vs total slots.

5. Determine total number of allocated slots for active users.


6. Plot time slot allocation and utilization using MATLAB graphs.

7. Display results in the command window for analysis..

OBJECTIVE-2.1

```
clc;
clear;
close all;
FrameTime = 4.615;
Slots = 8;
SlotDuration = FrameTime/Slots;
t = 0:SlotDuration:FrameTime;
figure
subplot(2,1,1);
stem(t,ones(size(t)),'filled');
title('TDMA Time Slot Structure');
xlabel('Time (ms)');
ylabel('Slot Level');
grid on
subplot(2,1,2);
plot(t,ones(size(t)),'-o','LineWidth',1.5);
title('Continuous View of Slot Allocation');
xlabel('Time (ms)');
ylabel('Slot Presence');
grid on;
```

OUTPUT:-




OBJECTIVE-2.2:-

```
clc;
clear;
close all;
TotalSlots = 8;
AllocatedSlots = 6;
FreeSlots = TotalSlots - AllocatedSlots;
Utilization = (AllocatedSlots/TotalSlots)*100;
disp('Frame Utilization (%)');
disp(Utilization)
figure
```

```
% Graph 1: Simple Line Plot (SAFE - no bar function);
subplot(2,1,1);
plot([1 2],[AllocatedSlots FreeSlots],'-o','LineWidth',2);
title('GSM Frame Utilization (Allocated vs Free)');
xlabel('Slot Type Index (1=Allocated, 2=Free)');
ylabel('Number of Slots');
grid on;
```

OUTPUT:-



OBJECTIVE-2.3

```
clc;
clear;
close all;
Users = 1:8;
TotalSlots = 5;
Alloc = zeros(1,8);
Alloc(1:TotalSlots) = 1;
```

```

Blocked = 1 - Alloc;
disp('User Wise Slot Allocation');
disp(table(Users',Alloc','VariableNames',{ 'User','Status(1=Allocated,0=Blocked)
'}));
figure
subplot(2,1,1);
stem(Users,Alloc,'filled','LineWidth',2);
title('TDMA Slot Allocation per User');
xlabel('User Index') ;
ylabel('Slot Status (1=Allocated, 0=Blocked)');
ylim([-0.2 1.2]);
grid on
subplot(2,1,2);
plot(Users,Alloc,'-o','LineWidth',2);
hold on;
plot(Users,Blocked,'-s','LineWidth',2);
title('TDMA Slot Utilization Analysis');
xlabel('User Index');
ylabel('Status');
legend('Allocated','Blocked');
grid on;

```

OUTPUT:-

