



SQL

SQL explained for beginners

The nine keywords that handle **90% of your day** with databases — and the gotchas nobody warns you about.

-- before the syntax

SQL is the skill that outlives frameworks

Frameworks come and go, but relational databases have run the world's data for 50 years. Learn to think in **sets** and the same model works everywhere.

- ▶ It's **declarative** — you say what you want, the engine finds how.
- ▶ Indexes and the optimizer do the heavy lifting, **if you let them**.

WHY IT MATTERS

Backend, analytics, ML — they all run on SQL. Learn it once, and it pays off for your whole career.



-- 01 · read data

Pick which columns you want

select.sql

```
SELECT * FROM users;  
SELECT id, name FROM users;
```

GOTCHA

`SELECT *` ships every column and breaks when the schema changes. Name the columns you actually use in production.



-- 02 · filter rows

Keep only the rows that match

● ● ● where.sql

```
SELECT * FROM users
WHERE country = 'MX'
      AND last_login IS NOT NULL;
```

GOTCHA · NULL

`= NULL` never matches — `NULL` means "unknown". Use `IS NULL`. And a function on the column blocks the index.



```
-- 03 · sort
```

●●● order.sql

```
SELECT * FROM users
ORDER BY created_at DESC, id;
```

GOTCHA

Ties sort in an undefined order — add a tiebreaker like `id`. Sorting big results is costly unless the column is indexed.



```
-- 04 · paginate
```

●●● limit.sql

```
SELECT * FROM users
ORDER BY id
LIMIT 20;
```

PRO TIP

OFFSET n re-scans n rows on every page. For deep pagination, filter by the last id (**WHERE id > ...**) instead.

-- 05 · combine tables

Glue two tables by a **shared key**

● ● ● join.sql

```
SELECT u.name, o.total
FROM users u
LEFT JOIN orders o ON o.user_id =
    u.id;
```

GOTCHA

INNER drops unmatched rows; LEFT keeps them as NULL. Many matches on the right **fan out** into duplicates — aggregate for one row per user.



-- 06 · aggregate

Collapse rows into one per group

group.sql

```
SELECT country, COUNT(*)  
FROM users  
GROUP BY country  
HAVING COUNT(*) > 100;
```

GOTCHA

Every selected column must be aggregated or in GROUP BY. **WHERE** filters rows before grouping; **HAVING** filters groups after.



-- 07 · search text

Match text by a pattern

like.sql

```
SELECT * FROM users
WHERE name LIKE 'A%';
```

GOTCHA

A leading wildcard (`'%term'`) can't use an index and scans the whole table. For real search, reach for full-text or trigram indexes.



-- 08 · add data

Add new rows to a table

insert.sql

```
INSERT INTO users (name, email)
VALUES
  ('Ada', 'ada@mail.com'),
  ('Alan', 'alan@mail.com');
```

PRO TIP

Insert many rows in one statement, not a loop — one round-trip instead of thousands.



-- 09 • change & remove

Edit or delete existing rows

● ● ● write.sql

```
UPDATE users SET active = false  
WHERE last_login < '2024-01-01';
```

```
DELETE FROM users WHERE id = 42;
```

GOTCHA

No **WHERE** means **every row**. Run your filter as a **SELECT** first to see exactly what you'll touch.



-- the mental model

SQL runs in a surprising order

You write **SELECT** first, but the engine runs it almost last — so a column alias isn't ready yet when **WHERE** runs.



how-sql-runs.sql

1. **FROM** -- pick the tables
2. **WHERE** -- filter rows
3. **GROUP BY** -- make groups
4. **HAVING** -- filter groups
5. **SELECT** -- choose columns
6. **ORDER BY** -- sort
7. **LIMIT** -- cut



-- that's the 90%

You just learned the **core of SQL**

Master these nine and you can query almost any database. Which one bites you most often?



Alejandro Sánchez Yalí

Software Developer | AI & Blockchain Enthusiast
www.asanchezyali.com



Study with me

The full source on GitHub

