

Development of R packages: ‘*NonCompart*’ and ‘*ncar*’ for noncompartmental analysis (NCA)

Hyungsub Kim, Sungpil Han, Yong-Soon Cho, Seok-Kyu Yoon and Kyun-Seop Bae*

Department of Clinical Pharmacology and Therapeutics, Asan Medical Center, University of Ulsan, Seoul 05505, Republic of Korea

*Correspondence: K. S. Bae; Tel: +82-2-3010-4611, Fax: +82-2-3010-4623, E-mail: ksbae@amc.seoul.kr



Received 2 Jan 2018

Revised 2 Mar 2018

Accepted 2 Mar 2018

Keywords

NonCompart,
ncar,
R,
noncompartmental analysis
(NCA)

pISSN: 2289-0882

eISSN: 2383-5427

Noncompartmental analysis (NCA) is a primary analytical approach for pharmacokinetic studies, and its parameters act as decision criteria in bioequivalent studies. Currently, NCA is usually carried out by commercial softwares such as WinNonlin®. In this article, we introduce our newly-developed two R packages, *NonCompart* (NonCompartmental analysis for pharmacokinetic data) and *ncar* (NonCompartmental Analysis for pharmacokinetic Report), which can perform NCA and produce complete NCA reports in both pdf and rtf formats. These packages are compatible with CDISC (Clinical Data Interchange Standards Consortium) standard as well. We demonstrate how the results of WinNonlin® are reproduced and how NCA reports can be obtained. With these R packages, we aimed to help researchers carry out NCA and utilize the output for early stages of drug development process. These R packages are freely available for download from the CRAN repository.

Introduction



The aim of pharmacokinetics (PK) studies is to examine the kinetics of a drug with regard to absorption, distribution, metabolism and elimination in the body. PK data analysis consists of noncompartmental analysis (NCA) and nonlinear regression analysis.[1,2] NCA uses the trapezoidal rule for measurement of area under the concentration-time curve (AUC), and requires fewer assumptions than model-based analysis.[2] NCA allows for estimation of various PK parameters such as AUC, peak observed drug concentration (C_{max}), time of peak concentration (T_{max}), and elimination half-life. Particularly, AUC and C_{max} are often accepted as the criteria for approval of bioequivalent drugs.

R, a widely-used computer language, is a suite of libraries of statistical and mathematical computations.[3] Despite its relatively small base system compared with other commercial softwares for NCA such as WinNonlin®[4] and Kinética,[5] R has robust functions for scientific computation and numerous

add-in packages for use in various fields.[6] Therefore, many efforts are being made to replace commercial softwares with R packages.

In this article, we introduce two newly-developed R packages, *NonCompart* and *ncar*, that are compatible with SDTM (Study Data Tabulation Model)-formatted dataset of CDISC (Clinical Data Interchange Standards Consortium), which is the standard of documentation submitted to regulatory authorities,[7] while providing a practical method for producing complete NCA reports.

Methods

R packages (*NonCompart* and *ncar*)

Two R packages (*NonCompart* and *ncar*) for NCA were developed in the open-source R programming language in order to allow free public use. R packages can be installed and loaded using the following scripts.

R code

```
install.packages("NonCompart", "ncar")
library(NonCompart)
library(ncar)
```

Copyright © 2018 Translational and Clinical Pharmacology
 © It is identical to the Creative Commons Attribution Non-Commercial License
 (<http://creativecommons.org/licenses/by-nc/3.0/>).
 © This paper meets the requirement of KS X ISO 9706, ISO 9706-1994 and
 ANSI/NISO Z.39.48-1992 (Permanence of Paper).

Reviewer

This article was reviewed by peer experts who are not TCP editors.

Detailed documentation and examples for each package can be found on the online user manual in the CRAN repository (<http://cran.r-project.org/web/packages/NonCompart/index.html>, <http://cran.r-project.org/web/packages/ncar/index.html>) or directly within the R console by entering ?function (e.g., ?NonCompart, ?ncar). These two packages are implemented in R and can accept a set of input arguments that allow for generation of NCA output. The names of most NCA metrics estimated by the function of these packages are consistent with those used in WinNonlin® (Table 1).

Software

WinNonlin® (Pharsight, Mountain View, CA, USA)[4] in Mi-

crosoft-Windows 7 (64 bit) was used for the computation. R 3.4.2 in Microsoft-Windows 7 (64 bit) was used for the comparison of calculated values.

Dataset

To compare the outputs generated by R packages and WinNonlin®, we used Theoph dataset obtained from the R software. The Theoph dataset has 132 observations from 12 subjects. A portion of the Theoph dataset (subject ID = 8) is shown in Table 2.

Table 1. Description of PK parameters of WinNonlin® and the R packages

Parameter	WinNonlin®	Description
b0	b0	Intercept
CMAX	Cmax	Max Concentration (Conc)
CMAXD	Cmax_D	Max Conc Norm by Dose
TMAX	Tmax_D	Time of Cmax
TLAG	Tlag	Time Until First Nonzero Conc
CLST	Clast	Last Nonzero Conc
CLSTP	Clast_pred	Last Nonzero Conc Pred
TLST	Tlast	Time of Last Nonzero Conc
LAMZHL	HL_Lambda_z	Half-Life Lambda z
LAMZ	Lambda_z	Lambda z
LAMZLL	Lambda_z lower	Lambda z Lower Limit
LAMZUL	Lambda_z upper	Lambda z Upper Limit
LAMZNPT	No_points_Lambda_z	Number of Points for Lambda z
CORRXY	Corr_XY	Correlation Between Time X and Log Conc Y
R2	Rsq	R Squared
R2ADJ	Rsq_adjusted	R Squared Adjusted
AUCLST	AUClast	AUC to Last Nonzero Conc
AUCALL	AUCall	AUC All
AUCIFO	AUCINF_obs	AUC Infinity Obs
AUCIFOD	AUCINF_D_obs	AUC Infinity Obs Norm by Dose
AUCIFFP	AUCINF_Pred	AUC Infinity Pred
AUCIFPD	AUCINF_D_pred	AUC Infinity Pred Norm by Dose
AUCPEO	AUC_Extrap_obs	AUC %Extrapolation Obs
AUCPEP	AUC_Extrap_pred	AUC %Extrapolation Pred
AUMCLST	AUMClast	AUMC to Last Nonzero Conc
AUMCIFO	AUMCINF_obs	AUMC Infinity Obs
AUMCIFFP	AUMCINF_pred	AUMC Infinity Pred
AUMCPEO	AUMC_Extrap_obs	AUMC %Extrapolation Obs
AUMCPEP	AUMC_Extrap_pred	AUMC % Extrapolation Pred
VZFO	Vz_F_obs	Vz Obs by F
VZFP	Vz_F_p	Vz Pred by F
CLFO	Cl_F_obs	Total CL Obs by F
CLFP	Cl_F_pred	Total CL Pred by F
MRTEVLST	MRTlast	MRT Extravasc to Last Nonzero Conc
MRTEVIFO	MRTINF_obs	MRT Extravasc Infinity Obs
MRTEVIFFP	MRTINF_pred	MRT Extravasc Infinity Pred

Table 2. Part of Theoph dataset with information on key (subject), time, and concentration

Subject	Weight (kg)	Dose (mg)	Time (h)	Concentration (mg/ml)
8	70.5	4.53	0	0.00
8	70.5	4.53	0.25	3.05
8	70.5	4.53	0.52	3.05
8	70.5	4.53	0.98	7.31
8	70.5	4.53	2.02	7.56
8	70.5	4.53	3.53	6.59
8	70.5	4.53	5.05	5.88
8	70.5	4.53	7.15	4.73
8	70.5	4.53	9.05	4.57
8	70.5	4.53	12.10	3.00
8	70.5	4.53	24.12	1.25

Results

NonCompart package: performance of NCA

This package conducts NCA as similarly as possible to the most widely used commercial PK analysis software. The *NonCompart* package has two main functions, `tblNCA` and `sNCA`, for use in multiple subjects and one subject, respectively. Figure 1 shows an example of output by `tblNCA`. The input data for `tblNCA()` should be in a long format as exemplified by the Theoph dataset.

It is possible to input several keys such as subject demographics and information regarding dose, period, or sequence; the result of `tblNCA()` will print the key columns and the carried keys can be further used for additional statistical analysis (i.e. descriptive statistics, bioequivalence test, t-test, or ANOVA). The `adm` argument can be 'Extravascular', 'Bolus', or 'Infusion' and the `down` argument can be either 'Linear' or 'Log'. The greatest advantage of this package is that the outputs produced by this package are compatible with those of pharmacokinetic parameter (PP) TESTCD of CDISC SDTM.

R code

```
tblNCA(Theoph, key = "Subject", colTime = "Time", colConc = "conc", dose = 320, adm = "Extravascular", dur = 0, doseUnit = "mg", timeUnit = "h", concUnit = "mg/L", down = "Linear")
```

`IntAUC()` function calculates interval (partial) AUC (from t_1 and t_2) with the given series of time and concentration. The interval AUC (0.5 to 11 hour) of the subject 8 can be calculated using the Theoph dataset with the following R script.

R code

```
Time = Theoph[Theoph$Subject == 8, "Time"]
Concentration = Theoph[Theoph$Subject == 8, "conc"]
Res = sNCA(Time, Concentration, dose = 320, concUnit = "mg/L")
IntAUC(Time, Concentration, t1 = 0.5, t2 = 11, Res)
[1] 58.26022
```

ncar package: generation of NCA reports

This package generates complete NCA reports including plots with both linear and logarithmic scale. Its two main functions are `pdfNCA` and `rtfNCA`, which produce pdf file format and rtf file format, respectively. The generated reports are similar to those generated from commercial softwares, but like *NonCompart*, this package has the advantage of using PPT-

```
> tblNCA(Theoph, key = "Subject", colTime = "Time", colConc = "conc", dose = 320, + adm = "Extravascular", dur = 0, doseUnit = "mg", timeUnit = "h", concUnit = "ug/L", down = "Linear")
# Subject b0
   CMAX    CMAXD     TMAX    TLAG    CLST    CLSTP      TLST    LAMZHL
[1,] "2.36878509420585" "10.5" "0.0328125" "1.12" "0" "3.28" "3.28014647414312" "24.37" "14.304377571097"
[2,] "2.41123733696293" "8.33" "0.02603125" "1.92" "0" "0.9" "0.888639849106919" "24.3" "6.65934156262252"
[3,] "2.52971150145858" "8.2"  "0.025625"   "1.02" "0" "1.05" "1.05509670837553" "24.17" "6.76608737718236"
[4,] "2.59275546723663" "8.6"  "0.026875"   "1.07" "0" "1.15" "1.15642160174997" "24.65" "6.98124666099893"
[5,] "2.55109229061238" "11.4" "0.035625"   "1"    "0" "1.57" "1.55569511595616" "24.35" "8.0022640410078"
[6,] "2.0334043955261"  "6.44" "0.020125"   "1.15" "0" "0.92" "0.941271173708175" "23.85" "7.89499786796582"
[7,] "2.28854976005424" "7.09" "0.02215625" "3.48" "0" "1.15" "1.16071921229933" "24.22" "7.84666826130148"
[8,] "2.17040271754659" "7.56" "0.023625"   "2.02" "0" "1.25" "1.22852675835656" "24.12" "8.51003788342506"
[9,] "2.12464810390587" "9.03" "0.02821875" "0.63" "0" "1.12" "1.11648311706515" "24.43" "8.40599880716182"
[10,] "2.65770546248091" "10.21" "0.03190625" "3.55" "0" "2.42" "2.41369227401111" "23.7" "9.24691582297898"
[11,] "2.1475943307927"  "8"    "0.025"    "0.98" "0" "0.86" "0.859806606884089" "24.08" "7.26123651504339"
[12,] "2.82449347826545" "9.75" "0.03046875" "3.52" "0" "1.17" "1.17553904959565" "24.15" "6.28650816367189"
```

Figure 1. Example of *NonCompart* package functions. Example by `tblNCA`.

ESTCD of CDISC SDTM. *ncar* produces NCA reports through *NonCompart* and converts them into Microsoft Word format when using `rtnfNCA()`, which is convenient for editing. Reports generated by `pdfNCA()` function show individual plots with trend lines that joins the dots used for calculating terminal slopes. Figure 2 shows an example of an NCA report in pdf format and an individual concentration-time plot.

R code

```
pdfNCA(fileName = "pdfNCA-Theoph.pdf",
Theoph, colSubj = "Subject", colTime =
"Time", colConc = "conc", dose = 320,
doseUnit = "mg", timeUnit = "h", concUnit =
"mg/L", down = "Linear")
```

Validation of NCA results between R packages and WinNonlin®

To demonstrate the accordance of outputs by *ncar* package and WinNonlin®, we performed NCA using *Theoph* dataset obtained from the R software. For comparison of the NCA results, we selected the following conditions: extravascular, linear-up linear-down, and best fit. We found no discrepancy between the two results as shown in Table 3 (a randomized subject, Subject ID = 8).

In order to further validate these packages, we compared NCA results using *Indometh*, another available dataset of the R software as well as other datasets of a number of subjects from several phase 1 clinical trials with different dosing routes such as infusion, bolus, and oral route. As a result, we could not find

Table 3. Comparison of NCA results generated from WinNonlin® and *ncar* package

Parameter	WinNonlin®	<i>ncar</i>
CMAX	7.56 mg/L	7.5600 mg/L
CMAXD	0.023625 mg/L/mg	0.0236 mg/L/mg
TMAX	2.02 h	2.0200 h
TLAG	0 h	0.0000 h
CLST	1.25 mg/L	1.2500 mg/L
TLST	24.12 h	24.1200 h
LAMZHL	8.510037883 h	8.5100 h
LAMZ	0.08145054 /h	0.0815 /h
LAMZLL	3.53 h	3.5300 h
LAMZUL	24.12 h	24.1200 h
LAMZNPT	6	6
CORRXY	-0.995496053	-0.9955
R2	0.991012391	0.991
R2ADJ	0.988765489	0.9888
AUCLST	88.55995 h*mg/L	88.5600 h*mg/L
AUCALL	88.55995 h*mg/L	88.5600 h*mg/L
AUCIFO	103.906687 h*mg/L	103.9067 h*mg/L
AUCIFOD	0.324708 h*mg/L/mg	0.3247 h*mg/L/mg
AUCIFF	103.643051 h*mg/L	103.6431 h*mg/L
AUCIFFP	0.323884 h*mg/L/mg	0.3239 h*mg/L/mg
AUCPEO	14.77%	14.77%
AUCPEP	14.55%	14.55%
AUMCLST	739.534598 h ² *mg/L	739.5346 h ² *mg/L
AUMCIFO	1298.115755 h ² *mg/L	1298.1158 h ² *mg/L
AUMCIFF	1288.520116 h ² *mg/L	1288.5201 h ² *mg/L
AUMCPEO	43.03%	43.03%
AUMCPEP	42.61%	42.61%
VZFO	37.81050811 L	37.8105 L
VZFP	37.90668616 L	37.9067 L
CLFO	3.079686301 L/h	3.0797 L/h
CLFP	3.087520055 L/h	3.0875 L/h
MRTEVLST	8.35066639 h	8.3507 h
MRTEVIFO	12.49309159 h	12.4931 h
MRTEVIFP	12.43228656 h	12.4323 h

(A) Subject ID = 8

NONCOMPARTMENTAL ANALYSIS REPORT
Package version 0.3.7 (2017-08-16 KST)
R version 3.4.2 (2017-09-28)

Date and Time: 2017-11-07 02:04:35 NA

Calculation Setting

Drug Administration: Extravascular
Observation count excluding trailing zeros: 11
Dose at time 0: 320 mg
AUC Calculation Method: Linear-up Linear-down
Weighting for lambda z: Uniform (Ordinary Least Square, OLS)
Lambda z selection criterion: Highest adjusted R-squared value with precision=le-4

Fitting, AUC, AUMC Result

Time	Conc.	Fred.	Residual	AUC	AUMC
0.0000	0.0000			0.0000	0.0000
0.2500	3.6500			0.3813	0.0953
0.5200	3.6500			1.2048	0.4124
0.9800	7.3100			3.5875	2.4248
2.0200	7.5600			11.3200	14.0910
3.5300 *	6.5900	6.5724 +1.758e-02	22.0032	43.1841	
5.0500 *	5.8800	5.8071 +7.292e-02	31.4804	83.4312	
7.1500 *	4.7300	4.8941 -1.641e-01	42.4209	150.1204	
9.0700 *	4.5700	4.1856 +3.844e-01	51.5489	222.3790	
12.1000 *	3.0000	3.2702 -2.702e-01	63.0175	340.1701	
24.1200 *	1.2500	1.2285 +2.147e-02	88.5600	739.5346	

*: Used for the calculation of Lambda z.

Calculated Values	
CMAX	Max Conc 7.5600 mg/L
CMAXD	Max Conc Norm by Dose 0.0236 mg/L/mg
TMAX	Time of CMAX 2.0200 h
TLAG	Time Until First Nonzero Conc 0.0000 h
CLST	Last Nonzero Conc 1.2500 mg/L
CLSTP	Last Nonzero Conc Pred 1.2285 mg/L
TLST	Time of Last Nonzero Conc 24.1200 h
LAMEHL	Half-Life Lambda z 8.5100 h
LAMEZ	Lambda z 0.0815 /h
LAMELL	Lambda z Lower Limit 3.5300 h
LAMEUL	Lambda z Upper Limit 24.1200 h
LAMENPT	Number of Points for Lambda z 6
CORRXY	Correlation Between TimeX and Log ConcY -0.9955
R2	R Squared 0.9910
R2ADJ	R Squared Adjusted 0.9888
AUCLET	AUC to Last Nonzero Conc 88.5600 h*mg/L
AUCALL	AUC All 88.5600 h*mg/L
AUCIF0	AUC Infinity Obs 103.9067 h*mg/L
AUCIFOD	AUC Infinity Obs Norm by Dose 0.3247 h*mg/L/mg
AUCIFP	AUC Infinity Fred 103.6431 h*mg/L
AUCIFPD	AUC Infinity Fred Norm by Dose 0.3239 h*mg/L/mg
AUCIFPEx	AUC %Extrapolation Obs 14.7697 %
AUCIFPF	AUC %Extrapolation Fred 14.5529 %
AUMCLST	AUMC to Last Nonzero Conc 739.5346 h2*mg/L
AUMCIP0	AUMC Infinity Obs 1298.1158 h2*mg/L
AUMCIPF	AUMC Infinity Fred 1288.5201 h2*mg/L
AUMCPEO	AUMC %Extrapolation Obs 43.0302 %
AUMCPEF	AUMC % Extrapolation Fred 42.6059 %
VIF0	Vs Obs by F 37.8105 L
VIFP	Vs Fred by F 37.9067 L
CLFO	Total CL Obs by F 3.0797 L/h
CLFP	Total CL Fred by F 3.0875 L/h
MRTEVLIST	MRT Extravasc to Last Nonzero Conc 8.3507 h
MRTEVIFO	MRT Extravasc Infinity Obs 12.4931 h
MRTEVIFF	MRT Extravasc Infinity Fred 12.4323 h

(B)




Figure 2. Examples of *ncar* package functions. (A) Example of a NCA report in pdf format by *pdfNCA*, (B) Individual concentration-time plots (left: linear scale, right: log-linear scale).

any discrepancy between outputs generated by the R packages and WinNonlin®.

Discussion

We developed two R packages—*NonCompart* and *ncar* for NCA. Through these packages, we aimed to implement the following functionalities for performing NCA: 1) CDISC SDTM terms; 2) automatic slope selection with the same criterion of WinNonlin®; 3) supporting both ‘linear-up linear-down’ and ‘linear-up log-down’ method; and 4) interval (partial) AUCs with ‘linear’ or ‘log’ interpolation method. These packages are convenient and efficient because they enable preparation of data and NCA as well as generation of reports including plots together in R software. As shown in Figure 2B, the

NCA plot allows for automatic slope selection, however, it is not possible to manually choose the points used for calculating terminal slope. In addition, any error or change can easily be fixed, and users may choose calculation methods between linear and logarithmic, which support ‘linear-up linear-down’ and ‘linear-up log-down’ method, respectively. Our results showed that our R packages meet the aforementioned objectives.

Since the PPTESTCD of SDTM is used in the R packages, it is helpful to construct PP domain. In the present practice, one has to change variables from WinNonlin® one by one, which is an especially difficult task for those without specific knowledge on SDTM. A number of packages can perform NCA, but no package—even commercial softwares—can give outputs in the format of SDTM or receive SDTM-formatted input data. It is

important to ensure that the reports are legible to sponsors and regulatory bodies by generating a consistent and systematic result, as well as the exact results of NCA.

As shown in Table 3, comparison of NCA results obtained by WinNonlin® and *ncar* package (including another package) showed no significant discrepancies. These two R packages are fast and easy-to-use tool-set that can successfully perform NCA with concentration–time data. Specifically, the *ncar* package can produce a comprehensive set of graphical and tabular outputs that summarize the NCA results, which is a complete report in pdf or rtf format. Our two newly-developed packages are free and open-source, so they can be used to develop other useful packages as well. We hope that *NonCompart* and *ncar* packages will enable researchers to easily perform NCA, and contribute to facilitation of drug discovery process.

Acknowledgements

This research was supported by the EDISON (EDucation-research Integration through Simulation On the Net) Program through the National Research Foundation of Korea (NRF) funded by the Ministry of Education, Science and Technology (Grant number: 016M3C1A6936614). We thank Dr. Joon Seo Lim from the Scientific Publications Team at Asan Medical Center for his editorial assistance in preparing this manuscript.

Conflicts of interests

- Authors: The authors declare that they have no conflict of interests
- Reviewers: Nothing to declare
- Editors: Nothing to declare

References

1. Acharya C, Hooker AC, Turkyilmaz GY, Jonsson S, Karlsson MO. A diagnostic tool for population models using non-compartmental analysis: The ncappc package for R. *Comput Methods Programs Biomed* 2016;127: 83-93. doi: 10.1016/j.cmpb.2016.01.013.
2. Gabrielsson J, Weiner D. Non-compartmental analysis. *Methods Mol Biol* 2012;929:377–389.
3. The R Project for Statistical Computing. R. <http://www.r-project.org/> Accessed 6 November 2017.
4. Kinetica. <http://www.kinetica.com/> Accessed 28 February 2018
5. Certara. Phenix WinNonlin®. <https://www.certara.com/software/pkpd-modeling-and-simulation/phoenix-winnonlin/?ap%5B0%5D=PKPD/> Accessed 28 February 2018.
6. Kim MG, Yim DS, Bae KS. R-based reproduction of the estimation process hidden behind NONMEM Part 1: first-order approximation method. *Transl Clin Pharmacol* 2015;23:1-7.
7. Study Data Tabulation Model Implementation Guide: Human Clinical Trials Version 3.2, Clinical Data Interchange Standards Consortium. https://www.cdisc.org/system/files/all/standard_category/application/pdf/sdtmig_v3.2.pdf. Accessed 28 February 2018.