PlussMic User Documentation

PlussMa Contributors

Mar 01, 2026

CONTENTS

1 Quickstart **3**
- 1.1 Include Paths . . . 3
- 1.2 Load A Table Fast . . . 3
- 1.3 Start With A Small In-Memory Frame . . . 3
- 1.4 Typical DataFrame Workflow . . . 3
- 1.5 Convert Between Models . . . 4
- 1.6 Save Results . . . 4

2 Demo Catalog **5**
- 2.1 Table Examples . . . 5
- 2.2 Kindle Examples . . . 5
- 2.3 Bundle Examples . . . 5

3 DataFrame Guide **7**
- 3.1 What DataFrame Is Good At . . . 7
- 3.2 Construction And Loading . . . 7
- 3.3 Inspect Rows, Features, And Cases . . . 7
- 3.4 Cast And Derive Features . . . 8
- 3.5 Filter, Query, And Sort . . . 8
- 3.6 Grouping, Pivoting, And Summaries . . . 9
- 3.7 Missing Data And Rolling Windows . . . 9
- 3.8 Join And Combine . . . 9
- 3.9 Time-Aware Table Verbs . . . 10
- 3.10 SQL And IO . . . 10

4 DataFrame API Reference **11**

5 Practical DataFrame API Reference **13**
- 5.1 API Reference Style . . . 13

6 ColumnRef API Reference **221**

7 Practical ColumnRef API Reference **223**
- 7.1 API Reference Style . . . 223

8 DataFramePlotAccessor API Reference **229**

9 Practical DataFramePlotAccessor API Reference **231**
- 9.1 API Reference Style . . . 231

10 DataFrameSqlAccessor API Reference **235**

11 Practical DataFrameSqlAccessor API Reference **237**
11.1 API Reference Style . . . 237

12 DataFrameSqlPrepared API Reference **239**

13 Practical DataFrameSqlPrepared API Reference **241**
13.1 API Reference Style . . . 241

14 Thread And Atlas Guide **245**
14.1 Thread . . . 245
14.2 Row-Space Helpers . . . 245
14.3 Atlas . . . 245
14.4 Atlas To Kindle . . . 246

15 Thread API Reference **247**

16 Practical Thread API Reference **249**
16.1 API Reference Style . . . 249

17 ThreadValue API Reference **293**

18 Practical ThreadValue API Reference **295**
18.1 API Reference Style . . . 295

19 Atlas API Reference **303**

20 Practical Atlas API Reference **305**
20.1 API Reference Style . . . 305

21 Kindle Model Guide **329**
21.1 When To Use Kindle Types . . . 329
21.2 Stream Basics . . . 329
21.3 Catalog Basics . . . 329
21.4 Text And Similarity Helpers . . . 330
21.5 Archive Basics . . . 330
21.6 Convert Back To Table Model . . . 330

22 Stream API Reference **331**

23 Practical Stream API Reference **333**
23.1 API Reference Style . . . 333

24 Catalog API Reference **369**

25 Practical Catalog API Reference **371**
25.1 API Reference Style . . . 371

26 Archive API Reference **463**

27 Practical Archive API Reference **465**
27.1 API Reference Style . . . 465

28 Bundle Model Guide **485**
28.1 When To Use Bundle Types . . . 485
28.2 Slot . . . 485
28.3 Registry . . . 485
28.4 Aisle . . . 486

28.5 Kindle Bridge 486

29 Slot API Reference **487**

30 Practical Slot API Reference **489**
30.1 API Reference Style 489

31 Registry API Reference **503**

32 Practical Registry API Reference **505**
32.1 API Reference Style 505

33 Aisle API Reference **581**

34 Practical Aisle API Reference **583**
34.1 API Reference Style 583

35 Build Outputs **599**
35.1 HTML 599
35.2 PDF 599
35.3 Notes 599

PlussMic is the data-analysis layer in the Pluss stack. It gives you three related models:

- `table`: `DataFrame`, `Thread`, `Atlas`
- `kindle`: `Stream`, `Catalog`, `Archive`
- `bundle`: `Slot`, `Registry`, `Aisle`

This manual is organized the same way users usually approach the library:

- start with `DataFrame` for table-style analysis
- use `Thread` when you want typed column operations outside a frame
- use `Catalog` and `Archive` when streams/case-aligned data are a better fit
- use `Registry` and `Aisle` when you want heterogeneous record bundles

CHAPTER

ONE

QUICKSTART

1.1 Include Paths

```
#include <pluss/pluss.h>
// or, when you only want PlussMic:
#include <pluss/mic.h>
```

1.2 Load A Table Fast

```
auto df = pluss::table::DataFrame::load_csv(
    "path/to/data.csv",
    {{"nrows", 16}});

std::cout << df << "\n";
df.info();
df.describe();
```

1.3 Start With A Small In-Memory Frame

```
auto sales = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
    {"revenue", pluss::table::Thread(pluss::make_series({120.0, 95.0, 140.0}))},
    {"opened_at", pluss::table::Thread(pluss::make_timeline({
        "2024-01-01T09:00:00Z",
        "2024-01-02T09:00:00Z",
        "2024-01-03T09:00:00Z",
    }))},
});

sales.head();
```

1.4 Typical DataFrame Workflow

```
auto accidents = pluss::table::DataFrame::load_csv(
    "path/to/data.csv",
    {{"nrows", 64}})
    .fillna(0.0, {"Lifecycle Cost", "Cost Variance (%)"})
```

(continues on next page)

(continued from previous page)

```
    .query("isnotnull(Agency Name)")
    .sort_values({"Lifecycle Cost"}, false)
    .head(10, false);

accidents.show();
```

1.5 Convert Between Models

```
auto df = pluss::table::DataFrame::load_csv("path/to/data.csv", {{"nrows", 8}});
auto catalog = df.kindelize();
auto roundtrip_df = catalog.tabelize();

auto registry = pluss::bundle::Registry::from_kindle(catalog);
auto back_catalog = registry.to_kindle();
```

1.6 Save Results

```
auto out = pluss::table::DataFrame::load_json("path/to/data.json", {{"nrows", 12}});

out.save_csv("path/to/output.csv");
out.save_excel("path/to/output.xlsx");
out.save_json("path/to/output.json");
```

CHAPTER

TWO

DEMO CATALOG

2.1 Table Examples

- `PlussMic/examples/table/dataframe_initial_demo.cpp`: loading CSV files, viewing rows, info, describe, and a simple `Atlas`
- `PlussMic/examples/table/dataframe_describe_demo.cpp`: summary statistics plus CSV loader benchmarking
- `PlussMic/examples/table/dataframe_view_demo.cpp`: row windows and quick inspection patterns
- `PlussMic/examples/table/dataframe_thread_values_demo.cpp`: working with typed `Thread` columns
- `PlussMic/examples/table/dataframe_versatile_methods_demo.cpp`: selection, transforms, grouping, joins, and reshaping verbs
- `PlussMic/examples/table/loader_saver_parity_demo.cpp`: CSV, TXT, JSON, Excel, and Parquet loader/saver parity
- `PlussMic/examples/table/dataframe_plot_demo.cpp`: plotting accessors and integration with PlussPl
- `PlussMic/examples/table/display_policy_demo.cpp`: terminal display policy and compact rendering
- `PlussMic/examples/table/eda_us_accidents.cpp`: end-to-end exploratory analysis workflow on the accidents dataset
- `PlussMic/examples/table/us_accidents_eda_verbs_demo.cpp`: richer EDA verbs and derived-feature workflow

2.2 Kindle Examples

- `PlussMic/examples/kindle/kindle_model_demo.cpp`: `Stream`, `Catalog`, and `Archive` workflows

2.3 Bundle Examples

- `PlussMic/examples/bundle/bundle_model_demo.cpp`: `Slot`, `Registry`, and `Aisle` workflows

CHAPTER

THREE

DATAFRAME GUIDE

3.1 What DataFrame Is Good At

`pluss::table::DataFrame` is the main table-analysis surface in PlussMic. Use it when you want:

- named features with mixed typed columns
- a case axis that can be numeric, note-based, timeline-based, or time-index based
- table verbs such as `query`, `assign`, `group_by`, `pivot_table`, `join`, `fillna`, and `describe`
- import/export across CSV, TXT, JSON, Excel, and Parquet

3.2 Construction And Loading

```
auto df = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"opened", pluss::table::Thread(pluss::make_timeline({
        "2024-01-01T08:00:00Z",
        "2024-01-02T08:00:00Z",
        "2024-01-03T08:00:00Z",
    }))},
});

auto csv_df = pluss::table::DataFrame::load_csv(
    "path/to/data.csv",
    {{"nrows", 32}});

auto excel_df = pluss::table::DataFrame::load_excel(
    "path/to/data.xlsx",
    {{"sheetindex", 0}, {"header", true}});

auto json_df = pluss::table::DataFrame::load_json(
    "path/to/data.json",
    {{"nrows", 24}});
```

3.3 Inspect Rows, Features, And Cases

```
df.head();
df.tail();
```

(continues on next page)

(continued from previous page)

```
df.info();
df.describe();

auto city = df.features("city");
auto sales = df.features("sales");
auto case_axis = df.cases();

auto first_row = df.iloc(0);
auto first_value = df.at(0, "city");
```

Notes:

- `features("name")` returns a typed `Thread`
- `cases()` is the row axis, not just a display index
- `describe()` is the fastest way to check whether numeric casts and missing values look right

3.4 Cast And Derive Features

```
auto work = csv_df
    .cast_timeline({"Business Case ID"})
    .astype({{"Lifecycle Cost", pluss::codem::ScalarType::Float64}})
    .assign({
        pluss::table::DataFrame::DeriveSpec{
            "Cost_plus_buffer",
            [](const pluss::table::DataFrame& f) {
              return pluss::table::Thread(f.features("Lifecycle Cost").as_series().
↪add(500.0));
            },
        },
    });
```

3.5 Filter, Query, And Sort

```
auto positive = df.filter(df.features("sales").as_series().gt(95.0));

auto queried = df.query("sales > 95");

auto sorted = df.sort_values({"sales"}, false);

auto top3 = df.top("sales", 3);
```

Notes:

- use `filter(bool_mask)` when you already have a boolean `Series`
- use `query("...")` when the filter is easier to read as a table expression
- `top` and `bottom` are good for ranking tasks without writing extra sort/slice steps

3.6 Grouping, Pivoting, And Summaries

```
auto grouped = df.group_by(
    {"city"},
    {{"avg_sales", "sales", pluss::table::DataFrame::GroupOp::Mean}},
    true,
    false);

auto pivoted = df.pivot_table(
    "city",
    "city",
    "sales",
    pluss::table::DataFrame::GroupOp::Mean,
    true,
    false);

auto stats = df.aggregate({
    {"sales_mean", "sales", pluss::table::DataFrame::SummaryOp::Mean},
    {"sales_max", "sales", pluss::table::DataFrame::SummaryOp::Max},
}, false);
```

3.7 Missing Data And Rolling Windows

```
auto cleaned = df.fillna(0.0, {"sales"});
auto dropped = df.dropna();
auto carried = df.ffill();

auto rolling = df.window({
    {"sales_roll3", "sales", pluss::table::ThreadWindowOp::RollingMean, 3, 1},
});
```

3.8 Join And Combine

```
auto left = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema"}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0}))},
});

auto right = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema"}))},
    {"manager", pluss::table::Thread(pluss::make_note({"Ama", "Kojo"}))},
});

auto joined = left.stitch_on({"city"}, right, {"city"}, "_r");
auto updated = left.update(right, true);
```

3.9 Time-Aware Table Verbs

```
auto schedule = pluss::table::DataFrame({
    {"ts", pluss::table::Thread(pluss::make_timeline({
        "2024-01-01T09:10:00Z",
        "2024-01-01T09:40:00Z",
        "2024-01-01T10:05:00Z",
    }))},
    {"value", pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}))},
});

auto hourly = schedule.resample("ts", {"value"}, "1H", "mean", 1, false);
auto floored = schedule.floor_time({"ts"}, "hour");
auto utc = schedule.to_utc({"ts"});
```

3.10 SQL And IO

```
auto result = df.sql().query("SELECT city, sales FROM self ORDER BY sales DESC");

result.save_csv("path/to/output.csv");
result.save_excel("path/to/output.xlsx");
result.save_json("path/to/output.json");
```

CHAPTER

FOUR

DATAFRAME API REFERENCE

CHAPTER

FIVE

PRACTICAL DATAFRAME API REFERENCE

5.1 API Reference Style

This page documents the full public `DataFrame` surface with usage-first examples generated from the current table API.

5.1.1 add

Signature

```
DataFrame add(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame add(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.add(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.2 add

Signature

```
DataFrame add(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame add(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.add(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.3 add_prefix

Signature

```
DataFrame add_prefix(self, std::string_view prefix) const
```

Parameters

`prefix` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Prepends the supplied text to every feature name. Row values, row order, and case labels stay unchanged.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.add_prefix("feat_");
```

Output

```
df.head():
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi

out.head():
feat_id  feat_sales  feat_city
1        100.0       Accra
2        120.0       Tema
3         90.0       Kumasi
```

5.1.4 add_suffix

Signature

```
DataFrame add_suffix(self, std::string_view suffix) const
```

Parameters

`suffix` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Appends the supplied text to every feature name. Row values, row order, and case labels stay unchanged.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.add_suffix("_2024");
```

Output

```
df.head():
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi

out.head():
id_2024  sales_2024  city_2024
1        100.0       Accra
2        120.0       Tema
3         90.0       Kumasi
```

5.1.5 aggregate

Signature

```
DataFrame aggregate(self, std::initializer_list<SummarySpec> specs, bool render = true)␣
↪const
```

Parameters

`specs` : `std::initializer_list<SummarySpec>` See the signature for the supported argument form.

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Builds a compact summary frame from one or more aggregation specs, so you can inspect computed metrics instead of the full row set.

Examples

```
auto df = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Accra", "Tema", "Tema"}))},
    {"product", pluss::table::Thread(pluss::make_note({"A", "B", "A", "B"}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0, 150.0}))},
});

auto out = df.aggregate({{"sales_mean", "sales",␣
↪pluss::table::DataFrame::SummaryOp::Mean}}, false);
```

Output

```
metric       value
sales_mean    115.0
```

5.1.6 align_cases

Signature

```
DataFrame align_cases(self, const Thread& new_cases) const
```

Parameters

`new_cases` : `const Thread&` Replacement case labels in the exact order you want the rows to follow.

Returns

`DataFrame` Value produced by this call.

Notes

Reorders rows so their case labels match the supplied `new_cases` order. Every requested case must already exist, and the output case axis is rewritten to that order.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df = df.with_cases(pluss::table::Thread(pluss::make_note({"cs0", "cs1", "cs2"})));
auto new_cases = pluss::table::Thread(pluss::make_note({"cs1", "cs0", "cs2"}));
auto out = df.align_cases(new_cases);
```

Output

```
df.cases():
["cs0", "cs1", "cs2"]
```

(continues on next page)

(continued from previous page)

```
out.cases():
["cs1", "cs0", "cs2"]

out.head():
id  sales  city
2   120.0  Tema
1   100.0  Accra
3    90.0  Kumasi
```

5.1.7 assign

Signature

```
DataFrame assign(self, std::initializer_list<DeriveSpec> specs) const
```

Parameters

specs : std::initializer_list<DeriveSpec> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Adds or replaces derived features computed from the current frame. Use this when the new column depends on one or more existing columns.

See also

- DataFrame assign(self, std::initializer_list<std::pair<std::string, Thread>> assignments) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.assign({{.feature = "profit", .expr = [](const pluss::table::DataFrame&␣
↪frame) { return pluss::table::Thread(frame.features("sales").as_series().sub(60)); }}}
↪);
```

Output

```
id  sales  city    profit
1   100.0  Accra   40.0
2   120.0  Tema    35.0
3    90.0  Kumasi  30.0
```

5.1.8 assign

Signature

```
DataFrame assign(self, std::initializer_list<std::pair<std::string, Thread>>␣
↪assignments) const
```

Parameters

`assignments` : `std::initializer_list<std::pair<std::string, Thread>>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Adds or replaces derived features computed from the current frame. Use this when the new column depends on one or more existing columns.

See also

- `DataFrame assign(self, std::initializer_list<DeriveSpec> specs) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.assign({{"profit", pluss::table::Thread(pluss::make_series({40.0, 35.0, 30.
↪0}))}});
```

Output

```
id  sales  city    profit
1   100.0  Accra   40.0
2   120.0  Tema    35.0
3    90.0  Kumasi  30.0
```

5.1.9 astype

Signature

```
DataFrame astype(self,  std::initializer_list<std::pair<std::string_view,␣
↪pluss::codem::ScalarType>> feature_dtypes) const
```

Parameters

`feature_dtypes` : `std::initializer_list<std::pair<std::string_view, pluss::codem::ScalarType>>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

See also

- `DataFrame astype(self, std::initializer_list<std::string_view> features, pluss::codem::ScalarType dtype) const`

Examples

```
auto df = pluss::table::DataFrame({{"sales", pluss::table::Thread(pluss::make_note({"100.
↪0", "120.0", "90.0"}))}});

auto out = df.astype({{"sales", pluss::codem::ScalarType::Float64}});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.10 astype

Signature

```
DataFrame astype(self, std::initializer_list<std::string_view> features,␣
↪pluss::codem::ScalarType dtype) const
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`dtype` : `pluss::codem::ScalarType` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

See also

- DataFrame astype(self, std::initializer_list<std::pair<std::string_view, pluss::codem::ScalarType>> feature_dtypes) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.astype();
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.11 at

Signature

```
std::string at(self, std::int64_t row, std::string_view feature_name) const
```

Parameters

row : std::int64_t See the signature for the supported argument form.

feature_name : std::string_view Name of the target feature to read, rewrite, sort by, or promote to cases.

Returns

std::string Rendered string result.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.at(0, "city");
```

Output

```
1
```

5.1.12 bfill

Signature

```
DataFrame bfill(self) const
```

Parameters

None

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.bfill();
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.13 bottom

Signature

```
DataFrame bottom(self, std::string_view feature, std::int64_t n) const
```

Parameters

`feature` : `std::string_view` See the signature for the supported argument form.

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

Returns

`DataFrame` Value produced by this call.

Notes

Returns the rows with the smallest values in the selected feature.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.bottom("sales", 2);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.14 cases

Signature

```
const Thread& cases(self) const
```

Parameters

None

Returns

`const Thread&` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- `DataFrame cases(self, std::int64_t row) const`
- `DataFrame cases(self, std::pair<std::int64_t, std::int64_t> row_span) const`
- `std::string cases(self, std::int64_t row, std::size_t feature_idx) const`
- `std::string cases(self, std::int64_t row, std::string_view feature_name) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.cases(0);
```

5.1.15 cases

Signature

```
DataFrame cases(self, std::int64_t row) const
```

Parameters

`row` : `std::int64_t` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- `const Thread& cases(self) const`
- `DataFrame cases(self, std::pair<std::int64_t, std::int64_t> row_span) const`
- `std::string cases(self, std::int64_t row, std::size_t feature_idx) const`
- `std::string cases(self, std::int64_t row, std::string_view feature_name) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.cases(0);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.16 cases

Signature

```
DataFrame cases(self, std::pair<std::int64_t, std::int64_t> row_span) const
```

Parameters

row_span : std::pair<std::int64_t, std::int64_t> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- const Thread& cases(self) const
- DataFrame cases(self, std::int64_t row) const
- std::string cases(self, std::int64_t row, std::size_t feature_idx) const
- std::string cases(self, std::int64_t row, std::string_view feature_name) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.cases({0, 2});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.17 cases

Signature

```
std::string cases(self, std::int64_t row, std::size_t feature_idx) const
```

Parameters

`row` : `std::int64_t` See the signature for the supported argument form.

`feature_idx` : `std::size_t` See the signature for the supported argument form.

Returns

`std::string` Rendered string result.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- `const Thread& cases(self) const`
- `DataFrame cases(self, std::int64_t row) const`
- `DataFrame cases(self, std::pair<std::int64_t, std::int64_t> row_span) const`
- `std::string cases(self, std::int64_t row, std::string_view feature_name) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.cases(0, 0);
```

Output

```
1
```

5.1.18 cases

Signature

```
std::string cases(self, std::int64_t row, std::string_view feature_name) const
```

Parameters

`row` : `std::int64_t` See the signature for the supported argument form.

`feature_name` : `std::string_view` Name of the target feature to read, rewrite, sort by, or promote to cases.

Returns

`std::string` Rendered string result.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- `const Thread& cases(self) const`
- `DataFrame cases(self, std::int64_t row) const`
- `DataFrame cases(self, std::pair<std::int64_t, std::int64_t> row_span) const`
- `std::string cases(self, std::int64_t row, std::size_t feature_idx) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.cases(0, "city");
```

Output

```
1
```

5.1.19 cases_series

Signature

```
pluss::Series cases_series(self) const
```

Parameters

None

Returns

`pluss::Series` Value produced by this call.

Notes

Returns the current case axis as a `Series`, which is useful when you need the row labels as data.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.cases_series();
```

Output

```
[0, 1, 2]
```

5.1.20 cast

Signature

```
DataFrame cast(self,  std::initializer_list<std::pair<std::string_view,␣
↪pluss::codem::ScalarType>> feature_dtypes) const
```

Parameters

feature_dtypes : std::initializer_list<std::pair<std::string_view, pluss::codem::ScalarType>> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

See also

- DataFrame cast(self, std::initializer_list<CastSpec> specs) const

Examples

```
auto df = pluss::table::DataFrame({{"sales", pluss::table::Thread(pluss::make_note({"100.
↪0", "120.0", "90.0"}))}});

auto out = df.astype({{"sales", pluss::codem::ScalarType::Float64}});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.21 cast

Signature

```
DataFrame cast(self, std::initializer_list<CastSpec> specs) const
```

Parameters

specs : std::initializer_list<CastSpec> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

See also

- DataFrame cast(self, std::initializer_list<std::pair<std::string_view, pluss::codem::ScalarType>> feature_dtypes) const

Examples

```
auto df = pluss::table::DataFrame({{"sales", pluss::table::Thread(pluss::make_note({"100.
↪0", "120.0", "90.0"}))}});

auto out = df.cast({{.feature = "sales", .target =␣
↪pluss::table::ThreadCastTarget::Series, .series_dtype =␣
↪pluss::codem::ScalarType::Float64}});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.22 cast_note

Signature

```
DataFrame cast_note(self, std::initializer_list<std::string_view> features) const
```

Parameters

features : std::initializer_list<std::string_view> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
```

(continues on next page)

(continued from previous page)

```
auto out = df.cast_note({"sales"});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.23 cast_series

Signature

```
DataFrame cast_series(self, std::initializer_list<std::string_view> features,␣
↪std::optional<pluss::codem::ScalarType> dtype = std::nullopt) const
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`dtype` : `std::optional<pluss::codem::ScalarType>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
auto df = pluss::table::DataFrame({{"sales", pluss::table::Thread(pluss::make_note({"100.
↪0", "120.0", "90.0"}))}});

auto out = df.cast_series({"sales"}, pluss::codem::ScalarType::Float64);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.24 cast_timeindex

Signature

```
DataFrame cast_timeindex(self, std::initializer_list<std::string_view> features) const
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.cast_timeindex({"sales"});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.25 `cast_timeline`

Signature

```
DataFrame cast_timeline(self, std::initializer_list<std::string_view> features) const
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
auto df = pluss::table::DataFrame({{"ts", pluss::table::Thread(pluss::make_note({"2024-
↪01-01T09:10:00Z", "2024-01-01T09:40:00Z"}))}});

auto out = df.cast_timeline({"ts"});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.26 ceil_time

Signature

```
DataFrame ceil_time(self, std::initializer_list<std::string_view> features, std::string_
↪view unit) const
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`unit` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto df = pluss::table::DataFrame({
    {"ts", pluss::table::Thread(pluss::make_timeline({
        "2024-01-01T09:10:00Z",
        "2024-01-01T09:40:00Z",
        "2024-01-01T10:05:00Z",
    }))},
    {"load", pluss::table::Thread(pluss::make_series({10.0, 20.0, 15.0}))},
});

auto out = df.ceil_time({"ts"}, "hour");
```

Output

```
ts
2024-01-01T09:00:00Z
2024-01-01T10:00:00Z
```

5.1.27 column

Signature

```
Thread column(self, std::string_view name) const
```

Parameters

name : std::string_view See the signature for the supported argument form.

Returns

Thread Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.column("sales");
```

Output

```
Thread([100.0, 120.0, 90.0])
```

5.1.28 column_names

Signature

```
const std::vector<std::string>& column_names(self) const
```

Parameters

None

Returns

const std::vector<std::string>& Borrowed list of names.

Notes

Returns the current labels used to address fields, slots, rows, or depth items.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.column_names();
```

Output

```
["id", "sales", "city"]
```

5.1.29 column_ref

Signature

```
ColumnRef column_ref(self, std::string_view name) const
```

Parameters

name : std::string_view See the signature for the supported argument form.

Returns

ColumnRef Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.column_ref("sales");
```

5.1.30 columns

Signature

```
std::vector<Thread> columns(self) const
```

Parameters

None

Returns

std::vector<Thread> Materialized collection of thread objects.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.columns();
```

Output

```
[Thread(id), Thread(sales), Thread(city)]
```

5.1.31 combine

Signature

```
DataFrame combine(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Combines this frame with another frame according to the supplied combine policy, such as feature-wise update or join-like alignment.

See also

- `DataFrame combine(self, const DataFrame& other, const CombineSpec& spec) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.combine(right);
```

Output

```
id  sales  cost
1   100.0  60.0
2   120.0  80.0
3    90.0  55.0
```

5.1.32 combine

Signature

```
DataFrame combine(self, const DataFrame& other, const CombineSpec& spec) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

`spec` : `const CombineSpec&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Combines this frame with another frame according to the supplied combine policy, such as feature-wise update or join-like alignment.

See also

- `DataFrame combine(self, const DataFrame& other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

pluss::table::DataFrame::CombineSpec spec;
spec.op = pluss::table::DataFrame::CombineOp::Update;
auto out = left.combine(right, spec);
```

Output

```
id  sales  cost
1   100.0  60.0
2   120.0  80.0
3    90.0  55.0
```

5.1.33 compare

Signature

```
DataFrame compare(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame compare(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.compare(right);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.34 compare

Signature

```
DataFrame compare(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame compare(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.compare(10);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.35 `conform_to`

Signature

```
DataFrame conform_to(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Reorders and aligns this frame so it is compatible with another frame for downstream joins or arithmetic.

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
```

(continues on next page)

(continued from previous page)

```
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.conform_to(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.36 copy

Signature

```
DataFrame copy(self) const
```

Parameters

None

Returns

`DataFrame` Value produced by this call.

Notes

Returns a detached copy of the frame so later edits to the result do not affect the source object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.copy();
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.37 count

Signature

```
DataFrame count(self, bool render = true) const
```

Parameters

render : bool See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.count(false);
```

Output

```
feature  value
sales    310.0
```

5.1.38 count_by

Signature

```
DataFrame count_by(self, std::string_view feature, std::int64_t top_n = 0, bool dropna =␣
↪true, bool render = true) const
```

Parameters

feature : std::string_view See the signature for the supported argument form.

top_n : std::int64_t See the signature for the supported argument form.

dropna : bool See the signature for the supported argument form.

render : bool See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Groups by one feature and returns per-group row counts.

Examples

```
auto df = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Accra", "Tema", "Tema"}))},
    {"product", pluss::table::Thread(pluss::make_note({"A", "B", "A", "B"}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0, 150.0}))},
});

auto out = df.count_by("city", 3, true, false);
```

Output

```
city    count
Accra   2
Tema    2
```

5.1.39 count_null_rows

Signature

```
std::int64_t count_null_rows(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Counts how many rows contain at least one null value.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.count_null_rows();
```

Output

```
3
```

5.1.40 defined

Signature

```
bool defined(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object owns a concrete payload that can be used safely in later operations.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.defined();
```

Output

```
true
```

5.1.41 describe

Signature

```
DataFrame describe(self, bool render = true) const
```

Parameters

render : bool See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Returns descriptive summary statistics for the selected numeric features.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.describe(false);
```

Output

```
feature  count  mean   min   max
sales    3      103.3  90.0  120.0
```

5.1.42 div

Signature

```
DataFrame div(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame div(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.div(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.43 div

Signature

```
DataFrame div(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame div(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.div(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.44 divide

Signature

```
DataFrame divide(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame divide(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.divide(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.45 divide

Signature

```
DataFrame divide(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame divide(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.divide(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.46 drop

Signature

```
DataFrame drop(self, std::initializer_list<std::string_view> names) const
```

Parameters

`names` : `std::initializer_list<std::string_view>` Collection of feature, slot, or stream names supplied in positional order.

Returns

`DataFrame` Value produced by this call.

Notes

Removes one or more features and returns the remaining frame.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.drop({"city"});
```

Output

```
id  sales
1   100.0
2   120.0
3    90.0
```

5.1.47 dropna

Signature

```
DataFrame dropna(self) const
```

Parameters

None

Returns

DataFrame Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.dropna();
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.48 dropna_all

Signature

```
DataFrame dropna_all(self, std::initializer_list<std::string_view> features =
```

Parameters

features : std::initializer_list<std::string_view> See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.dropna_all({"sales"});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.49 eq

Signature

```
DataFrame eq(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame eq(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
```

(continues on next page)

(continued from previous page)

```
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.eq(right);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.50 eq

Signature

```
DataFrame eq(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame eq(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.eq(10);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.51 equals

Signature

```
bool equals(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`bool` Boolean status or membership result.

Notes

Checks whether two frames have the same structure, labels, and values.

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.equals(right);
```

Output

```
true
```

5.1.52 feature_names

Signature

```
const std::vector<std::string>& feature_names(self) const
```

Parameters

None

Returns

`const std::vector<std::string>&` Borrowed list of names.

Notes

Returns the current labels used to address fields, slots, rows, or depth items.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.feature_names();
```

Output

```
["id", "sales", "city"]
```

5.1.53 feature_ref

Signature

```
ColumnRef feature_ref(self, std::string_view name) const
```

Parameters

`name` : `std::string_view` See the signature for the supported argument form.

Returns

`ColumnRef` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.feature_ref("sales");
```

5.1.54 features

Signature

```
DataFrame features(self, std::initializer_list<std::string_view> names)
```

Parameters

`names` : `std::initializer_list<std::string_view>` Collection of feature, slot, or stream names supplied in positional order.

Returns

DataFrame Value produced by this call.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

See also

- std::vector<Thread> features(self) const
- Thread features(self, std::string_view name)
- Thread features(self, std::string_view name) const
- DataFrame features(self, std::initializer_list<std::string_view> names) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.features({"id", "sales"});
```

Output

```
Thread([100.0, 120.0, 90.0])
```

5.1.55 features

Signature

```
DataFrame features(self, std::initializer_list<std::string_view> names) const
```

Parameters

names : std::initializer_list<std::string_view> Collection of feature, slot, or stream names supplied in positional order.

Returns

DataFrame Value produced by this call.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

See also

- std::vector<Thread> features(self) const
- Thread features(self, std::string_view name)

- Thread features(self, std::string_view name) const
- DataFrame features(self, std::initializer_list<std::string_view> names)

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.features({"id", "sales"});
```

Output

```
Thread([100.0, 120.0, 90.0])
```

5.1.56 features

Signature

```
std::vector<Thread> features(self) const
```

Parameters

None

Returns

std::vector<Thread> Materialized collection of thread objects.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

See also

- Thread features(self, std::string_view name)
- Thread features(self, std::string_view name) const
- DataFrame features(self, std::initializer_list<std::string_view> names)
- DataFrame features(self, std::initializer_list<std::string_view> names) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.features();
```

Output

```
[Thread(id), Thread(sales), Thread(city)]
```

5.1.57 features

Signature

```
Thread features(self, std::string_view name)
```

Parameters

name : std::string_view See the signature for the supported argument form.

Returns

Thread Value produced by this call.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

See also

- std::vector<Thread> features(self) const
- Thread features(self, std::string_view name) const
- DataFrame features(self, std::initializer_list<std::string_view> names)
- DataFrame features(self, std::initializer_list<std::string_view> names) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.features("sales");
```

Output

```
Thread([100.0, 120.0, 90.0])
```

5.1.58 features

Signature

```
Thread features(self, std::string_view name) const
```

Parameters

name : std::string_view See the signature for the supported argument form.

Returns

Thread Value produced by this call.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

See also

- std::vector<Thread> features(self) const
- Thread features(self, std::string_view name)
- DataFrame features(self, std::initializer_list<std::string_view> names)
- DataFrame features(self, std::initializer_list<std::string_view> names) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.features("sales");
```

Output

```
Thread([100.0, 120.0, 90.0])
```

5.1.59 ffill

Signature

```
DataFrame ffill(self) const
```

Parameters

None

Returns

DataFrame Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.ffill();
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.60 fillna

Signature

```
DataFrame fillna(self, const char* value) const
```

Parameters

`value` : `const char*` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `DataFrame fillna(self, scalar value) const`
- `DataFrame fillna(self, scalar value, std::initializer_list<std::string_view> features) const`
- `DataFrame fillna(self, std::string_view value) const`
- `DataFrame fillna(self, std::string_view value, std::initializer_list<std::string_view> features) const`
- `DataFrame fillna(self, const char* value, std::initializer_list<std::string_view> features) const`
- `DataFrame fillna(self, const pluss::Timeline& value) const`
- `DataFrame fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> features) const`
- `DataFrame fillna(self, const pluss::TimeIndex& value) const`

- DataFrame fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> features) const

Examples

```
auto df = pluss::table::DataFrame({{"city", pluss::table::Thread(pluss::make_note({"Accra
↪", "Tema", "Kumasi"}))}});

auto out = df.fillna("Unknown");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.61 fillna

Signature

```
DataFrame fillna(self, const char* value, std::initializer_list<std::string_view>␣
↪features) const
```

Parameters

`value` : `const char*` See the signature for the supported argument form.

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame fillna(self, scalar value) const
- DataFrame fillna(self, scalar value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, std::string_view value) const
- DataFrame fillna(self, std::string_view value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const char* value) const
- DataFrame fillna(self, const pluss::Timeline& value) const
- DataFrame fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::TimeIndex& value) const

- DataFrame fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> features) const

Examples

```
auto df = pluss::table::DataFrame({{"city", pluss::table::Thread(pluss::make_note({"Accra
↪", "Tema", "Kumasi"}))}});

auto out = df.fillna("Unknown");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.62 fillna

Signature

```
DataFrame fillna(self, const pluss::TimeIndex& value) const
```

Parameters

value : const pluss::TimeIndex& See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame fillna(self, scalar value) const
- DataFrame fillna(self, scalar value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, std::string_view value) const
- DataFrame fillna(self, std::string_view value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const char* value) const
- DataFrame fillna(self, const char* value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::Timeline& value) const
- DataFrame fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> features) const

- DataFrame fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> features) const

Examples

```
auto df = pluss::table::DataFrame({{"idx", pluss::table::Thread(pluss::make_timeindex({
↪"2024-01-01T09:10:00Z", "2024-01-01T09:40:00Z"}))}});

auto out = df.fillna(pluss::make_timeindex("2024-01-01T00:00:00Z"));
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.63 fillna

Signature

```
DataFrame fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_
↪view> features) const
```

Parameters

value : const pluss::TimeIndex& See the signature for the supported argument form.

features : std::initializer_list<std::string_view> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame fillna(self, scalar value) const
- DataFrame fillna(self, scalar value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, std::string_view value) const
- DataFrame fillna(self, std::string_view value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const char* value) const
- DataFrame fillna(self, const char* value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::Timeline& value) const

- DataFrame fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::TimeIndex& value) const

Examples

```
auto df = pluss::table::DataFrame({{"city", pluss::table::Thread(pluss::make_note({"Accra
↪", "Tema", "Kumasi"}))}});

auto out = df.fillna("Unknown");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.64 fillna

Signature

```
DataFrame fillna(self, const pluss::Timeline& value) const
```

Parameters

value : const pluss::Timeline& See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame fillna(self, scalar value) const
- DataFrame fillna(self, scalar value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, std::string_view value) const
- DataFrame fillna(self, std::string_view value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const char* value) const
- DataFrame fillna(self, const char* value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::TimeIndex& value) const

- DataFrame fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> features) const

Examples

```
auto df = pluss::table::DataFrame({{"ts", pluss::table::Thread(pluss::make_timeline({
↪"2024-01-01T09:10:00Z", "2024-01-01T09:40:00Z"}))}});

auto out = df.fillna(pluss::make_timeline("2024-01-01T00:00:00Z"));
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.65 fillna

Signature

```
DataFrame fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_
↪view> features) const
```

Parameters

value : const pluss::Timeline& See the signature for the supported argument form.

features : std::initializer_list<std::string_view> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame fillna(self, scalar value) const
- DataFrame fillna(self, scalar value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, std::string_view value) const
- DataFrame fillna(self, std::string_view value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const char* value) const
- DataFrame fillna(self, const char* value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::Timeline& value) const
- DataFrame fillna(self, const pluss::TimeIndex& value) const

- DataFrame fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> features) const

Examples

```
auto df = pluss::table::DataFrame({{"city", pluss::table::Thread(pluss::make_note({"Accra
↪", "Tema", "Kumasi"}))}});

auto out = df.fillna("Unknown");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.66 fillna

Signature

```
DataFrame fillna(self, scalar value) const
```

Parameters

value : scalar See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame fillna(self, scalar value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, std::string_view value) const
- DataFrame fillna(self, std::string_view value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const char* value) const
- DataFrame fillna(self, const char* value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::Timeline& value) const
- DataFrame fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::TimeIndex& value) const

- DataFrame fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> features) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.fillna(0.0, {"sales"});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.67 fillna

Signature

```
DataFrame fillna(self, scalar value, std::initializer_list<std::string_view> features)␣
↪const
```

Parameters

value : scalar See the signature for the supported argument form.

features : std::initializer_list<std::string_view> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame fillna(self, scalar value) const
- DataFrame fillna(self, std::string_view value) const
- DataFrame fillna(self, std::string_view value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const char* value) const
- DataFrame fillna(self, const char* value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::Timeline& value) const

- DataFrame fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::TimeIndex& value) const
- DataFrame fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> features) const

Examples

```
auto df = pluss::table::DataFrame({{"city", pluss::table::Thread(pluss::make_note({"Accra
↪", "Tema", "Kumasi"}))}});

auto out = df.fillna("Unknown");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.68 fillna

Signature

```
DataFrame fillna(self, std::string_view value) const
```

Parameters

`value` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame fillna(self, scalar value) const
- DataFrame fillna(self, scalar value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, std::string_view value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const char* value) const
- DataFrame fillna(self, const char* value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::Timeline& value) const

- DataFrame fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::TimeIndex& value) const
- DataFrame fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> features) const

Examples

```
auto df = pluss::table::DataFrame({{"city", pluss::table::Thread(pluss::make_note({"Accra
↪", "Tema", "Kumasi"}))}});

auto out = df.fillna("Unknown");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.69 fillna

Signature

```
DataFrame fillna(self, std::string_view value, std::initializer_list<std::string_view>␣
↪features) const
```

Parameters

`value` : `std::string_view` See the signature for the supported argument form.

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame fillna(self, scalar value) const
- DataFrame fillna(self, scalar value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, std::string_view value) const
- DataFrame fillna(self, const char* value) const
- DataFrame fillna(self, const char* value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::Timeline& value) const

- DataFrame fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> features) const
- DataFrame fillna(self, const pluss::TimeIndex& value) const
- DataFrame fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> features) const

Examples

```
auto df = pluss::table::DataFrame({{"city", pluss::table::Thread(pluss::make_note({"Accra
↪", "Tema", "Kumasi"}))}});

auto out = df.fillna("Unknown");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.70 fillna_

Signature

```
DataFrame& fillna_(self, const char* value)
```

Parameters

value : const char* See the signature for the supported argument form.

Returns

DataFrame& Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame& fillna_(self, scalar value)
- DataFrame& fillna_(self, std::string_view value)
- DataFrame& fillna_(self, const pluss::Timeline& value)
- DataFrame& fillna_(self, const pluss::TimeIndex& value)

Examples

```
auto df = pluss::table::DataFrame({{"city", pluss::table::Thread(pluss::make_note({"Accra
↪", "Tema", "Kumasi"}))}});

df.fillna_("Unknown");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.71 fillna_

Signature

```
DataFrame& fillna_(self, const pluss::TimeIndex& value)
```

Parameters

`value` : `const pluss::TimeIndex&` See the signature for the supported argument form.

Returns

`DataFrame&` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `DataFrame& fillna_(self, scalar value)`
- `DataFrame& fillna_(self, std::string_view value)`
- `DataFrame& fillna_(self, const char* value)`
- `DataFrame& fillna_(self, const pluss::Timeline& value)`

Examples

```
auto df = pluss::table::DataFrame({{"idx", pluss::table::Thread(pluss::make_timeindex({
↪"2024-01-01T09:10:00Z", "2024-01-01T09:40:00Z"}))}});

df.fillna_(pluss::make_timeindex("2024-01-01T00:00:00Z"));
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.72 fillna_

Signature

```
DataFrame& fillna_(self, const pluss::Timeline& value)
```

Parameters

`value` : `const pluss::Timeline&` See the signature for the supported argument form.

Returns

`DataFrame&` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `DataFrame& fillna_(self, scalar value)`
- `DataFrame& fillna_(self, std::string_view value)`
- `DataFrame& fillna_(self, const char* value)`
- `DataFrame& fillna_(self, const pluss::TimeIndex& value)`

Examples

```
auto df = pluss::table::DataFrame({{"ts", pluss::table::Thread(pluss::make_timeline({
↪"2024-01-01T09:10:00Z", "2024-01-01T09:40:00Z"}))}});

df.fillna_(pluss::make_timeline("2024-01-01T00:00:00Z"));
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.73 `fillna_`

Signature

```
DataFrame& fillna_(self, scalar value)
```

Parameters

`value` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame&` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame& fillna_(self, std::string_view value)
- DataFrame& fillna_(self, const char* value)
- DataFrame& fillna_(self, const pluss::Timeline& value)
- DataFrame& fillna_(self, const pluss::TimeIndex& value)

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.fillna_(0.0);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.74 fillna_

Signature

```
DataFrame& fillna_(self, std::string_view value)
```

Parameters

value : std::string_view See the signature for the supported argument form.

Returns

DataFrame& Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- DataFrame& fillna_(self, scalar value)
- DataFrame& fillna_(self, const char* value)
- DataFrame& fillna_(self, const pluss::Timeline& value)
- DataFrame& fillna_(self, const pluss::TimeIndex& value)

Examples

```
auto df = pluss::table::DataFrame({{"city", pluss::table::Thread(pluss::make_note({"Accra
↪", "Tema", "Kumasi"}))}});

df.fillna_("Unknown");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.75 filter

Signature

```
DataFrame filter(self, const pluss::Series& bool_mask) const
```

Parameters

bool_mask : const pluss::Series& See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Keeps only the rows where the supplied boolean mask is true.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto out = df.filter(mask);
```

Output

```
id  sales  city
1   100.0  Accra
3    90.0  Kumasi
```

5.1.76 floor_time

Signature

```
DataFrame floor_time(self, std::initializer_list<std::string_view> features, std::string_
↪view unit) const
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`unit` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto df = pluss::table::DataFrame({
    {"ts", pluss::table::Thread(pluss::make_timeline({
        "2024-01-01T09:10:00Z",
        "2024-01-01T09:40:00Z",
        "2024-01-01T10:05:00Z",
    }))},
    {"load", pluss::table::Thread(pluss::make_series({10.0, 20.0, 15.0}))},
});

auto out = df.floor_time({"ts"}, "hour");
```

Output

```
ts
2024-01-01T09:00:00Z
2024-01-01T10:00:00Z
```

5.1.77 floordiv

Signature

```
DataFrame floordiv(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame floordiv(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.floordiv(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.78 `floordiv`

Signature

```
DataFrame floordiv(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame floordiv(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.floordiv(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.79 ge

Signature

```
DataFrame ge(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame ge(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});
```

(continues on next page)

(continued from previous page)

```
auto out = left.ge(right);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.80 ge

Signature

```
DataFrame ge(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame ge(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.ge(10);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.81 get

Signature

```
std::optional<Thread> get(self, std::string_view feature_name) const
```

Parameters

`feature_name` : `std::string_view` Name of the target feature to read, rewrite, sort by, or promote to cases.

Returns

`std::optional<Thread>` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.get("sales");
```

Output

```
Thread([100.0, 120.0, 90.0])
```

5.1.82 group_by

Signature

```
DataFrame group_by(self, std::initializer_list<std::string_view> keys, std::initializer_
↪list<GroupSpec> specs, bool dropna_keys = true, bool render = true) const
```

Parameters

`keys` : `std::initializer_list<std::string_view>` Collection of slot or stream names to keep, drop, or rewrite together.

`specs` : `std::initializer_list<GroupSpec>` See the signature for the supported argument form.

`dropna_keys` : `bool` See the signature for the supported argument form.

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Groups rows by one or more key features and computes the requested aggregations for each group.

Examples

```
auto df = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Accra", "Tema", "Tema"}))},
    {"product", pluss::table::Thread(pluss::make_note({"A", "B", "A", "B"}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0, 150.0}))},
});

auto out = df.group_by({"city"}, {{"sales_sum", "sales",␣
↪pluss::table::DataFrame::GroupOp::Sum}}, true, false);
```

Output

```
city    sales_sum
Accra   220.0
Tema    240.0
```

5.1.83 gt

Signature

```
DataFrame gt(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame gt(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});
```

(continues on next page)

(continued from previous page)

```
auto out = left.gt(right);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.84 gt

Signature

```
DataFrame gt(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame gt(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.gt(10);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.85 has_column

Signature

```
bool has_column(self, std::string_view name) const
```

Parameters

name : std::string_view See the signature for the supported argument form.

Returns

bool Boolean status or membership result.

Notes

Checks whether a feature name exists in the frame.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.has_column("sales");
```

Output

```
true
```

5.1.86 has_feature

Signature

```
bool has_feature(self, std::string_view name) const
```

Parameters

name : std::string_view See the signature for the supported argument form.

Returns

bool Boolean status or membership result.

Notes

Checks whether a feature name exists in the frame.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.has_feature("sales");
```

Output

```
true
```

5.1.87 head

Signature

```
DataFrame head(self, std::int64_t n = 5, bool render = true) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Returns the first `n` rows of the frame.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.head(2, false);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.88 iat

Signature

```
std::string iat(self, std::int64_t row, std::size_t feature_idx) const
```

Parameters

`row` : `std::int64_t` See the signature for the supported argument form.

`feature_idx` : `std::size_t` See the signature for the supported argument form.

Returns

`std::string` Rendered string result.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.iat(0, 0);
```

Output

```
1
```

5.1.89 iloc

Signature

```
DataFrame iloc(self, std::int64_t row) const
```

Parameters

`row` : `std::int64_t` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- DataFrame iloc(self, std::int64_t start, std::int64_t stop) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.iloc(1);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.90 iloc

Signature

```
DataFrame iloc(self, std::int64_t start, std::int64_t stop) const
```

Parameters

start : std::int64_t Inclusive starting position of the slice.

stop : std::int64_t Exclusive ending position of the slice.

Returns

DataFrame Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- DataFrame iloc(self, std::int64_t row) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.iloc(0, 2);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.91 info

Signature

```
void info(self, const display::DisplayOptions& options =
```

Parameters

`options` : `const display::DisplayOptions&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

See also

- `void info(self, std::ostream& os, const display::DisplayOptions& options =`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.info();
```

Output

```
rows: 3
features: 3
numeric: id, sales
note: city
```

5.1.92 info

Signature

```
void info(self, std::ostream& os, const display::DisplayOptions& options =
```

Parameters

`os` : `std::ostream&` See the signature for the supported argument form.

`options` : `const display::DisplayOptions&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

See also

- `void info(self, const display::DisplayOptions& options =`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.info();
```

Output

```
rows: 3
features: 3
numeric: id, sales
note: city
```

5.1.93 `info_string`

Signature

```
std::string info_string(self, const display::DisplayOptions& options =
```

Parameters

`options` : `const display::DisplayOptions&` See the signature for the supported argument form.

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.info_string();
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.94 insert

Signature

```
DataFrame insert(self, std::int64_t feature_index, std::string name, const Thread&␣
↪feature) const
```

Parameters

`feature_index` : `std::int64_t` See the signature for the supported argument form.

`name` : `std::string` See the signature for the supported argument form.

`feature` : `const Thread&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Inserts a new feature at the requested position and shifts the later features to the right.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.insert(1, "profit", pluss::table::Thread(pluss::make_series({40.0, 35.0,␣
↪30.0})));
```

Output

```
id  sales  city    profit
1   100.0  Accra   40.0
2   120.0  Tema    35.0
3    90.0  Kumasi  30.0
```

5.1.95 isna

Signature

```
DataFrame isna(self, std::initializer_list<std::string_view> features =
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.isna({"sales"});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.96 isnull

Signature

```
DataFrame isnull(self, std::initializer_list<std::string_view> features =
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.isnull({"sales"});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.97 join

Signature

```
DataFrame join(self, const DataFrame& other, std::string collision_suffix = "_right")␣
↪const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

`collision_suffix` : `std::string` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Adds compatible features from another frame, aligning rows by the shared case axis.

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
```

(continues on next page)

(continued from previous page)

```
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.join(right);
```

Output

```
id  sales  cost
1   100.0  60.0
2   120.0  80.0
3    90.0  55.0
```

5.1.98 kindelize

Signature

```
pluss::kindle::Catalog kindelize(self) const
```

Parameters

None

Returns

`pluss::kindle::Catalog` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

See also

- `pluss::kindle::Catalog kindelize(self, const pluss::kindle::KindelizePolicy& policy) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.kindelize();
```

5.1.99 kindelize

Signature

```
pluss::kindle::Catalog kindelize(self, const pluss::kindle::KindelizePolicy& policy)␣
↪const
```

Parameters

`policy` : `const pluss::kindle::KindelizePolicy&` See the signature for the supported argument form.

Returns

`pluss::kindle::Catalog` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

See also

- `pluss::kindle::Catalog kindelize(self) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.kindelize();
```

5.1.100 `le`

Signature

```
DataFrame le(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame le(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
```

(continues on next page)

(continued from previous page)

```
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.le(right);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.101 le

Signature

```
DataFrame le(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame le(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.le(10);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.102 load

Signature

```
static DataFrame load(std::string_view source_type, std::string_view filepath)
```

Parameters

`source_type` : `std::string_view` Storage format selector such as `"csv"`, `"xlsx"`, `"json"`, or `"parquet"`.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load(std::string_view source_type, std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, char sep, std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols =`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, char sep, std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines = pluss::loader::BadLinePolicy::Error)`

Examples

```
auto out = pluss::table::DataFrame::load("csv", "path/to/data.csv");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.103 load

Signature

```
static DataFrame load(std::string_view source_type, std::string_view filepath, char sep,␣
↪std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols =
```

Parameters

`source_type` : `std::string_view` Storage format selector such as `"csv"`, `"xlsx"`, `"json"`, or `"parquet"`.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`sep` : `char` Column separator used for delimited text files such as CSV.

`nrows` : `std::optional<std::size_t>` See the signature for the supported argument form.

`usecols` : `std::vector<std::string>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load(std::string_view source_type, std::string_view filepath)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, char sep, std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines = pluss::loader::BadLinePolicy::Error)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", ',', 16, std::vector
↪<std::string>{"Agency Name"}, std::nullopt);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.104 load

Signature

```
static DataFrame load(std::string_view source_type, std::string_view filepath, char sep,␣
↪std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols,␣
↪std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_
↪bad_lines = pluss::loader::BadLinePolicy::Error)
```

Parameters

`source_type` : `std::string_view` Storage format selector such as `"csv"`, `"xlsx"`, `"json"`, or `"parquet"`.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`sep` : `char` Column separator used for delimited text files such as CSV.

`nrows` : `std::optional<std::size_t>` See the signature for the supported argument form.

`usecols` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`case_col` : `std::optional<std::string>` See the signature for the supported argument form.

`on_bad_lines` : `pluss::loader::BadLinePolicy` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load(std::string_view source_type, std::string_view filepath)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, char sep, std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols =`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", ',', 16, std::vector
↪<std::string>{"Agency Name"}, std::nullopt);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.105 load

Signature

```
static DataFrame load(std::string_view source_type, std::string_view filepath, const␣
↪pluss::loader::Config& config)
```

Parameters

`source_type` : `std::string_view` Storage format selector such as `"csv"`, `"xlsx"`, `"json"`, or `"parquet"`.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load(std::string_view source_type, std::string_view filepath)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, char sep, std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols =`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, char sep, std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines = pluss::loader::BadLinePolicy::Error)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.106 load

Signature

```
static DataFrame load(std::string_view source_type, std::string_view filepath, const␣
↪pluss::loader::ReadCsvOptions& options)
```

Parameters

`source_type` : `std::string_view` Storage format selector such as `"csv"`, `"xlsx"`, `"json"`, or `"parquet"`.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`options` : `const pluss::loader::ReadCsvOptions&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load(std::string_view source_type, std::string_view filepath)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, char sep, std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols =`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, char sep, std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines = pluss::loader::BadLinePolicy::Error)`

Examples

```
pluss::loader::ReadCsvOptions options;
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", options);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.107 load

Signature

```
static DataFrame load(std::string_view source_type, std::string_view filepath,␣
↪std::initializer_list<pluss::loader::ConfigEntry> config_entries)
```

Parameters

`source_type` : `std::string_view` Storage format selector such as `"csv"`, `"xlsx"`, `"json"`, or `"parquet"`.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config_entries` : `std::initializer_list<pluss::loader::ConfigEntry>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load(std::string_view source_type, std::string_view filepath)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, char sep, std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols =`
- `static DataFrame load(std::string_view source_type, std::string_view filepath, char sep, std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines = pluss::loader::BadLinePolicy::Error)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.108 load_csv

Signature

```
static DataFrame load_csv(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`
- `static DataFrame load_csv(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_csv(std::string_view filepath, std::initializer_list<pluss::loader::ConfigEnt config_entries)`
- `static DataFrame load_csv(std::string_view filepath, std::string_view header, std::string_view case_feature = "none", std::string_view engine = "auto", std::optional<std::size_t> ncases = std::nullopt)`
- `static DataFrame load_csv(std::string_view filepath, std::string_view header, std::size_t ncases)`
- `static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols =`
- `static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines = pluss::loader::BadLinePolicy::Error)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.109 load_csv

Signature

```
static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t>
↪ nrows = std::nullopt, std::vector<std::string> usecols =
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`sep` : `char` Column separator used for delimited text files such as CSV.

`nrows` : `std::optional<std::size_t>` See the signature for the supported argument form.

`usecols` : `std::vector<std::string>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_csv(std::string_view filepath)`
- `static DataFrame load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`
- `static DataFrame load_csv(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_csv(std::string_view filepath, std::initializer_list<pluss::loader::ConfigEnt config_entries)`
- `static DataFrame load_csv(std::string_view filepath, std::string_view header, std::string_view case_feature = "none", std::string_view engine = "auto", std::optional<std::size_t> ncases = std::nullopt)`
- `static DataFrame load_csv(std::string_view filepath, std::string_view header, std::size_t ncases)`

- static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines = pluss::loader::BadLinePolicy::Error)

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", ',', 16, std::vector
↪<std::string>{"Agency Name"}, std::nullopt);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.110 load_csv

Signature

```
static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t>
↪ nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string>␣
↪case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines =␣
↪pluss::loader::BadLinePolicy::Error)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`sep` : `char` Column separator used for delimited text files such as CSV.

`nrows` : `std::optional<std::size_t>` See the signature for the supported argument form.

`usecols` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`case_col` : `std::optional<std::string>` See the signature for the supported argument form.

`on_bad_lines` : `pluss::loader::BadLinePolicy` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- static DataFrame load_csv(std::string_view filepath)
- static DataFrame load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions& options)
- static DataFrame load_csv(std::string_view filepath, const pluss::loader::Config& config)

- static DataFrame load_csv(std::string_view filepath, std::initializer_list<pluss::loader::ConfigEnt
  config_entries)
- static DataFrame load_csv(std::string_view filepath, std::string_view header,
  std::string_view case_feature = "none", std::string_view engine = "auto",
  std::optional<std::size_t> ncases = std::nullopt)
- static DataFrame load_csv(std::string_view filepath, std::string_view header,
  std::size_t ncases)
- static DataFrame load_csv(std::string_view filepath, char sep,
  std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols
  =

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", ',', 16, std::vector
↪<std::string>{"Agency Name"}, std::nullopt);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.111 load_csv

Signature

```
static DataFrame load_csv(std::string_view filepath, const pluss::loader::Config& config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- static DataFrame load_csv(std::string_view filepath)
- static DataFrame load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions&
  options)
- static DataFrame load_csv(std::string_view filepath, std::initializer_list<pluss::loader::ConfigEnt
  config_entries)

- static DataFrame load_csv(std::string_view filepath, std::string_view header, std::string_view case_feature = "none", std::string_view engine = "auto", std::optional<std::size_t> ncases = std::nullopt)
- static DataFrame load_csv(std::string_view filepath, std::string_view header, std::size_t ncases)
- static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols =
- static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines = pluss::loader::BadLinePolicy::Error)

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.112 load_csv

Signature

```
static DataFrame load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions&
↪ options)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`options` : `const pluss::loader::ReadCsvOptions&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- static DataFrame load_csv(std::string_view filepath)
- static DataFrame load_csv(std::string_view filepath, const pluss::loader::Config& config)

- static DataFrame load_csv(std::string_view filepath, std::initializer_list<pluss::loader::ConfigEnt
  config_entries)
- static DataFrame load_csv(std::string_view filepath, std::string_view header,
  std::string_view case_feature = "none", std::string_view engine = "auto",
  std::optional<std::size_t> ncases = std::nullopt)
- static DataFrame load_csv(std::string_view filepath, std::string_view header,
  std::size_t ncases)
- static DataFrame load_csv(std::string_view filepath, char sep,
  std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols
  =
- static DataFrame load_csv(std::string_view filepath, char sep,
  std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols,
  std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy
  on_bad_lines = pluss::loader::BadLinePolicy::Error)

Examples

```
pluss::loader::ReadCsvOptions options;
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", options);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.113 load_csv

Signature

```
static DataFrame load_csv(std::string_view filepath, std::initializer_list
↪<pluss::loader::ConfigEntry> config_entries)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config_entries` : `std::initializer_list<pluss::loader::ConfigEntry>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- static DataFrame load_csv(std::string_view filepath)
- static DataFrame load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions& options)
- static DataFrame load_csv(std::string_view filepath, const pluss::loader::Config& config)
- static DataFrame load_csv(std::string_view filepath, std::string_view header, std::string_view case_feature = "none", std::string_view engine = "auto", std::optional<std::size_t> ncases = std::nullopt)
- static DataFrame load_csv(std::string_view filepath, std::string_view header, std::size_t ncases)
- static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols =
- static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines = pluss::loader::BadLinePolicy::Error)

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.114 load_csv

Signature

```
static DataFrame load_csv(std::string_view filepath, std::string_view header, std::size_
↪t ncases)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`header` : `std::string_view` Controls whether feature names are written to, or expected from, the file header row.

`ncases` : `std::size_t` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_csv(std::string_view filepath)`
- `static DataFrame load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`
- `static DataFrame load_csv(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_csv(std::string_view filepath, std::initializer_list<pluss::loader::ConfigEnt`
  `config_entries)`
- `static DataFrame load_csv(std::string_view filepath, std::string_view header, std::string_view case_feature = "none", std::string_view engine = "auto", std::optional<std::size_t> ncases = std::nullopt)`
- `static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols =`
- `static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines = pluss::loader::BadLinePolicy::Error)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.115 load_csv

Signature

```
static DataFrame load_csv(std::string_view filepath, std::string_view header,␣
↪std::string_view case_feature = "none", std::string_view engine = "auto", std::optional
↪<std::size_t> ncases = std::nullopt)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`header` : `std::string_view` Controls whether feature names are written to, or expected from, the file header row.

`case_feature` : `std::string_view` See the signature for the supported argument form.

`engine` : `std::string_view` See the signature for the supported argument form.

`ncases` : `std::optional<std::size_t>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_csv(std::string_view filepath)`
- `static DataFrame load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`
- `static DataFrame load_csv(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_csv(std::string_view filepath, std::initializer_list<pluss::loader::ConfigEnt config_entries)`
- `static DataFrame load_csv(std::string_view filepath, std::string_view header, std::size_t ncases)`
- `static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t> nrows = std::nullopt, std::vector<std::string> usecols =`
- `static DataFrame load_csv(std::string_view filepath, char sep, std::optional<std::size_t> nrows, std::initializer_list<std::string_view> usecols, std::optional<std::string> case_col = std::nullopt, pluss::loader::BadLinePolicy on_bad_lines = pluss::loader::BadLinePolicy::Error)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.116 load_excel

Signature

```
static DataFrame load_excel(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_excel(std::string_view filepath, std::initializer_list<pluss::loader::ConfigE config_entries)`
- `static DataFrame load_excel(std::string_view filepath, std::string_view sheet_name, bool header = true)`
- `static DataFrame load_excel(std::string_view filepath, std::int64_t sheet_index, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::nullptr_t, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::string>& sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::string_view> sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::int64_t>& sheet_indices, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::int64_t> sheet_indices, bool header = true)`

Examples

```
auto out = pluss::table::DataFrame::load_excel("path/to/data.xlsx");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.117 load_excel

Signature

```
static DataFrame load_excel(std::string_view filepath, const pluss::loader::Config&␣
↪config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_excel(std::string_view filepath)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)`
- `static DataFrame load_excel(std::string_view filepath, std::initializer_list<pluss::loader::ConfigE config_entries)`
- `static DataFrame load_excel(std::string_view filepath, std::string_view sheet_name, bool header = true)`
- `static DataFrame load_excel(std::string_view filepath, std::int64_t sheet_index, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::nullptr_t, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::string>& sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::string_view> sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::int64_t>& sheet_indices, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::int64_t> sheet_indices, bool header = true)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.118 load_excel

Signature

```
static DataFrame load_excel(std::string_view filepath, const␣
↪pluss::loader::ReadExcelOptions& options)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`options` : `const pluss::loader::ReadExcelOptions&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_excel(std::string_view filepath)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_excel(std::string_view filepath, std::initializer_list<pluss::loader::ConfigE config_entries)`
- `static DataFrame load_excel(std::string_view filepath, std::string_view sheet_name, bool header = true)`
- `static DataFrame load_excel(std::string_view filepath, std::int64_t sheet_index, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::nullptr_t, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::string>& sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::string_view> sheet_names, bool header = true)`

- static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::int64_t>& sheet_indices, bool header = true)
- static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::int64_t> sheet_indices, bool header = true)

Examples

```
pluss::loader::ReadExcelOptions options;
auto out = pluss::table::DataFrame::load_excel("path/to/data.xlsx", options);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.119 load_excel

Signature

```
static DataFrame load_excel(std::string_view filepath, std::initializer_list
↪<pluss::loader::ConfigEntry> config_entries)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config_entries` : `std::initializer_list<pluss::loader::ConfigEntry>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- static DataFrame load_excel(std::string_view filepath)
- static DataFrame load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)
- static DataFrame load_excel(std::string_view filepath, const pluss::loader::Config& config)
- static DataFrame load_excel(std::string_view filepath, std::string_view sheet_name, bool header = true)
- static DataFrame load_excel(std::string_view filepath, std::int64_t sheet_index, bool header = true)

- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::nullptr_t, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::string>& sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::string_view> sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::int64_t>& sheet_indices, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::int64_t> sheet_indices, bool header = true)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.120 load_excel

Signature

```
static DataFrame load_excel(std::string_view filepath, std::int64_t sheet_index, bool␣
↪header = true)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`sheet_index` : `std::int64_t` Zero-based worksheet position inside an Excel workbook.

`header` : `bool` Controls whether feature names are written to, or expected from, the file header row.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_excel(std::string_view filepath)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)`

- static DataFrame load_excel(std::string_view filepath, const pluss::loader::Config& config)
- static DataFrame load_excel(std::string_view filepath, std::initializer_list<pluss::loader::ConfigE config_entries)
- static DataFrame load_excel(std::string_view filepath, std::string_view sheet_name, bool header = true)
- static pluss::loader::LoadResult load_excel(std::string_view filepath, std::nullptr_t, bool header = true)
- static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::string>& sheet_names, bool header = true)
- static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::string_view> sheet_names, bool header = true)
- static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::int64_t>& sheet_indices, bool header = true)
- static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::int64_t> sheet_indices, bool header = true)

Examples

```
auto out = pluss::table::DataFrame::load_excel("path/to/data.xlsx", 0, true);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.121 load_excel

Signature

```
static DataFrame load_excel(std::string_view filepath, std::string_view sheet_name, bool␣
↪header = true)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`sheet_name` : `std::string_view` Worksheet name to read from or write to inside an Excel workbook.

`header` : `bool` Controls whether feature names are written to, or expected from, the file header row.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_excel(std::string_view filepath)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_excel(std::string_view filepath, std::initializer_list<pluss::loader::ConfigE config_entries)`
- `static DataFrame load_excel(std::string_view filepath, std::int64_t sheet_index, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::nullptr_t, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::string>& sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::string_view> sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::int64_t>& sheet_indices, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::int64_t> sheet_indices, bool header = true)`

Examples

```
auto out = pluss::table::DataFrame::load_excel("path/to/data.xlsx", "Sheet1", true);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.122 load_excel

Signature

```
static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector
↪<std::int64_t>& sheet_indices, bool header = true)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`sheet_indices` : `const std::vector<std::int64_t>&` See the signature for the supported argument form.

header : bool Controls whether feature names are written to, or expected from, the file header row.

Returns

pluss::loader::LoadResult Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- static DataFrame load_excel(std::string_view filepath)
- static DataFrame load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)
- static DataFrame load_excel(std::string_view filepath, const pluss::loader::Config& config)
- static DataFrame load_excel(std::string_view filepath, std::initializer_list<pluss::loader::ConfigE config_entries)
- static DataFrame load_excel(std::string_view filepath, std::string_view sheet_name, bool header = true)
- static DataFrame load_excel(std::string_view filepath, std::int64_t sheet_index, bool header = true)
- static pluss::loader::LoadResult load_excel(std::string_view filepath, std::nullptr_t, bool header = true)
- static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::string>& sheet_names, bool header = true)
- static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::string_view> sheet_names, bool header = true)
- static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::int64_t> sheet_indices, bool header = true)

Examples

```
auto out = pluss::table::DataFrame::load_excel("path/to/data.xlsx");
```

5.1.123 load_excel

Signature

```
static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector
↪<std::string>& sheet_names, bool header = true)
```

Parameters

filepath : std::string_view File location to read from or write to. Use a neutral project path such as path/to/data.csv.

sheet_names : const std::vector<std::string>& See the signature for the supported argument form.

header : bool Controls whether feature names are written to, or expected from, the file header row.

Returns

`pluss::loader::LoadResult` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_excel(std::string_view filepath)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_excel(std::string_view filepath, std::initializer_list<pluss::loader::ConfigE config_entries)`
- `static DataFrame load_excel(std::string_view filepath, std::string_view sheet_name, bool header = true)`
- `static DataFrame load_excel(std::string_view filepath, std::int64_t sheet_index, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::nullptr_t, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::string_view> sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::int64_t>& sheet_indices, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::int64_t> sheet_indices, bool header = true)`

Examples

```
auto out = pluss::table::DataFrame::load_excel("path/to/data.xlsx", "Sheet1", true);
```

5.1.124 load_excel

Signature

```
static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_
↪list<std::int64_t> sheet_indices, bool header = true)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`sheet_indices` : `std::initializer_list<std::int64_t>` See the signature for the supported argument form.

`header` : `bool` Controls whether feature names are written to, or expected from, the file header row.

Returns

`pluss::loader::LoadResult` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_excel(std::string_view filepath)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_excel(std::string_view filepath, std::initializer_list<pluss::loader::ConfigE config_entries)`
- `static DataFrame load_excel(std::string_view filepath, std::string_view sheet_name, bool header = true)`
- `static DataFrame load_excel(std::string_view filepath, std::int64_t sheet_index, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::nullptr_t, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::string>& sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::string_view> sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::int64_t>& sheet_indices, bool header = true)`

Examples

```
auto out = pluss::table::DataFrame::load_excel("path/to/data.xlsx");
```

5.1.125 load_excel

Signature

```
static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_
↪list<std::string_view> sheet_names, bool header = true)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`sheet_names` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`header` : `bool` Controls whether feature names are written to, or expected from, the file header row.

Returns

`pluss::loader::LoadResult` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_excel(std::string_view filepath)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_excel(std::string_view filepath, std::initializer_list<pluss::loader::ConfigE config_entries)`
- `static DataFrame load_excel(std::string_view filepath, std::string_view sheet_name, bool header = true)`
- `static DataFrame load_excel(std::string_view filepath, std::int64_t sheet_index, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::nullptr_t, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::string>& sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::int64_t>& sheet_indices, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::int64_t> sheet_indices, bool header = true)`

Examples

```
auto out = pluss::table::DataFrame::load_excel("path/to/data.xlsx", "Sheet1", true);
```

5.1.126 load_excel

Signature

```
static pluss::loader::LoadResult load_excel(std::string_view filepath, std::nullptr_t,␣
↪bool header = true)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`arg2` : `std::nullptr_t` See the signature for the supported argument form.

`header` : `bool` Controls whether feature names are written to, or expected from, the file header row.

Returns

`pluss::loader::LoadResult` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_excel(std::string_view filepath)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)`
- `static DataFrame load_excel(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_excel(std::string_view filepath, std::initializer_list<pluss::loader::ConfigE config_entries)`
- `static DataFrame load_excel(std::string_view filepath, std::string_view sheet_name, bool header = true)`
- `static DataFrame load_excel(std::string_view filepath, std::int64_t sheet_index, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::string>& sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::string_view> sheet_names, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, const std::vector<std::int64_t>& sheet_indices, bool header = true)`
- `static pluss::loader::LoadResult load_excel(std::string_view filepath, std::initializer_list<std::int64_t> sheet_indices, bool header = true)`

Examples

```
auto out = pluss::table::DataFrame::load_excel("path/to/data.xlsx", nullptr, true);
```

5.1.127 load_json

Signature

```
static DataFrame load_json(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_json(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_json(std::string_view filepath, std::initializer_list<pluss::loader::ConfigEr config_entries)`

Examples

```
auto out = pluss::table::DataFrame::load_json("path/to/data.json");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.128 load_json

Signature

```
static DataFrame load_json(std::string_view filepath, const pluss::loader::Config&␣
↪config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_json(std::string_view filepath)`
- `static DataFrame load_json(std::string_view filepath, std::initializer_list<pluss::loader::ConfigEr config_entries)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.129 load_json

Signature

```
static DataFrame load_json(std::string_view filepath, std::initializer_list
↪<pluss::loader::ConfigEntry> config_entries)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config_entries` : `std::initializer_list<pluss::loader::ConfigEntry>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_json(std::string_view filepath)`
- `static DataFrame load_json(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.130 load_parquet

Signature

```
static DataFrame load_parquet(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_parquet(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_parquet(std::string_view filepath, std::initializer_list<pluss::loader::Confi config_entries)`

Examples

```
auto out = pluss::table::DataFrame::load_parquet("path/to/data.parquet");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.131 load_parquet

Signature

```
static DataFrame load_parquet(std::string_view filepath, const pluss::loader::Config&␣
↪config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- static DataFrame load_parquet(std::string_view filepath)
- static DataFrame load_parquet(std::string_view filepath, std::initializer_list<pluss::loader::Confi
  config_entries)

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.132 load_parquet

Signature

```
static DataFrame load_parquet(std::string_view filepath, std::initializer_list
↪<pluss::loader::ConfigEntry> config_entries)
```

Parameters

filepath : std::string_view File location to read from or write to. Use a neutral project path such as path/to/data.csv.

config_entries : std::initializer_list<pluss::loader::ConfigEntry> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- static DataFrame load_parquet(std::string_view filepath)
- static DataFrame load_parquet(std::string_view filepath, const
  pluss::loader::Config& config)

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.133 load_txt

Signature

```
static DataFrame load_txt(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_txt(std::string_view filepath, const pluss::loader::Config& config)`
- `static DataFrame load_txt(std::string_view filepath, std::initializer_list<pluss::loader::ConfigEnt config_entries)`

Examples

```
auto out = pluss::table::DataFrame::load_txt("path/to/data.txt");
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.134 load_txt

Signature

```
static DataFrame load_txt(std::string_view filepath, const pluss::loader::Config& config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_txt(std::string_view filepath)`
- `static DataFrame load_txt(std::string_view filepath, std::initializer_list<pluss::loader::ConfigEnt config_entries)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.135 load_txt

Signature

```
static DataFrame load_txt(std::string_view filepath, std::initializer_list
↪<pluss::loader::ConfigEntry> config_entries)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config_entries` : `std::initializer_list<pluss::loader::ConfigEntry>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static DataFrame load_txt(std::string_view filepath)`
- `static DataFrame load_txt(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::table::DataFrame::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.136 `lt`

Signature

```
DataFrame lt(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame lt(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
```

(continues on next page)

(continued from previous page)

```
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.lt(right);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.137 lt

Signature

```
DataFrame lt(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame lt(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.lt(10);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.138 max

Signature

```
DataFrame max(self, bool render = true) const
```

Parameters

render : bool See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Computes per-feature maxima for the selected numeric features.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.max(false);
```

Output

```
feature  value
sales    310.0
```

5.1.139 mean

Signature

```
DataFrame mean(self, bool render = true) const
```

Parameters

render : bool See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Computes per-feature means for the selected numeric features.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.mean(false);
```

Output

```
feature  value
sales    310.0
```

5.1.140 mean_by

Signature

```
DataFrame mean_by(self, std::string_view group_feature, std::string_view value_feature,␣
↪std::int64_t top_n = 0, std::int64_t min_count = 1, bool dropna_group = true, bool␣
↪render = true) const
```

Parameters

`group_feature` : `std::string_view` See the signature for the supported argument form.

`value_feature` : `std::string_view` See the signature for the supported argument form.

`top_n` : `std::int64_t` See the signature for the supported argument form.

`min_count` : `std::int64_t` See the signature for the supported argument form.

`dropna_group` : `bool` See the signature for the supported argument form.

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Groups by one feature and returns the mean of another feature within each group.

Examples

```
auto df = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Accra", "Tema", "Tema"}))},
    {"product", pluss::table::Thread(pluss::make_note({"A", "B", "A", "B"}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0, 150.0}))},
});

auto out = df.mean_by("city", "sales", 3, 1, true, false);
```

Output

```
city    sales_mean
Accra   110.0
Tema    120.0
```

5.1.141 min

Signature

```
DataFrame min(self, bool render = true) const
```

Parameters

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Computes per-feature minima for the selected numeric features.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.min(false);
```

Output

```
feature  value
sales    310.0
```

5.1.142 mod

Signature

```
DataFrame mod(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame mod(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.mod(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.143 mod

Signature

```
DataFrame mod(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- DataFrame mod(self, const DataFrame& other) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.mod(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.144 mul

Signature

```
DataFrame mul(self, const DataFrame& other) const
```

Parameters

other : const DataFrame& See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- DataFrame mul(self, scalar other) const

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});
```

(continues on next page)

(continued from previous page)

```
auto out = left.mul(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.145 mul

Signature

```
DataFrame mul(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame mul(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.mul(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.146 multiply

Signature

```
DataFrame multiply(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame multiply(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.multiply(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.147 multiply

Signature

```
DataFrame multiply(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- DataFrame multiply(self, const DataFrame& other) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.multiply(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.148 ncols

Signature

```
std::int64_t ncols(self) const
```

Parameters

None

Returns

std::int64_t Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
```

(continues on next page)

(continued from previous page)

```
auto out = df.ncols();
```

Output

```
3
```

5.1.149 ne

Signature

```
DataFrame ne(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame ne(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.ne(right);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.150 ne

Signature

```
DataFrame ne(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `DataFrame ne(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.ne(10);
```

Output

```
id  sales
1   true
2   true
3   false
```

5.1.151 nfeatures

Signature

```
std::int64_t nfeatures(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.nfeatures();
```

Output

```
3
```

5.1.152 note_features

Signature

```
DataFrame note_features(self) const
```

Parameters

None

Returns

`DataFrame` Value produced by this call.

Notes

Returns only the note-backed features.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.note_features();
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.153 notna

Signature

```
DataFrame notna(self, std::initializer_list<std::string_view> features =
```

Parameters

features : std::initializer_list<std::string_view> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.notna({"sales"});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.154 notnull

Signature

```
DataFrame notnull(self, std::initializer_list<std::string_view> features =
```

Parameters

features : std::initializer_list<std::string_view> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.notnull({"sales"});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.155 nrows

Signature

```
std::int64_t nrows(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.nrows();
```

Output

```
3
```

5.1.156 nunique

Signature

```
DataFrame nunique(self, bool render = true) const
```

Parameters

render : bool See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Counts distinct values for each selected feature.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.nunique(false);
```

Output

```
feature  value
sales    310.0
```

5.1.157 pivot

Signature

```
DataFrame pivot(self, std::string_view case_feature, std::string_view feature_feature,␣
↪std::string_view value_feature, bool dropna_keys = true, bool render = true) const
```

Parameters

case_feature : std::string_view See the signature for the supported argument form.

feature_feature : std::string_view See the signature for the supported argument form.

value_feature : std::string_view See the signature for the supported argument form.

dropna_keys : bool See the signature for the supported argument form.

render : bool See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Reshapes long-form rows into a wider table indexed by one feature and expanded by another.

Examples

```
auto df = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Accra", "Tema", "Tema"}))},
    {"product", pluss::table::Thread(pluss::make_note({"A", "B", "A", "B"}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0, 150.0}))},
});

auto out = df.pivot("city", "product", "sales", true, false);
```

Output

```
city   A      B
Accra  100.0  120.0
Tema    90.0  150.0
```

5.1.158 `pivot_table`

Signature

```
DataFrame pivot_table(self, std::string_view case_feature, std::string_view feature_
↪feature, std::string_view value_feature, GroupOp op = GroupOp::Mean, bool dropna_keys␣
↪= true, bool render = true) const
```

Parameters

`case_feature` : `std::string_view` See the signature for the supported argument form.

`feature_feature` : `std::string_view` See the signature for the supported argument form.

`value_feature` : `std::string_view` See the signature for the supported argument form.

`op` : `GroupOp` See the signature for the supported argument form.

`dropna_keys` : `bool` See the signature for the supported argument form.

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Builds a pivoted summary table using an aggregation function when multiple rows map to the same cell.

Examples

```
auto df = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Accra", "Tema", "Tema"}))},
    {"product", pluss::table::Thread(pluss::make_note({"A", "B", "A", "B"}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0, 150.0}))},
});

auto out = df.pivot_table("city", "product", "sales",␣
↪pluss::table::DataFrame::GroupOp::Mean, true, false);
```

Output

```
city   A      B
Accra  100.0  120.0
Tema    90.0  150.0
```

5.1.159 plot

Signature

```
DataFramePlotAccessor plot(self) const
```

Parameters

None

Returns

`DataFramePlotAccessor` Value produced by this call.

Notes

This opens the plotting accessor for the current data object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto fig = df.plot().line("sales");
```

Output

```
Figure(line/scatter/bar/hist)
```

5.1.160 pow

Signature

```
DataFrame pow(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame pow(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.pow(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.161 pow

Signature

```
DataFrame pow(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame pow(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.pow(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.162 prepare_sql

Signature

```
DataFrameSqlPrepared prepare_sql(self, std::string_view statement) const
```

Parameters

`statement` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrameSqlPrepared` Value produced by this call.

Notes

Use this when the transformation is easier to express as SQL than as a chained sequence of table verbs.

See also

- `DataFrameSqlPrepared prepare_sql(self, std::string_view statement, SqlOptions options) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto stmt = df.prepare_sql("SELECT id, sales FROM self WHERE sales > {min_sales}");
```

Output

```
SQL accessor / prepared statement created
```

5.1.163 prepare_sql

Signature

```
DataFrameSqlPrepared prepare_sql(self, std::string_view statement, SqlOptions options)␣
↪const
```

Parameters

`statement` : `std::string_view` See the signature for the supported argument form.

`options` : `SqlOptions` See the signature for the supported argument form.

Returns

`DataFrameSqlPrepared` Value produced by this call.

Notes

Use this when the transformation is easier to express as SQL than as a chained sequence of table verbs.

See also

- `DataFrameSqlPrepared prepare_sql(self, std::string_view statement) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto stmt = df.prepare_sql("SELECT id, sales FROM self WHERE sales > {min_sales}");
```

Output

```
SQL accessor / prepared statement created
```

5.1.164 query

Signature

```
DataFrame query(self, std::string_view expression) const
```

Parameters

`expression` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Keeps only the rows that satisfy the supplied filter expression or mask-producing query.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.query("sales > 95");
```

Output

```
id  sales  city
1   100.0  Accra
3    90.0  Kumasi
```

5.1.165 radd

Signature

```
DataFrame radd(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.radd(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.166 `rdiv`

Signature

```
DataFrame rdiv(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.rdiv(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.167 reindex_cases

Signature

```
DataFrame reindex_cases(self, const Thread& new_cases) const
```

Parameters

`new_cases` : `const Thread&` Replacement case labels in the exact order you want the rows to follow.

Returns

`DataFrame` Value produced by this call.

Notes

Builds a new case axis from the supplied labels and aligns rows onto that case order.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto cases = pluss::table::Thread(pluss::make_note({"cs1", "cs0", "cs2"}));
auto out = df.reindex_cases(cases);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.168 reindex_like

Signature

```
DataFrame reindex_like(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Realigns this frame so its cases match another frame.

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.reindex_like(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.169 relabel_features

Signature

```
DataFrame relabel_features(self, std::initializer_list<std::string_view> feature_names)␣
↪const
```

Parameters

`feature_names` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Replaces the full feature label set with the supplied names in positional order.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.relabel_features({"revenue", "location", "id_new"});
```

Output

```
id  revenue  city
1   100.0    Accra
2   120.0    Tema
3    90.0    Kumasi
```

5.1.170 rename

Signature

```
DataFrame rename(self, std::string_view old_name, std::string new_name) const
```

Parameters

old_name : std::string_view See the signature for the supported argument form.

new_name : std::string See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Renames one feature without changing its values.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.rename("sales", "revenue");
```

Output

```
id  revenue  city
1   100.0    Accra
2   120.0    Tema
3    90.0    Kumasi
```

5.1.171 rename_

Signature

```
DataFrame& rename_(self, std::string_view old_name, std::string new_name)
```

Parameters

`old_name` : `std::string_view` See the signature for the supported argument form.

`new_name` : `std::string` See the signature for the supported argument form.

Returns

`DataFrame&` Value produced by this call.

Notes

Renames one feature in place without changing its values.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.rename_("sales", "revenue");
```

Output

```
id  revenue  city
1   100.0    Accra
2   120.0    Tema
3    90.0    Kumasi
```

5.1.172 `rename_features`

Signature

```
DataFrame rename_features(self,  std::initializer_list<std::pair<std::string_view,␣
↪std::string_view>> renames) const
```

Parameters

`renames` : `std::initializer_list<std::pair<std::string_view, std::string_view>>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Renames several features in one call.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.rename_features({{"sales", "revenue"}, {"city", "location"}});
```

Output

```
id  revenue  city
1   100.0    Accra
2   120.0    Tema
3    90.0    Kumasi
```

5.1.173 reorder

Signature

```
DataFrame reorder(self, std::initializer_list<std::string_view> names) const
```

Parameters

names : std::initializer_list<std::string_view> Collection of feature, slot, or stream names supplied in positional order.

Returns

DataFrame Value produced by this call.

Notes

Reorders the feature columns without changing any row values.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.reorder({"sales", "id", "city"});
```

Output

```
sales  id  city
100.0  1  Accra
120.0  2  Tema
90.0   3  Kumasi
```

5.1.174 repeated_cases

Signature

```
pluss::Series repeated_cases(self, std::initializer_list<std::string_view> features =
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`pluss::Series` Value produced by this call.

Notes

Returns the rows whose current case labels are duplicates of an earlier row.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.repeated_cases();
```

5.1.175 resample

Signature

```
DataFrame resample(self, std::string_view time_feature, std::initializer_list
↪<std::string_view> value_features, std::string_view freq, std::string_view op = "mean",
↪ std::int64_t step = 1, bool render = true) const
```

Parameters

`time_feature` : `std::string_view` See the signature for the supported argument form.

`value_features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`freq` : `std::string_view` See the signature for the supported argument form.

`op` : `std::string_view` See the signature for the supported argument form.

`step` : `std::int64_t` See the signature for the supported argument form.

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto df = pluss::table::DataFrame({
    {"ts", pluss::table::Thread(pluss::make_timeline({
        "2024-01-01T09:10:00Z",
        "2024-01-01T09:40:00Z",
        "2024-01-01T10:05:00Z",
    }))},
    {"load", pluss::table::Thread(pluss::make_series({10.0, 20.0, 15.0}))},
});

auto out = df.resample("ts", {"load"}, "1h", "mean", 1, false);
```

Output

```
ts                   load
2024-01-01T09:00:00Z  15.0
2024-01-01T10:00:00Z  15.0
```

5.1.176 reset_cases

Signature

```
DataFrame reset_cases(self, std::string case_feature = "case") const
```

Parameters

`case_feature` : `std::string` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Materializes the current case axis as a normal feature, then restores the default positional cases `0..n-1`.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto with_cases = df.set_cases("city", true);
auto out = with_cases.reset_cases("case");
```

Output

```
with_cases.cases():
["Accra", "Tema", "Kumasi"]

out.cases():
[0, 1, 2]

out.head():
id  sales  case
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.177 `rfloordiv`

Signature

```
DataFrame rfloordiv(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.rfloordiv(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.178 rmod

Signature

```
DataFrame rmod(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.rmod(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.179 rmul

Signature

```
DataFrame rmul(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.rmul(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.180 `rolling`

Signature

```
DataFrame rolling(self, std::initializer_list<WindowSpec> specs, bool keep_input = true)␣
↪const
```

Parameters

`specs` : `std::initializer_list<WindowSpec>` See the signature for the supported argument form.

`keep_input` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Computes rolling-window features and returns them as a derived frame.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.rolling({{.output = "sales_roll", .feature = "sales", .op =␣
↪pluss::table::ThreadWindowOp::RollingMean, .window = 2, .min_periods = 1}}, true);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.181 round_time

Signature

```
DataFrame round_time(self, std::initializer_list<std::string_view> features, std::string_
↪view unit) const
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`unit` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto df = pluss::table::DataFrame({
    {"ts", pluss::table::Thread(pluss::make_timeline({
        "2024-01-01T09:10:00Z",
        "2024-01-01T09:40:00Z",
        "2024-01-01T10:05:00Z",
    }))},
    {"load", pluss::table::Thread(pluss::make_series({10.0, 20.0, 15.0}))},
});

auto out = df.round_time({"ts"}, "hour");
```

Output

```
ts
2024-01-01T09:00:00Z
2024-01-01T10:00:00Z
```

5.1.182 rpow

Signature

```
DataFrame rpow(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.rpow(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.183 `rsub`

Signature

```
DataFrame rsub(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
```

(continues on next page)

(continued from previous page)

```
auto out = df.rsub(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.184 rtruediv

Signature

```
DataFrame rtruediv(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.rtruediv(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.185 sample

Signature

```
DataFrame sample(self, std::int64_t n, std::optional<std::uint64_t> random_state =␣
↪std::nullopt) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

`random_state` : `std::optional<std::uint64_t>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Returns a random sample of rows.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.sample(2, 7);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.186 save_as

Signature

```
void save_as(self, std::string_view target_type, std::string_view filepath, const␣
↪pluss::loader::Config& config =
```

Parameters

`target_type` : `std::string_view` See the signature for the supported argument form.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame using the explicitly supplied output format selector rather than a dedicated saver overload.

See also

- void save_as(self, std::string_view target_type, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_as("json", "path/to/output.json");
```

Output

```
saved: out.*
```

5.1.187 save_as

Signature

```
void save_as(self, std::string_view target_type, std::string_view filepath,␣
↪std::initializer_list<pluss::loader::ConfigEntry> config_entries) const
```

Parameters

`target_type` : `std::string_view` See the signature for the supported argument form.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config_entries` : `std::initializer_list<pluss::loader::ConfigEntry>` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame using the explicitly supplied output format selector rather than a dedicated saver overload.

See also

- void save_as(self, std::string_view target_type, std::string_view filepath, const pluss::loader::Config& config =

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
```

(continues on next page)

(continued from previous page)

```
});

df.save_as("json", "path/to/output.json");
```

Output

```
saved: out.*
```

5.1.188 save_csv

Signature

```
void save_csv(self, std::string_view filepath) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to CSV. Set `add_cases=true` when you want the current case axis exported as a regular column so row labels survive the round trip.

See also

- `void save_csv(self, std::string_view filepath, bool add_cases, bool header = true, char sep = ',', std::string na_rep = "NA", std::optional<std::string> case_label = std::nullopt, std::optional<std::string> float_format = std::nullopt, char quotechar = '"', bool scalarquote = true, std::string line_terminator = "\n", char decimal = '.', std::string encoding = "utf-8") const`
- `void save_csv(self, std::string_view filepath, const pluss::loader::WriteCsvOptions& options) const`
- `void save_csv(self, std::string_view filepath, const pluss::loader::Config& config) const`
- `void save_csv(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_csv("path/to/output.csv");
```

Output

```
saved: out.*
```

5.1.189 save_csv

Signature

```
void save_csv(self, std::string_view filepath, bool add_cases, bool header = true, char␣
↪sep = ',', std::string na_rep = "NA", std::optional<std::string> case_label =␣
↪std::nullopt, std::optional<std::string> float_format = std::nullopt, char quotechar =
↪'"', bool scalarquote = true, std::string line_terminator = "\n", char decimal = '.',␣
↪std::string encoding = "utf-8") const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`add_cases` : `bool` When `true`, the current case axis is exported as its own column so row labels can be reconstructed when the file is loaded again.

`header` : `bool` Controls whether feature names are written to, or expected from, the file header row.

`sep` : `char` Column separator used for delimited text files such as CSV.

`arg5` : `'` See the signature for the supported argument form.

`na_rep` : `std::string` String written anywhere a null or missing value must be serialized.

`case_label` : `std::optional<std::string>` Optional column label to use for the exported case axis when `add_cases=true`.

`float_format` : `std::optional<std::string>` Optional numeric formatting string used when floating-point values are written to text output.

`quotechar` : `char` Quote character used when writing delimited text output.

`doublequote` : `bool` When `true`, embedded quote characters are escaped by doubling them in CSV-style output.

`line_terminator` : `std::string` Line ending written between serialized rows in text-based export.

`decimal` : `char` Decimal marker used when formatting floating-point output.

`encoding` : `std::string` Text encoding used when reading or writing text-based files.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to CSV. Set `add_cases=true` when you want the current case axis exported as a regular column so row labels survive the round trip.

See also

- `void save_csv(self, std::string_view filepath) const`
- `void save_csv(self, std::string_view filepath, const pluss::loader::WriteCsvOptions& options) const`

- void save_csv(self, std::string_view filepath, const pluss::loader::Config& config) const
- void save_csv(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_csv("path/to/output.csv");
```

Output

```
saved: out.*
```

5.1.190 save_csv

Signature

```
void save_csv(self, std::string_view filepath, const pluss::loader::Config& config) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to CSV. Set `add_cases=true` when you want the current case axis exported as a regular column so row labels survive the round trip.

See also

- void save_csv(self, std::string_view filepath) const
- void save_csv(self, std::string_view filepath, bool add_cases, bool header = true, char sep = ',', std::string na_rep = "NA", std::optional<std::string> case_label = std::nullopt, std::optional<std::string> float_format = std::nullopt, char quotechar = '"', bool scalarquote = true, std::string line_terminator = "\n", char decimal = '.', std::string encoding = "utf-8") const
- void save_csv(self, std::string_view filepath, const pluss::loader::WriteCsvOptions& options) const
- void save_csv(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_csv("path/to/output.csv");
```

Output

```
saved: out.*
```

5.1.191 save_csv

Signature

```
void save_csv(self, std::string_view filepath, const pluss::loader::WriteCsvOptions&␣
↪options) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`options` : `const pluss::loader::WriteCsvOptions&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to CSV. Set `add_cases=true` when you want the current case axis exported as a regular column so row labels survive the round trip.

See also

- `void save_csv(self, std::string_view filepath) const`
- `void save_csv(self, std::string_view filepath, bool add_cases, bool header = true, char sep = ',', std::string na_rep = "NA", std::optional<std::string> case_label = std::nullopt, std::optional<std::string> float_format = std::nullopt, char quotechar = '"', bool scalarquote = true, std::string line_terminator = "\n", char decimal = '.', std::string encoding = "utf-8") const`
- `void save_csv(self, std::string_view filepath, const pluss::loader::Config& config) const`
- `void save_csv(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_csv("path/to/output.csv");
```

Output

```
saved: out.*
```

5.1.192 save_csv

Signature

```
void save_csv(self, std::string_view filepath, std::initializer_list
↪<pluss::loader::ConfigEntry> config_entries) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config_entries` : `std::initializer_list<pluss::loader::ConfigEntry>` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to CSV. Set `add_cases=true` when you want the current case axis exported as a regular column so row labels survive the round trip.

See also

- `void save_csv(self, std::string_view filepath) const`
- `void save_csv(self, std::string_view filepath, bool add_cases, bool header = true, char sep = ',', std::string na_rep = "NA", std::optional<std::string> case_label = std::nullopt, std::optional<std::string> float_format = std::nullopt, char quotechar = '"', bool scalarquote = true, std::string line_terminator = "\n", char decimal = '.', std::string encoding = "utf-8") const`
- `void save_csv(self, std::string_view filepath, const pluss::loader::WriteCsvOptions& options) const`
- `void save_csv(self, std::string_view filepath, const pluss::loader::Config& config) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_csv("path/to/output.csv");
```

Output

```
saved: out.*
```

5.1.193 save_excel

Signature

```
void save_excel(self, std::string_view filepath) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to an Excel sheet. Set `add_cases=true` when you want the current case axis exported as a regular column.

See also

- `void save_excel(self, std::string_view filepath, std::string sheet_name, bool add_cases = false, bool header = true, std::string na_rep = "NA", std::optional<std::string> case_label = std::nullopt) const`
- `void save_excel(self, std::string_view filepath, const pluss::loader::WriteExcelOptions& options) const`
- `void save_excel(self, std::string_view filepath, const pluss::loader::Config& config) const`
- `void save_excel(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
```

(continues on next page)

(continued from previous page)

```
});

df.save_excel("path/to/output.xlsx");
```

Output

```
saved: out.*
```

5.1.194 save_excel

Signature

```
void save_excel(self, std::string_view filepath, const pluss::loader::Config& config)␣
↪const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to an Excel sheet. Set `add_cases=true` when you want the current case axis exported as a regular column.

See also

- `void save_excel(self, std::string_view filepath) const`
- `void save_excel(self, std::string_view filepath, std::string sheet_name, bool add_cases = false, bool header = true, std::string na_rep = "NA", std::optional<std::string> case_label = std::nullopt) const`
- `void save_excel(self, std::string_view filepath, const pluss::loader::WriteExcelOptions& options) const`
- `void save_excel(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_excel("path/to/output.xlsx");
```

Output

```
saved: out.*
```

5.1.195 save_excel

Signature

```
void save_excel(self, std::string_view filepath, const pluss::loader::WriteExcelOptions&␣
↪options) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`options` : `const pluss::loader::WriteExcelOptions&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to an Excel sheet. Set `add_cases=true` when you want the current case axis exported as a regular column.

See also

- `void save_excel(self, std::string_view filepath) const`
- `void save_excel(self, std::string_view filepath, std::string sheet_name, bool add_cases = false, bool header = true, std::string na_rep = "NA", std::optional<std::string> case_label = std::nullopt) const`
- `void save_excel(self, std::string_view filepath, const pluss::loader::Config& config) const`
- `void save_excel(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_excel("path/to/output.xlsx");
```

Output

```
saved: out.*
```

5.1.196 save_excel

Signature

```
void save_excel(self, std::string_view filepath, std::initializer_list
↪<pluss::loader::ConfigEntry> config_entries) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config_entries` : `std::initializer_list<pluss::loader::ConfigEntry>` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to an Excel sheet. Set `add_cases=true` when you want the current case axis exported as a regular column.

See also

- `void save_excel(self, std::string_view filepath) const`
- `void save_excel(self, std::string_view filepath, std::string sheet_name, bool add_cases = false, bool header = true, std::string na_rep = "NA", std::optional<std::string> case_label = std::nullopt) const`
- `void save_excel(self, std::string_view filepath, const pluss::loader::WriteExcelOptions& options) const`
- `void save_excel(self, std::string_view filepath, const pluss::loader::Config& config) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_excel("path/to/output.xlsx");
```

Output

```
saved: out.*
```

5.1.197 save_excel

Signature

```
void save_excel(self, std::string_view filepath, std::string sheet_name, bool add_cases␣
↪= false, bool header = true, std::string na_rep = "NA", std::optional<std::string>␣
↪case_label = std::nullopt) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`sheet_name` : `std::string` Worksheet name to read from or write to inside an Excel workbook.

`add_cases` : `bool` When `true`, the current case axis is exported as its own column so row labels can be reconstructed when the file is loaded again.

`header` : `bool` Controls whether feature names are written to, or expected from, the file header row.

`na_rep` : `std::string` String written anywhere a null or missing value must be serialized.

`case_label` : `std::optional<std::string>` Optional column label to use for the exported case axis when `add_cases=true`.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to an Excel sheet. Set `add_cases=true` when you want the current case axis exported as a regular column.

See also

- `void save_excel(self, std::string_view filepath) const`
- `void save_excel(self, std::string_view filepath, const pluss::loader::WriteExcelOptions& options) const`
- `void save_excel(self, std::string_view filepath, const pluss::loader::Config& config) const`
- `void save_excel(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_excel("path/to/output.xlsx");
```

Output

```
saved: out.*
```

5.1.198 save_json

Signature

```
void save_json(self, std::string_view filepath) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to JSON using the table export route for later reload or interchange.

See also

- `void save_json(self, std::string_view filepath, const pluss::loader::Config& config) const`
- `void save_json(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_json("path/to/output.json");
```

Output

```
saved: out.*
```

5.1.199 save_json

Signature

```
void save_json(self, std::string_view filepath, const pluss::loader::Config& config)␣
↪const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to JSON using the table export route for later reload or interchange.

See also

- `void save_json(self, std::string_view filepath) const`
- `void save_json(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_json("path/to/output.json");
```

Output

```
saved: out.*
```

5.1.200 save_json

Signature

```
void save_json(self, std::string_view filepath, std::initializer_list
↪<pluss::loader::ConfigEntry> config_entries) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config_entries` : `std::initializer_list<pluss::loader::ConfigEntry>` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to JSON using the table export route for later reload or interchange.

See also

- `void save_json(self, std::string_view filepath) const`
- `void save_json(self, std::string_view filepath, const pluss::loader::Config& config) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_json("path/to/output.json");
```

Output

```
saved: out.*
```

5.1.201 save_parquet

Signature

```
void save_parquet(self, std::string_view filepath) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to Parquet for compact typed storage.

See also

- `void save_parquet(self, std::string_view filepath, const pluss::loader::Config& config) const`
- `void save_parquet(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_parquet("path/to/output.parquet");
```

Output

```
saved: out.*
```

5.1.202 save_parquet

Signature

```
void save_parquet(self, std::string_view filepath, const pluss::loader::Config& config)␣
↪const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to Parquet for compact typed storage.

See also

- `void save_parquet(self, std::string_view filepath) const`
- `void save_parquet(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_parquet("path/to/output.parquet");
```

Output

```
saved: out.*
```

5.1.203 save_parquet

Signature

```
void save_parquet(self, std::string_view filepath, std::initializer_list
↪<pluss::loader::ConfigEntry> config_entries) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config_entries` : `std::initializer_list<pluss::loader::ConfigEntry>` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to Parquet for compact typed storage.

See also

- `void save_parquet(self, std::string_view filepath) const`
- `void save_parquet(self, std::string_view filepath, const pluss::loader::Config& config) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_parquet("path/to/output.parquet");
```

Output

```
saved: out.*
```

5.1.204 save_txt

Signature

```
void save_txt(self, std::string_view filepath) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to a plain-text table preview suitable for inspection or lightweight logging.

See also

- `void save_txt(self, std::string_view filepath, const pluss::loader::Config& config) const`
- `void save_txt(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_txt("path/to/output.txt");
```

Output

```
saved: out.*
```

5.1.205 save_txt

Signature

```
void save_txt(self, std::string_view filepath, const pluss::loader::Config& config) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to a plain-text table preview suitable for inspection or lightweight logging.

See also

- `void save_txt(self, std::string_view filepath) const`
- `void save_txt(self, std::string_view filepath, std::initializer_list<pluss::loader::ConfigEntry> config_entries) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_txt("path/to/output.txt");
```

Output

```
saved: out.*
```

5.1.206 `save_txt`

Signature

```
void save_txt(self, std::string_view filepath, std::initializer_list
↪<pluss::loader::ConfigEntry> config_entries) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config_entries` : `std::initializer_list<pluss::loader::ConfigEntry>` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the frame to a plain-text table preview suitable for inspection or lightweight logging.

See also

- `void save_txt(self, std::string_view filepath) const`
- `void save_txt(self, std::string_view filepath, const pluss::loader::Config& config) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.save_txt("path/to/output.txt");
```

Output

```
saved: out.*
```

5.1.207 series_features

Signature

```
DataFrame series_features(self) const
```

Parameters

None

Returns

DataFrame Value produced by this call.

Notes

Returns only the numeric series-backed features.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.series_features();
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.208 set

Signature

```
LetSlot set(self, std::string_view name)
```

Parameters

name : std::string_view See the signature for the supported argument form.

Returns

LetSlot Value produced by this call.

Notes

Opens an assignment helper so you can write df.set(...) = ... and replace or create features declaratively.

See also

- LetSlots set(self, std::initializer_list<std::string_view> names)

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.set("profit") = pluss::table::Thread(pluss::make_series({40.0, 35.0, 30.0}));
```

5.1.209 set

Signature

```
LetSlots set(self, std::initializer_list<std::string_view> names)
```

Parameters

names : std::initializer_list<std::string_view> Collection of feature, slot, or stream names supplied in positional order.

Returns

LetSlots Value produced by this call.

Notes

Opens an assignment helper so you can write df.set(...) = ... and replace or create features declaratively.

See also

- LetSlot set(self, std::string_view name)

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.set({"profit", "cost"}) = {pluss::table::Thread(pluss::make_series({40.0, 35.0, 30.0}
↪)), pluss::table::Thread(pluss::make_series({60.0, 85.0, 60.0}))};
```

5.1.210 set_axis

Signature

```
DataFrame set_axis(self, std::initializer_list<std::string_view> feature_names) const
```

Parameters

feature_names : std::initializer_list<std::string_view> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Replaces the full feature label set with the supplied names in positional order.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.set_axis({"revenue", "location", "id_new"});
```

Output

```
id  revenue  city
1   100.0    Accra
2   120.0    Tema
3    90.0    Kumasi
```

5.1.211 set_cases

Signature

```
DataFrame set_cases(self, std::string_view feature_name, bool drop_feature = true) const
```

Parameters

`feature_name` : `std::string_view` Name of the target feature to read, rewrite, sort by, or promote to cases.

`drop_feature` : `bool` When `true`, the feature promoted to cases is removed from the ordinary feature columns.

Returns

`DataFrame` Value produced by this call.

Notes

Promotes one feature to become the case axis. With the default `drop_feature=true`, that feature stops being a normal column and becomes the row labels instead.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.set_cases("city");
```

Output

```
df.head():
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi

out.cases():
["Accra", "Tema", "Kumasi"]

out.head():
id  sales
1   100.0
2   120.0
3    90.0
```

5.1.212 set_feature_axis

Signature

```
DataFrame set_feature_axis(self, std::initializer_list<std::string_view> feature_names)␣
↪const
```

Parameters

`feature_names` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Replaces the full feature label set with the supplied names in positional order.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.set_feature_axis({"revenue", "location", "id_new"});
```

Output

```
id  revenue  city
1   100.0    Accra
2   120.0    Tema
3    90.0    Kumasi
```

5.1.213 set_features

Signature

```
DataFrame set_features(self, std::initializer_list<std::string_view> names,␣
↪std::initializer_list<Thread> values) const
```

Parameters

`names` : `std::initializer_list<std::string_view>` Collection of feature, slot, or stream names supplied in positional order.

`values` : `std::initializer_list<Thread>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Adds or replaces one or more features and returns the updated frame.

See also

- DataFrame set_features(self, std::string_view name, const Thread& value) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.set_features(
    {"profit", "cost"},
    {
        pluss::table::Thread(pluss::make_series({40.0, 35.0, 30.0})),
        pluss::table::Thread(pluss::make_series({60.0, 85.0, 60.0})),
    });
```

Output

```
id  sales  city    profit
1   100.0  Accra   40.0
2   120.0  Tema    35.0
3    90.0  Kumasi  30.0
```

5.1.214 set_features

Signature

```
DataFrame set_features(self, std::string_view name, const Thread& value) const
```

Parameters

name : std::string_view See the signature for the supported argument form.

value : const Thread& See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Adds or replaces one or more features and returns the updated frame.

See also

- DataFrame set_features(self, std::initializer_list<std::string_view> names, std::initializer_list<Thread> values) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.set_features("profit", pluss::table::Thread(pluss::make_series({40.0, 35.0,
↪ 30.0})));
```

Output

```
id  sales  city    profit
1   100.0  Accra   40.0
2   120.0  Tema    35.0
3    90.0  Kumasi  30.0
```

5.1.215 set_features_

Signature

```
DataFrame& set_features_(self, std::initializer_list<std::string_view> names,␣
↪std::initializer_list<Thread> values)
```

Parameters

`names` : `std::initializer_list<std::string_view>` Collection of feature, slot, or stream names supplied in positional order.

`values` : `std::initializer_list<Thread>` See the signature for the supported argument form.

Returns

`DataFrame&` Value produced by this call.

Notes

Adds or replaces one or more features in place.

See also

- `DataFrame& set_features_(self, std::string_view name, const Thread& value)`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.set_features_(
    {"profit", "cost"},
```

(continues on next page)

(continued from previous page)

```
    {
        pluss::table::Thread(pluss::make_series({40.0, 35.0, 30.0})),
        pluss::table::Thread(pluss::make_series({60.0, 85.0, 60.0})),
    });
```

Output

```
id  sales  city    profit
1   100.0  Accra   40.0
2   120.0  Tema    35.0
3    90.0  Kumasi  30.0
```

5.1.216 set_features_

Signature

```
DataFrame& set_features_(self, std::string_view name, const Thread& value)
```

Parameters

`name` : `std::string_view` See the signature for the supported argument form.

`value` : `const Thread&` See the signature for the supported argument form.

Returns

`DataFrame&` Value produced by this call.

Notes

Adds or replaces one or more features in place.

See also

- `DataFrame& set_features_(self, std::initializer_list<std::string_view> names, std::initializer_list<Thread> values)`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.set_features_("profit", pluss::table::Thread(pluss::make_series({40.0, 35.0, 30.0})));
```

Output

```
id  sales  city    profit
1   100.0  Accra   40.0
2   120.0  Tema    35.0
3    90.0  Kumasi  30.0
```

5.1.217 shift_time

Signature

```
DataFrame shift_time(self, std::initializer_list<std::string_view> features, int periods,
↪ std::string_view freq) const
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`periods` : `int` See the signature for the supported argument form.

`freq` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto df = pluss::table::DataFrame({
    {"ts", pluss::table::Thread(pluss::make_timeline({
        "2024-01-01T09:10:00Z",
        "2024-01-01T09:40:00Z",
        "2024-01-01T10:05:00Z",
    }))},
    {"load", pluss::table::Thread(pluss::make_series({10.0, 20.0, 15.0}))},
});

auto out = df.shift_time({"ts"}, 1, "hour");
```

Output

```
ts
2024-01-01T09:00:00Z
2024-01-01T10:00:00Z
```

5.1.218 slice

Signature

```
DataFrame slice(self, std::int64_t start, std::int64_t stop) const
```

Parameters

`start` : `std::int64_t` Inclusive starting position of the slice.

`stop` : `std::int64_t` Exclusive ending position of the slice.

Returns

`DataFrame` Value produced by this call.

Notes

Returns a contiguous row slice `[start, stop)` from the frame.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.slice(0, 2);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.219 sort_cases

Signature

```
DataFrame sort_cases(self, bool ascending = true, bool nulls_last = true) const
```

Parameters

`ascending` : `bool` See the signature for the supported argument form.

`nulls_last` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Sorts rows by the current case axis rather than by a data feature.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto with_cases = df.with_cases(pluss::table::Thread(pluss::make_note({"cs2", "cs0", "cs1
```

(continues on next page)

(continued from previous page)

```
↪"}}));
auto out = with_cases.sort_cases(true, true);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.220 sort_values

Signature

```
DataFrame sort_values(self, std::initializer_list<ArrangeSpec> specs) const
```

Parameters

specs : std::initializer_list<ArrangeSpec> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Reorders rows using one or more feature values as sort keys.

See also

- DataFrame sort_values(self, std::initializer_list<std::string_view> features, bool ascending = true, bool nulls_last = true) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.sort_values({{.feature = "sales", .ascending = false}});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.221 sort_values

Signature

```
DataFrame sort_values(self, std::initializer_list<std::string_view> features, bool␣
↪ascending = true, bool nulls_last = true) const
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`ascending` : `bool` See the signature for the supported argument form.

`nulls_last` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Reorders rows using one or more feature values as sort keys.

See also

- `DataFrame sort_values(self, std::initializer_list<ArrangeSpec> specs) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.sort_values({"sales"}, false, true);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.222 sql

Signature

```
DataFrameSqlAccessor sql(self) const
```

Parameters

None

Returns

`DataFrameSqlAccessor` Value produced by this call.

Notes

Use this when the transformation is easier to express as SQL than as a chained sequence of table verbs.

See also

- `DataFrameSqlAccessor sql(self, SqlOptions options) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.sql().execute("SELECT id, sales FROM self WHERE sales > 95");
```

Output

```
SQL accessor / prepared statement created
```

5.1.223 sql

Signature

```
DataFrameSqlAccessor sql(self, SqlOptions options) const
```

Parameters

`options` : `SqlOptions` See the signature for the supported argument form.

Returns

`DataFrameSqlAccessor` Value produced by this call.

Notes

Use this when the transformation is easier to express as SQL than as a chained sequence of table verbs.

See also

- `DataFrameSqlAccessor sql(self) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
```

(continues on next page)

(continued from previous page)

```
});

auto out = df.sql().execute("SELECT id, sales FROM self WHERE sales > 95");
```

Output

```
SQL accessor / prepared statement created
```

5.1.224 std

Signature

```
DataFrame std(self, bool render = true) const
```

Parameters

render : bool See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Computes per-feature standard deviations for the selected numeric features.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.std(false);
```

Output

```
feature  value
sales    310.0
```

5.1.225 stitch_on

Signature

```
DataFrame stitch_on(self, std::initializer_list<std::string_view> left_features, const␣
↪DataFrame& right, std::initializer_list<std::string_view> right_features =
```

Parameters

`left_features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`right` : `const DataFrame&` See the signature for the supported argument form.

`right_features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Matches rows from two frames using key features and appends the matched features from the right-hand frame.

See also

- `DataFrame stitch_on(self, std::string_view left_feature, const DataFrame& right, std::string_view right_feature = "", std::string right_suffix = "_right") const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.stitch_on({"id"}, right, {"id"}, "_right");
```

Output

```
id  sales  cost
1   100.0  60.0
2   120.0  80.0
3    90.0  55.0
```

5.1.226 `stitch_on`

Signature

```
DataFrame stitch_on(self, std::string_view left_feature, const DataFrame& right,␣
↪std::string_view right_feature = "", std::string right_suffix = "_right") const
```

Parameters

`left_feature` : `std::string_view` See the signature for the supported argument form.

`right` : `const DataFrame&` See the signature for the supported argument form.

`right_feature` : `std::string_view` See the signature for the supported argument form.

`right_suffix` : `std::string` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Matches rows from two frames using key features and appends the matched features from the right-hand frame.

See also

- `DataFrame stitch_on(self, std::initializer_list<std::string_view> left_features, const DataFrame& right, std::initializer_list<std::string_view> right_features =`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.stitch_on("id", right, "id", "_right");
```

Output

```
id  sales  cost
1   100.0  60.0
2   120.0  80.0
3    90.0  55.0
```

5.1.227 sub

Signature

```
DataFrame sub(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame sub(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.sub(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.228 sub

Signature

```
DataFrame sub(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame sub(self, const DataFrame& other) const`

Examples

```cpp
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.sub(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.229 subtract

Signature

```cpp
DataFrame subtract(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame subtract(self, scalar other) const`

Examples

```cpp
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.subtract(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.230 subtract

Signature

```
DataFrame subtract(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame subtract(self, const DataFrame& other) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.subtract(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.231 sum

Signature

```
DataFrame sum(self, bool render = true) const
```

Parameters

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Computes per-feature sums for the selected numeric features.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.sum(false);
```

Output

```
feature  value
sales    310.0
```

5.1.232 `tabelize`

Signature

```
static DataFrame tabelize(const pluss::kindle::Catalog& catalog)
```

Parameters

`catalog` : `const pluss::kindle::Catalog&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

See also

- `static DataFrame tabelize(const pluss::kindle::Catalog& catalog, const pluss::kindle::TabelizePolicy& policy)`

Examples

```
using namespace pluss::kindle::literals;
auto catalog = pluss::kindle::Catalog({"sales"_k = pluss::kindle::Stream(pluss::make_
↪series({10.0, 20.0, 30.0}))});
auto out = pluss::table::DataFrame::tabelize(catalog);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.233 tabelize

Signature

```
static DataFrame tabelize(const pluss::kindle::Catalog& catalog, const␣
↪pluss::kindle::TabelizePolicy& policy)
```

Parameters

`catalog` : `const pluss::kindle::Catalog&` See the signature for the supported argument form.

`policy` : `const pluss::kindle::TabelizePolicy&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

See also

- `static DataFrame tabelize(const pluss::kindle::Catalog& catalog)`

Examples

```
using namespace pluss::kindle::literals;
auto catalog = pluss::kindle::Catalog({"sales"_k = pluss::kindle::Stream(pluss::make_
↪series({10.0, 20.0, 30.0}))});
auto out = pluss::table::DataFrame::tabelize(catalog);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.234 tail

Signature

```
DataFrame tail(self, std::int64_t n = 5, bool render = true) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Returns the last `n` rows of the frame.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.tail(2, false);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.235 take

Signature

```
DataFrame take(self, std::span<const std::int64_t> indices) const
```

Parameters

`indices` : `std::span<const std::int64_t>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Returns the rows at the requested integer positions.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

std::vector<std::int64_t> picks{0, 2};
auto out = df.take(picks);
```

Output

```
id  sales  city
1   100.0  Accra
3    90.0  Kumasi
```

5.1.236 tally

Signature

```
DataFrame tally(self, std::string_view feature, std::int64_t top_n = 0, bool dropna =␣
↪true, bool render = true) const
```

Parameters

`feature` : `std::string_view` See the signature for the supported argument form.

`top_n` : `std::int64_t` See the signature for the supported argument form.

`dropna` : `bool` See the signature for the supported argument form.

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Counts how many rows fall into each distinct value of the grouping feature.

Examples

```
auto df = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Accra", "Tema", "Tema"}))},
    {"product", pluss::table::Thread(pluss::make_note({"A", "B", "A", "B"}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0, 150.0}))},
});

auto out = df.tally("city", 3, true, false);
```

Output

```
city    count
Accra   2
Tema    2
```

5.1.237 timeline_features

Signature

```
DataFrame timeline_features(self) const
```

Parameters

None

Returns

DataFrame Value produced by this call.

Notes

Returns only the timeline-backed features.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.timeline_features();
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.238 to_string

Signature

```
std::string to_string(self, const display::DisplayOptions& options =
```

Parameters

options : const display::DisplayOptions& See the signature for the supported argument form.

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.to_string();
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.239 to_utc

Signature

```
DataFrame to_utc(self, std::initializer_list<std::string_view> features) const
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto df = pluss::table::DataFrame({
    {"ts", pluss::table::Thread(pluss::make_timeline({
        "2024-01-01T09:10:00Z",
        "2024-01-01T09:40:00Z",
        "2024-01-01T10:05:00Z",
    }))},
    {"load", pluss::table::Thread(pluss::make_series({10.0, 20.0, 15.0}))},
});
```

(continues on next page)

(continued from previous page)

```
auto out = df.to_utc({"ts"});
```

Output

```
ts
2024-01-01T09:00:00Z
2024-01-01T10:00:00Z
```

5.1.240 top

Signature

```
DataFrame top(self, std::string_view feature, std::int64_t n) const
```

Parameters

`feature` : `std::string_view` See the signature for the supported argument form.

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

Returns

`DataFrame` Value produced by this call.

Notes

Returns the rows with the largest values in the selected feature.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.top("sales", 2);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.241 transform

Signature

```
DataFrame transform(self, const std::function<Thread(const Thread&)>& fn) const
```

Parameters

fn : const std::function<Thread(const Thread&)>& See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Rewrites one feature, several features, or all features by applying a user function to each targeted thread.

See also

- DataFrame transform(self, std::string_view feature, const std::function<Thread(const Thread&)>& fn) const
- DataFrame transform(self, std::initializer_list<TransformSpec> specs) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.transform([](const pluss::table::Thread& thread) { return thread.kind() ==␣
↪pluss::table::ThreadKind::Series ? thread.clip(0.0, 110.0) : thread; });
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.242 transform

Signature

```
DataFrame transform(self, std::initializer_list<TransformSpec> specs) const
```

Parameters

specs : std::initializer_list<TransformSpec> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Rewrites one feature, several features, or all features by applying a user function to each targeted thread.

See also

- `DataFrame transform(self, const std::function<Thread(const Thread&)>& fn) const`
- `DataFrame transform(self, std::string_view feature, const std::function<Thread(const Thread&)>& fn) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.transform({{.feature = "sales", .expr = [](const pluss::table::Thread&␣
↪thread) { return thread.clip(0.0, 110.0); }}});
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.243 `transform`

Signature

```
DataFrame transform(self, std::string_view feature, const std::function<Thread(const␣
↪Thread&)>& fn) const
```

Parameters

`feature` : `std::string_view` See the signature for the supported argument form.

`fn` : `const std::function<Thread(const Thread&)>&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Rewrites one feature, several features, or all features by applying a user function to each targeted thread.

See also

- `DataFrame transform(self, const std::function<Thread(const Thread&)>& fn) const`
- `DataFrame transform(self, std::initializer_list<TransformSpec> specs) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.transform("sales", [](const pluss::table::Thread& thread) { return thread.
↪clip(0.0, 110.0); });
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.244 `transpose`

Signature

```
DataFrame transpose(self, bool render = false) const
```

Parameters

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Swaps rows and features so former feature names become row labels.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.transpose(false);
```

Output

```
feature  row0   row1   row2
id       1      2      3
sales    100.0  120.0  90.0
```

5.1.245 truediv

Signature

```
DataFrame truediv(self, const DataFrame& other) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `DataFrame truediv(self, scalar other) const`

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.truediv(right);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.246 truediv

Signature

```
DataFrame truediv(self, scalar other) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- DataFrame truediv(self, const DataFrame& other) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.truediv(10);
```

Output

```
id  sales  city
11  110.0  Accra
12  130.0  Tema
13  100.0  Kumasi
```

5.1.247 tz_convert

Signature

```
DataFrame tz_convert(self, std::initializer_list<std::string_view> features, std::string_
↪view tz_name) const
```

Parameters

features : std::initializer_list<std::string_view> See the signature for the supported argument form.

tz_name : std::string_view See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto df = pluss::table::DataFrame({
    {"ts", pluss::table::Thread(pluss::make_timeline({
        "2024-01-01T09:10:00Z",
        "2024-01-01T09:40:00Z",
        "2024-01-01T10:05:00Z",
    }))},
    {"load", pluss::table::Thread(pluss::make_series({10.0, 20.0, 15.0}))},
});

auto out = df.tz_convert({"ts"}, "America/Edmonton");
```

Output

```
ts
2024-01-01T09:00:00Z
2024-01-01T10:00:00Z
```

5.1.248 tz_localize

Signature

```
DataFrame tz_localize(self, std::initializer_list<std::string_view> features,␣
↪std::string_view tz_name, int fold = 0, std::string_view nonexistent = "raise") const
```

Parameters

`features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`tz_name` : `std::string_view` See the signature for the supported argument form.

`fold` : `int` See the signature for the supported argument form.

`nonexistent` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto df = pluss::table::DataFrame({
    {"ts", pluss::table::Thread(pluss::make_timeline({
        "2024-01-01T09:10:00Z",
        "2024-01-01T09:40:00Z",
        "2024-01-01T10:05:00Z",
    }))},
    {"load", pluss::table::Thread(pluss::make_series({10.0, 20.0, 15.0}))},
});

auto out = df.tz_localize({"ts"}, "America/Edmonton", 0, "shift_forward");
```

Output

```
ts
2024-01-01T09:00:00Z
2024-01-01T10:00:00Z
```

5.1.249 unique

Signature

```
bool unique(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the object satisfies the uniqueness constraint expected by its model, such as distinct labels or keys.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.unique();
```

Output

```
true
```

5.1.250 unique_cases

Signature

```
DataFrame unique_cases(self, std::initializer_list<std::string_view> features =
```

Parameters

features : std::initializer_list<std::string_view> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Keeps only the first occurrence of each case label and drops later duplicates.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.unique_cases();
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.251 unsqueeze

Signature

```
Atlas unsqueeze(self) const
```

Parameters

None

Returns

`Atlas` Value produced by this call.

Notes

Promotes the frame into a depth-1 `Atlas` so it can participate in multi-frame workflows.

See also

- `Atlas unsqueeze(self, const Thread& depth_labels) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.unsqueeze();
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

5.1.252 unsqueeze

Signature

```
Atlas unsqueeze(self, const Thread& depth_labels) const
```

Parameters

`depth_labels` : `const Thread&` See the signature for the supported argument form.

Returns

`Atlas` Value produced by this call.

Notes

Promotes the frame into a depth-1 `Atlas` so it can participate in multi-frame workflows.

See also

- `Atlas unsqueeze(self) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto labels = pluss::table::Thread(pluss::make_note({"train"}));
auto out = df.unsqueeze(labels);
```

Output

```
frame0:
sales
10.0
20.0

frame1:
```

(continues on next page)

(continued from previous page)

```
sales
30.0
40.0
```

5.1.253 update

Signature

```
DataFrame update(self, const DataFrame& other, bool overwrite = true) const
```

Parameters

`other` : `const DataFrame&` See the signature for the supported argument form.

`overwrite` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Overlays matching features from another frame onto this frame using aligned cases.

Examples

```
auto left = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
});
auto right = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"cost", pluss::table::Thread(pluss::make_series({60.0, 80.0, 55.0}))},
});

auto out = left.update(right);
```

Output

```
id  sales  cost
1   100.0  60.0
2   120.0  80.0
3    90.0  55.0
```

5.1.254 values

Signature

```
std::vector<Thread> values(self) const
```

Parameters

None

Returns

std::vector<Thread> Materialized collection of thread objects.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.values();
```

Output

```
[Thread(id), Thread(sales), Thread(city)]
```

5.1.255 var

Signature

```
DataFrame var(self, bool render = true) const
```

Parameters

render : bool See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Computes per-feature variances for the selected numeric features.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.var(false);
```

Output

```
feature  value
sales    310.0
```

5.1.256 view

Signature

```
DataFrame view(self, std::int64_t start, std::int64_t stop, bool render = true) const
```

Parameters

`start` : `std::int64_t` Inclusive starting position of the slice.

`stop` : `std::int64_t` Exclusive ending position of the slice.

`render` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Returns a lightweight row view of the requested slice.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.view(0, 2, false);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.257 where

Signature

```
DataFrame where(self, const pluss::Series& bool_mask) const
```

Parameters

`bool_mask` : `const pluss::Series&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Keeps only the rows where the supplied boolean mask is true.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto out = df.where(mask);
```

Output

```
id  sales  city
1   100.0  Accra
3    90.0  Kumasi
```

5.1.258 window

Signature

```
DataFrame window(self, std::initializer_list<WindowSpec> specs, bool keep_input = true)␣
↪const
```

Parameters

`specs` : `std::initializer_list<WindowSpec>` See the signature for the supported argument form.

`keep_input` : `bool` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Computes one or more window-based features such as rolling means over selected columns.

Examples

```cpp
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.window({{.output = "sales_roll", .feature = "sales", .op =␣
↪pluss::table::ThreadWindowOp::RollingMean, .window = 2, .min_periods = 1}}, true);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.259 with_cases

Signature

```cpp
DataFrame with_cases(self, const Thread& cases) const
```

Parameters

`cases` : `const Thread&` Case-label thread to attach to the current object.

Returns

`DataFrame` Value produced by this call.

Notes

Replaces the current case axis with the supplied thread. The row values stay in the same order, but later case-aware operations now use the new labels.

Examples

```cpp
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto cases = pluss::table::Thread(pluss::make_note({"cs0", "cs1", "cs2"}));
auto out = df.with_cases(cases);
```

Output

```
df.cases():
[0, 1, 2]

out.cases():
```

(continues on next page)

(continued from previous page)

```
["cs0", "cs1", "cs2"]

out.head():
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.260 with_cases_

Signature

```
DataFrame& with_cases_(self, const Thread& cases)
```

Parameters

`cases` : `const Thread&` Case-label thread to attach to the current object.

Returns

`DataFrame&` Value produced by this call.

Notes

Replaces the current case axis in place. The row values stay in the same order, but later case-aware operations now use the new labels.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto cases = pluss::table::Thread(pluss::make_note({"cs0", "cs1", "cs2"}));
df.with_cases_(cases);
```

Output

```
df.cases():
["cs0", "cs1", "cs2"]

df.head():
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

5.1.261 with_column

Signature

```
DataFrame with_column(self, std::string name, const Thread& column) const
```

Parameters

`name` : `std::string` See the signature for the supported argument form.

`column` : `const Thread&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Returns a new frame with one added or replaced feature.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = df.with_column("profit", pluss::table::Thread(pluss::make_series({40.0, 35.0,␣
↪30.0})));
```

Output

```
id  sales  city    profit
1   100.0  Accra   40.0
2   120.0  Tema    35.0
3    90.0  Kumasi  30.0
```

5.1.262 with_column_

Signature

```
DataFrame& with_column_(self, std::string name, const Thread& column)
```

Parameters

`name` : `std::string` See the signature for the supported argument form.

`column` : `const Thread&` See the signature for the supported argument form.

Returns

`DataFrame&` Value produced by this call.

Notes

Adds or replaces one feature in place.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

df.with_column_("profit", pluss::table::Thread(pluss::make_series({40.0, 35.0, 30.0})));
```

Output

```
id  sales  city    profit
1   100.0  Accra   40.0
2   120.0  Tema    35.0
3    90.0  Kumasi  30.0
```

CHAPTER

SIX

COLUMNREF API REFERENCE

CHAPTER

SEVEN

PRACTICAL COLUMNREF API REFERENCE

7.1 API Reference Style

This page documents the public `ColumnRef` helper returned by DataFrame column-reference calls.

7.1.1 head

Signature

```
Thread head(self, std::int64_t n) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

Returns

`Thread` Value produced by this call.

Notes

Returns the first `n` values from the referenced column as a thread.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto ref = df.column_ref("sales");

auto out = ref.head(2);
```

Output

```
[100.0, 120.0]
```

7.1.2 mean

Signature

```
pluss::Series mean(self) const
```

Parameters

None

Returns

`pluss::Series` Value produced by this call.

Notes

Computes the mean of the referenced numeric column.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto ref = df.column_ref("sales");

auto out = ref.mean();
```

Output

```
103.3
```

7.1.3 name

Signature

```
const std::string& name(self) const
```

Parameters

None

Returns

`const std::string&` Value produced by this call.

Notes

Returns the feature name associated with this column reference.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto ref = df.column_ref("sales");

auto out = ref.name();
```

Output

```
sales
```

7.1.4 thread

Signature

```
const Thread& thread(self) const
```

Parameters

None

Returns

`const Thread&` Value produced by this call.

Notes

Returns the referenced column as a `Thread` object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto ref = df.column_ref("sales");

auto out = ref.thread();
```

Output

```
[10.0, 20.0, 30.0]
```

7.1.5 value

Signature

```
ThreadValue value(self) const
```

Parameters

None

Returns

`ThreadValue` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto ref = df.column_ref("sales");

auto out = ref.value();
```

Output

```
100.0
```

7.1.6 values

Signature

```
Thread values(self) const
```

Parameters

None

Returns

`Thread` Value produced by this call.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto ref = df.column_ref("sales");

auto out = ref.values();
```

Output

```
[10.0, 20.0, 30.0]
```

CHAPTER

EIGHT

DATAFRAMEPLOTACCESSOR API REFERENCE

CHAPTER

NINE

PRACTICAL DATAFRAMEPLOTACCESSOR API REFERENCE

9.1 API Reference Style

This page documents the public plotting accessor returned by `DataFrame::plot()` and `Atlas::plot()`.

9.1.1 bar

Signature

```
pluss::plotism::Figure bar(self, std::string_view y_feature, std::optional<std::string_
↪view> x_feature = std::nullopt) const
```

Parameters

`y_feature` : `std::string_view` See the signature for the supported argument form.

`x_feature` : `std::optional<std::string_view>` See the signature for the supported argument form.

Returns

`pluss::plotism::Figure` Value produced by this call.

Notes

Builds a bar chart from one feature, optionally using another feature as the x-axis.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto plot = df.plot();

auto fig = plot.bar("sales", std::nullopt);
```

Output

```
Figure(...)
```

9.1.2 hist

Signature

```
pluss::plotism::Figure hist(self, std::string_view feature, std::int64_t bins = 20) const
```

Parameters

`feature` : `std::string_view` See the signature for the supported argument form.

`bins` : `std::int64_t` See the signature for the supported argument form.

Returns

`pluss::plotism::Figure` Value produced by this call.

Notes

Builds a histogram for one feature using the requested number of bins.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto plot = df.plot();

auto fig = plot.hist("sales", 12);
```

Output

```
Figure(...)
```

9.1.3 line

Signature

```
pluss::plotism::Figure line(self, std::initializer_list<std::string_view> y_features,␣
↪std::optional<std::string_view> x_feature = std::nullopt) const
```

Parameters

`y_features` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

`x_feature` : `std::optional<std::string_view>` See the signature for the supported argument form.

Returns

`pluss::plotism::Figure` Value produced by this call.

Notes

Builds a line chart for one or more y-features, optionally against a chosen x-feature.

See also

- `pluss::plotism::Figure line(self, std::string_view y_feature, std::optional<std::string_view> x_feature = std::nullopt) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto plot = df.plot();

auto fig = plot.line({"sales"}, std::nullopt);
```

Output

```
Figure(...)
```

9.1.4 `line`

Signature

```
pluss::plotism::Figure line(self, std::string_view y_feature, std::optional<std::string_
↪view> x_feature = std::nullopt) const
```

Parameters

`y_feature` : `std::string_view` See the signature for the supported argument form.

`x_feature` : `std::optional<std::string_view>` See the signature for the supported argument form.

Returns

`pluss::plotism::Figure` Value produced by this call.

Notes

Builds a line chart for one or more y-features, optionally against a chosen x-feature.

See also

- `pluss::plotism::Figure line(self, std::initializer_list<std::string_view> y_features, std::optional<std::string_view> x_feature = std::nullopt) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto plot = df.plot();

auto fig = plot.line("sales");
```

Output

```
Figure(...)
```

9.1.5 scatter

Signature

```
pluss::plotism::Figure scatter(self, std::string_view x_feature, std::string_view y_
↪feature) const
```

Parameters

`x_feature` : `std::string_view` See the signature for the supported argument form.

`y_feature` : `std::string_view` See the signature for the supported argument form.

Returns

`pluss::plotism::Figure` Value produced by this call.

Notes

Builds a scatter plot using one feature for x and another for y.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto plot = df.plot();

auto fig = plot.scatter("id", "sales");
```

Output

```
Figure(...)
```

CHAPTER

TEN

DATAFRAMESQLACCESSOR API REFERENCE

CHAPTER

ELEVEN

PRACTICAL DATAFRAMESQLACCESSOR API REFERENCE

11.1 API Reference Style

This page documents the public SQL accessor returned by `DataFrame::sql()`.

11.1.1 execute

Signature

```
DataFrame execute(self, std::string_view statement) const
```

Parameters

`statement` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Runs a SQL query against the current frame and returns the result as a new `DataFrame`.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto sql = df.sql();

auto out = sql.execute("SELECT id, sales FROM self WHERE sales > 95");
```

Output

```
id  sales  city
1   100.0  Accra
3    90.0  Kumasi
```

11.1.2 prepare

Signature

```
DataFrameSqlPrepared prepare(self, std::string_view statement) const
```

Parameters

`statement` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrameSqlPrepared` Value produced by this call.

Notes

Compiles a parameterized SQL statement that can be executed repeatedly with different bindings.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto sql = df.sql();

auto out = sql.prepare("SELECT id, sales FROM self WHERE sales > {min_sales}");
```

Output

```
Prepared statement ready
```

CHAPTER

TWELVE

DATAFRAMESQLPREPARED API REFERENCE

CHAPTER

THIRTEEN

PRACTICAL DATAFRAMESQLPREPARED API REFERENCE

13.1 API Reference Style

This page documents the public prepared-statement helper returned by `DataFrame::prepare_sql()` or `DataFrameSqlAccessor::prepare()`.

13.1.1 execute

Signature

```
DataFrame execute(self) const
```

Parameters

None

Returns

`DataFrame` Value produced by this call.

Notes

Runs the prepared SQL statement with the supplied parameters and returns the result as a new `DataFrame`.

See also

- `DataFrame execute(self, std::unordered_map<std::string, DataFrame::SqlOptions::SqlParam> params) const`
- `DataFrame execute(self, std::unordered_map<std::string, DataFrame::SqlOptions::SqlParam> params, std::unordered_map<std::string, std::string> identifier_params) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto stmt = df.prepare_sql("SELECT id, sales FROM self WHERE sales > {min_sales}");

auto out = stmt.execute();
```

Output

```
id  sales  city
1   100.0  Accra
3    90.0  Kumasi
```

13.1.2 execute

Signature

```
DataFrame execute(self, std::unordered_map<std::string, DataFrame::SqlOptions::SqlParam>␣
↪params) const
```

Parameters

params : std::unordered_map<std::string, DataFrame::SqlOptions::SqlParam> See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Runs the prepared SQL statement with the supplied parameters and returns the result as a new DataFrame.

See also

- DataFrame execute(self) const
- DataFrame execute(self, std::unordered_map<std::string, DataFrame::SqlOptions::SqlParam> params, std::unordered_map<std::string, std::string> identifier_params) const

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto stmt = df.prepare_sql("SELECT id, sales FROM self WHERE sales > {min_sales}");

auto out = stmt.execute({{"min_sales", 95.0}});
```

Output

```
id  sales  city
1   100.0  Accra
3    90.0  Kumasi
```

13.1.3 execute

Signature

```
DataFrame execute(self, std::unordered_map<std::string, DataFrame::SqlOptions::SqlParam>␣
↪params, std::unordered_map<std::string, std::string> identifier_params) const
```

Parameters

`params` : `std::unordered_map<std::string, DataFrame::SqlOptions::SqlParam>` See the signature for the supported argument form.

`identifier_params` : `std::unordered_map<std::string, std::string>` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Runs the prepared SQL statement with the supplied parameters and returns the result as a new `DataFrame`.

See also

- `DataFrame execute(self) const`
- `DataFrame execute(self, std::unordered_map<std::string, DataFrame::SqlOptions::SqlParam> params) const`

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});
auto stmt = df.prepare_sql("SELECT id, sales FROM self WHERE sales > {min_sales}");

auto out = stmt.execute({{"min_sales", 95.0}}, {{"table_name", "self"}});
```

Output

```
id  sales  city
1   100.0  Accra
3    90.0  Kumasi
```

CHAPTER

FOURTEEN

THREAD AND ATLAS GUIDE

14.1 Thread

`Thread` is a typed column wrapper around `Series`, `Note`, `Timeline`, or `TimeIndex`. Use it when you want column operations without carrying the full `DataFrame` around.

```
auto sales = pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}));
auto cities = pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}));

auto cleaned = sales.fillna(0.0).clip(0.0, 150.0);
auto avg = cleaned.mean();
auto city_mask = cities.contains("Accra");
```

Notes:

- `Thread` is the easiest bridge point between the Pluss domain types and table verbs
- when you want the original typed payload back, use `as_series()`, `as_note()`, `as_timeline()`, or `as_timeindex()`

14.2 Row-Space Helpers

```
auto head = sales.head(2);
auto tail = sales.tail(2);
auto slice = sales.slice(0, 2);
auto taken = sales.take(std::array<std::int64_t, 2>{0, 2});
auto filtered = sales.filter(city_mask);
```

14.3 Atlas

`Atlas` is the frame-stack model in PlussMic. It is useful when you want a small set of aligned `DataFrame` objects with an optional depth axis.

```
auto f0 = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema"}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0}))},
});

auto f1 = pluss::table::DataFrame({
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema"}))},
```

(continues on next page)

(continued from previous page)

```
    {"sales", pluss::table::Thread(pluss::make_series({130.0, 125.0}))},
});

auto labels = pluss::table::Thread(pluss::make_note({"train", "test"}));
auto atlas = pluss::table::Atlas({f0, f1}, labels);

atlas.head(1).show();
auto sorted = atlas.sort_depth();
auto first = atlas.frame(0);
```

14.4 Atlas To Kindle

```
auto archive = atlas.kindelize();
auto roundtrip = archive.tabelize();
```

CHAPTER

FIFTEEN

THREAD API REFERENCE

CHAPTER

SIXTEEN

PRACTICAL THREAD API REFERENCE

16.1 API Reference Style

This page documents the full public `Thread` surface with direct typed-column examples.

16.1.1 abs

Signature

```
Thread abs(self) const
```

Parameters

None

Returns

`Thread` Value produced by this call.

Notes

Returns a numeric thread whose values are the absolute values of the current numeric payload.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.abs();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.2 as_note

Signature

```
const pluss::Note& as_note(self) const
```

Parameters

None

Returns

`const pluss::Note&` Value produced by this call.

Notes

Interprets or converts the current payload as a note/text thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}));

auto out = thread.as_note();
```

Output

```
["Accra", "Tema", "Kumasi"]
```

16.1.3 as_series

Signature

```
const pluss::Series& as_series(self) const
```

Parameters

None

Returns

`const pluss::Series&` Value produced by this call.

Notes

Interprets or converts the current payload as a numeric series thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.as_series();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.4 as_timeindex

Signature

```
const pluss::TimeIndex& as_timeindex(self) const
```

Parameters

None

Returns

const pluss::TimeIndex& Value produced by this call.

Notes

Interprets or converts the current payload as a time-index thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z", "2024-03-05T15:30:00Z"}));

auto out = thread.as_timeindex();
```

Output

```
["2024-01-01T09:10:00Z", "2024-02-01T11:00:00Z", "2024-03-05T15:30:00Z"]
```

16.1.5 as_timeline

Signature

```
const pluss::Timeline& as_timeline(self) const
```

Parameters

None

Returns

const pluss::Timeline& Value produced by this call.

Notes

Interprets or converts the current payload as a timeline thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z", "2024-03-05T15:30:00Z"}));

auto out = thread.as_timeline();
```

Output

```
["2024-01-01T09:10:00Z", "2024-02-01T11:00:00Z", "2024-03-05T15:30:00Z"]
```

16.1.6 astype

Signature

```
Thread astype(self, pluss::codem::ScalarType dtype) const
```

Parameters

`dtype` : `pluss::codem::ScalarType` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.astype(pluss::codem::ScalarType::Float64);
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.7 bfill

Signature

```
Thread bfill(self) const
```

Parameters

`None`

Returns

`Thread` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.bfill();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.8 cast

Signature

```
Thread cast(self, ThreadCastTarget target, std::optional<pluss::codem::ScalarType>␣
↪series_dtype = std::nullopt) const
```

Parameters

`target` : `ThreadCastTarget` See the signature for the supported argument form.

`series_dtype` : `std::optional<pluss::codem::ScalarType>` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
auto thread = pluss::table::Thread(pluss::make_note({"1.0", "2.0", "3.0"}));

auto out = thread.cast(pluss::table::ThreadCastTarget::Series,␣
↪pluss::codem::ScalarType::Float64);
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.9 clear_validity_mask

Signature

```
Thread clear_validity_mask(self) const
```

Parameters

None

Returns

Thread Value produced by this call.

Notes

Returns a thread with the validity mask removed, so all entries are treated as valid again.

Examples

```
auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.clear_validity_mask();
```

16.1.10 clear_validity_mask_

Signature

```
Thread& clear_validity_mask_(self)
```

Parameters

None

Returns

Thread& Value produced by this call.

Notes

Removes the validity mask in place, so all entries are treated as valid again.

Examples

```
auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

thread.clear_validity_mask_();
```

16.1.11 clip

Signature

```
Thread clip(self, scalar min_value, scalar max_value) const
```

Parameters

`min_value` : `scalar` See the signature for the supported argument form.

`max_value` : `scalar` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

Clamps numeric values to the supplied lower and upper bounds.

Examples

```cpp
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.clip(0.0, 25.0);
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.12 `compare`

Signature

```
Thread compare(self, const Thread& other, ThreadBinaryCompareOp op) const
```

Parameters

`other` : `const Thread&` See the signature for the supported argument form.

`op` : `ThreadBinaryCompareOp` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `Thread compare(self, scalar other, ThreadBinaryCompareOp op) const`

Examples

```cpp
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto other = pluss::table::Thread(pluss::make_series({15.0, 10.0, 35.0}));
auto out = thread.compare(other, pluss::table::ThreadBinaryCompareOp::Gt);
```

Output

```
1
```

16.1.13 compare

Signature

```
Thread compare(self, scalar other, ThreadBinaryCompareOp op) const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

`op` : `ThreadBinaryCompareOp` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

This produces a comparison-style result you can inspect directly or reuse as a mask.

See also

- `Thread compare(self, const Thread& other, ThreadBinaryCompareOp op) const`

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.compare(15.0, pluss::table::ThreadBinaryCompareOp::Gt);
```

Output

```
1
```

16.1.14 compare_rows

Signature

```
int compare_rows(self, std::int64_t lhs_row, std::int64_t rhs_row, bool nulls_last =␣
↪true) const
```

Parameters

`lhs_row` : `std::int64_t` See the signature for the supported argument form.

`rhs_row` : `std::int64_t` See the signature for the supported argument form.

`nulls_last` : `bool` See the signature for the supported argument form.

Returns

`int` Value produced by this call.

Notes

Compares two positions inside the same thread and returns the comparison result.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.compare_rows(0, 1, true);
```

Output

```
1
```

16.1.15 contains

Signature

```
pluss::Series contains(self, std::string_view needle) const
```

Parameters

`needle` : `std::string_view` See the signature for the supported argument form.

Returns

`pluss::Series` Value produced by this call.

Notes

This is part of the text-processing surface for note-backed or text-oriented data.

Examples

```
auto thread = pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}));

auto out = thread.contains("Accra");
```

Output

```
[true, false, true]
```

16.1.16 day

Signature

```
Thread day(self) const
```

Parameters

None

Returns

Thread Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z", "2024-03-05T15:30:00Z"}));

auto out = thread.day();
```

Output

```
[1, 2, 3]
```

16.1.17 defined

Signature

```
bool defined(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object owns a concrete payload that can be used safely in later operations.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.defined();
```

Output

```
true
```

16.1.18 dropna

Signature

```
Thread dropna(self) const
```

Parameters

None

Returns

Thread Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.dropna();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.19 dtype_name

Signature

```
std::string dtype_name(self) const
```

Parameters

None

Returns

std::string Rendered string result.

Notes

Returns the scalar dtype name used by the current numeric payload.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.dtype_name();
```

Output

```
Float64
```

16.1.20 exp

Signature

```
Thread exp(self) const
```

Parameters

None

Returns

Thread Value produced by this call.

Notes

Applies the elementwise exponential to a numeric thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.exp();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.21 ffill

Signature

```
Thread ffill(self) const
```

Parameters

None

Returns

Thread Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.ffill();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.22 fillna

Signature

```
Thread fillna(self, const char* value) const
```

Parameters

`value` : `const char*` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `Thread fillna(self, scalar value) const`
- `Thread fillna(self, std::string_view value) const`
- `Thread fillna(self, const pluss::Timeline& value) const`
- `Thread fillna(self, const pluss::TimeIndex& value) const`

Examples

```
auto thread = pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}));

auto out = thread.fillna("Unknown");
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.23 fillna

Signature

```
Thread fillna(self, const pluss::TimeIndex& value) const
```

Parameters

`value` : `const pluss::TimeIndex&` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `Thread fillna(self, scalar value) const`
- `Thread fillna(self, std::string_view value) const`
- `Thread fillna(self, const char* value) const`
- `Thread fillna(self, const pluss::Timeline& value) const`

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeindex({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z"}));

auto out = thread.fillna(pluss::make_timeindex("2024-01-01T00:00:00Z"));
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.24 `fillna`

Signature

```
Thread fillna(self, const pluss::Timeline& value) const
```

Parameters

`value` : `const pluss::Timeline&` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `Thread fillna(self, scalar value) const`
- `Thread fillna(self, std::string_view value) const`
- `Thread fillna(self, const char* value) const`

- `Thread fillna(self, const pluss::TimeIndex& value) const`

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z", "2024-03-05T15:30:00Z"}));

auto out = thread.fillna(pluss::make_timeline("2024-01-01T00:00:00Z"));
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.25 `fillna`

Signature

```
Thread fillna(self, scalar value) const
```

Parameters

`value` : `scalar` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `Thread fillna(self, std::string_view value) const`
- `Thread fillna(self, const char* value) const`
- `Thread fillna(self, const pluss::Timeline& value) const`
- `Thread fillna(self, const pluss::TimeIndex& value) const`

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.fillna(0.0);
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.26 fillna

Signature

```
Thread fillna(self, std::string_view value) const
```

Parameters

value : std::string_view See the signature for the supported argument form.

Returns

Thread Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- Thread fillna(self, scalar value) const
- Thread fillna(self, const char* value) const
- Thread fillna(self, const pluss::Timeline& value) const
- Thread fillna(self, const pluss::TimeIndex& value) const

Examples

```
auto thread = pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}));

auto out = thread.fillna("Unknown");
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.27 fillna_

Signature

```
Thread& fillna_(self, const char* value)
```

Parameters

value : const char* See the signature for the supported argument form.

Returns

Thread& Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `Thread& fillna_(self, scalar value)`
- `Thread& fillna_(self, std::string_view value)`
- `Thread& fillna_(self, const pluss::Timeline& value)`
- `Thread& fillna_(self, const pluss::TimeIndex& value)`

Examples

```
auto thread = pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}));

thread.fillna_("Unknown");
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.28 `fillna_`

Signature

```
Thread& fillna_(self, const pluss::TimeIndex& value)
```

Parameters

`value` : `const pluss::TimeIndex&` See the signature for the supported argument form.

Returns

`Thread&` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `Thread& fillna_(self, scalar value)`
- `Thread& fillna_(self, std::string_view value)`
- `Thread& fillna_(self, const char* value)`
- `Thread& fillna_(self, const pluss::Timeline& value)`

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeindex({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z"}));

thread.fillna_(pluss::make_timeindex("2024-01-01T00:00:00Z"));
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.29 fillna_

Signature

```
Thread& fillna_(self, const pluss::Timeline& value)
```

Parameters

value : const pluss::Timeline& See the signature for the supported argument form.

Returns

Thread& Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- Thread& fillna_(self, scalar value)
- Thread& fillna_(self, std::string_view value)
- Thread& fillna_(self, const char* value)
- Thread& fillna_(self, const pluss::TimeIndex& value)

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z", "2024-03-05T15:30:00Z"}));

thread.fillna_(pluss::make_timeline("2024-01-01T00:00:00Z"));
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.30 fillna_

Signature

```
Thread& fillna_(self, scalar value)
```

Parameters

value : scalar See the signature for the supported argument form.

Returns

Thread& Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- Thread& fillna_(self, std::string_view value)
- Thread& fillna_(self, const char* value)
- Thread& fillna_(self, const pluss::Timeline& value)
- Thread& fillna_(self, const pluss::TimeIndex& value)

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

thread.fillna_(0.0);
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.31 fillna_

Signature

```
Thread& fillna_(self, std::string_view value)
```

Parameters

value : std::string_view See the signature for the supported argument form.

Returns

Thread& Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- Thread& fillna_(self, scalar value)
- Thread& fillna_(self, const char* value)
- Thread& fillna_(self, const pluss::Timeline& value)
- Thread& fillna_(self, const pluss::TimeIndex& value)

Examples

```
auto thread = pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}));

thread.fillna_("Unknown");
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.32 filter

Signature

```
Thread filter(self, const pluss::Series& bool_mask) const
```

Parameters

bool_mask : const pluss::Series& See the signature for the supported argument form.

Returns

Thread Value produced by this call.

Notes

Keeps only the entries where the supplied boolean mask is true.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto out = thread.filter(mask);
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.33 has_validity_mask

Signature

```
bool has_validity_mask(self) const
```

Parameters

None

Returns

`bool` Boolean status or membership result.

Notes

Reports whether the thread currently carries a validity mask.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.has_validity_mask();
```

16.1.34 head

Signature

```
Thread head(self, std::int64_t n) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

Returns

`Thread` Value produced by this call.

Notes

Returns the first `n` entries of the thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.head(2);
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.35 hour

Signature

```
Thread hour(self) const
```

Parameters

`None`

Returns

Thread Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z", "2024-03-05T15:30:00Z"}));

auto out = thread.hour();
```

Output

```
[1, 2, 3]
```

16.1.36 is_valid

Signature

```
bool is_valid(self, std::int64_t row) const
```

Parameters

row : std::int64_t See the signature for the supported argument form.

Returns

bool Boolean status or membership result.

Notes

Checks whether the value at one position is marked valid by the thread validity mask.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.is_valid(0);
```

Output

```
true
```

16.1.37 isfinite

Signature

```
pluss::Series isfinite(self) const
```

Parameters

None

Returns

`pluss::Series` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.isfinite();
```

Output

```
[true, false, true]
```

16.1.38 `isnan`

Signature

```
pluss::Series isnan(self) const
```

Parameters

None

Returns

`pluss::Series` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.isnan();
```

Output

```
[true, false, true]
```

16.1.39 isnull

Signature

```
pluss::Series isnull(self) const
```

Parameters

None

Returns

pluss::Series Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.isnull();
```

Output

```
[true, false, true]
```

16.1.40 kind

Signature

```
ThreadKind kind(self) const
```

Parameters

None

Returns

ThreadKind Value produced by this call.

Notes

Returns which payload kind this thread currently stores, such as Series, Note, Timeline, or TimeIndex.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.kind();
```

Output

```
Series
```

16.1.41 log

Signature

```
Thread log(self) const
```

Parameters

None

Returns

Thread Value produced by this call.

Notes

Applies the elementwise natural logarithm to a numeric thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.log();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.42 lower

Signature

```
Thread lower(self) const
```

Parameters

None

Returns

Thread Value produced by this call.

Notes

This is part of the text-processing surface for note-backed or text-oriented data.

Examples

```
auto thread = pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}));

auto out = thread.lower();
```

Output

```
["Accra", "Tema", "Kumasi"]
```

16.1.43 max

Signature

```
pluss::Series max(self) const
```

Parameters

None

Returns

`pluss::Series` Value produced by this call.

Notes

Returns the maximum value of a numeric thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.max();
```

Output

```
20.0
```

16.1.44 mean

Signature

```
pluss::Series mean(self) const
```

Parameters

None

Returns

`pluss::Series` Value produced by this call.

Notes

Returns the mean value of a numeric thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.mean();
```

Output

```
20.0
```

16.1.45 min

Signature

```
pluss::Series min(self) const
```

Parameters

None

Returns

`pluss::Series` Value produced by this call.

Notes

Returns the minimum value of a numeric thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.min();
```

Output

```
20.0
```

16.1.46 month

Signature

```
Thread month(self) const
```

Parameters

None

Returns

Thread Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z", "2024-03-05T15:30:00Z"}));

auto out = thread.month();
```

Output

```
[1, 2, 3]
```

16.1.47 note

Signature

```
const pluss::Note& note(self) const
```

Parameters

None

Returns

const pluss::Note& Value produced by this call.

Notes

Returns the current payload as a note/text object.

Examples

```
auto thread = pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}));

auto out = thread.note();
```

Output

```
["Accra", "Tema", "Kumasi"]
```

16.1.48 notnull

Signature

```
pluss::Series notnull(self) const
```

Parameters

None

Returns

`pluss::Series` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.notnull();
```

Output

```
[true, false, true]
```

16.1.49 numeric_binary

Signature

```
Thread numeric_binary(self, const Thread& other, ThreadBinaryMathOp op) const
```

Parameters

`other` : `const Thread&` See the signature for the supported argument form.

`op` : `ThreadBinaryMathOp` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `Thread numeric_binary(self, scalar other, ThreadBinaryMathOp op, bool reverse = false) const`

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.numeric_binary(10.0, pluss::table::ThreadBinaryMathOp::Add, false);
```

Output

```
[20.0, 30.0, 40.0]
```

16.1.50 numeric_binary

Signature

```
Thread numeric_binary(self, scalar other, ThreadBinaryMathOp op, bool reverse = false)␣
↪const
```

Parameters

`other` : `scalar` See the signature for the supported argument form.

`op` : `ThreadBinaryMathOp` See the signature for the supported argument form.

`reverse` : `bool` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

This applies arithmetic across the compatible numeric payloads in the current object.

See also

- `Thread numeric_binary(self, const Thread& other, ThreadBinaryMathOp op) const`

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.numeric_binary(10.0, pluss::table::ThreadBinaryMathOp::Add, false);
```

Output

```
[20.0, 30.0, 40.0]
```

16.1.51 replace

Signature

```
Thread replace(self, std::string_view from, std::string_view to) const
```

Parameters

`from` : `std::string_view` See the signature for the supported argument form.

`to` : `std::string_view` See the signature for the supported argument form.

Returns

Thread Value produced by this call.

Notes

This is part of the text-processing surface for note-backed or text-oriented data.

Examples

```
auto thread = pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}));

auto out = thread.replace("Tema", "Tamale");
```

Output

```
["Accra", "Tema", "Kumasi"]
```

16.1.52 series

Signature

```
const pluss::Series& series(self) const
```

Parameters

None

Returns

const pluss::Series& Value produced by this call.

Notes

Returns the current payload as a numeric series object.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.series();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.53 show

Signature

```
void show(self, const display::DisplayOptions& options =
```

Parameters

`options` : `const display::DisplayOptions&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

See also

- `void show(self, std::ostream& os, const display::DisplayOptions& options =`

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

thread.show();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.54 show

Signature

```
void show(self, std::ostream& os, const display::DisplayOptions& options =
```

Parameters

`os` : `std::ostream&` See the signature for the supported argument form.

`options` : `const display::DisplayOptions&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

See also

- `void show(self, const display::DisplayOptions& options =`

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

thread.show();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.55 size

Signature

```
std::int64_t size(self) const
```

Parameters

None

Returns

std::int64_t Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.size();
```

Output

```
3
```

16.1.56 slice

Signature

```
Thread slice(self, std::int64_t start, std::int64_t stop) const
```

Parameters

start : std::int64_t Inclusive starting position of the slice.

stop : std::int64_t Exclusive ending position of the slice.

Returns

Thread Value produced by this call.

Notes

Returns a contiguous slice [start, stop) of the thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.slice(0, 2);
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.57 std

Signature

```
pluss::Series std(self, bool unbiased = true) const
```

Parameters

`unbiased` : `bool` See the signature for the supported argument form.

Returns

`pluss::Series` Value produced by this call.

Notes

Returns the standard deviation of a numeric thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.std(true);
```

Output

```
20.0
```

16.1.58 sum

Signature

```
pluss::Series sum(self) const
```

Parameters

None

Returns

`pluss::Series` Value produced by this call.

Notes

Returns the sum of a numeric thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.sum();
```

Output

```
20.0
```

16.1.59 tail

Signature

```
Thread tail(self, std::int64_t n) const
```

Parameters

n : std::int64_t Number of rows, entries, or depth items to keep in the preview.

Returns

Thread Value produced by this call.

Notes

Returns the last n entries of the thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.tail(2);
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.60 take

Signature

```
Thread take(self, std::span<const std::int64_t> indices) const
```

Parameters

indices : std::span<const std::int64_t> See the signature for the supported argument form.

Returns

Thread Value produced by this call.

Notes

Returns the entries at the requested integer positions.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

std::vector<std::int64_t> picks{0, 2};
auto out = thread.take(picks);
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.61 timeindex

Signature

```
const pluss::TimeIndex& timeindex(self) const
```

Parameters

None

Returns

const pluss::TimeIndex& Value produced by this call.

Notes

Returns the current payload as a time-index object.

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z", "2024-03-05T15:30:00Z"}));

auto out = thread.timeindex();
```

Output

```
["2024-01-01T09:10:00Z", "2024-02-01T11:00:00Z", "2024-03-05T15:30:00Z"]
```

16.1.62 timeline

Signature

```
const pluss::Timeline& timeline(self) const
```

Parameters

None

Returns

`const pluss::Timeline&` Value produced by this call.

Notes

Returns the current payload as a timeline object.

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z", "2024-03-05T15:30:00Z"}));

auto out = thread.timeline();
```

Output

```
["2024-01-01T09:10:00Z", "2024-02-01T11:00:00Z", "2024-03-05T15:30:00Z"]
```

16.1.63 to_note_weekday

Signature

```
Thread to_note_weekday(self) const
```

Parameters

None

Returns

`Thread` Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z", "2024-03-05T15:30:00Z"}));

auto out = thread.to_note_weekday();
```

Output

```
[1, 2, 3]
```

16.1.64 to_string

Signature

```
std::string to_string(self, const display::DisplayOptions& options =
```

Parameters

`options` : `const display::DisplayOptions&` See the signature for the supported argument form.

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.to_string();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.65 unique

Signature

```
bool unique(self) const
```

Parameters

None

Returns

`bool` Boolean status or membership result.

Notes

Reports whether the object satisfies the uniqueness constraint expected by its model, such as distinct labels or keys.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.unique();
```

Output

```
true
```

16.1.66 validity_mask

Signature

```
const std::optional<pluss::Series>& validity_mask(self) const
```

Parameters

None

Returns

const std::optional<pluss::Series>& Value produced by this call.

Notes

Returns the current validity mask as a boolean series.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.validity_mask();
```

16.1.67 value

Signature

```
ThreadValue value(self) const
```

Parameters

None

Returns

ThreadValue Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.value();
```

Output

```
10.0
```

16.1.68 values

Signature

```
const Thread& values(self) const
```

Parameters

None

Returns

`const Thread&` Value produced by this call.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.values();
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.69 var

Signature

```
pluss::Series var(self, bool unbiased = true) const
```

Parameters

`unbiased` : `bool` See the signature for the supported argument form.

Returns

`pluss::Series` Value produced by this call.

Notes

Returns the variance of a numeric thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.var(true);
```

Output

```
20.0
```

16.1.70 window

Signature

```
Thread window(self, std::int64_t window, ThreadWindowOp op, std::int64_t min_periods =␣
↪1) const
```

Parameters

`window` : `std::int64_t` See the signature for the supported argument form.

`op` : `ThreadWindowOp` See the signature for the supported argument form.

`min_periods` : `std::int64_t` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

Computes a window-based transformation such as a rolling mean over the thread values.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.window(2, pluss::table::ThreadWindowOp::RollingMean, 1);
```

Output

```
[10.0, 20.0, 30.0]
```

16.1.71 with_validity_mask

Signature

```
Thread with_validity_mask(self, const pluss::Series& validity_mask) const
```

Parameters

`validity_mask` : `const pluss::Series&` See the signature for the supported argument form.

Returns

`Thread` Value produced by this call.

Notes

Returns a new thread with the supplied validity mask attached.

Examples

```
auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = thread.with_validity_mask(mask);
```

16.1.72 with_validity_mask_

Signature

```
Thread& with_validity_mask_(self, const pluss::Series& validity_mask)
```

Parameters

`validity_mask` : `const pluss::Series&` See the signature for the supported argument form.

Returns

`Thread&` Value produced by this call.

Notes

Attaches the supplied validity mask in place.

Examples

```
auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

thread.with_validity_mask_(mask);
```

16.1.73 year

Signature

```
Thread year(self) const
```

Parameters

None

Returns

Thread Value produced by this call.

Notes

This is part of the time-aware surface and expects timeline or time-index semantics.

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪02-01T11:00:00Z", "2024-03-05T15:30:00Z"}));

auto out = thread.year();
```

Output

```
[2024, 2024, 2024]
```

CHAPTER

SEVENTEEN

THREADVALUE API REFERENCE

CHAPTER

EIGHTEEN

PRACTICAL THREADVALUE API REFERENCE

18.1 API Reference Style

This page documents the public scalar-like `ThreadValue` wrapper returned by thread and column-value accessors.

18.1.1 as_note

Signature

```
pluss::Note as_note(self) const
```

Parameters

None

Returns

`pluss::Note` Value produced by this call.

Notes

Converts the wrapped scalar-like value into a `pluss::Note`.

Examples

```
auto thread = pluss::table::Thread(pluss::make_note({"Accra"}));
auto value = thread.value();

auto out = value.as_note();
```

Output

```
["Accra"]
```

18.1.2 as_series

Signature

```
pluss::Series as_series(self) const
```

Parameters

None

Returns

`pluss::Series` Value produced by this call.

Notes

Converts the wrapped scalar-like value into a `pluss::Series`.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0}));
auto value = thread.value();

auto out = value.as_series();
```

Output

```
[10.0]
```

18.1.3 as_timeindex

Signature

```
pluss::TimeIndex as_timeindex(self) const
```

Parameters

None

Returns

`pluss::TimeIndex` Value produced by this call.

Notes

Converts the wrapped scalar-like value into a `pluss::TimeIndex`.

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeindex({"2024-01-01T09:10:00Z"}));
auto value = thread.value();

auto out = value.as_timeindex();
```

Output

```
["2024-01-01T09:10:00Z"]
```

18.1.4 as_timeline

Signature

```
pluss::Timeline as_timeline(self) const
```

Parameters

None

Returns

`pluss::Timeline` Value produced by this call.

Notes

Converts the wrapped scalar-like value into a `pluss::Timeline`.

Examples

```
auto thread = pluss::table::Thread(pluss::make_timeline({"2024-01-01T09:10:00Z"}));
auto value = thread.value();

auto out = value.as_timeline();
```

Output

```
["2024-01-01T09:10:00Z"]
```

18.1.5 defined

Signature

```
bool defined(self) const
```

Parameters

None

Returns

`bool` Boolean status or membership result.

Notes

Reports whether the current object owns a concrete payload that can be used safely in later operations.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0}));
auto value = thread.value();

auto out = value.defined();
```

Output

```
true
```

18.1.6 kind

Signature

```
ThreadKind kind(self) const
```

Parameters

None

Returns

ThreadKind Value produced by this call.

Notes

Returns the underlying thread kind carried by this value wrapper.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0}));
auto value = thread.value();

auto out = value.kind();
```

Output

```
Series
```

18.1.7 pluss::Note

Signature

```
operator pluss::Note(self) const
```

Parameters

None

Returns

operator Value produced by this call.

Notes

Uses the implicit conversion operator to materialize the wrapped value as a `pluss::Note`.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0}));
auto value = thread.value();

auto out = value.pluss::Note();
```

18.1.8 pluss::Series

Signature

```
operator pluss::Series(self) const
```

Parameters

None

Returns

operator Value produced by this call.

Notes

Uses the implicit conversion operator to materialize the wrapped value as a `pluss::Series`.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0}));
auto value = thread.value();

auto out = value.pluss::Series();
```

18.1.9 pluss::TimeIndex

Signature

```
operator pluss::TimeIndex(self) const
```

Parameters

None

Returns

operator Value produced by this call.

Notes

Uses the implicit conversion operator to materialize the wrapped value as a `pluss::TimeIndex`.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0}));
auto value = thread.value();

auto out = value.pluss::TimeIndex();
```

18.1.10 pluss::Timeline

Signature

```
operator pluss::Timeline(self) const
```

Parameters

None

Returns

operator Value produced by this call.

Notes

Uses the implicit conversion operator to materialize the wrapped value as a pluss::Timeline.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0}));
auto value = thread.value();

auto out = value.pluss::Timeline();
```

18.1.11 thread

Signature

```
const Thread& thread(self) const
```

Parameters

None

Returns

const Thread& Value produced by this call.

Notes

Returns the wrapped single-value Thread object.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0}));
auto value = thread.value();

auto out = value.thread();
```

Output

```
[10.0]
```

CHAPTER

NINETEEN

ATLAS API REFERENCE

CHAPTER

TWENTY

PRACTICAL ATLAS API REFERENCE

20.1 API Reference Style

This page documents the full public `Atlas` surface for frame-stack workflows.

20.1.1 aggregate_over_frames

Signature

```
DataFrame aggregate_over_frames(self, const std::function<DataFrame(const std::vector
↪<DataFrame>&)>& fn) const
```

Parameters

`fn` : `const std::function<DataFrame(const std::vector<DataFrame>&)>&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Reduces the full frame stack to one output by applying an aggregation function across the contained frames.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.aggregate_over_frames([](const std::vector<pluss::table::DataFrame>&␣
↪frames) { return frames.front(); });
```

Output

```
sales
10.0
20.0
```

20.1.2 align_depth

Signature

```
Atlas align_depth(self, const Thread& labels) const
```

Parameters

`labels` : `const Thread&` See the signature for the supported argument form.

Returns

`Atlas` Value produced by this call.

Notes

Reorders frames so their depth labels match the supplied label order.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto labels = pluss::table::Thread(pluss::make_note({"baseline", "stress"}));
auto out = atlas.align_depth(labels);
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.3 axis0_labels

Signature

```
const std::optional<Thread>& axis0_labels(self) const
```

Parameters

None

Returns

const std::optional<Thread>& Value produced by this call.

Notes

Returns the current labels used to address fields, slots, rows, or depth items.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.axis0_labels();
```

Output

```
["train", "test"]
```

20.1.4 column_names

Signature

```
const std::vector<std::string>& column_names(self) const
```

Parameters

None

Returns

const std::vector<std::string>& Borrowed list of names.

Notes

Returns the current labels used to address fields, slots, rows, or depth items.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.column_names();
```

Output

```
["sales"]
```

20.1.5 defined

Signature

```
bool defined(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object owns a concrete payload that can be used safely in later operations.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.defined();
```

Output

```
true
```

20.1.6 depth

Signature

```
std::int64_t depth(self) const
```

Parameters

None

Returns

std::int64_t Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.depth();
```

Output

```
2
```

20.1.7 empty

Signature

```
bool empty(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object has no rows, entries, slots, or depth items.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.empty();
```

Output

```
false
```

20.1.8 `frame`

Signature

```
DataFrame frame(self, std::int64_t index) const
```

Parameters

`index` : `std::int64_t` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.frame(0);
```

Output

```
sales
10.0
20.0
```

20.1.9 frames

Signature

```
const std::vector<DataFrame>& frames(self) const
```

Parameters

None

Returns

`const std::vector<DataFrame>&` Borrowed collection of frames.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.frames();
```

Output

```
[frame0, frame1]
```

20.1.10 head

Signature

```
Atlas head(self, std::int64_t n = 5) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

Returns

`Atlas` Value produced by this call.

Notes

Returns the first `n` frames from the atlas depth axis.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.head(1);
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.11 iloc

Signature

```
DataFrame iloc(self, std::int64_t index) const
```

Parameters

`index` : `std::int64_t` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.iloc(0);
```

Output

```
sales
10.0
20.0
```

20.1.12 kindelize

Signature

```
pluss::kindle::Archive kindelize(self) const
```

Parameters

None

Returns

`pluss::kindle::Archive` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

See also

- `pluss::kindle::Archive kindelize(self, const pluss::kindle::KindelizePolicy& policy) const`

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.kindelize();
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

20.1.13 kindelize

Signature

```
pluss::kindle::Archive kindelize(self, const pluss::kindle::KindelizePolicy& policy)␣
↪const
```

Parameters

`policy` : `const pluss::kindle::KindelizePolicy&` See the signature for the supported argument form.

Returns

`pluss::kindle::Archive` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

See also

- `pluss::kindle::Archive kindelize(self) const`

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.kindelize();
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

20.1.14 `loc`

Signature

```
DataFrame loc(self, const pluss::Timeline& label) const
```

Parameters

`label` : `const pluss::Timeline&` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- DataFrame loc(self, std::string_view label) const
- DataFrame loc(self, std::int64_t label) const

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto labeled = pluss::table::Atlas({f0, f1}, pluss::table::Thread(pluss::make_note({
↪"train", "test"})));
auto out = labeled.loc("test");
```

Output

```
sales
10.0
20.0
```

20.1.15 loc

Signature

```
DataFrame loc(self, std::int64_t label) const
```

Parameters

label : std::int64_t See the signature for the supported argument form.

Returns

DataFrame Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- DataFrame loc(self, std::string_view label) const
- DataFrame loc(self, const pluss::Timeline& label) const

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
```

(continues on next page)

(continued from previous page)

```
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto labeled = pluss::table::Atlas({f0, f1}, pluss::table::Thread(pluss::make_note({
↪"train", "test"})));
auto out = labeled.loc("test");
```

Output

```
sales
10.0
20.0
```

20.1.16 loc

Signature

```
DataFrame loc(self, std::string_view label) const
```

Parameters

`label` : `std::string_view` See the signature for the supported argument form.

Returns

`DataFrame` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- `DataFrame loc(self, std::int64_t label) const`
- `DataFrame loc(self, const pluss::Timeline& label) const`

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto labeled = pluss::table::Atlas({f0, f1}, pluss::table::Thread(pluss::make_note({
↪"train", "test"})));
auto out = labeled.loc("test");
```

Output

```
sales
10.0
20.0
```

20.1.17 map_frames

Signature

```
Atlas map_frames(self, const std::function<DataFrame(const DataFrame&)>& fn) const
```

Parameters

`fn` : `const std::function<DataFrame(const DataFrame&)>&` See the signature for the supported argument form.

Returns

`Atlas` Value produced by this call.

Notes

Applies the same function to each frame and returns the transformed atlas.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.map_frames([](const pluss::table::DataFrame& frame) { return frame.
↪head(1, false); });
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.18 ncols

Signature

```
std::int64_t ncols(self) const
```

Parameters

None

Returns

std::int64_t Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.ncols();
```

Output

```
2
```

20.1.19 nrows

Signature

```
std::int64_t nrows(self) const
```

Parameters

None

Returns

std::int64_t Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.nrows();
```

Output

```
2
```

20.1.20 plot

Signature

```
DataFramePlotAccessor plot(self, std::int64_t frame_index = 0) const
```

Parameters

`frame_index` : `std::int64_t` See the signature for the supported argument form.

Returns

`DataFramePlotAccessor` Value produced by this call.

Notes

This opens the plotting accessor for the current data object.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto fig = atlas.plot(0).line("sales");
```

Output

```
Figure(line)
```

20.1.21 relabel_depth

Signature

```
Atlas relabel_depth(self, const Thread& labels) const
```

Parameters

`labels` : `const Thread&` See the signature for the supported argument form.

Returns

`Atlas` Value produced by this call.

Notes

Replaces the depth-label axis with the supplied labels while keeping frame contents unchanged.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto labels = pluss::table::Thread(pluss::make_note({"baseline", "stress"}));
auto out = atlas.relabel_depth(labels);
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.22 show

Signature

```
void show(self, const display::DisplayOptions& options =
```

Parameters

`options` : `const display::DisplayOptions&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

See also

- `void show(self, std::ostream& os, const display::DisplayOptions& options =`

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

atlas.show();
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.23 show

Signature

```
void show(self, std::ostream& os, const display::DisplayOptions& options =
```

Parameters

`os` : `std::ostream&` See the signature for the supported argument form.

`options` : `const display::DisplayOptions&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

See also

- `void show(self, const display::DisplayOptions& options =`

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

atlas.show();
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.24 slice_frames

Signature

```
Atlas slice_frames(self, std::int64_t start, std::int64_t stop) const
```

Parameters

`start` : `std::int64_t` Inclusive starting position of the slice.

`stop` : `std::int64_t` Exclusive ending position of the slice.

Returns

`Atlas` Value produced by this call.

Notes

Returns a contiguous depth slice `[start, stop)` from the atlas.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.slice_frames(0, 1);
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.25 `sort_depth`

Signature

```
Atlas sort_depth(self, bool ascending = true, bool nulls_last = true) const
```

Parameters

`ascending` : `bool` See the signature for the supported argument form.

`nulls_last` : `bool` See the signature for the supported argument form.

Returns

`Atlas` Value produced by this call.

Notes

Sorts frames by their current depth labels.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});
```

(continues on next page)

(continued from previous page)

```
auto labeled = pluss::table::Atlas({f0, f1}, pluss::table::Thread(pluss::make_note({"test
↪", "train"})));
auto out = labeled.sort_depth(true, true);
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.26 squeeze

Signature

```
DataFrame squeeze(self) const
```

Parameters

None

Returns

`DataFrame` Value produced by this call.

Notes

Collapses a depth-1 atlas back into a single `DataFrame`.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.squeeze();
```

Output

```
sales
10.0
20.0
```

20.1.27 `tabelize`

Signature

```
static Atlas tabelize(const pluss::kindle::Archive& archive)
```

Parameters

`archive` : `const pluss::kindle::Archive&` See the signature for the supported argument form.

Returns

`Atlas` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

See also

- `static Atlas tabelize(const pluss::kindle::Archive& archive, const pluss::kindle::TabelizePolicy& policy)`

Examples

```
using namespace pluss::kindle::literals;
auto c0 = pluss::kindle::Catalog({"sales"_k = pluss::kindle::Stream(pluss::make_series(
↪{10.0, 20.0}))});
auto c1 = pluss::kindle::Catalog({"sales"_k = pluss::kindle::Stream(pluss::make_series(
↪{30.0, 40.0}))});
auto archive = pluss::kindle::Archive({c0, c1});
auto out = pluss::table::Atlas::tabelize(archive);
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.28 `tabelize`

Signature

```
static Atlas tabelize(const pluss::kindle::Archive& archive, const␣
↪pluss::kindle::TabelizePolicy& policy)
```

Parameters

`archive` : `const pluss::kindle::Archive&` See the signature for the supported argument form.

`policy` : `const pluss::kindle::TabelizePolicy&` See the signature for the supported argument form.

Returns

`Atlas` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

See also

- `static Atlas tabelize(const pluss::kindle::Archive& archive)`

Examples

```
using namespace pluss::kindle::literals;
auto c0 = pluss::kindle::Catalog({"sales"_k = pluss::kindle::Stream(pluss::make_series(
↪{10.0, 20.0}))});
auto c1 = pluss::kindle::Catalog({"sales"_k = pluss::kindle::Stream(pluss::make_series(
↪{30.0, 40.0}))});
auto archive = pluss::kindle::Archive({c0, c1});
auto out = pluss::table::Atlas::tabelize(archive);
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.29 `tail`

Signature

```
Atlas tail(self, std::int64_t n = 5) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

Returns

`Atlas` Value produced by this call.

Notes

Returns the last `n` frames from the atlas depth axis.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.tail(1);
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.30 `to_string`

Signature

```
std::string to_string(self, const display::DisplayOptions& options =
```

Parameters

`options` : `const display::DisplayOptions&` See the signature for the supported argument form.

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
```

(continues on next page)

(continued from previous page)

```
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.to_string();
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

20.1.31 unique

Signature

```
bool unique(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the object satisfies the uniqueness constraint expected by its model, such as distinct labels or keys.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = atlas.unique();
```

Output

```
true
```

CHAPTER

TWENTYONE

KINDLE MODEL GUIDE

21.1 When To Use Kindle Types

The kindle model is stream-first:

- `Stream`: one typed vector plus optional validity mask and case labels
- `Catalog`: named collection of streams
- `Archive`: depth stack of catalogs

This is the right model when case alignment and stream-native transforms matter more than table presentation.

21.2 Stream Basics

```
auto metric = pluss::kindle::Stream(
    pluss::make_series({10.0, 20.0, 30.0}),
    std::nullopt,
    pluss::table::Thread(pluss::make_note({"cs0", "cs1", "cs2"})));

metric = metric.with_meta("source", "demo").with_meta("unit", "km");

auto cleaned = metric.fillna(0.0).clip(0.0, 35.0);
auto filtered = cleaned.filter(cleaned.as_series().gt(15.0));
```

21.3 Catalog Basics

```
using namespace pluss::kindle::literals;

auto id = pluss::kindle::Stream(pluss::make_series({1, 2, 3}));
auto city = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"}));
auto value = pluss::kindle::Stream(pluss::make_series({10.0, 15.0, 20.0}));

auto catalog = pluss::kindle::Catalog({
    "id"_k = id,
    "city"_k = city,
    "value"_k = value,
});

catalog.select({"id", "value"}).show();
catalog.sort("value").show();
```

21.4 Text And Similarity Helpers

```
auto text_catalog = pluss::kindle::Catalog({
    "text"_k = pluss::kindle::Stream(pluss::make_note({
        "heavy rain on road",
        "clear weather downtown",
        "storm warning issued",
    })),
});

auto clean = text_catalog.text_preprocess("text");
auto keywords = text_catalog.extract_keywords("text", 5);
auto tfidf = text_catalog.tfidf("text");
```

21.5 Archive Basics

```
auto c0 = catalog;
auto c1 = catalog.rename({{"value", "value_test"}});
auto depth = pluss::kindle::Stream(pluss::make_note({"train", "test"}));

auto archive = pluss::kindle::Archive({c0, c1}, depth);

auto first = archive.catalog(0);
auto mapped = archive.map_catalogs([](const pluss::kindle::Catalog& c) {
  return c.head(2);
});
```

21.6 Convert Back To Table Model

```
pluss::kindle::TabelizePolicy policy;
policy.align = pluss::kindle::AlignPolicy::Outer;
policy.index_mode = pluss::kindle::IndexMode::Positional;

auto df = catalog.tabelize(policy);
auto atlas = archive.tabelize(policy);
```

CHAPTER

TWENTYTWO

STREAM API REFERENCE

CHAPTER

TWENTYTHREE

PRACTICAL STREAM API REFERENCE

23.1 API Reference Style

This page documents the full public `Stream` surface for the Kindle model.

23.1.1 abs

Signature

```
Stream abs(self) const
```

Parameters

None

Returns

`Stream` Value produced by this call.

Notes

Returns a numeric stream whose values are the absolute values of the current numeric payload.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.abs();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.2 as_note

Signature

```
const pluss::Note& as_note(self) const
```

Parameters

None

Returns

`const pluss::Note&` Value produced by this call.

Notes

Interprets or converts the current payload as a note/text stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"}));

auto out = stream.as_note();
```

Output

```
Note(["Accra", "Tema", "Kumasi"])
```

23.1.3 as_series

Signature

```
const pluss::Series& as_series(self) const
```

Parameters

None

Returns

`const pluss::Series&` Value produced by this call.

Notes

Interprets or converts the current payload as a numeric series stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.as_series();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.4 as_timeindex

Signature

```
const pluss::TimeIndex& as_timeindex(self) const
```

Parameters

None

Returns

const pluss::TimeIndex& Value produced by this call.

Notes

Interprets or converts the current payload as a time-index stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_timeindex({"2024-01-01T09:10:00Z", "2024-
↪01-01T09:40:00Z"}));

auto out = stream.as_timeindex();
```

Output

```
Timeline([...])
```

23.1.5 as_timeline

Signature

```
const pluss::Timeline& as_timeline(self) const
```

Parameters

None

Returns

const pluss::Timeline& Value produced by this call.

Notes

Interprets or converts the current payload as a timeline stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪01-01T09:40:00Z", "2024-01-01T10:05:00Z"}));

auto out = stream.as_timeline();
```

Output

```
Timeline([...])
```

23.1.6 astype

Signature

```
Stream astype(self, pluss::codem::ScalarType dtype) const
```

Parameters

`dtype` : `pluss::codem::ScalarType` See the signature for the supported argument form.

Returns

`Stream` Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.astype(pluss::codem::ScalarType::Float64);
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.7 bfill

Signature

```
Stream bfill(self) const
```

Parameters

`None`

Returns

`Stream` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.bfill();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.8 cases

Signature

```
const std::optional<pluss::table::Thread>& cases(self) const
```

Parameters

None

Returns

const std::optional<pluss::table::Thread>& Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.cases();
```

Output

```
["cs0", "cs1", "cs2"]
```

23.1.9 cast

Signature

```
Stream cast(self, pluss::table::ThreadCastTarget target, std::optional
↪<pluss::codem::ScalarType> series_dtype = std::nullopt) const
```

Parameters

target : pluss::table::ThreadCastTarget See the signature for the supported argument form.

series_dtype : std::optional<pluss::codem::ScalarType> See the signature for the supported argument form.

Returns

`Stream` Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_note({"1.0", "2.0", "3.0"}));

auto out = stream.cast(pluss::table::ThreadCastTarget::Series,␣
↪pluss::codem::ScalarType::Float64);
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.10 clear_cases

Signature

```
Stream clear_cases(self) const
```

Parameters

`None`

Returns

`Stream` Value produced by this call.

Notes

Returns a stream with its case labels removed.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.clear_cases();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.11 clear_cases_

Signature

```
Stream& clear_cases_(self)
```

Parameters

None

Returns

Stream& Value produced by this call.

Notes

Removes the stream case labels in place.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

stream.clear_cases_();
```

23.1.12 clear_validity_mask

Signature

```
Stream clear_validity_mask(self) const
```

Parameters

None

Returns

Stream Value produced by this call.

Notes

Returns a stream with the validity mask removed, so all entries are treated as valid again.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.clear_validity_mask();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.13 clear_validity_mask_

Signature

```
Stream& clear_validity_mask_(self)
```

Parameters

None

Returns

Stream& Value produced by this call.

Notes

Removes the validity mask in place, so all entries are treated as valid again.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

stream.clear_validity_mask_();
```

23.1.14 clip

Signature

```
Stream clip(self, scalar min_value, scalar max_value) const
```

Parameters

min_value : scalar See the signature for the supported argument form.

max_value : scalar See the signature for the supported argument form.

Returns

Stream Value produced by this call.

Notes

Clamps numeric stream values to the supplied lower and upper bounds.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.clip(0.0, 25.0);
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.15 defined

Signature

```
bool defined(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object owns a concrete payload that can be used safely in later operations.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.defined();
```

Output

```
true
```

23.1.16 drop_meta

Signature

```
Stream drop_meta(self, std::string_view key) const
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

Stream Value produced by this call.

Notes

Returns a stream with one metadata key removed.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));
stream = stream.with_meta("unit", "km");

auto out = stream.drop_meta("unit");
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.17 drop_meta_

Signature

```
Stream& drop_meta_(self, std::string_view key)
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

Stream& Value produced by this call.

Notes

Removes one metadata key in place.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));
stream = stream.with_meta("unit", "km");

stream.drop_meta_("unit");
```

23.1.18 dropna

Signature

```
Stream dropna(self) const
```

Parameters

None

Returns

Stream Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.dropna();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.19 dtype_name

Signature

```
std::string dtype_name(self) const
```

Parameters

None

Returns

std::string Rendered string result.

Notes

Returns the scalar dtype name used by the current numeric payload.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.dtype_name();
```

Output

```
Float64
```

23.1.20 exp

Signature

```
Stream exp(self) const
```

Parameters

None

Returns

Stream Value produced by this call.

Notes

Applies the elementwise exponential to a numeric stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.exp();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.21 ffill

Signature

```
Stream ffill(self) const
```

Parameters

None

Returns

Stream Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.ffill();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.22 fillna

Signature

```
Stream fillna(self, const char* value) const
```

Parameters

value : const char* See the signature for the supported argument form.

Returns

Stream Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- Stream fillna(self, scalar value) const
- Stream fillna(self, std::string_view value) const
- Stream fillna(self, const pluss::Timeline& value) const
- Stream fillna(self, const pluss::TimeIndex& value) const

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"}));

auto out = stream.fillna("Unknown");
```

Output

```
Note(["Accra", "Tema", "Kumasi"])
```

23.1.23 fillna

Signature

```
Stream fillna(self, const pluss::TimeIndex& value) const
```

Parameters

value : const pluss::TimeIndex& See the signature for the supported argument form.

Returns

Stream Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- Stream fillna(self, scalar value) const
- Stream fillna(self, std::string_view value) const
- Stream fillna(self, const char* value) const
- Stream fillna(self, const pluss::Timeline& value) const

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_timeindex({"2024-01-01T09:10:00Z", "2024-
↪01-01T09:40:00Z"}));

auto out = stream.fillna(pluss::make_timeindex("2024-01-01T00:00:00Z"));
```

Output

```
Note(["Accra", "Tema", "Kumasi"])
```

23.1.24 fillna

Signature

```
Stream fillna(self, const pluss::Timeline& value) const
```

Parameters

`value` : `const pluss::Timeline&` See the signature for the supported argument form.

Returns

`Stream` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `Stream fillna(self, scalar value) const`
- `Stream fillna(self, std::string_view value) const`
- `Stream fillna(self, const char* value) const`
- `Stream fillna(self, const pluss::TimeIndex& value) const`

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_timeline({"2024-01-01T09:10:00Z", "2024-
↪01-01T09:40:00Z", "2024-01-01T10:05:00Z"}));

auto out = stream.fillna(pluss::make_timeline("2024-01-01T00:00:00Z"));
```

Output

```
Note(["Accra", "Tema", "Kumasi"])
```

23.1.25 fillna

Signature

```
Stream fillna(self, scalar value) const
```

Parameters

`value` : `scalar` See the signature for the supported argument form.

Returns

`Stream` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `Stream fillna(self, std::string_view value) const`
- `Stream fillna(self, const char* value) const`
- `Stream fillna(self, const pluss::Timeline& value) const`
- `Stream fillna(self, const pluss::TimeIndex& value) const`

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.fillna(0.0);
```

Output

```
Note(["Accra", "Tema", "Kumasi"])
```

23.1.26 `fillna`

Signature

```
Stream fillna(self, std::string_view value) const
```

Parameters

`value` : `std::string_view` See the signature for the supported argument form.

Returns

`Stream` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `Stream fillna(self, scalar value) const`
- `Stream fillna(self, const char* value) const`
- `Stream fillna(self, const pluss::Timeline& value) const`
- `Stream fillna(self, const pluss::TimeIndex& value) const`

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"}));

auto out = stream.fillna("Unknown");
```

Output

```
Note(["Accra", "Tema", "Kumasi"])
```

23.1.27 filter

Signature

```
Stream filter(self, const pluss::Series& bool_mask) const
```

Parameters

bool_mask : const pluss::Series& See the signature for the supported argument form.

Returns

Stream Value produced by this call.

Notes

Keeps only the entries where the supplied boolean mask is true.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto out = stream.filter(mask);
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.28 from_thread

Signature

```
static Stream from_thread(const pluss::table::Thread& thread, std::optional
↪<pluss::table::Thread> cases = std::nullopt)
```

Parameters

thread : const pluss::table::Thread& See the signature for the supported argument form.

cases : std::optional<pluss::table::Thread> Case-label thread to attach to the current object.

Returns

`Stream` Value produced by this call.

Notes

Builds a Kindle stream from a table thread.

Examples

```
auto thread = pluss::table::Thread(pluss::make_series({10.0, 20.0, 30.0}));

auto out = pluss::kindle::Stream::from_thread(thread);
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.29 has_cases

Signature

```
bool has_cases(self) const
```

Parameters

None

Returns

`bool` Boolean status or membership result.

Notes

Reports whether the stream currently carries explicit case labels.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.has_cases();
```

Output

```
true
```

23.1.30 has_meta

Signature

```
bool has_meta(self, std::string_view key) const
```

Parameters

key : `std::string_view` Name of the target slot or stream.

Returns

`bool` Boolean status or membership result.

Notes

Reports whether a metadata key exists on the stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

stream = stream.with_meta("unit", "km");
auto out = stream.has_meta("unit");
```

Output

```
true
```

23.1.31 has_validity_mask

Signature

```
bool has_validity_mask(self) const
```

Parameters

None

Returns

`bool` Boolean status or membership result.

Notes

Reports whether the stream currently carries a validity mask.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.has_validity_mask();
```

Output

```
true
```

23.1.32 head

Signature

```
Stream head(self, std::int64_t n) const
```

Parameters

n : std::int64_t Number of rows, entries, or depth items to keep in the preview.

Returns

Stream Value produced by this call.

Notes

Returns the first n entries of the stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.head();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.33 isnull

Signature

```
Stream isnull(self) const
```

Parameters

None

Returns

Stream Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.isnull();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.34 kind

Signature

```
StreamKind kind(self) const
```

Parameters

None

Returns

StreamKind Value produced by this call.

Notes

Returns which payload kind this stream currently stores, such as Series, Note, Timeline, or TimeIndex.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.kind();
```

Output

```
Series
```

23.1.35 log

Signature

```
Stream log(self) const
```

Parameters

None

Returns

Stream Value produced by this call.

Notes

Applies the elementwise natural logarithm to a numeric stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.log();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.36 max

Signature

```
Stream max(self) const
```

Parameters

None

Returns

`Stream` Value produced by this call.

Notes

Returns the maximum value of a numeric stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.max();
```

Output

```
Series([20.0])
```

23.1.37 mean

Signature

```
Stream mean(self) const
```

Parameters

None

Returns

`Stream` Value produced by this call.

Notes

Returns the mean value of a numeric stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.mean();
```

Output

```
Series([20.0])
```

23.1.38 meta

Signature

```
const std::unordered_map<std::string, std::string>& meta(self) const
```

Parameters

None

Returns

const std::unordered_map<std::string, std::string>& Value produced by this call.

Notes

Returns the value stored under one metadata key.

See also

- std::optional<std::string> meta(self, std::string_view key) const

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

stream = stream.with_meta("unit", "km");
auto out = stream.meta("unit");
```

Output

```
km
```

23.1.39 meta

Signature

```
std::optional<std::string> meta(self, std::string_view key) const
```

Parameters

key : `std::string_view` Name of the target slot or stream.

Returns

`std::optional<std::string>` Value produced by this call.

Notes

Returns the value stored under one metadata key.

See also

- `const std::unordered_map<std::string, std::string>& meta(self) const`

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

stream = stream.with_meta("unit", "km");
auto out = stream.meta("unit");
```

Output

```
km
```

23.1.40 `min`

Signature

```
Stream min(self) const
```

Parameters

None

Returns

`Stream` Value produced by this call.

Notes

Returns the minimum value of a numeric stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.min();
```

Output

```
Series([20.0])
```

23.1.41 notnull

Signature

```
Stream notnull(self) const
```

Parameters

None

Returns

Stream Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.notnull();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.42 show

Signature

```
void show(self, std::ostream& os) const
```

Parameters

os : std::ostream& See the signature for the supported argument form.

Returns

void Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

stream.show(std::cout);
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.43 size

Signature

```
std::int64_t size(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.size();
```

Output

```
3
```

23.1.44 slice

Signature

```
Stream slice(self, std::int64_t start, std::int64_t stop) const
```

Parameters

`start` : `std::int64_t` Inclusive starting position of the slice.

`stop` : `std::int64_t` Exclusive ending position of the slice.

Returns

`Stream` Value produced by this call.

Notes

Returns a contiguous slice `[start, stop)` of the stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.slice(0, 2);
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.45 `std`

Signature

```
Stream std(self, bool unbiased = true) const
```

Parameters

`unbiased` : `bool` See the signature for the supported argument form.

Returns

`Stream` Value produced by this call.

Notes

Returns the standard deviation of a numeric stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.std(true);
```

Output

```
Series([20.0])
```

23.1.46 `sum`

Signature

```
Stream sum(self) const
```

Parameters

None

Returns

Stream Value produced by this call.

Notes

Returns the sum of a numeric stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.sum();
```

Output

```
Series([20.0])
```

23.1.47 tail

Signature

```
Stream tail(self, std::int64_t n) const
```

Parameters

n : std::int64_t Number of rows, entries, or depth items to keep in the preview.

Returns

Stream Value produced by this call.

Notes

Returns the last n entries of the stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.tail();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.48 take

Signature

```
Stream take(self, std::span<const std::int64_t> indices) const
```

Parameters

indices : std::span<const std::int64_t> See the signature for the supported argument form.

Returns

Stream Value produced by this call.

Notes

Returns the entries at the requested integer positions.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

std::vector<std::int64_t> picks{0, 2};
auto out = stream.take(picks);
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.49 to_json

Signature

```
std::string to_json(self) const
```

Parameters

None

Returns

std::string Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.to_json();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.50 to_string

Signature

```
std::string to_string(self) const
```

Parameters

None

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.to_string();
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.51 to_thread

Signature

```
pluss::table::Thread to_thread(self) const
```

Parameters

None

Returns

`pluss::table::Thread` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

See also

- pluss::table::Thread to_thread(self, std::int64_t start, std::int64_t stop) const

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.to_thread();
```

Output

```
[10.0, 20.0, 30.0]
```

23.1.52 to_thread

Signature

```
pluss::table::Thread to_thread(self, std::int64_t start, std::int64_t stop) const
```

Parameters

start : std::int64_t Inclusive starting position of the slice.

stop : std::int64_t Exclusive ending position of the slice.

Returns

pluss::table::Thread Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

See also

- pluss::table::Thread to_thread(self) const

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.to_thread(0, 2);
```

Output

```
[10.0, 20.0, 30.0]
```

23.1.53 unique

Signature

```
bool unique(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the object satisfies the uniqueness constraint expected by its model, such as distinct labels or keys.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.unique();
```

Output

```
true
```

23.1.54 validity_mask

Signature

```
const std::optional<pluss::Series>& validity_mask(self) const
```

Parameters

None

Returns

const std::optional<pluss::Series>& Value produced by this call.

Notes

Returns the current validity mask as a boolean series.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.validity_mask();
```

Output

```
[true, false, true]
```

23.1.55 var

Signature

```
Stream var(self, bool unbiased = true) const
```

Parameters

unbiased : bool See the signature for the supported argument form.

Returns

Stream Value produced by this call.

Notes

Returns the variance of a numeric stream.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.var(true);
```

Output

```
Series([20.0])
```

23.1.56 with_cases

Signature

```
Stream with_cases(self, const pluss::table::Thread& cases) const
```

Parameters

cases : const pluss::table::Thread& Case-label thread to attach to the current object.

Returns

Stream Value produced by this call.

Notes

Returns a new stream with the supplied case labels attached.

Examples

```
auto cases = pluss::table::Thread(pluss::make_note({"cs0", "cs1", "cs2"}));
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.with_cases(cases);
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.57 with_cases_

Signature

```
Stream& with_cases_(self, const pluss::table::Thread& cases)
```

Parameters

`cases` : `const pluss::table::Thread&` Case-label thread to attach to the current object.

Returns

`Stream&` Value produced by this call.

Notes

Attaches the supplied case labels in place.

Examples

```
auto cases = pluss::table::Thread(pluss::make_note({"cs0", "cs1", "cs2"}));
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

stream.with_cases_(cases);
```

23.1.58 with_meta

Signature

```
Stream with_meta(self, std::initializer_list<std::pair<std::string_view, std::string_
↪view>> items) const
```

Parameters

`items` : `std::initializer_list<std::pair<std::string_view, std::string_view>>` See the signature for the supported argument form.

Returns

`Stream` Value produced by this call.

Notes

Returns a new stream with one metadata key/value attached.

See also

- `Stream with_meta(self, std::string key, std::string value) const`

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.with_meta("unit", "km");
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.59 with_meta

Signature

```
Stream with_meta(self, std::string key, std::string value) const
```

Parameters

`key` : `std::string` Name of the target slot or stream.

`value` : `std::string` See the signature for the supported argument form.

Returns

`Stream` Value produced by this call.

Notes

Returns a new stream with one metadata key/value attached.

See also

- `Stream with_meta(self, std::initializer_list<std::pair<std::string_view, std::string_view>> items) const`

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.with_meta("unit", "km");
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.60 with_meta_

Signature

```
Stream& with_meta_(self, std::initializer_list<std::pair<std::string_view, std::string_
↪view>> items)
```

Parameters

`items` : `std::initializer_list<std::pair<std::string_view, std::string_view>>` See the signature for the supported argument form.

Returns

`Stream&` Value produced by this call.

Notes

Adds or updates one metadata key/value in place.

See also

- `Stream& with_meta_(self, std::string key, std::string value)`

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

stream.with_meta_("unit", "km");
```

23.1.61 `with_meta_`

Signature

```
Stream& with_meta_(self, std::string key, std::string value)
```

Parameters

`key` : `std::string` Name of the target slot or stream.

`value` : `std::string` See the signature for the supported argument form.

Returns

`Stream&` Value produced by this call.

Notes

Adds or updates one metadata key/value in place.

See also

- `Stream& with_meta_(self, std::initializer_list<std::pair<std::string_view, std::string_view>> items)`

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

stream.with_meta_("unit", "km");
```

23.1.62 with_validity_mask

Signature

```
Stream with_validity_mask(self, const pluss::Series& mask) const
```

Parameters

mask : const pluss::Series& See the signature for the supported argument form.

Returns

Stream Value produced by this call.

Notes

Returns a new stream with the supplied validity mask attached.

Examples

```
auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = stream.with_validity_mask(mask);
```

Output

```
Series([10.0, 20.0, 30.0])
```

23.1.63 with_validity_mask_

Signature

```
Stream& with_validity_mask_(self, const pluss::Series& mask)
```

Parameters

mask : const pluss::Series& See the signature for the supported argument form.

Returns

Stream& Value produced by this call.

Notes

Attaches the supplied validity mask in place.

Examples

```
auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

stream.with_validity_mask_(mask);
```

CHAPTER

TWENTYFOUR

CATALOG API REFERENCE

CHAPTER

TWENTYFIVE

PRACTICAL CATALOG API REFERENCE

25.1 API Reference Style

This page documents the full public `Catalog` surface for named stream collections.

25.1.1 add_text_features

Signature

```
Catalog add_text_features(self, std::string_view field) const
```

Parameters

`field` : `std::string_view` Name of the target stream in the catalog.

Returns

`Catalog` Value produced by this call.

Notes

This is part of the text-processing surface for note-backed or text-oriented data.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "text"_k = pluss::kindle::Stream(pluss::make_note({
        "heavy rain on road",
        "clear weather downtown",
        "storm warning issued",
    })),
});

auto out = ct.add_text_features("text");
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.2 aggregate_text_stats

Signature

```
Catalog aggregate_text_stats(self, std::string_view field, std::string_view stat_type)␣
↪const
```

Parameters

`field` : `std::string_view` Name of the target stream in the catalog.

`stat_type` : `std::string_view` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

This is part of the text-processing surface for note-backed or text-oriented data.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "text"_k = pluss::kindle::Stream(pluss::make_note({
        "heavy rain on road",
        "clear weather downtown",
        "storm warning issued",
    })),
});

auto out = ct.aggregate_text_stats("text", "mean");
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

(continues on next page)

(continued from previous page)

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.3 apply

Signature

```
Catalog apply(self, std::string_view field, const std::function<Stream(const Stream&)>&
↪func) const
```

Parameters

`field` : `std::string_view` Name of the target stream in the catalog.

`func` : `const std::function<Stream(const Stream&)>&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Applies a function to one named stream and returns the updated catalog.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.apply("metric", [](const pluss::kindle::Stream& s) { return s.clip(0.0, 25.
↪0); });
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.4 apply_

Signature

```
Catalog& apply_(self, std::string_view field, const std::function<Stream(const Stream&)>&
↪ func)
```

Parameters

`field` : `std::string_view` Name of the target stream in the catalog.

`func` : `const std::function<Stream(const Stream&)>&` See the signature for the supported argument form.

Returns

`Catalog&` Value produced by this call.

Notes

Applies a function to one named stream in place.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.apply_("metric", [](const pluss::kindle::Stream& s) { return s.clip(0.0, 25.0); });
```

25.1.5 apply_all

Signature

```
Catalog apply_all(self, const std::function<Stream(const Stream&)>& fn) const
```

Parameters

`fn` : `const std::function<Stream(const Stream&)>&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Applies the same function to every stream and returns the updated catalog.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.apply_all([](const pluss::kindle::Stream& s) { return s.kind() ==␣
↪pluss::kindle::StreamKind::Series ? s.clip(0.0, 25.0) : s; });
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.6 apply_all_

Signature

```
Catalog& apply_all_(self, const std::function<Stream(const Stream&)>& fn)
```

Parameters

`fn` : `const std::function<Stream(const Stream&)>&` See the signature for the supported argument form.

Returns

`Catalog&` Value produced by this call.

Notes

Applies the same function to every stream in place.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});
```

(continues on next page)

(continued from previous page)

```
ct.apply_all_([](const pluss::kindle::Stream& s) { return s.kind() ==␣
↪pluss::kindle::StreamKind::Series ? s.clip(0.0, 25.0) : s; });
```

25.1.7 astype

Signature

```
Catalog astype(self, std::initializer_list<std::string_view> keys,␣
↪pluss::codem::ScalarType dtype) const
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

dtype : pluss::codem::ScalarType See the signature for the supported argument form.

Returns

Catalog Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.astype({"metric"}, pluss::codem::ScalarType::Float64);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.8 at

Signature

```
Stream at(self, std::string_view key) const
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

Stream Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.at("metric");
```

Output

```
Series([10.0, 20.0, 30.0])
```

25.1.9 begin

Signature

```
const_iterator begin(self) const
```

Parameters

None

Returns

const_iterator Value produced by this call.

Notes

Exposes iterator boundaries so the object can be traversed with a range-based loop or manual iteration.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

for (const auto& key : ct) {
  (void)key;
}
```

25.1.10 bfill

Signature

```
Catalog bfill(self, std::initializer_list<std::string_view> keys =
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

Catalog Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.bfill();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
```

(continues on next page)

(continued from previous page)

```
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.11 cast_note

Signature

```
Catalog cast_note(self, std::initializer_list<std::string_view> keys) const
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

Catalog Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.cast_note({"metric"});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.12 cast_series

Signature

```
Catalog cast_series(self, std::initializer_list<std::string_view> keys, std::optional
↪<pluss::codem::ScalarType> dtype = std::nullopt) const
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

dtype : std::optional<pluss::codem::ScalarType> See the signature for the supported argument form.

Returns

Catalog Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
using namespace pluss::kindle::literals;
auto ct = pluss::kindle::Catalog({"metric"_k = pluss::kindle::Stream(pluss::make_note({
↪"10.0", "20.0", "30.0"}))});

auto out = ct.cast_series({"metric"}, pluss::codem::ScalarType::Float64);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.13 cast_timeindex

Signature

```
Catalog cast_timeindex(self, std::initializer_list<std::string_view> keys) const
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

`Catalog` Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.cast_timeindex({"metric"});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.14 `cast_timeline`

Signature

```
Catalog cast_timeline(self, std::initializer_list<std::string_view> keys) const
```

Parameters

`keys` : `std::initializer_list<std::string_view>` Collection of slot or stream names to keep, drop, or rewrite together.

Returns

`Catalog` Value produced by this call.

Notes

This changes the semantic or numeric type so later operations route through the correct implementation path.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.cast_timeline({"metric"});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.15 compute_similarity

Signature

```
Catalog compute_similarity(self, std::string_view field1, std::string_view field2,␣
↪std::string_view method = "cosine") const
```

Parameters

`field1` : `std::string_view` See the signature for the supported argument form.

`field2` : `std::string_view` See the signature for the supported argument form.

`method` : `std::string_view` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

This is part of the text-processing surface for note-backed or text-oriented data.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "text"_k = pluss::kindle::Stream(pluss::make_note({
        "heavy rain on road",
```

(continues on next page)

(continued from previous page)

```
        "clear weather downtown",
        "storm warning issued",
    })),
});

auto out = ct.compute_similarity("text", "text", "cosine");
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.16 count

Signature

```
std::int64_t count(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.count();
```

Output

```
3
```

25.1.17 defined

Signature

```
bool defined(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object owns a concrete payload that can be used safely in later operations.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.defined();
```

Output

```
true
```

25.1.18 display

Signature

```
void display(self) const
```

Parameters

None

Returns

void Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.display();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.19 drop

Signature

```
Catalog drop(self, const std::vector<std::string>& field_names) const
```

Parameters

`field_names` : `const std::vector<std::string>&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Removes the named streams and keeps the remaining catalog structure intact.

See also

- `Catalog drop(self, std::string_view field_name) const`
- `Catalog drop(self, std::initializer_list<std::string_view> keys) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
```

(continues on next page)

(continued from previous page)

```
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

std::vector<std::string> names{"city"};
auto out = ct.drop(names);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.20 drop

Signature

```
Catalog drop(self, std::initializer_list<std::string_view> keys) const
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

Catalog Value produced by this call.

Notes

Removes the named streams and keeps the remaining catalog structure intact.

See also

- Catalog drop(self, std::string_view field_name) const
- Catalog drop(self, const std::vector<std::string>& field_names) const

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});
```

(continues on next page)

(continued from previous page)

```
auto out = ct.drop({"city"});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.21 drop

Signature

```
Catalog drop(self, std::string_view field_name) const
```

Parameters

`field_name` : `std::string_view` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Removes the named streams and keeps the remaining catalog structure intact.

See also

- `Catalog drop(self, const std::vector<std::string>& field_names) const`
- `Catalog drop(self, std::initializer_list<std::string_view> keys) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.drop("city");
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.22 dropna

Signature

```
Catalog dropna(self, std::initializer_list<std::string_view> keys =
```

Parameters

`keys` : `std::initializer_list<std::string_view>` Collection of slot or stream names to keep, drop, or rewrite together.

Returns

`Catalog` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.dropna();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.23 empty

Signature

```
bool empty(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object has no rows, entries, slots, or depth items.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.empty();
```

Output

```
false
```

25.1.24 end

Signature

```
const_iterator end(self) const
```

Parameters

None

Returns

const_iterator Value produced by this call.

Notes

Exposes iterator boundaries so the object can be traversed with a range-based loop or manual iteration.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

for (const auto& key : ct) {
  (void)key;
}
```

25.1.25 extract_keywords

Signature

```
Catalog extract_keywords(self, std::string_view field, int top_n = 10) const
```

Parameters

`field` : `std::string_view` Name of the target stream in the catalog.

`top_n` : `int` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

This is part of the text-processing surface for note-backed or text-oriented data.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "text"_k = pluss::kindle::Stream(pluss::make_note({
        "heavy rain on road",
        "clear weather downtown",
        "storm warning issued",
    })),
});

auto out = ct.extract_keywords("text", 5);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
```

(continues on next page)

(continued from previous page)

```
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.26 `ffill`

Signature

```
Catalog ffill(self, std::initializer_list<std::string_view> keys =
```

Parameters

`keys` : `std::initializer_list<std::string_view>` Collection of slot or stream names to keep, drop, or rewrite together.

Returns

`Catalog` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.ffill();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.27 fillna

Signature

```
Catalog fillna(self, const char* value, std::initializer_list<std::string_view> keys =
```

Parameters

value : const char* See the signature for the supported argument form.

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

Catalog Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- Catalog fillna(self, scalar value, std::initializer_list<std::string_view> keys =
- Catalog fillna(self, std::string_view value, std::initializer_list<std::string_view> keys =
- Catalog fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> keys =
- Catalog fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> keys =

Examples

```
using namespace pluss::kindle::literals;
auto ct = pluss::kindle::Catalog({"city"_k = pluss::kindle::Stream(pluss::make_note({
↪"Accra", "Tema", "Kumasi"}))});

auto out = ct.fillna("Unknown", {"city"});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.28 `fillna`

Signature

```
Catalog fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_
↪view> keys =
```

Parameters

`value` : `const pluss::TimeIndex&` See the signature for the supported argument form.

`keys` : `std::initializer_list<std::string_view>` Collection of slot or stream names to keep, drop, or rewrite together.

Returns

`Catalog` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `Catalog fillna(self, scalar value, std::initializer_list<std::string_view> keys =`
- `Catalog fillna(self, std::string_view value, std::initializer_list<std::string_view> keys =`
- `Catalog fillna(self, const char* value, std::initializer_list<std::string_view> keys =`
- `Catalog fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> keys =`

Examples

```
using namespace pluss::kindle::literals;
auto ct = pluss::kindle::Catalog({"city"_k = pluss::kindle::Stream(pluss::make_note({
↪"Accra", "Tema", "Kumasi"}))});

auto out = ct.fillna("Unknown", {"city"});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.29 fillna

Signature

```
Catalog fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_
↪view> keys =
```

Parameters

value : const pluss::Timeline& See the signature for the supported argument form.

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

Catalog Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- Catalog fillna(self, scalar value, std::initializer_list<std::string_view> keys =
- Catalog fillna(self, std::string_view value, std::initializer_list<std::string_view> keys =
- Catalog fillna(self, const char* value, std::initializer_list<std::string_view> keys =
- Catalog fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> keys =

Examples

```
using namespace pluss::kindle::literals;
auto ct = pluss::kindle::Catalog({"city"_k = pluss::kindle::Stream(pluss::make_note({
↪"Accra", "Tema", "Kumasi"}))});

auto out = ct.fillna("Unknown", {"city"});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.30 `fillna`

Signature

```
Catalog fillna(self, scalar value, std::initializer_list<std::string_view> keys =
```

Parameters

`value` : `scalar` See the signature for the supported argument form.

`keys` : `std::initializer_list<std::string_view>` Collection of slot or stream names to keep, drop, or rewrite together.

Returns

`Catalog` Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- `Catalog fillna(self, std::string_view value, std::initializer_list<std::string_view> keys =`
- `Catalog fillna(self, const char* value, std::initializer_list<std::string_view> keys =`
- `Catalog fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> keys =`
- `Catalog fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> keys =`

Examples

```
using namespace pluss::kindle::literals;
auto ct = pluss::kindle::Catalog({"city"_k = pluss::kindle::Stream(pluss::make_note({
↪"Accra", "Tema", "Kumasi"}))});

auto out = ct.fillna("Unknown", {"city"});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.31 fillna

Signature

```
Catalog fillna(self, std::string_view value, std::initializer_list<std::string_view>␣
↪keys =
```

Parameters

value : std::string_view See the signature for the supported argument form.

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

Catalog Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

See also

- Catalog fillna(self, scalar value, std::initializer_list<std::string_view> keys =
- Catalog fillna(self, const char* value, std::initializer_list<std::string_view> keys =
- Catalog fillna(self, const pluss::Timeline& value, std::initializer_list<std::string_view> keys =
- Catalog fillna(self, const pluss::TimeIndex& value, std::initializer_list<std::string_view> keys =

Examples

```
using namespace pluss::kindle::literals;
auto ct = pluss::kindle::Catalog({"city"_k = pluss::kindle::Stream(pluss::make_note({
↪"Accra", "Tema", "Kumasi"}))});

auto out = ct.fillna("Unknown", {"city"});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.32 filter

Signature

```
Catalog filter(self, const pluss::Series& condition) const
```

Parameters

condition : const pluss::Series& See the signature for the supported argument form.

Returns

Catalog Value produced by this call.

Notes

Keeps only the rows where the supplied mask stream is true.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto out = ct.filter(mask);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.33 filter_by_text

Signature

```
Catalog filter_by_text(self, std::string_view field, std::string_view pattern) const
```

Parameters

field : std::string_view Name of the target stream in the catalog.

pattern : std::string_view See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

This is part of the text-processing surface for note-backed or text-oriented data.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "text"_k = pluss::kindle::Stream(pluss::make_note({
        "heavy rain on road",
        "clear weather downtown",
        "storm warning issued",
    })),
});

auto out = ct.filter_by_text("text", "rain");
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.34 `from_json`

Signature

```
static Catalog from_json(std::string_view json_text)
```

Parameters

`json_text` : `std::string_view` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Builds a catalog from JSON input using the PlussMic JSON loader route.

Examples

```
auto out = pluss::kindle::Catalog::from_json(R"([{"id":1,"city":"Accra"},{"id":2,"city":
↪"Tema"}])");
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.35 get

Signature

```
std::optional<Stream> get(self, std::string_view key) const
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

std::optional<Stream> Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.get("metric");
```

Output

```
Series([10.0, 20.0, 30.0])
```

25.1.36 get_stream

Signature

```
std::optional<Stream> get_stream(self, std::string_view key) const
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

std::optional<Stream> Value produced by this call.

Notes

Returns one named stream from the catalog.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.get_stream("metric");
```

Output

```
Series([10.0, 20.0, 30.0])
```

25.1.37 group_by

Signature

```
std::unordered_map<std::string, Catalog> group_by(self, std::string_view key_field) const
```

Parameters

key_field : std::string_view See the signature for the supported argument form.

Returns

std::unordered_map<std::string, Catalog> Value produced by this call.

Notes

Splits the catalog into sub-catalogs keyed by the distinct values in the grouping stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
```

(continues on next page)

(continued from previous page)

```
});

auto out = ct.group_by("city");
```

Output

```
{"Accra": Catalog(...), "Tema": Catalog(...)}
```

25.1.38 has

Signature

```
bool has(self, std::string_view key) const
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

bool Boolean status or membership result.

Notes

Checks whether a named stream exists.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.has("metric");
```

Output

```
true
```

25.1.39 has_stream

Signature

```
bool has_stream(self, std::string_view key) const
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

bool Boolean status or membership result.

Notes

Checks whether a named stream exists.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.has_stream("metric");
```

Output

```
true
```

25.1.40 head

Signature

```
Catalog head(self, std::int64_t n) const
```

Parameters

n : std::int64_t Number of rows, entries, or depth items to keep in the preview.

Returns

Catalog Value produced by this call.

Notes

Returns the first n rows across every stream in the catalog.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
```

(continues on next page)

(continued from previous page)

```
});

auto out = ct.head(2);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.41 `iloc`

Signature

```
Catalog iloc(self, std::int64_t row) const
```

Parameters

`row` : `std::int64_t` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- `Catalog iloc(self, std::int64_t start, std::int64_t stop) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.iloc(1);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.42 `iloc`

Signature

```
Catalog iloc(self, std::int64_t start, std::int64_t stop) const
```

Parameters

`start` : `std::int64_t` Inclusive starting position of the slice.

`stop` : `std::int64_t` Exclusive ending position of the slice.

Returns

`Catalog` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- `Catalog iloc(self, std::int64_t row) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.iloc(0, 2);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

(continues on next page)

(continued from previous page)

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.43 info

Signature

```
void info(self) const
```

Parameters

None

Returns

void Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.info();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.44 isnull

Signature

```
Catalog isnull(self, std::initializer_list<std::string_view> keys =
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

Catalog Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.isnull();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.45 keys

Signature

```
const std::vector<std::string>& keys(self) const
```

Parameters

None

Returns

const std::vector<std::string>& Borrowed list of names.

Notes

Returns the current labels used to address fields, slots, rows, or depth items.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.keys();
```

Output

```
["id", "metric", "city"]
```

25.1.46 kindelize

Signature

```
static Catalog kindelize(const pluss::table::DataFrame& frame, const KindelizePolicy&␣
↪policy =
```

Parameters

`frame` : `const pluss::table::DataFrame&` See the signature for the supported argument form.

`policy` : `const KindelizePolicy&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto df = pluss::table::DataFrame({
    {"id", pluss::table::Thread(pluss::make_series({1, 2, 3}))},
    {"sales", pluss::table::Thread(pluss::make_series({100.0, 120.0, 90.0}))},
    {"city", pluss::table::Thread(pluss::make_note({"Accra", "Tema", "Kumasi"}))},
});

auto out = pluss::kindle::Catalog::kindelize(df);
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.47 load

Signature

```
static Catalog load(std::string_view source_type, std::string_view filepath)
```

Parameters

`source_type` : `std::string_view` Storage format selector such as `"csv"`, `"xlsx"`, `"json"`, or `"parquet"`.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load(std::string_view source_type, std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::kindle::Catalog::load("csv", "path/to/data.csv");
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.48 load

Signature

```
static Catalog load(std::string_view source_type, std::string_view filepath, const␣
↪pluss::loader::Config& config)
```

Parameters

`source_type` : `std::string_view` Storage format selector such as `"csv"`, `"xlsx"`, `"json"`, or `"parquet"`.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load(std::string_view source_type, std::string_view filepath)`

Examples

```
auto out = pluss::kindle::Catalog::load("csv", "path/to/data.csv");
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.49 `load_csv`

Signature

```
static Catalog load_csv(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`

Examples

```
auto out = pluss::kindle::Catalog::load_csv("path/to/data.csv");
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.50 load_csv

Signature

```
static Catalog load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions&␣
↪options)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`options` : `const pluss::loader::ReadCsvOptions&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load_csv(std::string_view filepath)`

Examples

```
pluss::loader::ReadCsvOptions options;
auto out = pluss::kindle::Catalog::load_csv("path/to/data.csv", options);
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.51 load_csv_with_key

Signature

```
static Catalog load_csv_with_key(std::string_view filepath, std::string_view key_field,␣
↪const pluss::loader::ReadCsvOptions& options =
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`key_field` : `std::string_view` See the signature for the supported argument form.

`options` : `const pluss::loader::ReadCsvOptions&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

Examples

```
auto out = pluss::kindle::Catalog::load_csv_with_key("path/to/data.csv", "id");
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.52 `load_excel`

Signature

```
static Catalog load_excel(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)`

Examples

```
auto out = pluss::kindle::Catalog::load_excel("path/to/data.xlsx");
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.53 load_excel

Signature

```
static Catalog load_excel(std::string_view filepath, const␣
↪pluss::loader::ReadExcelOptions& options)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`options` : `const pluss::loader::ReadExcelOptions&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load_excel(std::string_view filepath)`

Examples

```
pluss::loader::ReadExcelOptions options;
auto out = pluss::kindle::Catalog::load_excel("path/to/data.xlsx", options);
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.54 load_json

Signature

```
static Catalog load_json(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load_json(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::kindle::Catalog::load_json("path/to/data.json");
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.55 load_json

Signature

```
static Catalog load_json(std::string_view filepath, const pluss::loader::Config& config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load_json(std::string_view filepath)`

Examples

```
auto out = pluss::kindle::Catalog::load_json("path/to/data.json", {"nrows", 16});
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.56 load_parquet

Signature

```
static Catalog load_parquet(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load_parquet(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::kindle::Catalog::load_parquet("path/to/data.parquet");
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.57 load_parquet

Signature

```
static Catalog load_parquet(std::string_view filepath, const pluss::loader::Config&␣
↪config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load_parquet(std::string_view filepath)`

Examples

```
auto out = pluss::kindle::Catalog::load_parquet("path/to/data.parquet", {"nrows", 16});
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.58 load_txt

Signature

```
static Catalog load_txt(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load_txt(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::kindle::Catalog::load_txt("path/to/data.txt");
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.59 `load_txt`

Signature

```
static Catalog load_txt(std::string_view filepath, const pluss::loader::Config& config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Catalog load_txt(std::string_view filepath)`

Examples

```
auto out = pluss::kindle::Catalog::load_txt("path/to/data.txt", {"nrows", 16});
```

Output

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.60 masked_select

Signature

```
Catalog masked_select(self, const pluss::Series& mask) const
```

Parameters

mask : const pluss::Series& See the signature for the supported argument form.

Returns

Catalog Value produced by this call.

Notes

Keeps only the rows where the supplied mask stream is true.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto out = ct.masked_select(mask);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.61 max

Signature

```
Stream max(self, std::string_view field) const
```

Parameters

field : std::string_view Name of the target stream in the catalog.

Returns

`Stream` Value produced by this call.

Notes

Computes the maximum value of one named numeric stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.max("metric");
```

Output

```
Series([20.0])
```

25.1.62 mean

Signature

```
Stream mean(self, std::string_view field) const
```

Parameters

`field` : `std::string_view` Name of the target stream in the catalog.

Returns

`Stream` Value produced by this call.

Notes

Computes the mean value of one named numeric stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.mean("metric");
```

Output

```
Series([20.0])
```

25.1.63 merge

Signature

```
Catalog merge(self, const Catalog& other, std::string_view on, std::string_view how =
↪"inner") const
```

Parameters

other : const Catalog& See the signature for the supported argument form.

on : std::string_view See the signature for the supported argument form.

how : std::string_view See the signature for the supported argument form.

Returns

Catalog Value produced by this call.

Notes

Combines two catalogs by matching rows on a key stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

using namespace pluss::kindle::literals;
auto right = pluss::kindle::Catalog({"id"_k = pluss::kindle::Stream(pluss::make_series(
↪{1, 2, 3})), "score"_k = pluss::kindle::Stream(pluss::make_series({0.9, 0.7, 0.8}))});
auto out = ct.merge(right, "id", "inner");
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.64 min

Signature

```
Stream min(self, std::string_view field) const
```

Parameters

`field` : `std::string_view` Name of the target stream in the catalog.

Returns

`Stream` Value produced by this call.

Notes

Computes the minimum value of one named numeric stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.min("metric");
```

Output

```
Series([20.0])
```

25.1.65 nfields

Signature

```
std::int64_t nfields(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.nfields();
```

Output

```
3
```

25.1.66 note

Signature

```
Catalog note(self) const
```

Parameters

None

Returns

Catalog Value produced by this call.

Notes

Returns one named stream interpreted as a note/text stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.note();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

(continues on next page)

(continued from previous page)

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.67 notnull

Signature

```
Catalog notnull(self, std::initializer_list<std::string_view> keys =
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

Catalog Value produced by this call.

Notes

This is part of the missing-data cleanup path and is usually applied before summaries, grouping, or export.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.notnull();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.68 nstreams

Signature

```
std::int64_t nstreams(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.nstreams();
```

Output

```
3
```

25.1.69 query

Signature

```
Catalog query(self, const QueryFn& fn) const
```

Parameters

`fn` : `const QueryFn&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Keeps only the rows selected by the supplied row-wise query function or expression.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.query([](const pluss::kindle::Catalog& c) { return c.stream("metric").as_
↪series().gt(15.0); });
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.70 `rename`

Signature

```
Catalog rename(self, const std::unordered_map<std::string, std::string>& mapping) const
```

Parameters

`mapping` : `const std::unordered_map<std::string, std::string>&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Renames one or more streams without changing their values.

See also

- `Catalog rename(self, std::initializer_list<std::pair<std::string_view, std::string_view>> mapping) const`
- `Catalog rename(self, std::string_view from, std::string_view to) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

std::unordered_map<std::string, std::string> renames{{"metric", "distance_km"}};
auto out = ct.rename(renames);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.71 `rename`

Signature

```
Catalog rename(self, std::initializer_list<std::pair<std::string_view, std::string_view>>
↪ mapping) const
```

Parameters

`mapping` : `std::initializer_list<std::pair<std::string_view, std::string_view>>` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Renames one or more streams without changing their values.

See also

- `Catalog rename(self, std::string_view from, std::string_view to) const`
- `Catalog rename(self, const std::unordered_map<std::string, std::string>& mapping) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.rename({{"metric", "distance_km"}});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.72 `rename`

Signature

```
Catalog rename(self, std::string_view from, std::string_view to) const
```

Parameters

`from` : `std::string_view` See the signature for the supported argument form.

`to` : `std::string_view` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Renames one or more streams without changing their values.

See also

- `Catalog rename(self, std::initializer_list<std::pair<std::string_view, std::string_view>> mapping) const`
- `Catalog rename(self, const std::unordered_map<std::string, std::string>& mapping) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.rename("metric", "distance_km");
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.73 rename_

Signature

```
Catalog& rename_(self, std::string_view from, std::string_view to)
```

Parameters

`from` : `std::string_view` See the signature for the supported argument form.

`to` : `std::string_view` See the signature for the supported argument form.

Returns

`Catalog&` Value produced by this call.

Notes

Renames one or more streams in place without changing their values.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});
```

(continues on next page)

(continued from previous page)

```
ct.rename_("metric", "distance_km");
```

25.1.74 sample

Signature

```
Catalog sample(self, std::int64_t n, std::optional<std::uint64_t> random_state =␣
↪std::nullopt) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

`random_state` : `std::optional<std::uint64_t>` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Returns a random sample of rows across all streams.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.sample(2, 7);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.75 save_as

Signature

```
void save_as(self, std::string_view target_type, std::string_view filename, const␣
↪pluss::loader::Config& config =
```

Parameters

`target_type` : `std::string_view` See the signature for the supported argument form.

`filename` : `std::string_view` See the signature for the supported argument form.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the catalog using the explicitly supplied output format selector.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.save_as("json", "path/to/output.json");
```

Output

```
saved: out.*
```

25.1.76 save_csv

Signature

```
void save_csv(self, std::string_view filename) const
```

Parameters

`filename` : `std::string_view` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the catalog to CSV after aligning its streams into a table-like representation.

See also

- `void save_csv(self, std::string_view filename, const pluss::loader::Config& config) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.save_csv("path/to/output.csv");
```

Output

```
saved: out.*
```

25.1.77 save_csv

Signature

```
void save_csv(self, std::string_view filename, const pluss::loader::Config& config) const
```

Parameters

`filename` : `std::string_view` See the signature for the supported argument form.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the catalog to CSV after aligning its streams into a table-like representation.

See also

- `void save_csv(self, std::string_view filename) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
```

(continues on next page)

(continued from previous page)

```
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.save_csv("path/to/output.csv");
```

Output

```
saved: out.*
```

25.1.78 save_excel

Signature

```
void save_excel(self, std::string_view filename) const
```

Parameters

`filename` : `std::string_view` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the catalog to an Excel workbook after aligning its streams into a table-like representation.

See also

- `void save_excel(self, std::string_view filename, const pluss::loader::Config& config) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.save_excel("path/to/output.xlsx");
```

Output

```
saved: out.*
```

25.1.79 save_excel

Signature

```
void save_excel(self, std::string_view filename, const pluss::loader::Config& config)␣
↪const
```

Parameters

`filename` : `std::string_view` See the signature for the supported argument form.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the catalog to an Excel workbook after aligning its streams into a table-like representation.

See also

- `void save_excel(self, std::string_view filename) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.save_excel("path/to/output.xlsx");
```

Output

```
saved: out.*
```

25.1.80 save_json

Signature

```
void save_json(self, std::string_view filename) const
```

Parameters

`filename` : `std::string_view` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the catalog to JSON for interchange or later reload.

See also

- `void save_json(self, std::string_view filename, const pluss::loader::Config& config) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.save_json("path/to/output.json");
```

Output

```
saved: out.*
```

25.1.81 save_json

Signature

```
void save_json(self, std::string_view filename, const pluss::loader::Config& config)␣
↪const
```

Parameters

`filename` : `std::string_view` See the signature for the supported argument form.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the catalog to JSON for interchange or later reload.

See also

- `void save_json(self, std::string_view filename) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.save_json("path/to/output.json");
```

Output

```
saved: out.*
```

25.1.82 save_parquet

Signature

```
void save_parquet(self, std::string_view filename) const
```

Parameters

`filename` : `std::string_view` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the catalog to Parquet for compact typed storage.

See also

- `void save_parquet(self, std::string_view filename, const pluss::loader::Config& config) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.save_parquet("path/to/output.parquet");
```

Output

```
saved: out.*
```

25.1.83 save_parquet

Signature

```
void save_parquet(self, std::string_view filename, const pluss::loader::Config& config)␣
↪const
```

Parameters

`filename` : `std::string_view` See the signature for the supported argument form.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the catalog to Parquet for compact typed storage.

See also

- `void save_parquet(self, std::string_view filename) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.save_parquet("path/to/output.parquet");
```

Output

```
saved: out.*
```

25.1.84 save_txt

Signature

```
void save_txt(self, std::string_view filename) const
```

Parameters

`filename` : `std::string_view` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes a text rendering of the catalog for inspection or logging.

See also

- `void save_txt(self, std::string_view filename, const pluss::loader::Config& config) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.save_txt("path/to/output.txt");
```

Output

```
saved: out.*
```

25.1.85 `save_txt`

Signature

```
void save_txt(self, std::string_view filename, const pluss::loader::Config& config) const
```

Parameters

`filename` : `std::string_view` See the signature for the supported argument form.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes a text rendering of the catalog for inspection or logging.

See also

- `void save_txt(self, std::string_view filename) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.save_txt("path/to/output.txt");
```

Output

```
saved: out.*
```

25.1.86 `select`

Signature

```
Catalog select(self, const std::vector<std::string>& field_names) const
```

Parameters

`field_names` : `const std::vector<std::string>&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Keeps only the named streams and preserves their shared row alignment.

See also

- `Catalog select(self, std::initializer_list<std::string_view> field_names) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

std::vector<std::string> names{"id", "metric"};
auto out = ct.select(names);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.87 select

Signature

```
Catalog select(self, std::initializer_list<std::string_view> field_names) const
```

Parameters

`field_names` : `std::initializer_list<std::string_view>` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Keeps only the named streams and preserves their shared row alignment.

See also

- `Catalog select(self, const std::vector<std::string>& field_names) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.select({"id", "metric"});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

(continues on next page)

(continued from previous page)

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.88 `series`

Signature

```
Catalog series(self) const
```

Parameters

None

Returns

`Catalog` Value produced by this call.

Notes

Returns one named stream interpreted as a numeric series stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.series();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.89 `set`

Signature

```
Catalog set(self, std::string_view key, const Stream& value) const
```

Parameters

key : std::string_view Name of the target slot or stream.

value : const Stream& See the signature for the supported argument form.

Returns

Catalog Value produced by this call.

Notes

Adds or replaces one named stream and returns the updated catalog.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.set_stream("flag", pluss::kindle::Stream(pluss::make_series({1, 0, 1})));
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.90 set_

Signature

```
Catalog& set_(self, std::string_view key, const Stream& value)
```

Parameters

key : std::string_view Name of the target slot or stream.

value : const Stream& See the signature for the supported argument form.

Returns

`Catalog&` Value produced by this call.

Notes

Adds or replaces one named stream in place.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.set_stream_("flag", pluss::kindle::Stream(pluss::make_series({1, 0, 1})));
```

25.1.91 `set_stream`

Signature

```
Catalog set_stream(self, std::string_view key, const Stream& value) const
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

`value` : `const Stream&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Adds or replaces one named stream and returns the updated catalog.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.set_stream("flag", pluss::kindle::Stream(pluss::make_series({1, 0, 1})));
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.92 set_stream_

Signature

```
Catalog& set_stream_(self, std::string_view key, const Stream& value)
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

`value` : `const Stream&` See the signature for the supported argument form.

Returns

`Catalog&` Value produced by this call.

Notes

Adds or replaces one named stream in place.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.set_stream_("flag", pluss::kindle::Stream(pluss::make_series({1, 0, 1})));
```

25.1.93 set_streams

Signature

```
Catalog set_streams(self, std::initializer_list<NamedStream> items) const
```

Parameters

`items` : `std::initializer_list<NamedStream>` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Adds or replaces several named streams and returns the updated catalog.

See also

- `Catalog set_streams(self, std::initializer_list<std::pair<std::string_view, Stream>> items) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

using namespace pluss::kindle::literals;
auto out = ct.set_streams({
    "flag"_k = pluss::kindle::Stream(pluss::make_series({1, 0, 1})),
});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.94 `set_streams`

Signature

```
Catalog set_streams(self, std::initializer_list<std::pair<std::string_view, Stream>>␣
↪items) const
```

Parameters

`items` : `std::initializer_list<std::pair<std::string_view, Stream>>` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Adds or replaces several named streams and returns the updated catalog.

See also

- `Catalog set_streams(self, std::initializer_list<NamedStream> items) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.set_streams({
    {"flag", pluss::kindle::Stream(pluss::make_series({1, 0, 1}))},
});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.95 `set_streams_`

Signature

```
Catalog& set_streams_(self, std::initializer_list<NamedStream> items)
```

Parameters

`items` : `std::initializer_list<NamedStream>` See the signature for the supported argument form.

Returns

`Catalog&` Value produced by this call.

Notes

Adds or replaces several named streams in place.

See also

- `Catalog& set_streams_(self, std::initializer_list<std::pair<std::string_view, Stream>> items)`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

using namespace pluss::kindle::literals;
ct.set_streams_({
    "flag"_k = pluss::kindle::Stream(pluss::make_series({1, 0, 1})),
});
```

25.1.96 `set_streams_`

Signature

```
Catalog& set_streams_(self, std::initializer_list<std::pair<std::string_view, Stream>>␣
↪items)
```

Parameters

`items` : `std::initializer_list<std::pair<std::string_view, Stream>>` See the signature for the supported argument form.

Returns

`Catalog&` Value produced by this call.

Notes

Adds or replaces several named streams in place.

See also

- `Catalog& set_streams_(self, std::initializer_list<NamedStream> items)`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

ct.set_streams_({
    {"flag", pluss::kindle::Stream(pluss::make_series({1, 0, 1}))},
});
```

25.1.97 show

Signature

```
void show(self, std::ostream& os) const
```

Parameters

`os` : `std::ostream&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.show();
```

25.1.98 slice

Signature

```
Catalog slice(self, std::int64_t start, std::int64_t stop) const
```

Parameters

`start` : `std::int64_t` Inclusive starting position of the slice.

`stop` : `std::int64_t` Exclusive ending position of the slice.

Returns

`Catalog` Value produced by this call.

Notes

Returns a contiguous row slice `[start, stop)` across every stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.slice(0, 2);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.99 `sort`

Signature

```
Catalog sort(self, std::string_view by_field, bool ascending = true) const
```

Parameters

`by_field` : `std::string_view` See the signature for the supported argument form.

`ascending` : `bool` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Reorders rows using one stream as the sort key, while keeping the other streams aligned to the same row order.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.sort("metric", false);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.100 sort_by

Signature

```
Catalog sort_by(self, const std::vector<std::string>& fields, const std::vector<bool>&␣
↪ascending =
```

Parameters

`fields` : `const std::vector<std::string>&` See the signature for the supported argument form.

`ascending` : `const std::vector<bool>&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Reorders rows using multiple sort keys, while keeping all streams aligned.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
```

(continues on next page)

(continued from previous page)

```
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.sort_by({"city", "id"}, {true, false});
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.101 `stream`

Signature

```
Stream stream(self, std::string_view key) const
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

Returns

`Stream` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.stream("metric");
```

Output

```
Series([10.0, 20.0, 30.0])
```

25.1.102 streams

Signature

```
std::vector<Stream> streams(self) const
```

Parameters

None

Returns

`std::vector<Stream>` Materialized collection of stream objects.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.streams();
```

Output

```
[Stream(id), Stream(metric), Stream(city)]
```

25.1.103 sum

Signature

```
Stream sum(self, std::string_view field) const
```

Parameters

`field` : `std::string_view` Name of the target stream in the catalog.

Returns

`Stream` Value produced by this call.

Notes

Computes the sum of one named numeric stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.sum("metric");
```

Output

```
Series([20.0])
```

25.1.104 `tabelize`

Signature

```
pluss::table::DataFrame tabelize(self, const TabelizePolicy& policy =
```

Parameters

`policy` : `const TabelizePolicy&` See the signature for the supported argument form.

Returns

`pluss::table::DataFrame` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

pluss::kindle::TabelizePolicy policy;
policy.align = pluss::kindle::AlignPolicy::Inner;
auto out = ct.tabelize(policy);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

25.1.105 tail

Signature

```
Catalog tail(self, std::int64_t n) const
```

Parameters

n : std::int64_t Number of rows, entries, or depth items to keep in the preview.

Returns

Catalog Value produced by this call.

Notes

Returns the last n rows across every stream in the catalog.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.tail(2);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.106 take

Signature

```
Catalog take(self, std::span<const std::int64_t> indices) const
```

Parameters

indices : std::span<const std::int64_t> See the signature for the supported argument form.

Returns

Catalog Value produced by this call.

Notes

Returns the rows at the requested integer positions across every stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

std::vector<std::int64_t> picks{0, 2};
auto out = ct.take(picks);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.107 text_preprocess

Signature

```
Catalog text_preprocess(self, std::string_view field) const
```

Parameters

field : std::string_view Name of the target stream in the catalog.

Returns

`Catalog` Value produced by this call.

Notes

This is part of the text-processing surface for note-backed or text-oriented data.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "text"_k = pluss::kindle::Stream(pluss::make_note({
        "heavy rain on road",
        "clear weather downtown",
        "storm warning issued",
    })),
});

auto out = ct.text_preprocess("text");
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.108 `tfidf`

Signature

```
Catalog tfidf(self, std::string_view field) const
```

Parameters

`field` : `std::string_view` Name of the target stream in the catalog.

Returns

`Catalog` Value produced by this call.

Notes

This is part of the text-processing surface for note-backed or text-oriented data.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "text"_k = pluss::kindle::Stream(pluss::make_note({
        "heavy rain on road",
        "clear weather downtown",
        "storm warning issued",
    })),
});

auto out = ct.tfidf("text");
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.109 `timeindex`

Signature

```
Catalog timeindex(self) const
```

Parameters

None

Returns

`Catalog` Value produced by this call.

Notes

Returns one named stream interpreted as a time-index stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});
```

(continues on next page)

(continued from previous page)

```
auto out = ct.timeindex();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.110 `timeline`

Signature

```
Catalog timeline(self) const
```

Parameters

None

Returns

`Catalog` Value produced by this call.

Notes

Returns one named stream interpreted as a timeline stream.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.timeline();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

(continues on next page)

(continued from previous page)

```
out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.111 to_json

Signature

```
std::string to_json(self) const
```

Parameters

None

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.to_json();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.112 to_string

Signature

```
std::string to_string(self) const
```

Parameters

None

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.to_string();
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.113 `to_table`

Signature

```
pluss::table::DataFrame to_table(self, const TabelizePolicy& policy =
```

Parameters

`policy` : `const TabelizePolicy&` See the signature for the supported argument form.

Returns

`pluss::table::DataFrame` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
```

(continues on next page)

(continued from previous page)

```
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

pluss::kindle::TabelizePolicy policy;
policy.align = pluss::kindle::AlignPolicy::Inner;
auto out = ct.to_table(policy, true);
```

Output

```
id  sales  city
1   100.0  Accra
2   120.0  Tema
3    90.0  Kumasi
```

25.1.114 `transform`

Signature

```
Catalog transform(self, const std::function<Stream(const Stream&)>& fn) const
```

Parameters

`fn` : `const std::function<Stream(const Stream&)>&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Rewrites one stream, several streams, or all streams by applying a user function.

See also

- `Catalog transform(self, std::string_view field, const std::function<Stream(const Stream&)>& fn) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.transform([](const pluss::kindle::Stream& s) { return s.kind() ==␣
↪pluss::kindle::StreamKind::Series ? s.clip(0.0, 25.0) : s; });
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.115 transform

Signature

```
Catalog transform(self, std::string_view field, const std::function<Stream(const Stream&
↪)>& fn) const
```

Parameters

`field` : `std::string_view` Name of the target stream in the catalog.

`fn` : `const std::function<Stream(const Stream&)>&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Rewrites one stream, several streams, or all streams by applying a user function.

See also

- `Catalog transform(self, const std::function<Stream(const Stream&)>& fn) const`

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.transform("metric", [](const pluss::kindle::Stream& s) { return s.clip(0.0,
↪ 25.0); });
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

25.1.116 unique

Signature

```
bool unique(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the object satisfies the uniqueness constraint expected by its model, such as distinct labels or keys.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = ct.unique();
```

Output

```
true
```

25.1.117 where

Signature

```
Catalog where(self, const pluss::Series& condition) const
```

Parameters

`condition` : `const pluss::Series&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Keeps only the rows where the supplied mask stream is true.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto mask = pluss::make_series({true, false, true}, pluss::codem::ScalarType::Bool);
auto out = ct.where(mask);
```

Output

```
ct.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])

out.head():
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

CHAPTER

TWENTYSIX

ARCHIVE API REFERENCE

CHAPTER

TWENTYSEVEN

PRACTICAL ARCHIVE API REFERENCE

27.1 API Reference Style

This page documents the full public `Archive` surface for depth-stacked catalogs.

27.1.1 aggregate_over_catalogs

Signature

```
Catalog aggregate_over_catalogs(self, const std::function<Catalog(const std::vector
↪<Catalog>&)>& fn) const
```

Parameters

`fn` : `const std::function<Catalog(const std::vector<Catalog>&)>&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Reduces the full catalog stack to one output by applying an aggregation function across the contained catalogs.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.aggregate_over_catalogs([](const std::vector<pluss::kindle::Catalog>&␣
↪catalogs) { return catalogs.front(); });
```

Output

```
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

27.1.2 align_depth

Signature

```
Archive align_depth(self, const Stream& labels) const
```

Parameters

`labels` : `const Stream&` See the signature for the supported argument form.

Returns

`Archive` Value produced by this call.

Notes

Reorders catalogs so their depth labels match the supplied label order.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto labels = pluss::kindle::Stream(pluss::make_note({"baseline", "stress"}));
auto out = archive.align_depth(labels);
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

27.1.3 catalog

Signature

```
Catalog catalog(self, std::int64_t i) const
```

Parameters

`i` : `std::int64_t` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.catalog(0);
```

Output

```
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

27.1.4 `catalogs`

Signature

```
const std::vector<Catalog>& catalogs(self) const
```

Parameters

None

Returns

`const std::vector<Catalog>&` Borrowed collection of catalogs.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.catalogs();
```

Output

```
[Catalog(train), Catalog(test)]
```

27.1.5 defined

Signature

```
bool defined(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object owns a concrete payload that can be used safely in later operations.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.defined();
```

Output

```
true
```

27.1.6 depth

Signature

```
std::int64_t depth(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.depth();
```

Output

```
2
```

27.1.7 depth_labels

Signature

```
const std::optional<Stream>& depth_labels(self) const
```

Parameters

None

Returns

const std::optional<Stream>& Value produced by this call.

Notes

Returns the current labels used to address fields, slots, rows, or depth items.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.depth_labels();
```

Output

```
["train", "test"]
```

27.1.8 empty

Signature

```
bool empty(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object has no rows, entries, slots, or depth items.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
```

(continues on next page)

(continued from previous page)

```
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.empty();
```

Output

```
false
```

27.1.9 head

Signature

```
Archive head(self, std::int64_t n = 5) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

Returns

`Archive` Value produced by this call.

Notes

Returns the first `n` catalogs from the archive depth axis.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.head(1);
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

27.1.10 iloc

Signature

```
Catalog iloc(self, std::int64_t i) const
```

Parameters

i : std::int64_t See the signature for the supported argument form.

Returns

Catalog Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.iloc(0);
```

Output

```
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

27.1.11 kindelize

Signature

```
static Archive kindelize(const pluss::table::Atlas& atlas, const KindelizePolicy& policy␣
↪=
```

Parameters

atlas : const pluss::table::Atlas& See the signature for the supported argument form.

policy : const KindelizePolicy& See the signature for the supported argument form.

Returns

`Archive` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto f0 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({10.0, 20.0}))},
});
auto f1 = pluss::table::DataFrame({
    {"sales", pluss::table::Thread(pluss::make_series({30.0, 40.0}))},
});
auto atlas = pluss::table::Atlas({f0, f1});

auto out = pluss::kindle::Archive::kindelize(atlas);
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

27.1.12 `loc`

Signature

```
Catalog loc(self, const pluss::Timeline& label) const
```

Parameters

`label` : `const pluss::Timeline&` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- `Catalog loc(self, std::string_view label) const`
- `Catalog loc(self, std::int64_t label) const`

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
```

(continues on next page)

(continued from previous page)

```
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.loc("test");
```

Output

```
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

27.1.13 loc

Signature

```
Catalog loc(self, std::int64_t label) const
```

Parameters

`label` : `std::int64_t` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- `Catalog loc(self, std::string_view label) const`
- `Catalog loc(self, const pluss::Timeline& label) const`

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));
```

(continues on next page)

(continued from previous page)

```
auto out = archive.loc("test");
```

Output

```
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

27.1.14 loc

Signature

```
Catalog loc(self, std::string_view label) const
```

Parameters

`label` : `std::string_view` See the signature for the supported argument form.

Returns

`Catalog` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- `Catalog loc(self, std::int64_t label) const`
- `Catalog loc(self, const pluss::Timeline& label) const`

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.loc("test");
```

Output

```
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

27.1.15 map_catalogs

Signature

```
Archive map_catalogs(self, const std::function<Catalog(const Catalog&)>& fn) const
```

Parameters

`fn` : `const std::function<Catalog(const Catalog&)>&` See the signature for the supported argument form.

Returns

`Archive` Value produced by this call.

Notes

Applies the same function to each catalog and returns the transformed archive.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.map_catalogs([](const pluss::kindle::Catalog& catalog) { return␣
↪catalog.head(1); });
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

27.1.16 relabel_depth

Signature

```
Archive relabel_depth(self, const Stream& labels) const
```

Parameters

`labels` : `const Stream&` See the signature for the supported argument form.

Returns

`Archive` Value produced by this call.

Notes

Replaces the depth-label axis with the supplied labels while keeping catalog contents unchanged.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto labels = pluss::kindle::Stream(pluss::make_note({"baseline", "stress"}));
auto out = archive.relabel_depth(labels);
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

27.1.17 show

Signature

```
void show(self, std::ostream& os) const
```

Parameters

`os` : `std::ostream&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
```

(continues on next page)

(continued from previous page)

```
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

archive.show(std::cout);
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

27.1.18 slice_depth

Signature

```
Archive slice_depth(self, std::int64_t start, std::int64_t stop) const
```

Parameters

`start` : `std::int64_t` Inclusive starting position of the slice.

`stop` : `std::int64_t` Exclusive ending position of the slice.

Returns

`Archive` Value produced by this call.

Notes

Returns a contiguous depth slice `[start, stop)` from the archive.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.slice_depth(0, 1);
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

27.1.19 sort_depth

Signature

```
Archive sort_depth(self, bool ascending = true, bool nulls_last = true) const
```

Parameters

ascending : bool See the signature for the supported argument form.

nulls_last : bool See the signature for the supported argument form.

Returns

Archive Value produced by this call.

Notes

Sorts catalogs by their current depth labels.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.sort_depth(true, true);
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

27.1.20 tabelize

Signature

```
pluss::table::Atlas tabelize(self, const TabelizePolicy& policy =
```

Parameters

policy : const TabelizePolicy& See the signature for the supported argument form.

Returns

`pluss::table::Atlas` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

pluss::kindle::TabelizePolicy policy;
policy.align = pluss::kindle::AlignPolicy::Inner;
auto out = archive.tabelize(policy);
```

Output

```
frame0:
sales
10.0
20.0

frame1:
sales
30.0
40.0
```

27.1.21 `tail`

Signature

```
Archive tail(self, std::int64_t n = 5) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

Returns

`Archive` Value produced by this call.

Notes

Returns the last `n` catalogs from the archive depth axis.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.tail(1);
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

27.1.22 to_string

Signature

```
std::string to_string(self) const
```

Parameters

None

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
```

(continues on next page)

(continued from previous page)

```
↪"train", "test"})));

auto out = archive.to_string();
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

27.1.23 to_table

Signature

```
pluss::table::Atlas to_table(self, const TabelizePolicy& policy =
```

Parameters

`policy` : `const TabelizePolicy&` See the signature for the supported argument form.

Returns

`pluss::table::Atlas` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

pluss::kindle::TabelizePolicy policy;
policy.align = pluss::kindle::AlignPolicy::Inner;
auto out = archive.to_table(policy, true);
```

Output

```
frame0:
sales
10.0
20.0
```

(continues on next page)

(continued from previous page)

```
frame1:
sales
30.0
40.0
```

27.1.24 unique

Signature

```
bool unique(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the object satisfies the uniqueness constraint expected by its model, such as distinct labels or keys.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = archive.unique();
```

Output

```
true
```

CHAPTER

TWENTYEIGHT

BUNDLE MODEL GUIDE

28.1 When To Use Bundle Types

The bundle model is the heterogeneous record layer:

- `Slot`: sequence of heterogeneous Pluss values
- `Registry`: named set of slots
- `Aisle`: depth stack of registries

Use it when one field can hold different domain types, or when you want a lighter record/batch abstraction than `DataFrame`.

28.2 Slot

```
auto ids = pluss::bundle::Slot({
    pluss::make_series(1, pluss::codem::ScalarType::Int64),
    pluss::make_series(2, pluss::codem::ScalarType::Int64),
    pluss::make_series(3, pluss::codem::ScalarType::Int64),
});

ids.push_(pluss::make_series(4, pluss::codem::ScalarType::Int64));
auto even = ids.filter([](const pluss::bundle::Slot::Value& v) {
  return std::get<pluss::Series>(v).to_vec<std::int64_t>()[0] % 2 == 0;
});
```

28.3 Registry

```
auto cities = pluss::bundle::Slot({
    pluss::make_note("Accra"),
    pluss::make_note("Tema"),
    pluss::make_note("Kumasi"),
});

auto registry = pluss::bundle::Registry({
    {"id", ids},
    {"city", cities},
});

auto selected = registry.select({"id"});
```

(continues on next page)

(continued from previous page)

```
auto renamed = registry.rename({{"city", "location"}});
auto profiled = registry.type_profiles();
```

28.4 Aisle

```
auto train = registry;
auto test = registry.rename({{"city", "city_test"}});
auto labels = pluss::bundle::Slot({pluss::make_note("train"), pluss::make_note("test")});

auto aisle = pluss::bundle::Aisle({train, test}, labels);

auto first = aisle.head(1);
auto combined = aisle.concat_depth(first);
```

28.5 Kindle Bridge

```
auto stream = ids.to_kindle();
auto catalog = registry.to_kindle();
auto archive = aisle.to_kindle();

auto back_slot = pluss::bundle::Slot::from_kindle(stream);
auto back_registry = pluss::bundle::Registry::from_kindle(catalog);
auto back_aisle = pluss::bundle::Aisle::from_kindle(archive);
```

CHAPTER

TWENTYNINE

SLOT API REFERENCE

CHAPTER

THIRTY

PRACTICAL SLOT API REFERENCE

30.1 API Reference Style

This page documents the full public `Slot` surface for one-dimensional heterogeneous bundles.

30.1.1 as_kindle

Signature

```
pluss::kindle::Stream as_kindle(self) const
```

Parameters

None

Returns

`pluss::kindle::Stream` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.as_kindle();
```

Output

```
Series([10.0, 20.0, 30.0])
```

30.1.2 at

Signature

```
const Value& at(self, std::int64_t i) const
```

Parameters

`i` : `std::int64_t` See the signature for the supported argument form.

Returns

`const Value&` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.at(0);
```

Output

```
Series(1)
```

30.1.3 concat

Signature

```
Slot concat(self, const Slot& other) const
```

Parameters

`other` : `const Slot&` See the signature for the supported argument form.

Returns

`Slot` Value produced by this call.

Notes

Appends the values from another slot and returns the combined slot.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto other = pluss::bundle::Slot({pluss::make_series(4), pluss::make_series(5)});
auto out = slot.concat(other);
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.4 defined

Signature

```
bool defined(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object owns a concrete payload that can be used safely in later operations.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.defined();
```

Output

```
true
```

30.1.5 empty

Signature

```
bool empty(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object has no rows, entries, slots, or depth items.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.empty();
```

Output

```
false
```

30.1.6 filter

Signature

```
Slot filter(self, const std::function<bool(const Value&)>& predicate) const
```

Parameters

`predicate` : `const std::function<bool(const Value&)>&` See the signature for the supported argument form.

Returns

`Slot` Value produced by this call.

Notes

Keeps only the slot values that satisfy the supplied predicate.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_note("ok"),␣
↪pluss::make_series(3)});

auto out = slot.filter([](const pluss::bundle::Slot::Value& value) { return std::holds_
↪alternative<pluss::Series>(value); });
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.7 from_kindle

Signature

```
static Slot from_kindle(const pluss::kindle::Stream& stream)
```

Parameters

`stream` : `const pluss::kindle::Stream&` See the signature for the supported argument form.

Returns

`Slot` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto stream = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0}));

auto out = pluss::bundle::Slot::from_kindle(stream);
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.8 head

Signature

```
Slot head(self, std::int64_t n) const
```

Parameters

n : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

Returns

`Slot` Value produced by this call.

Notes

Returns the first `n` values from the slot.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.head(2);
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.9 kindelize

Signature

```
pluss::kindle::Stream kindelize(self) const
```

Parameters

None

Returns

`pluss::kindle::Stream` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.kindelize();
```

Output

```
Series([10.0, 20.0, 30.0])
```

30.1.10 push

Signature

```
Slot push(self, const Value& value) const
```

Parameters

`value` : `const Value&` See the signature for the supported argument form.

Returns

`Slot` Value produced by this call.

Notes

Returns a new slot with one additional value appended.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.push(pluss::make_note("tail"));
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.11 push_

Signature

```
Slot& push_(self, const Value& value)
```

Parameters

`value` : `const Value&` See the signature for the supported argument form.

Returns

`Slot&` Value produced by this call.

Notes

Appends one additional value to the slot in place.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

slot.push_(pluss::make_note("tail"));
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.12 show

Signature

```
void show(self, std::ostream& os) const
```

Parameters

`os` : `std::ostream&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

slot.show(std::cout);
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.13 size

Signature

```
std::int64_t size(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.size();
```

Output

```
3
```

30.1.14 slice

Signature

```
Slot slice(self, std::int64_t start, std::int64_t stop) const
```

Parameters

`start` : `std::int64_t` Inclusive starting position of the slice.

`stop` : `std::int64_t` Exclusive ending position of the slice.

Returns

`Slot` Value produced by this call.

Notes

Returns a contiguous positional slice `[start, stop)` from the slot.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.slice(0, 2);
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.15 tail

Signature

```
Slot tail(self, std::int64_t n) const
```

Parameters

n : std::int64_t Number of rows, entries, or depth items to keep in the preview.

Returns

Slot Value produced by this call.

Notes

Returns the last n values from the slot.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.tail(2);
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.16 take

Signature

```
Slot take(self, std::span<const std::int64_t> indices) const
```

Parameters

indices : std::span<const std::int64_t> See the signature for the supported argument form.

Returns

`Slot` Value produced by this call.

Notes

Returns the values at the requested integer positions.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

std::vector<std::int64_t> picks{0, 2};
auto out = slot.take(picks);
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.17 to_json

Signature

```
std::string to_json(self) const
```

Parameters

None

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.to_json();
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.18 to_kindle

Signature

```
pluss::kindle::Stream to_kindle(self) const
```

Parameters

None

Returns

`pluss::kindle::Stream` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.to_kindle();
```

Output

```
Series([10.0, 20.0, 30.0])
```

30.1.19 `to_string`

Signature

```
std::string to_string(self) const
```

Parameters

None

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.to_string();
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.20 transform

Signature

```
Slot transform(self, const std::function<Value(const Value&)>& fn) const
```

Parameters

fn : const std::function<Value(const Value&)>& See the signature for the supported argument form.

Returns

Slot Value produced by this call.

Notes

Applies a value-wise transform to each slot entry and returns the updated slot.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.transform([](const pluss::bundle::Slot::Value& value) ->␣
↪pluss::bundle::Slot::Value { if (std::holds_alternative<pluss::Series>(value)) return␣
↪std::get<pluss::Series>(value).add(10); return value; });
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

30.1.21 type_counts

Signature

```
std::unordered_map<std::string, std::int64_t> type_counts(self) const
```

Parameters

None

Returns

std::unordered_map<std::string, std::int64_t> Value produced by this call.

Notes

Counts how many slot entries belong to each stored pluss type.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_note("ok"),␣
↪pluss::make_series(3)});

auto out = slot.type_counts();
```

Output

```
{"Series": 2, "Note": 1}
```

30.1.22 unique

Signature

```
bool unique(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the object satisfies the uniqueness constraint expected by its model, such as distinct labels or keys.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.unique();
```

Output

```
true
```

30.1.23 values

Signature

```
const std::vector<Value>& values(self) const
```

Parameters

None

Returns

`const std::vector<Value>&` Value produced by this call.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

Examples

```
auto slot = pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)});

auto out = slot.values();
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

CHAPTER

THIRTYONE

REGISTRY API REFERENCE

CHAPTER

THIRTYTWO

PRACTICAL REGISTRY API REFERENCE

32.1 API Reference Style

This page documents the full public `Registry` surface for named bundle slots.

32.1.1 `apply`

Signature

```
Registry apply(self, std::initializer_list<std::string_view> keys, const std::function
↪<Slot(const Slot&)>& fn) const
```

Parameters

`keys` : `std::initializer_list<std::string_view>` Collection of slot or stream names to keep, drop, or rewrite together.

`fn` : `const std::function<Slot(const Slot&)>&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Applies a function to one or more named slots and returns the updated registry.

See also

- `Registry apply(self, std::string_view key, const std::function<Slot(const Slot&)>& fn) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.apply({"ids"}, [](const pluss::bundle::Slot& slot) { return slot; });
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.2 apply

Signature

```
Registry apply(self, std::string_view key, const std::function<Slot(const Slot&)>& fn)␣
↪const
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

`fn` : `const std::function<Slot(const Slot&)>&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Applies a function to one or more named slots and returns the updated registry.

See also

- `Registry apply(self, std::initializer_list<std::string_view> keys, const std::function<Slot(const Slot&)>& fn) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.apply("ids", [](const pluss::bundle::Slot& slot) { return slot; });
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
```

(continues on next page)

(continued from previous page)

```
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.3 apply_

Signature

```
Registry& apply_(self, std::initializer_list<std::string_view> keys, const std::function
↪<Slot(const Slot&)>& fn)
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

fn : const std::function<Slot(const Slot&)>& See the signature for the supported argument form.

Returns

Registry& Value produced by this call.

Notes

Applies a function to one or more named slots in place.

See also

- Registry& apply_(self, std::string_view key, const std::function<Slot(const Slot&)>& fn)

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.apply_({"ids"}, [](const pluss::bundle::Slot& slot) { return slot; });
```

32.1.4 apply_

Signature

```
Registry& apply_(self, std::string_view key, const std::function<Slot(const Slot&)>& fn)
```

Parameters

key : std::string_view Name of the target slot or stream.

fn : const std::function<Slot(const Slot&)>& See the signature for the supported argument form.

Returns

Registry& Value produced by this call.

Notes

Applies a function to one or more named slots in place.

See also

- Registry& apply_(self, std::initializer_list<std::string_view> keys, const std::function<Slot(const Slot&)>& fn)

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.apply_("ids", [](const pluss::bundle::Slot& slot) { return slot; });
```

32.1.5 apply_all

Signature

```
Registry apply_all(self, const std::function<Slot(const Slot&)>& fn) const
```

Parameters

fn : const std::function<Slot(const Slot&)>& See the signature for the supported argument form.

Returns

Registry Value produced by this call.

Notes

Applies the same function to every slot and returns the updated registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.apply_all([](const pluss::bundle::Slot& slot) { return slot; });
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.6 as_kindle

Signature

```
pluss::kindle::Catalog as_kindle(self) const
```

Parameters

None

Returns

`pluss::kindle::Catalog` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.as_kindle();
```

Output

```
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

32.1.7 at

Signature

```
Slot at(self, std::string_view key) const
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

Slot Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.at("ids");
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

32.1.8 begin

Signature

```
const_iterator begin(self) const
```

Parameters

None

Returns

const_iterator Value produced by this call.

Notes

Exposes iterator boundaries so the object can be traversed with a range-based loop or manual iteration.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});
```

(continues on next page)

(continued from previous page)

```
for (const auto& key : rg) {
  (void)key;
}
```

32.1.9 clear

Signature

```
Registry clear(self) const
```

Parameters

None

Returns

Registry Value produced by this call.

Notes

Removes all slots and returns an empty registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.clear();
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.10 clear_

Signature

```
Registry& clear_(self)
```

Parameters

None

Returns

Registry& Value produced by this call.

Notes

Removes all slots in place.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.clear_();
```

32.1.11 combine

Signature

```
Registry combine(self, const Registry& other, std::string suffix = "_other") const
```

Parameters

other : const Registry& See the signature for the supported argument form.

suffix : std::string See the signature for the supported argument form.

Returns

Registry Value produced by this call.

Notes

Merges slots from another registry into this one, applying the collision suffix when keys overlap.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto other = pluss::bundle::Registry({{"flag", pluss::bundle::Slot({pluss::make_
↪series(true, pluss::codem::ScalarType::Bool), pluss::make_series(false,␣
↪pluss::codem::ScalarType::Bool), pluss::make_series(true,␣
```

(continues on next page)

(continued from previous page)

```
↪pluss::codem::ScalarType::Bool)})}});
auto out = rg.combine(other, "_rhs");
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.12 concat_values

Signature

```
Registry concat_values(self, std::string_view key, const Slot& other) const
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

`other` : `const Slot&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Appends extra values onto one named slot and returns the updated registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto extra = pluss::bundle::Slot({pluss::make_series(4), pluss::make_series(5)});
auto out = rg.concat_values("ids", extra);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
```

(continues on next page)

(continued from previous page)

```
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.13 concat_values_

Signature

```
Registry& concat_values_(self, std::string_view key, const Slot& other)
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

`other` : `const Slot&` See the signature for the supported argument form.

Returns

`Registry&` Value produced by this call.

Notes

Appends extra values onto one named slot in place.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto extra = pluss::bundle::Slot({pluss::make_series(4), pluss::make_series(5)});
rg.concat_values_("ids", extra);
```

32.1.14 defined

Signature

```
bool defined(self) const
```

Parameters

None

Returns

`bool` Boolean status or membership result.

Notes

Reports whether the current object owns a concrete payload that can be used safely in later operations.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.defined();
```

Output

```
true
```

32.1.15 drop

Signature

```
Registry drop(self, const std::vector<std::string>& keys) const
```

Parameters

`keys` : `const std::vector<std::string>&` Collection of slot or stream names to keep, drop, or rewrite together.

Returns

`Registry` Value produced by this call.

Notes

Removes the named slots and keeps the remaining registry structure intact.

See also

- `Registry drop(self, std::initializer_list<std::string_view> keys) const`
- `Registry drop(self, std::string_view key) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

std::vector<std::string> names{"city"};
auto out = rg.drop(names);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.16 drop

Signature

```
Registry drop(self, std::initializer_list<std::string_view> keys) const
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

Registry Value produced by this call.

Notes

Removes the named slots and keeps the remaining registry structure intact.

See also

- Registry drop(self, const std::vector<std::string>& keys) const
- Registry drop(self, std::string_view key) const

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.drop({"city"});
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
```

(continues on next page)

(continued from previous page)

```
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.17 drop

Signature

```
Registry drop(self, std::string_view key) const
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

Registry Value produced by this call.

Notes

Removes the named slots and keeps the remaining registry structure intact.

See also

- Registry drop(self, std::initializer_list<std::string_view> keys) const
- Registry drop(self, const std::vector<std::string>& keys) const

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.drop("city");
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.18 drop_empty_slots

Signature

```
Registry drop_empty_slots(self) const
```

Parameters

None

Returns

`Registry` Value produced by this call.

Notes

Removes slots whose payload is empty and returns the reduced registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.drop_empty_slots();
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.19 drop_empty_slots_

Signature

```
Registry& drop_empty_slots_(self)
```

Parameters

None

Returns

`Registry&` Value produced by this call.

Notes

Removes empty slots in place.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.drop_empty_slots_();
```

32.1.20 empty

Signature

```
bool empty(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the current object has no rows, entries, slots, or depth items.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.empty();
```

Output

```
false
```

32.1.21 end

Signature

```
const_iterator end(self) const
```

Parameters

None

Returns

const_iterator Value produced by this call.

Notes

Exposes iterator boundaries so the object can be traversed with a range-based loop or manual iteration.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

for (const auto& key : rg) {
  (void)key;
}
```

32.1.22 ensure_stream_compatible

Signature

```
void ensure_stream_compatible(self, std::string_view where = "Registry") const
```

Parameters

where : std::string_view See the signature for the supported argument form.

Returns

void Performs the side effect and returns no value.

Notes

Validates that the registry can be converted to a Kindle catalog without incompatible slot contents.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.ensure_stream_compatible("demo");
```

Output

```
no error
```

32.1.23 field_names

Signature

```
const std::vector<std::string>& field_names(self) const
```

Parameters

None

Returns

const std::vector<std::string>& Borrowed list of names.

Notes

Returns the current labels used to address fields, slots, rows, or depth items.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.field_names();
```

Output

```
["ids", "city"]
```

32.1.24 filter_values

Signature

```
Registry filter_values(self, std::string_view key, const std::function<bool(const␣
↪Slot::Value&)>& predicate) const
```

Parameters

key : std::string_view Name of the target slot or stream.

predicate : const std::function<bool(const Slot::Value&)>& See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Keeps only the values in one named slot that satisfy the supplied predicate.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.filter_values("ids", [](const pluss::bundle::Slot::Value& value) { return␣
↪std::holds_alternative<pluss::Series>(value); });
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.25 `filter_values_`

Signature

```
Registry& filter_values_(self, std::string_view key, const std::function<bool(const␣
↪Slot::Value&)>& predicate)
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

`predicate` : `const std::function<bool(const Slot::Value&)>&` See the signature for the supported argument form.

Returns

`Registry&` Value produced by this call.

Notes

Filters the values in one named slot in place.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.filter_values_("ids", [](const pluss::bundle::Slot::Value& value) { return std::holds_
↪alternative<pluss::Series>(value); });
```

32.1.26 from_kindle

Signature

```
static Registry from_kindle(const pluss::kindle::Catalog& catalog)
```

Parameters

`catalog` : `const pluss::kindle::Catalog&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
using namespace pluss::kindle::literals;

auto ct = pluss::kindle::Catalog({
    "id"_k = pluss::kindle::Stream(pluss::make_series({1, 2, 3})),
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0, 30.0})),
    "city"_k = pluss::kindle::Stream(pluss::make_note({"Accra", "Tema", "Kumasi"})),
});

auto out = pluss::bundle::Registry::from_kindle(catalog);
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.27 get

Signature

```
std::optional<Slot> get(self, std::string_view key) const
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

std::optional<Slot> Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.get("ids");
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

32.1.28 get_slot

Signature

```
std::optional<Slot> get_slot(self, std::string_view key) const
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

std::optional<Slot> Value produced by this call.

Notes

Returns one named slot from the registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
```

(continues on next page)

(continued from previous page)

```
↪pluss::make_note("Kumasi")})},
});

auto out = rg.get_slot("ids");
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

32.1.29 has

Signature

```
bool has(self, std::string_view key) const
```

Parameters

key : `std::string_view` Name of the target slot or stream.

Returns

`bool` Boolean status or membership result.

Notes

Checks whether a named slot exists.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.has("ids");
```

Output

```
true
```

32.1.30 has_all

Signature

```
bool has_all(self, std::initializer_list<std::string_view> keys) const
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

bool Boolean status or membership result.

Notes

Checks whether every requested slot name exists.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.has_all({"ids", "city"});
```

Output

```
true
```

32.1.31 has_any

Signature

```
bool has_any(self, std::initializer_list<std::string_view> keys) const
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

bool Boolean status or membership result.

Notes

Checks whether at least one requested slot name exists.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
```

(continues on next page)

(continued from previous page)

```
});

auto out = rg.has_any({"ids", "city"});
```

Output

```
true
```

32.1.32 has_slot

Signature

```
bool has_slot(self, std::string_view key) const
```

Parameters

key : std::string_view Name of the target slot or stream.

Returns

bool Boolean status or membership result.

Notes

Checks whether a named slot exists.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.has_slot("ids");
```

Output

```
true
```

32.1.33 head

Signature

```
Registry head(self, std::int64_t n) const
```

Parameters

n : std::int64_t Number of rows, entries, or depth items to keep in the preview.

Returns

Registry Value produced by this call.

Notes

Returns the first n values from every slot in the registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.head(2);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.34 iloc

Signature

```
Registry iloc(self, std::int64_t row) const
```

Parameters

row : std::int64_t See the signature for the supported argument form.

Returns

Registry Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- Registry iloc(self, std::int64_t start, std::int64_t stop) const

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.iloc(1);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.35 iloc

Signature

```
Registry iloc(self, std::int64_t start, std::int64_t stop) const
```

Parameters

`start` : `std::int64_t` Inclusive starting position of the slice.

`stop` : `std::int64_t` Exclusive ending position of the slice.

Returns

`Registry` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

See also

- Registry iloc(self, std::int64_t row) const

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
```

(continues on next page)

(continued from previous page)

```
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.iloc(0, 2);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.36 is_stream_compatible

Signature

```
bool is_stream_compatible(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the registry can be converted to a Kindle catalog without incompatible slot contents.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.is_stream_compatible();
```

Output

```
true
```

32.1.37 keys

Signature

```
const std::vector<std::string>& keys(self) const
```

Parameters

None

Returns

const std::vector<std::string>& Borrowed list of names.

Notes

Returns the current labels used to address fields, slots, rows, or depth items.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.keys();
```

Output

```
["ids", "city"]
```

32.1.38 kindelize

Signature

```
pluss::kindle::Catalog kindelize(self) const
```

Parameters

None

Returns

pluss::kindle::Catalog Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.kindelize();
```

Output

```
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

32.1.39 load

Signature

```
static Registry load(std::string_view source_type, std::string_view filepath)
```

Parameters

`source_type` : `std::string_view` Storage format selector such as `"csv"`, `"xlsx"`, `"json"`, or `"parquet"`.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load(std::string_view source_type, std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::bundle::Registry::load("csv", "path/to/data.csv");
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.40 load

Signature

```
static Registry load(std::string_view source_type, std::string_view filepath, const␣
↪pluss::loader::Config& config)
```

Parameters

`source_type` : `std::string_view` Storage format selector such as `"csv"`, `"xlsx"`, `"json"`, or `"parquet"`.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load(std::string_view source_type, std::string_view filepath)`

Examples

```
auto out = pluss::bundle::Registry::load("csv", "path/to/data.csv");
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.41 load_csv

Signature

```
static Registry load_csv(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`
- `static Registry load_csv(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::bundle::Registry::load_csv("path/to/data.csv");
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.42 load_csv

Signature

```
static Registry load_csv(std::string_view filepath, const pluss::loader::Config& config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_csv(std::string_view filepath)`
- `static Registry load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions& options)`

Examples

```
auto out = pluss::bundle::Registry::load_csv("path/to/data.csv", {"nrows", 16});
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.43 load_csv

Signature

```
static Registry load_csv(std::string_view filepath, const pluss::loader::ReadCsvOptions&␣
↪options)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`options` : `const pluss::loader::ReadCsvOptions&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_csv(std::string_view filepath)`
- `static Registry load_csv(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
pluss::loader::ReadCsvOptions options;
auto out = pluss::bundle::Registry::load_csv("path/to/data.csv", options);
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.44 load_excel

Signature

```
static Registry load_excel(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)`
- `static Registry load_excel(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::bundle::Registry::load_excel("path/to/data.xlsx");
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.45 load_excel

Signature

```
static Registry load_excel(std::string_view filepath, const pluss::loader::Config&␣
↪config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_excel(std::string_view filepath)`
- `static Registry load_excel(std::string_view filepath, const pluss::loader::ReadExcelOptions& options)`

Examples

```
auto out = pluss::bundle::Registry::load_excel("path/to/data.xlsx", {"nrows", 16});
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.46 load_excel

Signature

```
static Registry load_excel(std::string_view filepath, const␣
↪pluss::loader::ReadExcelOptions& options)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`options` : `const pluss::loader::ReadExcelOptions&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_excel(std::string_view filepath)`
- `static Registry load_excel(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
pluss::loader::ReadExcelOptions options;
auto out = pluss::bundle::Registry::load_excel("path/to/data.xlsx", options);
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.47 load_json

Signature

```
static Registry load_json(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_json(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::bundle::Registry::load_json("path/to/data.json");
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.48 load_json

Signature

```
static Registry load_json(std::string_view filepath, const pluss::loader::Config& config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_json(std::string_view filepath)`

Examples

```
auto out = pluss::bundle::Registry::load_json("path/to/data.json", {"nrows", 16});
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.49 `load_parquet`

Signature

```
static Registry load_parquet(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_parquet(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::bundle::Registry::load_parquet("path/to/data.parquet");
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.50 load_parquet

Signature

```
static Registry load_parquet(std::string_view filepath, const pluss::loader::Config&␣
↪config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_parquet(std::string_view filepath)`

Examples

```
auto out = pluss::bundle::Registry::load_parquet("path/to/data.parquet", {"nrows", 16});
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.51 load_txt

Signature

```
static Registry load_txt(std::string_view filepath)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_txt(std::string_view filepath, const pluss::loader::Config& config)`

Examples

```
auto out = pluss::bundle::Registry::load_txt("path/to/data.txt");
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.52 `load_txt`

Signature

```
static Registry load_txt(std::string_view filepath, const pluss::loader::Config& config)
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Loads the object from disk using the corresponding PlussMic loader route.

See also

- `static Registry load_txt(std::string_view filepath)`

Examples

```
auto out = pluss::bundle::Registry::load_txt("path/to/data.txt", {"nrows", 16});
```

Output

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.53 map

Signature

```
Registry map(self, const std::function<Slot(const Slot&)>& fn) const
```

Parameters

fn : const std::function<Slot(const Slot&)>& See the signature for the supported argument form.

Returns

Registry Value produced by this call.

Notes

Transforms every slot with the same function and returns the updated registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.map([](const pluss::bundle::Slot& slot) { return slot; });
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.54 map_

Signature

```
Registry& map_(self, const std::function<Slot(const Slot&)>& fn)
```

Parameters

fn : const std::function<Slot(const Slot&)>& See the signature for the supported argument form.

Returns

Registry& Value produced by this call.

Notes

Transforms every slot in place with the same function.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.map_([](const pluss::bundle::Slot& slot) { return slot; });
```

32.1.55 nfields

Signature

```
std::int64_t nfields(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.nfields();
```

Output

```
2
```

32.1.56 nslots

Signature

```
std::int64_t nslots(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.nslots();
```

Output

```
2
```

32.1.57 push

Signature

```
Registry push(self, std::string_view key, const Slot::Value& value) const
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

`value` : `const Slot::Value&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Appends one new value to a named slot and returns the updated registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
```

(continues on next page)

(continued from previous page)

```
});

auto out = rg.push("ids", pluss::make_series(4));
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.58 push_

Signature

```
Registry& push_(self, std::string_view key, const Slot::Value& value)
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

`value` : `const Slot::Value&` See the signature for the supported argument form.

Returns

`Registry&` Value produced by this call.

Notes

Appends one new value to a named slot in place.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.push_("ids", pluss::make_series(4));
```

32.1.59 push_all

Signature

```
Registry push_all(self, const Slot::Value& value) const
```

Parameters

`value` : `const Slot::Value&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Appends the same new value to every slot and returns the updated registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.push_all(pluss::make_note("ok"));
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.60 push_all_

Signature

```
Registry& push_all_(self, const Slot::Value& value)
```

Parameters

`value` : `const Slot::Value&` See the signature for the supported argument form.

Returns

`Registry&` Value produced by this call.

Notes

Appends the same new value to every slot in place.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.push_all_(pluss::make_note("ok"));
```

32.1.61 `rename`

Signature

```
Registry rename(self, const std::unordered_map<std::string, std::string>& mapping) const
```

Parameters

`mapping` : `const std::unordered_map<std::string, std::string>&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Renames one or more slots without changing their stored values.

See also

- `Registry rename(self, std::initializer_list<std::pair<std::string_view, std::string_view>> mapping) const`
- `Registry rename(self, std::string_view from, std::string_view to) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

std::unordered_map<std::string, std::string> renames{{"ids", "ids_new"}};
auto out = rg.rename(renames);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

(continues on next page)

(continued from previous page)

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.62 `rename`

Signature

```
Registry rename(self, std::initializer_list<std::pair<std::string_view, std::string_view>
↪> mapping) const
```

Parameters

`mapping` : `std::initializer_list<std::pair<std::string_view, std::string_view>>` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Renames one or more slots without changing their stored values.

See also

- `Registry rename(self, const std::unordered_map<std::string, std::string>& mapping) const`
- `Registry rename(self, std::string_view from, std::string_view to) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.rename({{"ids", "ids_new"}});
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.63 rename

Signature

```
Registry rename(self, std::string_view from, std::string_view to) const
```

Parameters

`from` : `std::string_view` See the signature for the supported argument form.

`to` : `std::string_view` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Renames one or more slots without changing their stored values.

See also

- `Registry rename(self, std::initializer_list<std::pair<std::string_view, std::string_view>> mapping) const`
- `Registry rename(self, const std::unordered_map<std::string, std::string>& mapping) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.rename("ids", "ids_new");
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.64 rename_

Signature

```
Registry& rename_(self, std::string_view from, std::string_view to)
```

Parameters

`from` : `std::string_view` See the signature for the supported argument form.

`to` : `std::string_view` See the signature for the supported argument form.

Returns

`Registry&` Value produced by this call.

Notes

Renames one or more slots in place without changing their stored values.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.rename_("ids", "ids_new");
```

32.1.65 `sample`

Signature

```
Registry sample(self, std::int64_t n, std::optional<std::uint64_t> random_state =␣
↪std::nullopt) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

`random_state` : `std::optional<std::uint64_t>` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Returns a random sample of positions across every slot.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.sample(2, 7);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.66 save_as

Signature

```
void save_as(self, std::string_view target_type, std::string_view filepath, const␣
↪pluss::loader::Config& config =
```

Parameters

`target_type` : `std::string_view` See the signature for the supported argument form.

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the registry using the explicitly supplied output format selector.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.save_as("json", "path/to/output.json");
```

Output

```
saved: out.*
```

32.1.67 save_csv

Signature

```
void save_csv(self, std::string_view filepath) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the registry to CSV after materializing each slot into a tabular export form.

See also

- `void save_csv(self, std::string_view filepath, const pluss::loader::Config& config) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.save_csv("path/to/output.csv");
```

Output

```
saved: out.*
```

32.1.68 save_csv

Signature

```
void save_csv(self, std::string_view filepath, const pluss::loader::Config& config) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the registry to CSV after materializing each slot into a tabular export form.

See also

- `void save_csv(self, std::string_view filepath) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.save_csv("path/to/output.csv");
```

Output

```
saved: out.*
```

32.1.69 save_excel

Signature

```
void save_excel(self, std::string_view filepath) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the registry to an Excel workbook after materializing each slot into a tabular export form.

See also

- `void save_excel(self, std::string_view filepath, const pluss::loader::Config& config) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
```

(continues on next page)

(continued from previous page)

```
});

rg.save_excel("path/to/output.xlsx");
```

Output

```
saved: out.*
```

32.1.70 save_excel

Signature

```
void save_excel(self, std::string_view filepath, const pluss::loader::Config& config)␣
↪const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the registry to an Excel workbook after materializing each slot into a tabular export form.

See also

- `void save_excel(self, std::string_view filepath) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.save_excel("path/to/output.xlsx");
```

Output

```
saved: out.*
```

32.1.71 save_json

Signature

```
void save_json(self, std::string_view filepath) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the registry to JSON for interchange or later reload.

See also

- `void save_json(self, std::string_view filepath, const pluss::loader::Config& config) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.save_json("path/to/output.json");
```

Output

```
saved: out.*
```

32.1.72 save_json

Signature

```
void save_json(self, std::string_view filepath, const pluss::loader::Config& config)␣
↪const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the registry to JSON for interchange or later reload.

See also

- `void save_json(self, std::string_view filepath) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.save_json("path/to/output.json");
```

Output

```
saved: out.*
```

32.1.73 save_parquet

Signature

```
void save_parquet(self, std::string_view filepath) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the registry to Parquet for compact typed storage.

See also

- `void save_parquet(self, std::string_view filepath, const pluss::loader::Config& config) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.save_parquet("path/to/output.parquet");
```

Output

```
saved: out.*
```

32.1.74 save_parquet

Signature

```
void save_parquet(self, std::string_view filepath, const pluss::loader::Config& config)␣
↪const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes the registry to Parquet for compact typed storage.

See also

- `void save_parquet(self, std::string_view filepath) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.save_parquet("path/to/output.parquet");
```

Output

```
saved: out.*
```

32.1.75 save_txt

Signature

```
void save_txt(self, std::string_view filepath) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes a text rendering of the registry for inspection or logging.

See also

- `void save_txt(self, std::string_view filepath, const pluss::loader::Config& config) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.save_txt("path/to/output.txt");
```

Output

```
saved: out.*
```

32.1.76 save_txt

Signature

```
void save_txt(self, std::string_view filepath, const pluss::loader::Config& config) const
```

Parameters

`filepath` : `std::string_view` File location to read from or write to. Use a neutral project path such as `path/to/data.csv`.

`config` : `const pluss::loader::Config&` See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

Writes a text rendering of the registry for inspection or logging.

See also

- `void save_txt(self, std::string_view filepath) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.save_txt("path/to/output.txt");
```

Output

```
saved: out.*
```

32.1.77 `select`

Signature

```
Registry select(self, const std::vector<std::string>& keys) const
```

Parameters

`keys` : `const std::vector<std::string>&` Collection of slot or stream names to keep, drop, or rewrite together.

Returns

`Registry` Value produced by this call.

Notes

Keeps only the named slots and preserves their shared positional alignment.

See also

- `Registry select(self, std::initializer_list<std::string_view> keys) const`
- `Registry select(self, std::string_view key) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

std::vector<std::string> names{"ids"};
auto out = rg.select(names);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.78 `select`

Signature

```
Registry select(self, std::initializer_list<std::string_view> keys) const
```

Parameters

`keys` : `std::initializer_list<std::string_view>` Collection of slot or stream names to keep, drop, or rewrite together.

Returns

`Registry` Value produced by this call.

Notes

Keeps only the named slots and preserves their shared positional alignment.

See also

- `Registry select(self, const std::vector<std::string>& keys) const`
- `Registry select(self, std::string_view key) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.select({"ids"});
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.79 `select`

Signature

```
Registry select(self, std::string_view key) const
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

Returns

`Registry` Value produced by this call.

Notes

Keeps only the named slots and preserves their shared positional alignment.

See also

- `Registry select(self, std::initializer_list<std::string_view> keys) const`
- `Registry select(self, const std::vector<std::string>& keys) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});
```

(continues on next page)

(continued from previous page)

```
auto out = rg.select("ids");
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.80 set_slot

Signature

```
Registry set_slot(self, std::string_view key, const Slot& value) const
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

`value` : `const Slot&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Adds or replaces one named slot and returns the updated registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.set_slot("score", pluss::bundle::Slot({pluss::make_series(0.9),␣
↪pluss::make_series(0.7), pluss::make_series(0.8)}));
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
```

(continues on next page)

(continued from previous page)

```
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.81 set_slot_

Signature

```
Registry& set_slot_(self, std::string_view key, const Slot& value)
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

`value` : `const Slot&` See the signature for the supported argument form.

Returns

`Registry&` Value produced by this call.

Notes

Adds or replaces one named slot in place.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.set_slot_("score", pluss::bundle::Slot({pluss::make_series(0.9), pluss::make_series(0.
↪7), pluss::make_series(0.8)}));
```

32.1.82 set_slots

Signature

```
Registry set_slots(self, std::initializer_list<std::pair<std::string, Slot>> items) const
```

Parameters

`items` : `std::initializer_list<std::pair<std::string, Slot>>` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Adds or replaces several named slots in one call and returns the updated registry.

See also

- `Registry set_slots(self, std::initializer_list<std::pair<std::string_view, Slot>> items) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.set_slots({
    {"score", pluss::bundle::Slot({pluss::make_series(0.9), pluss::make_series(0.7),␣
↪pluss::make_series(0.8)})},
});
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.83 `set_slots`

Signature

```
Registry set_slots(self, std::initializer_list<std::pair<std::string_view, Slot>> items)␣
↪const
```

Parameters

`items` : `std::initializer_list<std::pair<std::string_view, Slot>>` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Adds or replaces several named slots in one call and returns the updated registry.

See also

- `Registry set_slots(self, std::initializer_list<std::pair<std::string, Slot>> items) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.set_slots({
    {"score", pluss::bundle::Slot({pluss::make_series(0.9), pluss::make_series(0.7),␣
↪pluss::make_series(0.8)})},
});
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.84 set_slots_

Signature

```
Registry& set_slots_(self, std::initializer_list<std::pair<std::string, Slot>> items)
```

Parameters

`items` : `std::initializer_list<std::pair<std::string, Slot>>` See the signature for the supported argument form.

Returns

`Registry&` Value produced by this call.

Notes

Adds or replaces several named slots in place.

See also

- `Registry& set_slots_(self, std::initializer_list<std::pair<std::string_view, Slot>> items)`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.set_slots_({
    {"score", pluss::bundle::Slot({pluss::make_series(0.9), pluss::make_series(0.7),␣
↪pluss::make_series(0.8)})},
});
```

32.1.85 set_slots_

Signature

```
Registry& set_slots_(self, std::initializer_list<std::pair<std::string_view, Slot>>␣
↪items)
```

Parameters

`items` : `std::initializer_list<std::pair<std::string_view, Slot>>` See the signature for the supported argument form.

Returns

`Registry&` Value produced by this call.

Notes

Adds or replaces several named slots in place.

See also

- `Registry& set_slots_(self, std::initializer_list<std::pair<std::string, Slot>> items)`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.set_slots_({
    {"score", pluss::bundle::Slot({pluss::make_series(0.9), pluss::make_series(0.7),␣
↪pluss::make_series(0.8)})},
});
```

32.1.86 show

Signature

```
void show(self, std::ostream& os) const
```

Parameters

os : std::ostream& See the signature for the supported argument form.

Returns

void Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.show(std::cout);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.87 slice

Signature

```
Registry slice(self, std::int64_t start, std::int64_t stop) const
```

Parameters

start : std::int64_t Inclusive starting position of the slice.

stop : std::int64_t Exclusive ending position of the slice.

Returns

Registry Value produced by this call.

Notes

Returns a contiguous positional slice `[start, stop)` across every slot.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.slice(0, 2);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.88 `slot`

Signature

```
Slot slot(self, std::string_view key) const
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

Returns

`Slot` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.slot("ids");
```

Output

```
Slot([Series(1), Series(2), Series(3)])
```

32.1.89 slot_sizes

Signature

```
std::unordered_map<std::string, std::int64_t> slot_sizes(self) const
```

Parameters

None

Returns

`std::unordered_map<std::string, std::int64_t>` Value produced by this call.

Notes

Returns the current length of each slot.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.slot_sizes();
```

Output

```
{"ids": 3, "city": 3}
```

32.1.90 slots

Signature

```
std::vector<Slot> slots(self) const
```

Parameters

None

Returns

`std::vector<Slot>` Materialized collection of slot objects.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.slots();
```

Output

```
[Slot(ids), Slot(city)]
```

32.1.91 tail

Signature

```
Registry tail(self, std::int64_t n) const
```

Parameters

`n` : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

Returns

`Registry` Value produced by this call.

Notes

Returns the last `n` values from every slot in the registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.tail(2);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

(continues on next page)

(continued from previous page)

```
out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.92 take

Signature

```
Registry take(self, const std::vector<std::int64_t>& indices) const
```

Parameters

`indices` : `const std::vector<std::int64_t>&` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Returns the values at the requested integer positions across every slot.

See also

- `Registry take(self, std::span<const std::int64_t> indices) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

std::vector<std::int64_t> picks{0, 2};
auto out = rg.take(picks);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.93 take

Signature

```
Registry take(self, std::span<const std::int64_t> indices) const
```

Parameters

`indices` : `std::span<const std::int64_t>` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Returns the values at the requested integer positions across every slot.

See also

- `Registry take(self, const std::vector<std::int64_t>& indices) const`

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

std::vector<std::int64_t> picks{0, 2};
auto out = rg.take(picks);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.94 take_values

Signature

```
Registry take_values(self, std::string_view key, std::span<const std::int64_t> indices)␣
↪const
```

Parameters

key : std::string_view Name of the target slot or stream.

indices : std::span<const std::int64_t> See the signature for the supported argument form.

Returns

Registry Value produced by this call.

Notes

Selects values from one named slot by integer position and returns the updated registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

std::vector<std::int64_t> picks{0, 2};
auto out = rg.take_values("ids", picks);
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.95 take_values_

Signature

```
Registry& take_values_(self, std::string_view key, std::span<const std::int64_t> indices)
```

Parameters

key : std::string_view Name of the target slot or stream.

indices : std::span<const std::int64_t> See the signature for the supported argument form.

Returns

Registry& Value produced by this call.

Notes

Selects values from one named slot by integer position in place.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

std::vector<std::int64_t> picks{0, 2};
rg.take_values_("ids", picks);
```

32.1.96 to_json

Signature

```
std::string to_json(self) const
```

Parameters

None

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.to_json();
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.97 to_kindle

Signature

```
pluss::kindle::Catalog to_kindle(self) const
```

Parameters

None

Returns

`pluss::kindle::Catalog` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.to_kindle();
```

Output

```
id     -> Series([1, 2, 3])
metric -> Series([10.0, 20.0, 30.0])
city   -> Note(["Accra", "Tema", "Kumasi"])
```

32.1.98 to_string

Signature

```
std::string to_string(self) const
```

Parameters

None

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.to_string();
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.99 transform_values

Signature

```
Registry transform_values(self, std::string_view key, const std::function
↪<Slot::Value(const Slot::Value&)>& fn) const
```

Parameters

key : std::string_view Name of the target slot or stream.

fn : const std::function<Slot::Value(const Slot::Value&)>& See the signature for the supported argument form.

Returns

Registry Value produced by this call.

Notes

Rewrites the values inside one named slot with a user function and returns the updated registry.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.transform_values("ids", [](const pluss::bundle::Slot::Value& value) ->␣
↪pluss::bundle::Slot::Value { if (std::holds_alternative<pluss::Series>(value)) return␣
↪std::get<pluss::Series>(value).add(10); return value; });
```

Output

```
rg.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])

out.head():
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

32.1.100 transform_values_

Signature

```
Registry& transform_values_(self, std::string_view key, const std::function
↪<Slot::Value(const Slot::Value&)>& fn)
```

Parameters

key : `std::string_view` Name of the target slot or stream.

fn : `const std::function<Slot::Value(const Slot::Value&)>&` See the signature for the supported argument form.

Returns

`Registry&` Value produced by this call.

Notes

Rewrites the values inside one named slot in place.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

rg.transform_values_("ids", [](const pluss::bundle::Slot::Value& value) ->␣
↪pluss::bundle::Slot::Value { if (std::holds_alternative<pluss::Series>(value)) return␣
↪std::get<pluss::Series>(value).add(10); return value; });
```

32.1.101 type_profiles

Signature

```
std::unordered_map<std::string, std::unordered_map<std::string, std::int64_t>> type_
↪profiles(self) const
```

Parameters

None

Returns

std::unordered_map<std::string, std::unordered_map<std::string, std::int64_t>> Value produced by this call.

Notes

Summarizes the value types stored inside each slot.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});

auto out = rg.type_profiles();
```

Output

```
{"ids": {"Series": 3}, "city": {"Note": 3}}
```

32.1.102 unique

Signature

```
bool unique(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the object satisfies the uniqueness constraint expected by its model, such as distinct labels or keys.

Examples

```
auto rg = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2),␣
↪pluss::make_series(3)})},
    {"city", pluss::bundle::Slot({pluss::make_note("Accra"), pluss::make_note("Tema"),␣
↪pluss::make_note("Kumasi")})},
});
```

(continues on next page)

(continued from previous page)

```
auto out = rg.unique();
```

Output

```
true
```

CHAPTER

THIRTYTHREE

AISLE API REFERENCE

CHAPTER

THIRTYFOUR

PRACTICAL AISLE API REFERENCE

34.1 API Reference Style

This page documents the full public `Aisle` surface for depth-stacked registries.

34.1.1 apply_slot

Signature

```
Aisle apply_slot(self, std::string_view key, const std::function<Slot(const Slot&)>& fn)␣
↪const
```

Parameters

`key` : `std::string_view` Name of the target slot or stream.

`fn` : `const std::function<Slot(const Slot&)>&` See the signature for the supported argument form.

Returns

`Aisle` Value produced by this call.

Notes

Applies a slot transform to one named key inside every registry and returns the updated aisle.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.apply_slot("ids", [](const pluss::bundle::Slot& slot) { return slot; });
```

Output

```
depth0 -> Registry(ids -> Slot([Series(1), Series(2)]))
depth1 -> Registry(ids -> Slot([Series(3), Series(4)]))
```

34.1.2 as_kindle

Signature

```
pluss::kindle::Archive as_kindle(self) const
```

Parameters

None

Returns

`pluss::kindle::Archive` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.as_kindle();
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

34.1.3 concat_depth

Signature

```
Aisle concat_depth(self, const Aisle& other) const
```

Parameters

`other` : `const Aisle&` See the signature for the supported argument form.

Returns

`Aisle` Value produced by this call.

Notes

Appends the registries from another aisle onto the current depth axis.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.concat_depth(aisle);
```

Output

```
depth0 -> Registry(ids -> Slot([Series(1), Series(2)]))
depth1 -> Registry(ids -> Slot([Series(3), Series(4)]))
```

34.1.4 `defined`

Signature

```
bool defined(self) const
```

Parameters

`None`

Returns

`bool` Boolean status or membership result.

Notes

Reports whether the current object owns a concrete payload that can be used safely in later operations.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.defined();
```

Output

```
true
```

34.1.5 depth

Signature

```
std::int64_t depth(self) const
```

Parameters

None

Returns

`std::int64_t` Integer count, size, or positional result.

Notes

Returns a size/count summary for the current object without changing it.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.depth();
```

Output

```
2
```

34.1.6 empty

Signature

```
bool empty(self) const
```

Parameters

None

Returns

`bool` Boolean status or membership result.

Notes

Reports whether the current object has no rows, entries, slots, or depth items.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.empty();
```

Output

```
false
```

34.1.7 from_kindle

Signature

```
static Aisle from_kindle(const pluss::kindle::Archive& archive)
```

Parameters

`archive` : `const pluss::kindle::Archive&` See the signature for the supported argument form.

Returns

`Aisle` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
using namespace pluss::kindle::literals;

auto c0 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({10.0, 20.0})),
});
auto c1 = pluss::kindle::Catalog({
    "metric"_k = pluss::kindle::Stream(pluss::make_series({30.0, 40.0})),
});
auto archive = pluss::kindle::Archive({c0, c1}, pluss::kindle::Stream(pluss::make_note({
↪"train", "test"})));

auto out = pluss::bundle::Aisle::from_kindle(archive);
```

Output

```
depth0 -> Registry(ids -> Slot([Series(1), Series(2)]))
depth1 -> Registry(ids -> Slot([Series(3), Series(4)]))
```

34.1.8 head

Signature

```
Aisle head(self, std::int64_t n) const
```

Parameters

n : std::int64_t Number of rows, entries, or depth items to keep in the preview.

Returns

Aisle Value produced by this call.

Notes

Returns the first n registries from the aisle depth axis.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.head(1);
```

Output

```
depth0 -> Registry(ids -> Slot([Series(1), Series(2)]))
depth1 -> Registry(ids -> Slot([Series(3), Series(4)]))
```

34.1.9 kindelize

Signature

```
pluss::kindle::Archive kindelize(self) const
```

Parameters

None

Returns

`pluss::kindle::Archive` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.kindelize();
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

34.1.10 `labels`

Signature

```
const std::optional<Slot>& labels(self) const
```

Parameters

None

Returns

`const std::optional<Slot>&` Value produced by this call.

Notes

Returns the current labels used to address fields, slots, rows, or depth items.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.labels();
```

Output

```
["train", "test"]
```

34.1.11 map

Signature

```
Aisle map(self, const std::function<Registry(const Registry&)>& fn) const
```

Parameters

fn : const std::function<Registry(const Registry&)>& See the signature for the supported argument form.

Returns

Aisle Value produced by this call.

Notes

Applies the same function to each registry and returns the transformed aisle.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.map([](const pluss::bundle::Registry& registry) { return registry; });
```

Output

```
depth0 -> Registry(ids -> Slot([Series(1), Series(2)]))
depth1 -> Registry(ids -> Slot([Series(3), Series(4)]))
```

34.1.12 registries

Signature

```
const std::vector<Registry>& registries(self) const
```

Parameters

None

Returns

`const std::vector<Registry>&` Borrowed collection of registries.

Notes

Materializes the current members as a collection you can inspect or reuse elsewhere.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.registries();
```

Output

```
[Registry(depth0), Registry(depth1)]
```

34.1.13 `registry`

Signature

```
Registry registry(self, std::int64_t i) const
```

Parameters

`i` : `std::int64_t` See the signature for the supported argument form.

Returns

`Registry` Value produced by this call.

Notes

Fetches one value, member, or slice from the current object without changing the source object.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.registry(0);
```

Output

```
ids  -> Slot([Series(1), Series(2), Series(3)])
city -> Slot([Note("Accra"), Note("Tema"), Note("Kumasi")])
```

34.1.14 select

Signature

```
Aisle select(self, std::initializer_list<std::string_view> keys) const
```

Parameters

keys : std::initializer_list<std::string_view> Collection of slot or stream names to keep, drop, or rewrite together.

Returns

Aisle Value produced by this call.

Notes

Keeps only the named keys inside every registry in the aisle.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.select({"ids"});
```

Output

```
depth0 -> Registry(ids -> Slot([Series(1), Series(2)]))
depth1 -> Registry(ids -> Slot([Series(3), Series(4)]))
```

34.1.15 show

Signature

```
void show(self, std::ostream& os) const
```

Parameters

os : std::ostream& See the signature for the supported argument form.

Returns

`void` Performs the side effect and returns no value.

Notes

This renders a human-readable view for inspection instead of creating a new analytic object.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

aisle.show(std::cout);
```

Output

```
depth0 -> Registry(ids -> Slot([Series(1), Series(2)]))
depth1 -> Registry(ids -> Slot([Series(3), Series(4)]))
```

34.1.16 `slice`

Signature

```
Aisle slice(self, std::int64_t start, std::int64_t stop) const
```

Parameters

`start` : `std::int64_t` Inclusive starting position of the slice.

`stop` : `std::int64_t` Exclusive ending position of the slice.

Returns

`Aisle` Value produced by this call.

Notes

Returns a contiguous depth slice `[start, stop)` from the aisle.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});
```

(continues on next page)

(continued from previous page)

```
auto out = aisle.slice(0, 1);
```

Output

```
depth0 -> Registry(ids -> Slot([Series(1), Series(2)]))
depth1 -> Registry(ids -> Slot([Series(3), Series(4)]))
```

34.1.17 tail

Signature

```
Aisle tail(self, std::int64_t n) const
```

Parameters

n : `std::int64_t` Number of rows, entries, or depth items to keep in the preview.

Returns

`Aisle` Value produced by this call.

Notes

Returns the last `n` registries from the aisle depth axis.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.tail(1);
```

Output

```
depth0 -> Registry(ids -> Slot([Series(1), Series(2)]))
depth1 -> Registry(ids -> Slot([Series(3), Series(4)]))
```

34.1.18 to_json

Signature

```
std::string to_json(self) const
```

Parameters

None

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.to_json();
```

Output

```
depth0 -> Registry(ids -> Slot([Series(1), Series(2)]))
depth1 -> Registry(ids -> Slot([Series(3), Series(4)]))
```

34.1.19 to_kindle

Signature

```
pluss::kindle::Archive to_kindle(self) const
```

Parameters

None

Returns

`pluss::kindle::Archive` Value produced by this call.

Notes

This is an explicit bridge between PlussMic models so you can switch to the representation that fits the next task.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
```

(continues on next page)

(continued from previous page)

```
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.to_kindle();
```

Output

```
train -> Catalog(metric -> Series([10.0, 20.0]))
test  -> Catalog(metric -> Series([30.0, 40.0]))
```

34.1.20 to_string

Signature

```
std::string to_string(self) const
```

Parameters

None

Returns

`std::string` Rendered string result.

Notes

Serializes or renders the current object into a text form you can inspect, log, or export.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.to_string();
```

Output

```
depth0 -> Registry(ids -> Slot([Series(1), Series(2)]))
depth1 -> Registry(ids -> Slot([Series(3), Series(4)]))
```

34.1.21 unique

Signature

```
bool unique(self) const
```

Parameters

None

Returns

bool Boolean status or membership result.

Notes

Reports whether the object satisfies the uniqueness constraint expected by its model, such as distinct labels or keys.

Examples

```
auto r0 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(1), pluss::make_series(2)})},
});
auto r1 = pluss::bundle::Registry({
    {"ids", pluss::bundle::Slot({pluss::make_series(3), pluss::make_series(4)})},
});
auto aisle = pluss::bundle::Aisle({r0, r1});

auto out = aisle.unique();
```

Output

```
true
```

CHAPTER

THIRTYFIVE

BUILD OUTPUTS

35.1 HTML

```
cd docs/sphinx
make html
```

Expected output:

- `_build/html/index.html`

35.2 PDF

```
cd docs/sphinx
make pdf
```

Expected output:

- `_build/latex/plussmic_user_docs.pdf`

35.3 Notes

- HTML uses the same custom left-sidebar/top-bar shell as the PlussQit docs.
- PDF is built through `latex` plus `latexmk`.
- Run the commands from an environment where Sphinx and the PDF toolchain are already available.
- If HTML looks stale after a rebuild, hard refresh the browser once.