

BOOTSTRAP, UN FRAMEWORK CSS

ADOLFO SANZ DE DIEGO

SEPTIEMBRE 2016

1 EL AUTOR

1.1 ADOLFO SANZ DE DIEGO

- Empecé desarrollando aplicaciones web, hasta que di el salto a la docencia.
- Actualmente soy **Asesor Técnico Docente** en el servicio TIC de la D.G de Infraestructuras y Servicios de la Consejería de Educación, Juventud y Deporte de la Comunidad de Madrid.
- Además colaboro como **formador especializado en tecnologías de desarrollo**.

1.2 ALGUNOS PROYECTOS

- **Hackathon Lovers** <http://hackathonlovers.com>: un grupo creado para emprendedores y desarrolladores amantes de los hackathones.
- **Password Manager Generator** <http://pasmangen.github.io>: un gestor de contraseñas online.
- **MarkdownSlides**
<https://github.com/asanzdiego/markdownslides>: un script para crear slides a partir de ficheros MD.

1.3 ¿DONDE ENCONTRARME?

- Mi nick: asanzdiego
 - AboutMe: <http://about.me/asanzdiego>
 - GitHub: <http://github.com/asanzdiego>
 - Twitter: <http://twitter.com/asanzdiego>
 - Blog: <http://asanzdiego.blogspot.com.es>
 - LinkedIn: <http://www.linkedin.com/in/asanzdiego>
 - Google+: <http://plus.google.com/+AdolfoSanzDeDiego>

2 INTRODUCCIÓN

2.1 ¿QUÉ ES?

- Bootstrap es un **framework CSS**, liberado por Twitter y muy popular hoy en día.
- Está pensado para hacer un desarrollo **Mobile First**
- Implementa un **sistema de rejillas**, que por defecto incluye 12 columnas.

2.2 VENTAJAS

- Utiliza **LESS**, y en la última versión **SASS**.
- Hay una enorme **comunidad detrás**.
- Herramienta **sencilla y ágil** para construir sitios web e interfaces.
- Tiene un **theme** por defecto bastante optimizado y que puedes modificar fácilmente.

2.3 DESVENTAJAS

- Es necesario adaptarse a su forma de trabajo.
- Debes adaptar tu diseño a un grid de 12 columnas.
- Trae anchos y márgenes por defecto, que a veces son un poco tediosos de cambiar.
- A veces hacer implementar un diseño impuesto, puede llegar a resultar bastante difícil, al menos si eres un perfeccionista.

2.4 DESCARGA

- <https://github.com/twbs/bootstrap/releases>

```
bootstrap/
  └── css/
    ├── bootstrap.css
    ├── bootstrap.min.css
    ├── bootstrap-theme.css
    └── bootstrap-theme.min.css
  └── js/
    ├── bootstrap.js
    └── bootstrap.min.js
  └── fonts/
```

2.5 PLANTILLA BÁSICA

```
<!DOCTYPE html>
<html lang="en">
  <head>
    <meta name="viewport" . . .>
    <title>Template</title>
    <link href="bootstrap.min.css" . . .>
  </head>
  <body>
    <h1>Hello, world!</h1>
    <script src=" . . . /jquery.min.js"></script>
    <script src="bootstrap.min.js"></script>
  </body>
</html>
```

3 RESUMEN CSS

3.1 HTML5 DOCTYPE

- Bootstrap necesita un doctype de HTML5:

```
<!DOCTYPE html>
<html lang="en">
  ...
</html>
```

3.2 MOBILE FIRST

- Desde la versión 3, Boostrap es **Mobile first**.
- Para garantizar un buen renderizado y un buen funcionamiento del zoom:

```
<meta name="viewport" content="width=device-width,initial-scale=1">
```

4 GRID SYSTEM

4.1 INTRODUCCIÓN

- Bootstrap incluye un sistema de rejilla responsive y mobile first de 12 columnas.

4.2 FUNCIONAMIENTO

- El sistema de rejilla de Bootstrap funciona así:
 - Se deben colocar .row dentro de un .container (ancho fijo) o .container-fluid (ancho completo).
 - Utilice .row para crear grupos horizontales.
 - El contenido se debe colocar entre .row y deben de ser **hijos inmediatos**.
 - Si hay más de 12 columnas en una .row, estas son desplazadas abajo.

4.3 1 COLUMNA (I)

- Ejemplo de 1 columna de un tamaño de 12

1 columna de un tamaño de 12

1
2
3
4

1 columna

4.4 1 COLUMNA (II)

- Ejemplo de 1 columna de un tamaño de 12

```
<div class="row">
  <div class="col-xs-12">1</div>
  <div class="col-xs-12">2</div>
  <div class="col-xs-12">3</div>
  <div class="col-xs-12">4</div>
</div>
```

4.5 2 COLUMNAS (I)

- Ejemplo de 2 columnas de un tamaño de 6

2 columnas de un tamaño de 6

1	2
3	4

2 columnas

4.6 2 COLUMNAS (II)

- Ejemplo de 2 columnas de un tamaño de 6

```
<div class="row">
  <div class="col-xs-6">1</div>
  <div class="col-xs-6">2</div>
  <div class="col-xs-6">3</div>
  <div class="col-xs-6">4</div>
</div>
```

4.7 3 COLUMNAS (I)

- Ejemplo de 3 columnas de un tamaño de 4

3 columnas de un tamaño de 4		
1	2	3
4		

3 columnas

4.8 3 COLUMNAS (II)

- Ejemplo de 3 columnas de un tamaño de 4

```
<div class="row">
  <div class="col-xs-4">1</div>
  <div class="col-xs-4">2</div>
  <div class="col-xs-4">3</div>
  <div class="col-xs-4">4</div>
</div>
```

4.9 4 COLUMNAS (I)

- Ejemplo de 4 columnas de un tamaño de 3

4 columnas de un tamaño de 3

1	2	3	4
---	---	---	---

4 columnas

4.10 4 COLUMNAS (II)

- Ejemplo de 4 columnas de un tamaño de 3

```
<div class="row">
  <div class="col-xs-3">1</div>
  <div class="col-xs-3">2</div>
  <div class="col-xs-3">3</div>
  <div class="col-xs-3">4</div>
</div>
```

4.11 MULTIDISPOSITIVO

- 1 columna para xs ($<768\text{px}$)
- 2 columnas para sm ($\geq 768\text{px}$)
- 3 columnas para md ($\geq 992\text{px}$)
- 4 columnas para lg ($\geq 1200\text{px}$)

4.12 NORMAL

```
<div class="row">
  <div class="col-xs-12 col-sm-6 col-md-4 col-lg-3">1</div>
  <div class="col-xs-12 col-sm-6 col-md-4 col-lg-3">2</div>
  <div class="col-xs-12 col-sm-6 col-md-4 col-lg-3">3</div>
  <div class="col-xs-12 col-sm-6 col-md-4 col-lg-3">4</div>
</div>
```

4.13 CLEARFIX (I)

- Problema cuando una capa tiene un alto mayor que la de los demás:

Multidispositivo normal

1 Resize your viewport or check it out on your phone for an example.	2
	3
4	

Multidispositivo con clearfix

1 Resize your viewport or check it out on your phone for an example.	2
3	4

Problemaclearfix

4.14 CLEARFIX (II)

```
<div class="row">
  <div class="...>1 Resize your viewport</div>
  <div class="...>2</div>
  <div class="clearfix visible-sm-block"></div>
  <div class="...>3</div>
  <div class="clearfix visible-md-block"></div>
  <div class="...>4</div>
</div>
```

4.15 HUECOS CON OFFSET (I)

Huecos con offset

.col-md-4

.col-md-3 .col-md-offset-3

.col-md-6 .col-md-offset-3

.col-md-4 .col-md-offset-4

.col-md-3 .col-md-offset-3

Huecos con offset

4.16 HUECOS CON OFFSET (II)

```
<div class="row">
  <div class="col-md-4">.col-md-4</div>
  <div class="col-md-4 col-md-offset-4">.col-md-4 .col-md-offset-4</div>
</div>
<div class="row">
  <div class="col-md-3 col-md-offset-3">.col-md-3 .col-md-offset-3</div>
  <div class="col-md-3 col-md-offset-3">.col-md-3 .col-md-offset-3</div>
</div>
<div class="row">
  <div class="col-md-6 col-md-offset-3">.col-md-6 .col-md-offset-3</div>
</div>
```

5 TIPOGRAFÍA

5.1 CABECERAS (I)

h1.Cabeceras con Bootstrap Texto secundario con small

h2.Cabeceras con Bootstrap Texto secundario con small

h3.Cabeceras con Bootstrap Texto secundario con small

h4.Cabeceras con Bootstrap Texto secundario con small

h5.Cabeceras con Bootstrap Texto secundario con small

h6.Cabeceras con Bootstrap Texto secundario con small

Cabeceras

5.2 CABECERAS (II)

```
<h1>h1.Cabeceras con Bootstrap  
<small>Texto secundario</small></h1>  
  
<h2>h2.Cabeceras con Bootstrap  
<small>Texto secundario</small></h2>
```

5.3 PÁRRAFOS (I)

PÁRRAFOS

Párrafo con class="lead"

bla, bla

Párrafo normal

bla, bla

Párrafo con class="small"

bla, bla

Párrafos

5.4 PÁRRAFOS (II)

```
<p class="lead">  
    Párrafo con class="lead"</p>  
  
<p>Párrafo normal</p>  
  
<p class="small">  
    Párrafo con class="small"</p>
```

5.5 TEXTOS EN LÍNEA (I)

TEXTOS EN LÍNEA

Puedes usar el tag strong para darle **mucho énfasis** a un texto

Puedes usar el tag em para darle *émfasis* a un texto

Puedes usar el tag mark para **marcar** un texto

Puedes usar el tag ins para insertar un texto

Puedes usar el tag del para ~~borrar~~ un texto

Textos en línea

5.6 TEXTOS EN LÍNEA (II)

```
<p>Puedes usar el tag strong para darle <strong>mucho énfasis</strong> a un texto</p>
<p>Puedes usar el tag em para darle <em>émfasis</em> a un texto</p>
<p>Puedes usar el tag mark para <mark>marcar</mark> un texto</p>
<p>Puedes usar el tag ins para <ins>insertar</ins> un texto</p>
<p>Puedes usar el tag del para <del>borrar</del> un texto</p>
```

5.7 ALINEACIÓN (I)

ALINEACIÓN DE TEXTOS

Texto alineado a la izquierda.

Texto centrado.

Texto alineado a la derecha.

Texto justificado. Texto justificado.

Texto sin ajuste. Texto sin ajuste.

Alineación

5.8 ALINEACIÓN (II)

```
<p class="text-left">Texto alineado a la izquierda.</p>
<p class="text-center">Texto centrado.</p>
<p class="text-right">Texto alineado a la derecha.</p>
<p class="text-justify">Texto justificado.</p>
<p class="text-nowrap">Texto sin ajuste.</p>
```

5.9 CAPITALIZACIÓN (I)

CAPITALIZACIÓN

texto en minúsculas

TEXTO EN MAYÚSCULAS

Texto Tipo Título

Capitalización

5.10 CAPITALIZACIÓN (II)

```
<p class="text-lowercase">Lowercased text.</p>
<p class="text-uppercase">Uppercased text.</p>
<p class="text-capitalize">Capitalized text.</p>
```

5.11 ABREVIATURAS (I)

ABREVITURAS

HTML es una abreviatura. Pasa el ratón por encima para averiguar de que se trata.

HyperText Markup Language

Abreviaturas

5.12 ABREVIATURAS (II)

<abbr title="HyperText Markup Language">HTML</abbr> es una abreviatura.

5.13 DIRECCIONES (I)

DIRECCIONES

Twitter, Inc.

795 Folsom Ave, Suite 600

San Francisco, CA 94107

P: (123) 456-7890

Full Name

first.last@example.com

Direcciones

5.14 DIRECCIONES (II)

```
<address>
  <strong>Twitter, Inc.</strong><br>
  795 Folsom Ave, Suite 600<br>
  San Francisco, CA 94107<br>
  <abbr title="Phone">P:</abbr>
  (123) 456-7890
</address>

<address>
  <strong>Full Name</strong><br>
  <a href="mailto:#">info@name.com</a>
</address>
```

5.15 CITAS (I)

CITAS

 Lorem ipsum dolor sit amet, consectetur adipiscing elit. Integer posuere erat a ante.

 Someone famous in Source Title —

Citas

5.16 CITAS (II)

```
<blockquote class="blockquote">  
    <p>Lorem ipsum dolor sit amet, consectetur adipiscing elit. Integer posuimus  
    <footer>Someone famous in <cite title="Source Title">Source Title</cite>  
</blockquote>
```

5.17 LISTAS (I)

LISTAS

Peras Manzanas Naranjas Platanos

Listas

5.18 LISTAS (II)

```
<ul class="list-inline">
  <li>Peras</li>
  <li>Manzanas</li>
  <li>Naranjas</li>
  <li>Platanos</li>
</ul>
```

5.19 DESCRIPCIONES (I)

DESCRIPCIONES

Descripción Perfecta para definir términos.

Euismod Vestibulum id ligula porta felis euismod semper eget lacinia odio sem nec elit.

Felis euismod sempe... Fusce dapibus, tellus ac cursus commodo, tortor mauris condimentum nibh, ut fermentum massa justo sit amet risus.

Descripciones

5.20 DESCRIPCIONES (II)

```
<dl class="dl-horizontal">
  <dt>Descripción</dt>
  <dd>Perfecta para definir.</dd>
  <dt>Euismod</dt>
  <dd>Vestibulum id ligula...</dd>
  <dt>Felis euismod semper eget</dt>
  <dd>Fusce dapibus, tellus ...</dd>
</dl>
```

6 TABLAS

6.1 CLASES

- **table**: para darle el formato
- **table-striped**: para darle formato a las pares y a las impares
- **table-bordered**: para ponerle bordes a la tabla
- **table-hover**: para oscurecer la fila en donde está el ratón
- **table-condensed**: para que ocupe menos espacio

6.2 RESPONSIVE

- Poniendo la tabla dentro de una capa con `class=table-responsive` aparecerá un scroll horizontal en la tabla en dispositivos pequeños.

6.3 EJEMPLO (I)

table ALL

#	First Name	Last Name	Username
1	Mark	Otto	@mdo
2	Jacob	Thornton	@fat
3	Larry	the Bird	@twitter

Tabla

6.4 EJEMPLO (II)

```
<div class="table-responsive">
  <table class="table table-striped table-bordered table-hover table-co
    <thead>
      <tr>
        <th>...
    </thead>
    <tbody>
      <tr>
        <td>...
    </tbody>
  </table>
</div>
```

7 FORMULARIOS

7.1 NORMAL

Ejemplo básico

Email address

Password

Remember me

Formulario normal

7.2 INLINE

form-inline

Remember me

Formulario inline

7.3 HORIZONTAL

form-horizontal

Email	<input type="text" value="Enter Email"/>
Password	<input type="password" value="Password"/>
<input type="checkbox"/> Remember me	
<input type="button" value="Sign in"/>	

Formulario horizontal

7.4 EJEMPLO

```
<form class="form" role="form">
  <div class="form-group">
    <label for="inputEmail3" class="col-sm-2 control-label">Email</label>
    <div class="col-sm-10">
      <input class="form-control" id="inputEmail3"
        placeholder="Enter Email" type="email">
    </div>
  </div>
  <div class="form-group">
    <div class="col-sm-offset-2 col-sm-10">
      <button type="submit" class="btn btn-default"> Sign in</button>
    </div>
  </div>
</form>
```

7.5 VALIDACIONES (I)

Validaciones

Input with success

✓

Input with warning

⚠

Input with error

✗

Formulario Validaciones

7.6 VALIDACIONES (II)

- Usar los helpers `has-success`, `has-warning` y `has-error`

```
<div class="form-group has-success has-feedback">
  <label class="control-label" for="inputSuccess2">
    Input with success</label>
  <input type="text" class="form-control" id="inputSuccess2">
  <span class="glyphicon glyphicon-ok form-control-feedback"></span>
</div>
```

7.7 TAMAÑOS (I)

Tamaños

.input-lg

Default input

.input-sm

Large label Large input

Small label Small input

This screenshot illustrates the use of CSS classes for input sizes. The '.input-lg' class creates a large input field, while the '.input-sm' class creates a smaller one. The 'Default input' is the standard size. The 'Large label' and 'Small label' are used to demonstrate how the input sizes relate to their respective labels.


Tamaños

7.8 TAMAÑOS (II)

- Usar los helpers **form-group-lg** o **form-group-sm** o bien, en caso de inputs aislados que no estén dentro de un form-group, usar **input-lg** o **input-sm**

8 BOTONES

8.1 TIPOS (I)




Tipos de botones

8.2 TIPOS (II)

```
<button type="button" class="btn">Button</button>
<button type="button" class="btn btn-default">Default</button>
<button type="button" class="btn btn-primary">Primary</button>
<button type="button" class="btn btn-success">Success</button>
<button type="button" class="btn btn-info">Info</button>
<button type="button" class="btn btn-warning">Warning</button>
<button type="button" class="btn btn-danger">Danger</button>
```

8.3 ACTIVADOS (I)



Botones activados

8.4 ACTIVADOS (II)

```
<button type="button" class="btn active">Button</button>
<button type="button" class="btn active btn-default">Default</button>
<button type="button" class="btn active btn-primary">Primary</button>
<button type="button" class="btn active btn-success">Success</button>
<button type="button" class="btn active btn-info">Info</button>
<button type="button" class="btn active btn-warning">Warning</button>
<button type="button" class="btn active btn-danger">Danger</button>
```

8.5 DESACTIVADOS (I)




Botones desactivados

8.6 DESACTIVADOS (II)

```
<button type="button" disabled="disabled" class="btn">Button</button>
<button type="button" disabled="disabled" class="btn btn-default">Default</button>
<button type="button" disabled="disabled" class="btn btn-primary">Primary</button>
<button type="button" disabled="disabled" class="btn btn-success">Success</button>
<button type="button" disabled="disabled" class="btn btn-info">Info</button>
<button type="button" disabled="disabled" class="btn btn-warning">Warning</button>
<button type="button" disabled="disabled" class="btn btn-danger">Danger</button>
```

8.7 ENLACES (I)



Enlaces como botones

8.8 ENLACES (II)

```
<a href="#" class="btn" role="button">Link as button</a>
<a href="#" class="btn active" role="button">Link as button Active</a>
<a href="#" class="btn disabled" role="button">Link as button Disabled<,
<br /><br />
<a href="#" class="btn btn-default" role="button">Default link</a>
<a href="#" class="btn btn-default active" role="button">Default link Ac
<a href="#" class="btn btn-default disabled" role="button">Default link
<br /><br />
<a href="#" class="btn btn-primary" role="button">Primary link</a>
<a href="#" class="btn btn-primary active" role="button">Primary link Ac
<a href="#" class="btn btn-primary disabled" role="button">Primary link
```

8.9 TAMAÑOS (I)




Tamaños de los botones

8.10 TAMAÑOS (II)

```
<button type="button" class="btn btn-primary btn-lg">Large button</button>
<button type="button" class="btn btn-primary">Default button</button>
<button type="button" class="btn btn-primary btn-sm">Small button</button>
<button type="button" class="btn btn-primary btn-xs">Extra small button</button>
```

8.11 EXPANDIR (I)



Expandir los botones

8.12 EXPANDIR (II)

```
<button type="button" class="btn btn-primary btn-lg btn-block">Large button</button>
<button type="button" class="btn btn-primary btn-block">Default button</button>
<button type="button" class="btn btn-primary btn-sm btn-block">Small button</button>
<button type="button" class="btn btn-primary btn-xs btn-block">Extra small button</button>
```

9 IMÁGENES

9.1 RESPONSIVE

- Añadir `class=img-responsive` pondrá `max-size=100%` y `height=auto`.

9.2 EFECTOS



Efectos de imágenes

10 HELPERS

10.1 TEXTOS COLOREADOS (I)

Textos coloreados

text-muted

text-primary

text-success

text-info

text-warning

text-danger

Textos coloreados

10.2 TEXTOS COLOREADOS (II)

```
<p class="text-muted">text-muted</p>
<p class="text-primary">text-primary</p>
<p class="text-success">text-success</p>
<p class="text-info">text-info</p>
<p class="text-warning">text-warning</p>
<p class="text-danger">text-danger</p>
```

10.3 COLORES DE FONDO (I)

Colores de fondo

bg-primary

bg-success

bg-info

bg-warning

bg-danger

Colores de fondo

10.4 COLORES DE FONDO (II)

```
<p class="bg-primary">bg-primary</p>
<p class="bg-success">bg-success</p>
<p class="bg-info">bg-info</p>
<p class="bg-warning">bg-warning</p>
<p class="bg-danger">bg-danger</p>
```

10.5 FLOAT

```
<div class="pull-left">pull-left</div>
<div class="pull-right">pull-right</div>
```

10.6 MOSTRAR Y OCULTAR

```
<p>class=show > display: block</p>
<div class="show">show</div>

<p>class=hidden > display: none</p>
<div class="hidden">hidden</div>

<p>class=invisible > visibility: hidden (no desaparece del dom) </p>
<div class="invisible">invisible</div>
```

10.7 ACCESIBILIDAD

```
<p>class=sr-only > solo aparece en los lectores de pantalla</p>  
<p>class=sr-only-focusable > aparece cuando se hace foco sobre él</p>  
<a class="sr-only sr-only-focusable" href="#content">Skip to main content</a>
```

11 RESPONSIVE

11.1 ESCONDER SEGÚN DISPOSITIVO

```
<p class="hidden-xs bg-primary">hidden-xs</p>
<p class="hidden-sm bg-primary">hidden-sm</p>
<p class="hidden-md bg-primary">hidden-md</p>
<p class="hidden-lg bg-primary">hidden-lg</p>
```

11.2 MOSTRAR COMO BLOCK SEGÚN DISPOSITIVO

```
<p class="visible-xs-block bg-primary">visible-block-xs</p>
<p class="visible-sm-block bg-primary">visible-block-sm</p>
<p class="visible-md-block bg-primary">visible-block-md</p>
<p class="visible-lg-block bg-primary">visible-block-lg</p>
```

11.3 MOSTRAR COMO INLINE SEGÚN DISPOSITIVO

```
<p class="visible-xs-inline bg-primary">visible-xs-inline</p>
<p class="visible-sm-inline bg-primary">visible-sm-inline</p>
<p class="visible-md-inline bg-primary">visible-md-inline</p>
<p class="visible-lg-inline bg-primary">visible-lg-inline</p>
```

11.4 MOSTRAR U OCULTAR PARA IMPRIMIR

```
<p class="hidden-print bg-primary">hidden-print</p>
<p class="visible-print-block bg-primary">visible-print-block</p>
<p class="visible-print-inline bg-primary">visible-print-inline</p>
```

12 COMPONENTES

12.1 ICONOS (I)

- Utiliza una versión reducida de **glyphicon**:
 - <http://glyphicon.com>
- Alternativa **Font-Awesome**:
 - <http://fortawesome.github.io/Font-Awesome>

12.2 ICONOS (II)



Ejemplo de iconos

12.3 ICONOS (III)

```
<button type="button" class="btn btn-default">  
  <span class="glyphicon glyphicon-star"></span> Star  
</button>
```

12.4 DROPODOWN (I)



Dropdown

12.5 DROPODOWN (II)

```
<div class="dropdown">
  <button ... data-toggle="dropdown">Dropdown</button>
  <ul ... class="dropdown-menu" role="menu">
    <li role="presentation" class="dropdown-header">Header</li>
    <li role="presentation" class="divider"></li>
    <li role="presentation">
      <a role="menuitem" ... href="#">Action</a></li>
    </ul>
</div>
```

12.6 BUTTON GROUPS (I)



Button groups

12.7 BUTTON GROUPS (II)

```
<div class="btn-group">
  <button type="button" class="btn btn-default">Left</button>
  <button type="button" class="btn btn-default">Middle</button>
  <button type="button" class="btn btn-default">Right</button>
</div>
```

12.8 INPUT GROUPS (I)

Input groups

The screenshot shows a web page with a title 'Input groups'. Below the title is a horizontal row of three input fields: a text input with a placeholder '@' and a label 'Username', a numeric input with a placeholder '0.00', and a numeric input with a placeholder '0.00' preceded by a '\$' sign. Below these are two sets of grouped inputs. Each set consists of a radio button input ('□') and a text input, followed by a radio button input ('○') and a text input. The first set has a 'Go!' button to its left, and the second set has a 'Go!' button to its right. At the bottom of the group are two 'Action ▾' dropdown menus.

@ Username

.00

.00

\$

□

○

Go!

Action ▾

Go!


Action ▾

Input groups

12.9 INPUT GROUPS (II)

```
<div class="input-group">
  <span class="input-group-addon">@</span>
  <input type="text" class="form-control" placeholder="Username">
</div>
```

12.10 VARIOS



Tabs, pills, navbars, breadcrumbs

12.11 TABS

```
<ul class="nav nav-tabs" role="tablist">
  <li class="active"><a href="#">Home</a></li>
  <li><a href="#">Help</a></li>
  ...
</ul>
```

12.12 PILLS

```
<ul class="nav nav-pills">
  <li class="active"><a href="#">Home</a></li>
  <li><a href="#">Help</a></li>
  ...
</ul>
```

12.13 NAVBARS

```
<nav ...>
  <div class="container-fluid">
    <div class="navbar-header">
      <button ... id="collapse-1">
        <span class="sr-only">Toggle navigation</span>
        ...
      </button>
      <a class="navbar-brand" href="#">Brand</a>
    <div ... id="collapse-1">
      <ul class="nav navbar-nav navbar-right">
        <li><a href="#">Link</a></li>
        ...
      </ul></div>
    </div>
  </nav>
```

12.14 BREADCRUMBS

```
<ol class="breadcrumb">
  <li><a href="#">Home</a></li>
  <li><a href="#">Library</a></li>
  <li class="active">Data</li>
</ol>
```

12.15 PAGINATION (I)



Pagination

12.16 PAGINATION (II)

```
<ul class="pagination">
  <li class="disabled"><span>&laquo;</span></li>
  <li class="active">
    <span>1<span class="sr-only">(current)</span></span></li>
  <li><a href="#">2</a></li>
  <li><a href="#">3</a></li>
  <li><a href="#">4</a></li>
  <li><a href="#">5</a></li>
  <li><a href="#">&raquo;</a></li>
</ul>
```

12.17 PAGER (I)




Pager

12.18 PAGER (II)

```
<ul class="pager">
  <li class="previous disabled"><a href="#">&larr; Older</a></li>
  <li class="next"><a href="#">Newer &rarr;</a></li>
</ul>
```

12.19 LABELS (I)




Labels

12.20 LABELS (II)

```
<span class="label label-default">Default</span>
<span class="label label-primary">Primary</span>
<span class="label label-success">Success</span>
<span class="label label-info">Info</span>
<span class="label label-warning">Warning</span>
<span class="label label-danger">Danger</span>
```

12.21 BADGES (I)



Badges

12.22 BADGES (II)

```
<ul class="nav nav-pills">
  <li class="active">
    <a href="#">Home<span class="badge">42</span></a></li>
  <li><a href="#">Profile</a></li>
  <li><a href="#">Messages<span class="badge">3</span></a></li>
</ul>
```

12.23 BADGES (III)

```
<button class="btn btn-default" type="button">Messages
  <span class="badge">4</span>
</button>
```

12.24 JUMBOTRON (I)

Jumbotron

Hello, world!

This is a simple hero unit, a simple jumbotron-style component for calling extra attention to featured content or information.

[Learn more](#)

Jumbotron

12.25 JUMBOTRON (II)

```
<div class="jumbotron">
  <h1>Hello, world!</h1>
  <p>...</p>
  <p><a class="btn btn-primary btn-lg" role="button">Learn more</a></p>
</div>
```

12.26 THUMBNAILS (I)

Thumbnails

242x200

Thumbnail label

Cras justo odio, dapibus ac facilisis in, egestas eget quam. Donec id elit non mi porta gravida at eget metus. Nullam id dolor id nibh ultricies vehicula ut id elit.

Button Button

242x200

Thumbnail label

Cras justo odio, dapibus ac facilisis in, egestas eget quam. Donec id elit non mi porta gravida at eget metus. Nullam id dolor id nibh ultricies vehicula ut id elit.

Button Button

242x200

Thumbnail label

Cras justo odio, dapibus ac facilisis in, egestas eget quam. Donec id elit non mi porta gravida at eget metus. Nullam id dolor id nibh ultricies vehicula ut id elit.

Button Button

Thumbnails

12.27 THUMBNAILS (II)

```
<div class="row">
  <div class="col-sm-6 col-md-4">
    <div class="thumbnail">
      
      <div class="caption">
        <h3>Thumbnail label</h3>
        <p>...</p>
      </div>
    </div>
  </div>
</div>
```

12.28 ALERTS (I)

Alerts

Well done! You successfully read this important alert message.

Heads up! This alert needs your attention, but it's not super important.

Warning! Better check yourself, you're not looking too good.


Oh snap! Change a few things up and try submitting again.

Alerts

12.29 ALERTS (II)

```
<div class="alert alert-success" role="alert">
  <strong>Well done!</strong></div>
<div class="alert alert-info" role="alert">
  <strong>Heads up!</strong></div>
<div class="alert alert-warning" role="alert">
  <strong>Warning!</strong></div>
<div class="alert alert-danger" role="alert">
  <strong>Oh snap!</strong></div>
```

12.30 PROGRESS BAR (I)



Progress Bar

12.31 PROGRESS BAR (II)

```
<div class="progress">
  <div class="progress-bar" role="progressbar"
    aria-valuenow="0" aria-valuemin="0"
    aria-valuemax="100">0%</div></div>
<div class="progress">
  <div class="progress-bar" role="progressbar"
    aria-valuenow="2" aria-valuemin="0"
    aria-valuemax="100" style="width: 2%; ">
  2%</div></div>
```

12.32 PROGRESS BAR (III)

```
<div class="progress">
  <div class="progress-bar progress-bar-success"
    ... style="width: 40%"><span class="sr-only">
      40% Complete (success)...
<div class="progress">
  <div class="progress-bar progress-bar-info progress-bar-striped"
    ... style="width: 20%"><span class="sr-only">
      20% Complete...
<div class="progress">
  <div class="progress-bar progress-bar-warning progress-bar-striped act
    ... style="width: 60%"><span class="sr-only">
      60% Complete (warning)...
```

12.33 PROGRESS BAR (IV)

```
<div class="progress">
  <div class="progress-bar" style="width: 35%">
    <span class="sr-only">35% Complete (success)</span></div>
  <div class="progress-bar progress-bar-warning progress-bar-striped"
       style="width: 20%"><span class="sr-only">
    20% Complete (warning)</span></div>
  <div class="progress-bar progress-bar-danger progress-bar-striped act:
       style="width: 10%"><span class="sr-only">
    10% Complete (danger)</span></div>
</div>
```

12.34 MEDIA (I)

Media

Media heading

64x64

Cras sit amet nibh libero, in gravida nulla. Nulla vel metus scelerisque ante sollicitudin commodo. Cras purus odio, vestibulum in vulputate at, tempus viverra turpis.

Nested media heading

64x64

Cras sit amet nibh libero, in gravida nulla. Nulla vel metus scelerisque ante sollicitudin commodo. Cras purus odio, vestibulum in vulputate at, tempus viverra turpis.

Nested media heading

64x64

Cras sit amet nibh libero, in gravida nulla. Nulla vel metus scelerisque ante sollicitudin commodo. Cras purus odio, vestibulum in vulputate at, tempus viverra turpis.

Nested media heading

64x64

Cras sit amet nibh libero, in gravida nulla. Nulla vel metus scelerisque ante sollicitudin commodo. Cras purus odio, vestibulum in vulputate at, tempus viverra turpis.

Media heading

Cras sit amet nibh libero, in gravida nulla. Nulla vel metus scelerisque ante sollicitudin commodo. Cras purus odio, vestibulum in vulputate at, tempus viverra turpis.

64x64

Media

12.35 MEDIA (II)

```
<ul class="media-list">
  <li class="media">
    <a class="pull-left" href="#">
      
    </a>
    <div class="media-body">
      <h4 class="media-heading">Media heading</h4>
      <p>...</p>
    </div>
  </li>
</ul>
```

12.36 LIST GROUP (I)

List group

Cras justo odio

Dapibus ac facilisis in

Morbi leo risus

Porta ac consectetur ac


Vestibulum at eros

List group

12.37 LIST GROUP (II)

```
<div class="list-group">
  <a href="#" class="list-group-item active">Cras justo odio</a>
  <a href="#" class="list-group-item">Dapibus ac facilisis in</a>
  ...
</div>
```

12.38 PANEL GROUP (I)




Panel group

12.39 PANEL GROUP (II)

```
<div class="panel panel-primary">
  <div class="panel-heading">
    <h3 class="panel-title">Panel title</h3></div>
    <div class="panel-body">Panel content</div>
    <div class="panel-footer">Panel footer</div>
</div>
```

13 JAVASCRIPT

13.1 MODAL (I)



Dialogos modales

13.2 MODAL (II)

```
<button class="btn btn-primary btn-lg" data-toggle="modal" data-target='
    Launch demo modal
</button>
```

13.3 MODAL (III)

```
<div class="modal fade" id="myModal" tabindex="-1" role="dialog"  
aria-labelledby="myModalLabel" aria-hidden="true">  
  <div class="modal-dialog">  
    <div class="modal-content">  
      <div class="modal-header">...</div>  
      <div class="modal-body">...</div>  
      <div class="modal-footer">...</div>  
    </div>  
  </div>  
</div>
```

13.4 TABS (I)

Tabs

Home Profile Dropdown ▾

Food truck fixie locavore, accusamus mcsweeney's marfa nulla single-origin coffee squid. Exercitation +1 labore velit, blog sartorial PBR leggings next level wes anderson artisan four loko farm-to-table craft beer twee. Qui photo booth letterpress, commodo enim craft beer mlkshk aliquip jean shorts ullamco ad vinyl cillum PBR. Homo nostrud organic, assumenda labore aesthetic magna delectus mollit. Keytar helvetica VHS salvia yr, vero magna velit sapiente labore stumptown. Vegan fanny pack odio cillum wes anderson 8-bit, sustainable jean shorts beard ut DIY ethical culpa terry richardson biodiesel. Art party scenester stumptown, tumblr butcher vero sint qui sapiente accusamus tattooed echo park.

Tabs

13.5 TABS (II)

```
<ul id="myTab" class="nav nav-tabs" role="tablist">
  <li class="">
    <a href="#home" role="tab" data-toggle="tab">Home</a></li>
  <li class="active">
    <a href="#profile" role="tab" data-toggle="tab">Profile</a></li>
  ...
</ul>
```

13.6 TABS (III)

```
<div id="myTabContent" class="tab-content">
  <div class="tab-pane fade" id="home">
    <p>...</p>
  </div>
  <div class="tab-pane fade active in" id="profile">
    <p>...</p>
  </div>
  ...
</div>
```

13.7 TOOLTIPS (I)

Tooltips

Tight pants next level keffiyeh [you probably](#) haven't heard of them. Photo booth beard raw denim letterpress vegan messenger bag stumptown. Farm-to-table seitan, mcsweeney's fixie sustainable quinoa 8-bit american apparel [have a](#) terry richardson vinyl chambray. Beard stumptown, cardigans banh mi lomo thundercats. Tofu biodiesel williamsburg marfa, four loko mcsweeney's cleanse vegan chambray. A really ironic artisan [whatever keytar](#), scenester farm-to-table banksy Austin [twitter handle](#) freegan cred raw denim single-origin coffee viral.

Tooltip on left

Tooltip on top

Tooltip on bottom

Tooltip on right

Tooltip on right

Tooltips

13.8 TOOLTIPS (II)

```
<script>
$( document ).ready( function() {
  $('[data-toggle="tooltip"]')
    .tooltip();
});
</script>
```


13.9 TOOLTIPS (III)

```
<p class="muted">  
  Farm-to-table seitan, mcsweeney's fixie sustainable quinoa 8-bit  
  american apparel  
  <a href="#" data-toggle="tooltip" title="Another tooltip">have a</a>  
  terry richardson vinyl chambray.</p>
```

13.10 TOOLTIPS (IV)

```
<button type="button" class="btn btn-default" data-toggle="tooltip"  
data-placement="right" title="Tooltip on right">  
  Tooltip on right</button>
```

13.11 POPOVER (I)



Popover

13.12 POPOVER (II)

```
<script>
$( document ).ready( function() {
  $('[data-toggle="popover"]')
    .popover();
});
</script>
```

13.13 POPOVER (III)

```
<button type="button" class="btn btn-default" title="Popover title"  
data-container="body" data-toggle="popover" data-placement="right"  
data-content="Vivamus sagittis lacus vel augue laoreet rutrum faucibus.  
Popover on right</button>
```

13.14 ACCORDION (I)

Accordion

Collapsible Group Item #1

Collapsible Group Item #2

Anim pariatur cliche reprehenderit, enim eiusmod high life accusamus terry richardson ad squid. 3 wolf moon officia aute, non cupidatat skateboard dolor brunch. Food truck quinoa nesciunt laborum eiusmod. Brunch 3 wolf moon tempor, sunt aliqua put a bird on it squid single-origin coffee nulla assumenda shoreditch et. Nihil anim keffiyeh helvetica, craft beer labore wes anderson cred nesciunt sapiente ea proident. Ad vegan excepteur butcher vice lomo. Leggings occaecat craft beer farm-to-table, raw denim aesthetic synth nesciunt you probably haven't heard of them accusamus labore sustainable VHS.


Collapsible Group Item #3

Accordion

13.15 ACCORDION (II)

```
<div class="panel-group" id="accordion">
  <div class="panel panel-default">
    <div class="panel-heading">
      <h4 class="panel-title">
        <a data-toggle="collapse" data-parent="#accordion" href="#collapseOne">
          Group Item #1</a></h4></div>
      <div id="collapseOne" class="panel-collapse collapse in">
        <div class="panel-body">...</div></div>
    </div>
    ...
  </div>
```

13.16 CAROUSEL (I)



Carousel

13.17 CAROUSEL (II)

```
<div class="container" style="max-width: 900px">
  <div id="carousel-example-generic" class="carousel slide" data-ride="c
    <ol class="carousel-indicators">...</ol>
    <div class="carousel-inner">...</div>
    <a class="left carousel-control" ...</a>
    <a class="right carousel-control" ...</a>
  </div>
</div>
```

13.18 CAROUSEL (III)

```
<ol class="carousel-indicators">
  <li data-target="#carousel-example-generic" data-slide-to="0"
      class=""></li>
  <li data-target="#carousel-example-generic" data-slide-to="1"
      class="active"></li>
  <li data-target="#carousel-example-generic" data-slide-to="2"
      class=""></li>
</ol>
```

13.19 CAROUSEL (IV)

```
<div class="carousel-inner">
  <div class="item active left">
    
  </div>
  <div class="item next left">
    
  </div>
  <div class="item">
    
  </div>
</div>
```


13.20 CAROUSEL (V)

```
<a class="left carousel-control" href="#carousel-example-generic"  
    role="button" data-slide="prev">  
    <span class="glyphicon glyphicon-chevron-left"></span>  
</a>  
<a class="right carousel-control" href="#carousel-example-generic"  
    role="button" data-slide="next">  
    <span class="glyphicon glyphicon-chevron-right"></span>  
</a>
```

14 EJEMPLOS

14.1 STARTER TEMPLATE

- <http://getbootstrap.com/examples/starter-template>



14.2 BOOTSTRAP THEME

- <http://getbootstrap.com/examples/theme>

The screenshot displays a website template using the Bootstrap theme. At the top is a dark navigation bar with the brand name "Bootstrap theme" and links for Home, About, Contact, and Dropdown. Below the navigation is a large callout area (hero unit) containing the text "Hello, world!". A descriptive paragraph follows, stating: "This is a template for a simple marketing or informational website. It includes a large callout called the hero unit and three supporting pieces of content. Use it as a starting point to create something more unique." A blue "Learn more »" button is located at the bottom of the callout. The main content area features a section titled "Buttons" with four rows of button samples. Each row contains seven buttons labeled Default, Primary, Success, Info, Warning, Danger, and Link, followed by a "Link" text label. Below the buttons is a section titled "Thumbnails" featuring a single placeholder thumbnail image with the dimensions "200x200".

14.3 GRIDS

- <http://getbootstrap.com/examples/grid>

Bootstrap grid examples

Basic grid layouts to get you familiar with building within the Bootstrap grid system.

Three equal columns

Get three equal-width columns starting at desktops and scaling to large desktops. On mobile devices, tablets and below, the columns will automatically stack.

.col-md-4	.col-md-4	.col-md-4
-----------	-----------	-----------

Three unequal columns

Get three columns starting at desktops and scaling to large desktops of various widths. Remember, grid columns should add up to twelve for a single horizontal block. More than that, and columns start stacking no matter the viewport.

.col-md-3	.col-md-6	.col-md-3
-----------	-----------	-----------

Two columns

Get two columns starting at desktops and scaling to large desktops.

.col-md-8	.col-md-4
-----------	-----------

Full width, single column

No grid classes are necessary for full-width elements.

Two columns with two nested columns


Per the documentation, nesting is easy—just put a row of columns within an existing row. This gives you two columns starting at desktops and scaling to large desktops, with another two (equal widths) within the larger column.

At mobile device sizes, tablets and down, these columns and their nested columns will stack.

.col-md-8	.col-md-4
.col-md-6	.col-md-6


14.4 JUMBOTRON

- <http://getbootstrap.com/examples/jumbotron>




14.5 NARROW JUMBOTRON

- <http://getbootstrap.com/examples/jumbotron-narrow>




14.6 NAVBAR

- <http://getbootstrap.com/examples/navbar>




14.7 STATIC TOP NAVBAR

- <http://getbootstrap.com/examples/navbar-static-top>




14.8 FIXED NAVBAR

- <http://getbootstrap.com/examples/navbar-fixed-top>




14.9 COVER

- <http://getbootstrap.com/examples/cover>




14.10 CAROUSEL

- <http://getbootstrap.com/examples/carousel>



14.11 BLOG

- <http://getbootstrap.com/examples/blog>



The screenshot shows the official example template for creating a blog with Bootstrap. The header features a blue navigation bar with links to Home, New features, Press, New hires, and About. The main title "The Bootstrap Blog" is prominently displayed, followed by a subtitle "The official example template of creating a blog with Bootstrap." Below the title, a sample blog post titled "Sample blog post" is shown, dated December 1, 2013, by Mark. The post content includes several paragraphs of text and a code block. To the right, there are two sidebar boxes: "About" and "Archives". The "About" box contains placeholder text. The "Archives" box lists months from December 2013 down to January 2013. At the bottom, there's a section titled "Elsewhere" with links to GitHub, Twitter, and Facebook.

Home New features Press New hires About

The Bootstrap Blog

The official example template of creating a blog with Bootstrap.

Sample blog post

December 1, 2013 by [Mark](#)

This blog post shows a few different types of content that's supported and styled with Bootstrap. Basic typography, images, and code are all supported.

Cum sociis natoque penatibus et magnis [dis parturient montes](#), nascetur ridiculus mus. Aenean eu leo quam. Pellentesque ornare sem lacinia quam venenatis vestibulum. Sed posuere consectetur est at lobortis. Cras mattis consectetur purus sit amet fermentum.

Curabitur blandit tempus porttitor. **Nullam quis risus eget urna mollis** ornare vel eu leo. Nullam id dolor id nibh ultricies vehicula ut id elit.

Etiam porta *sem malesuada magna* mollis euismod. Cras mattis consectetur purus sit amet fermentum. Aenean lacinia bibendum nulla sed consectetur.

Heading

Vivamus sagittis lacus vel augue laoreet rutrum faucibus dolor auctor. Duis mollis, est non commodo luctus, nisi erat porttitor ligula, eget lacinia odio sem nec elit. Morbi leo risus, porta ac consectetur ac, vestibulum at eros.

Sub-heading

Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus.

Example code block

Aenean lacinia bibendum nulla sed consectetur. Etiam porta *sem malesuada magna* mollis euismod. Fusce dapibus, tellus ac cursus commodo, tortor

About

Etiam porta sem malesuada magna mollis euismod. Cras mattis consectetur purus sit amet fermentum. Aenean lacinia bibendum nulla sed consectetur.

Archives

[December 2013](#)
[November 2013](#)
[October 2013](#)
[September 2013](#)
[August 2013](#)
[July 2013](#)
[June 2013](#)
[May 2013](#)
[April 2013](#)
[March 2013](#)
[February 2013](#)
[January 2013](#)

Elsewhere

[GitHub](#)
[Twitter](#)
[Facebook](#)

14.12 DASHBOARD


- <http://getbootstrap.com/examples/dashboard>

The screenshot shows a dashboard interface with a dark header bar containing a search input and navigation links for Dashboard, Settings, Profile, and Help. A sidebar on the left is titled 'Overview' and lists various navigation items: Reports, Analytics, Export, Nav item, Nav item again, One more nav, Another nav item, More navigation, and Nav item again. The main content area is titled 'Dashboard' and features four large circular icons labeled '200x200'. Below each icon is a label with placeholder text: 'Label Something else'. Underneath the icons is a section titled 'Section title' containing a table with 12 rows of placeholder data.

#	Header	Header	Header	Header
1,001	Lorem	ipsum	dolor	sit
1,002	amet	consectetur	adipiscing	elit
1,003	Integer	nec	odio	Praesent
1,003	libero	Sed	cursus	ante
1,004	dapibus	diam	Sed	ni
1,005	Nulla	quis	sem	at
1,006	nibh	elementum	imperdiet	Duis
1,007	sagittis	ipsum	Praesent	mauris
1,008	Fusce	nec	tellus	sed
1,009	augue	semper	porta	Mauris
1,010	massa	Vestibulum	lacinia	arcu
1,011	eg	nulla	Class	aptent
1,012	taciti	sociosqu	ad	litora

14.13 SIGN-IN PAGE

- <http://getbootstrap.com/examples/signin>



14.14 JUSTIFIED NAV

- <http://getbootstrap.com/examples/justified-nav>

The screenshot shows a website layout with a justified navigation bar at the top. The navigation bar is a horizontal row of six items: Home, Projects, Services, Downloads, About, and Contact. The 'Home' item is currently active, indicated by a darker background. Below the navigation bar, the main content area features a large heading 'Marketing stuff!' in bold black font. Underneath it is a short paragraph of placeholder text: 'Cras justo odio, dapibus ac facilisis in, egestas eget quam. Fusce dapibus, tellus ac cursus commodo, tortor mauris condimentum nibh, ut fermentum massa justo sit amet.' A green button labeled 'Get started today' is centered below the paragraph. The main content area is divided into three columns, each containing a heading, a short text description, and a 'View details >' button. The first column's heading is 'Heading', its text is a long placeholder sentence, and its button is blue. The second column's heading is 'Heading', its text is a long placeholder sentence, and its button is blue. The third column's heading is 'Heading', its text is a long placeholder sentence, and its button is blue. At the bottom of the page, there is a thin horizontal line followed by the copyright notice '© Company 2013'.

14.15 STICKY FOOTER

- <http://getbootstrap.com/examples/sticky-footer>

Sticky footer


Pin a fixed-height footer to the bottom of the viewport in desktop browsers with this custom HTML and CSS.

Use the sticky footer with a fixed navbar if need be, too.

Example courtesy [Martin Bean](#) and [Ryan Fait](#).

14.16 STICKY FOOTER WITH NAVBAR

- <http://getbootstrap.com/examples/sticky-footer-navbar>



14.17 NON-RESPONSIVE BOOTSTRAP

- <http://getbootstrap.com/examples/non-responsive>

The screenshot shows a web page titled "Non-responsive Bootstrap". At the top is a navigation bar with links: "Project name" (highlighted), "Home", "About", "Contact", "Dropdown", and three "Link" buttons. Below the navigation, the main content area has a heading "Non-responsive Bootstrap" and a sub-section "What changes" with a note about the lack of a meta viewport tag. It also includes sections for "Regarding navbars" and "Non-responsive grid system" with a three-column grid example.

Project name Home About Contact Dropdown Link Link Link

Non-responsive Bootstrap

Disable the responsiveness of Bootstrap by fixing the width of the container and using the first grid system tier.

What changes

Note the lack of the `<meta name="viewport" content="width=device-width, initial-scale=1.0">`, which disables the zooming aspect of sites in mobile devices. In addition, we reset our container's width and are basically good to go.

Regarding navbars

As a heads up, the navbar component is rather tricky here in that the styles for displaying it are rather specific and detailed. Overrides to ensure desktop styles display are not as performant or sleek as one would like. Just be aware there may be potential gotchas as you build on top of this example when using the navbar.

Non-responsive grid system

One third	One third	One third
-----------	-----------	-----------

14.18 OFFCANVAS

- <http://getbootstrap.com/examples/offcanvas>

The screenshot shows a website layout using the offcanvas pattern from Bootstrap. At the top is a dark navigation bar with the text "Project name" and links for "Home", "About", and "Contact". Below the navigation is a main content area containing a large heading "Hello, world!". A descriptive paragraph follows, stating: "This is an example to show the potential of an offcanvas layout pattern in Bootstrap. Try some responsive-range viewport sizes to see it in action." To the right of the main content is a sidebar with the title "Sidebar" and several "Link" items. The main content area contains three sets of cards, each with a heading and a "View details >" button. The footer at the bottom left includes the copyright notice "© Company 2013".

Project name Home About Contact

Hello, world!

This is an example to show the potential of an offcanvas layout pattern in Bootstrap. Try some responsive-range viewport sizes to see it in action.

Heading
Donec id elit non mi porta gravida at eget metus. Fusce dapibus, tellus ac cursus commodo, tortor mauris condimentum nibh, ut fermentum massa justo sit amet risus. Etiam porta sem malesuada magna mollis euismod. Donec sed odio dui.
[View details >](#)

Heading
Donec id elit non mi porta gravida at eget metus. Fusce dapibus, tellus ac cursus commodo, tortor mauris condimentum nibh, ut fermentum massa justo sit amet risus. Etiam porta sem malesuada magna mollis euismod. Donec sed odio dui.
[View details >](#)

Heading
Donec id elit non mi porta gravida at eget metus. Fusce dapibus, tellus ac cursus commodo, tortor mauris condimentum nibh, ut fermentum massa justo sit amet risus. Etiam porta sem malesuada magna mollis euismod. Donec sed odio dui.
[View details >](#)

Heading
Donec id elit non mi porta gravida at eget metus. Fusce dapibus, tellus ac cursus commodo, tortor mauris condimentum nibh, ut fermentum massa justo sit amet risus. Etiam porta sem malesuada magna mollis euismod. Donec sed odio dui.
[View details >](#)

Heading
Donec id elit non mi porta gravida at eget metus. Fusce dapibus, tellus ac cursus commodo, tortor mauris condimentum nibh, ut fermentum massa justo sit amet risus. Etiam porta sem malesuada magna mollis euismod. Donec sed odio dui.
[View details >](#)

Heading
Donec id elit non mi porta gravida at eget metus. Fusce dapibus, tellus ac cursus commodo, tortor mauris condimentum nibh, ut fermentum massa justo sit amet risus. Etiam porta sem malesuada magna mollis euismod. Donec sed odio dui.
[View details >](#)

© Company 2013

15 PERSONALIZACIÓN

15.1 TU PROPIO CSS

- Una forma de personalizar tu página web hecha con bootstrap, es **añadiendo un fichero CSS, después de las llamadas a los CSS de bootstrap** (para que sobrescriba los valores)
- Esta es una forma muy manual y muy poco productiva.

15.2 PÁGINA CUSTOMIZE

- Desde la página web de bootstrap <http://getbootstrap.com/customize> se pueden personalizar un montón de variables, y descargar una versión personalizada de bootstrap.

Download

Hooray! Your custom version of Bootstrap is now ready to be compiled. Just click the button below to finish the process.

Compile and Download

Personalizar desde la página web de bootstrap

- Esta forma es más productiva, pero sigue siendo bastante manual, y además no puedes tener un control de cambios eficiente.

15.3 COMPIALAR LESS

- La forma más productiva y eficiente de personalizar bootstrap es compilando los ficheros LESS del core a CSS.

16 ACERCA DE

16.1 LICENCIA

- Estas transparencias están hechas con:
 - MarkdownSlides:
<https://github.com/asanzdiego/markdownslides>
- Estas transparencias están bajo una licencia Creative Commons Reconocimiento-CompartirIgual 3.0:
 - <http://creativecommons.org/licenses/by-sa/3.0/es>

16.2 FUENTES

- Transparencias:
 - <https://github.com/asanzdiego/curso-interfaces-web-2016/tree/master/05-bootstrap/05-bootstrap-3.0/slides>
- Ejercicios:
 - <https://github.com/asanzdiego/curso-interfaces-web-2016/tree/master/05-bootstrap/05-bootstrap-3.0/src>

16.3 BIBLIOGRAFÍA

- Página oficial de Bootstrap:
 - <http://getbootstrap.com>
- Bootstrap sí, pero no
 - <http://bruno.garciaechevaray.com/Bootstrap.The.Meleo/pre>
- Ventajas y desventajas de usar Bootstrap
 - <http://jorgelessin.com/ventajas-y-desventajas-de-usar-boot>