



## Language Fundamentals



# Data Types

## Primitive Data Types:

- byte
- short
- int
- long
- float
- double
- char
- boolean

## Reference Data Types:

- Objects
- Arrays
- String
- Classes
- Interfaces
- Enums

## Special Data Type:

- void



# Variables, Keywords, Literals

## Variables:

- Store data values.
- Require declaration before use.
- Case-sensitive names.
- Have specific data types.
- Assigned values using =.

## Keywords:

- Reserved words in Java.
- Predefined meanings.
- Cannot be used as identifiers.
- Examples: class, public, static, void, if, for, etc.

## Literals:

- Constants representing fixed values.
  - Types include:
    - Integer literals (e.g., 42)
    - Floating-point literals (e.g., 3.14)
    - Character literals (e.g., 'A')
    - String literals (e.g., "Hello")
    - Boolean literals (true and false)



# Comments

- Comments are used for explanations and notes in code.
  - Three types of comments:
  - Single-line comments with `//`.
  - Multi-line comments with `/* ... */`.
  - Documentation comments with `/** ... */`.
- Comments are ignored by the compiler.
- Good comments enhance code readability and understanding.
- Avoid excessive or redundant comments; focus on clarity and relevance.

# Assignment, Initialization

## Assignment:

- Process of storing a value in a variable.
- Done using = operator.
- Variables must be declared before assignment.

## Initialization:

- Giving a variable an initial value at the time of declaration.
- Best practice to initialize variables to avoid default values.
- Example: `int count = 0;`
- They can be initialized during declaration or in constructors/static initializer blocks.

# Assignment, Initialization

## Default Initialization:

- Variables automatically initialized to default values if not explicitly initialized.
- Default values depend on data type.

## Final Variables:

- final variables are constants and cannot be reassigned.
- Declared using final keyword.
- Example: `final int MAX_VALUE = 100;`

## Instance and Class Variables:

- Instance variables are associated with instances (objects) of a class.
- Class variables are shared among all instances of a class.

# Control Structures

## IF-ELSE Statements:

- Used for conditional branching.
- else if clauses can be used for multiple condition checks.
- Useful for handling different cases based on conditions.

## SWITCH-CASE Statements:

- Used for performing actions based on the value of an expression.
- break statements are used to exit the switch block after a case is executed.
- default case is optional and executes when no other cases match.
- Efficient for handling multiple values or options.

# Loops - For, While, Do While, ForEach

## For Loop:

- Iterates a specific number of times.
- Syntax: `for (initialization; condition; update) { ... }`

## While Loop:

- Repeatedly executes code while a condition is true.
- Syntax: `while (condition) { ... }`

## Do-While Loop:

- Executes code at least once, then continues while a condition is true.
- Syntax: `do { ... } while (condition);`

## For-Each (Enhanced for) Loop:

- Iterates over elements in an array or collection.
- Syntax: `for (elementType element : arrayOrCollection) { ... }`





Any or all third-party material that are available in this content are provided "as is" without warranty of any kind, either expressed or implied and such material is to be used at your own risk. Each third-party content provider is solely responsible for any content it provides, including any warranties (to the extent that such warranties have not been disclaimed), for any claims you may have relating to that content or your use of that content."

[xebia.com](https://xebia.com)

