

```
create database flightbookssystem;
use flightbookssystem;
create table passengers(
passID int primary key auto_increment,
name varchar(20) not null,
country varchar(20) not null,
passport_Number varchar(20) unique not null,
phone_Number int,
createdAt timestamp default current_timestamp
);
```

```
insert into passengers(name,country,passport_Number,phone_Number)
values("asaye", "baharder", "ET987654",0934526715),
("getachew","makele","ET123456",0934590734),("estifanos","dese","ET678654",093
4594575);
select *from passengers;
```

passID	name	country	passport_Numb er	phone_Numb er	createdAt
1	asaye	baharde r	ET987654	934526715	4/13/2026 12:11
2	getache w	makele	ET123456	934590734	4/13/2026 12:11
3	estifanos	dese	ET678654	934594575	4/13/2026 12:11

```
create table Airline(
airID int primary key auto_increment,
country varchar(20) not null
);
insert into Airline(country) values( "ethiopian airlines"),
("emirates airlines"),("kenya airwayes");
select *from Airline;
```

airID	country
1	ethiopian airlines
2	emirates airlines
3	kenya airwayes

```
create table flight(
flightID int primary key auto_increment,
flihtcode varchar(40) not null,
origin varchar(70),
destination varchar(70),
departure_time datetime,
airID int,
arrival_time datetime ,
```

foreign key (airID) references airline(airID)
);

```
insert into flight(flihtcode,origin,destination,departure_time,arrival_time,airID)
values("ET057", "ethiopia", "keneya","2026-07-09 03:07:55","2026-07-09
08:07:55",1),
("KQ456", "keneya", "nirobi","2026-04-24 03:07:55","2026-04-24 01:07:55",2),
("KQ456", "keneya", "ethiopia","2026-09-24 04:07:20","2026-09-24 01:07:55",3);
select *from flight;
```

flightID	flihtcode	origin	destination	departure_time	airID	arrival_time
1	ET057	ethiopia	keneya	7/9/2026 3:07	1	7/9/2026 8:07
2	KQ456	keneya	nirobi	4/24/2026 3:07	2	4/24/2026 1:07
3	KQ456	keneya	ethiopia	9/24/2026 4:07	3	9/24/2026 1:07