

```
foreign key (airID) references airline(airID)
);
```

```
insert into flight(flihtcode,origin,destination,departure_time,arrival_time,airID)
values("ET057", "ethiopia", "keneya","2026-07-09 03:07:55","2026-07-09
08:07:55",1),
("KQ456", "keneya", "nirobi","2026-04-24 03:07:55","2026-04-24 01:07:55",2),
("KQ456", "keneya", "ethiopia","2026-09-24 04:07:20","2026-09-24 01:07:55",3);
select *from flight;
```

flightID	flihtcode	origin	destination	departure_time	airID	arrival_time
1	ET057	ethiopia	keneya	7/9/2026 3:07	1	7/9/2026 8:07
2	KQ456	keneya	nirobi	4/24/2026 3:07	2	4/24/2026 1:07
3	KQ456	keneya	ethiopia	9/24/2026 4:07	3	9/24/2026 1:07

```
create table seat(
seatID int primary key auto_increment,
flightID int,
seat_number varchar(15),
status varchar(30),
unique(flightID,seat_number),
foreign key (flightID) references flight(flightID)
);
```

```
insert into seat (seatID,flightID,seat_number,status) values( 4,1,"seat
1C","Available"),
( 5,2,"seat 2C","Available"),( 6,3,"seat 3C","Booked");
select *from seat;
```

seatID	flightID	seat_number	status
4	1	seat 1C	Available
5	2	seat 2C	Available
6	3	seat 3C	Booked

```
create table booking(
bookID int primary key auto_increment,
flightID int,
passID int,
seatID int,
status varchar(30),
```

```

booking_date timestamp default current_timestamp,
foreign key (flightID) references flight(flightID),
foreign key (passID) references passengers (passID),
foreign key (seatID) references seat(seatID),
unique(flightID,seatID)
);

```

```

insert into booking (paymentID,bookID,flightID,passID,seatID,status) values(7,1,
1,4,"confirmed"),
(8,2, 2,5,"confirmed"),
(9,3, 3,6,"pending");

```

```

select *from booking;

```

bookID	passID	seatID	status	booking_date
7	1	4	confirmed	4/13/2026 12:42
8	2	5	confirmed	4/13/2026 12:42
9	3	6	pending	4/13/2026 12:42

```

create table payment(
paymentID int primary key auto_increment,
bookID int,
method varchar(20),
status varchar(15),
payment_date timestamp default current_timestamp,
foreign key (bookID) references booking(bookID)
);

```

```

insert into payment (paymentID,bookID,method,status)
values(10,7,"telebirr","completed"),
(11,8, "card","pending"),
(12,9, "CBE","pending");

```

```

select *from payment ;

```

paymentID	bookID	method	status	payment_date
10	7	telebirr	completed	4/13/2026 12:51
11	8	card	pending	4/13/2026 12:51
12	9	CBE	pending	4/13/2026 12:51

```

start transaction;
select status from seat where seatID=6 for update;
update seat set status="booked" where seatID=6;
commit;
/*lost update user A*/

```