REPO ONE-PAGE SUMMARY

Baylio

AI call assistant for auto repair shops

Evidence-only summary
Generated from local repo files

WHAT IT IS

Baylio is a multi-tenant SaaS app that gives auto repair shops an AI receptionist. The repo shows a React/Vite dashboard plus an Express/tRPC backend that connects Twilio phone calls to ElevenLabs voice agents, logs calls, analyzes outcomes, and manages billing.

WHO IT'S FOR

Primary: auto repair shop owners/operators who want 24/7 call answering, appointment capture, missed-call recovery, and visibility into call performance. Secondary repo personas include partners and admins.

WHAT IT DOES

- Answers inbound shop calls through Twilio and an ElevenLabs conversational AI agent.
- Captures caller, vehicle, service, appointment, and upsell context during calls.
- Provides shop dashboards for call logs, analytics, missed-call audits, notifications, integrations, and costs.
- Configures shops, Twilio numbers, voices, agent behavior, business hours, and service catalogs.
- Runs post-call workflows for transcription/classification, usage metering, SMS/email recaps, and scorecards.
- Handles Stripe checkout, billing portal, subscriptions, setup fees, tiers, and webhook updates.
- Includes partner/admin portals plus integrations for Google, HubSpot, Sheets, and Shopmonkey services.

HOW IT WORKS

React/Vite SPA - main, partner, and admin routes

v

tRPC client -> Express `/api/trpc` routers

v

Domain routers call services and Drizzle DB helpers

v

PostgreSQL schema via Drizzle; Supabase env vars present

- **Call path:** Twilio `/api/twilio` -> rate limit/signature validation -> context cache/prompt compiler -> ElevenLabs WebSocket -> post-call pipeline.
- **Billing path:** Stripe `/api/stripe` webhooks feed subscription and usage records.
- **Repo conflict:** current Drizzle config/server driver are PostgreSQL; older setup docs still mention MySQL/TiDB.

HOW TO RUN

1. Install prerequisites from docs: Node.js 20+ and pnpm 10+.
2. From the repo root, run `pnpm install`.
3. Create `.env` with the service secrets referenced by docs and `server/_core/env.ts`.
4. Run `pnpm dev`. Build/test scripts are `pnpm build`, `pnpm test`, and `pnpm db:push`.

RUN NOTES / GAPS

Environment: docs list `DATABASE_URL`, `JWT_SECRET`, Twilio, ElevenLabs, and Stripe keys; code also references `SUPABASE_*` and `ANTHROPIC_API_KEY`.

Not found in repo: a canonical `.env.example`; docs say copy secrets from the team vault.

Port detail: `server/_core/index.ts` defaults to `PORT || 3000`; `docs/DEV_SETUP.md` says port 5000.

Use `pnpm drizzle-kit generate` and `pnpm drizzle-kit push` for schema work per setup docs/package scripts.

Evidence checked: README.md, package.json, docs/DEV_SETUP.md, docs/ARCHITECTURE.md, client/src/App.tsx, server/_core/index.ts, server/routers.ts, server/db.ts, drizzle.config.ts, drizzle/schema.ts, and source tree names. No external sources used.