

Carnegie Mellon University

DATABASE SYSTEMS

Modern SQL



LECTURE #02 » 15-445/645 FALL 2025 » PROF. ANDY PAVLO

ADMINISTRIVIA



Project #0 is due Sunday Sept 7th @ 11:59pm

Homework #1 is due Sunday Sept 7th @ 11:59pm

No in-class lecture next Wednesday Sept 3rd

LAST CLASS



We introduced the Relational Model as the superior data model for databases.

We then showed how Relational Algebra is the building blocks that will allow us to query and modify a relational database.

SQL HISTORY



In 1971, IBM created its first relational query language called SQUARE.

IBM then created "SEQUEL" in 1972 for IBM System R prototype DBMS.

→ Structured English Query Language

IBM releases commercial SQL-based DBMSs:

→ System/38 (1979), SQL/DS (1981), and DB2 (1983).

SQL HISTORY

In 1971, IBM created its called SQUARE.

IBM then created "SEQU" prototype DBMS.

→ Structured English Query

IBM releases commercial

→ System/38 (1979), SQL/1

Q2. Find the average salary of employees in the Shoe Department.

AVG ($\overset{\text{EMP}}{\text{SAL}}$ $\overset{\text{DEPT}}{('SHOE')}$)

Mappings may be *composed* by applying one mapping to the result of another, as illustrated by Q3.

Q3. Find those items sold by departments on the second floor.

ITEM $\overset{\text{SALES}}{\text{DEPT}} \circ \overset{\text{LOC}}{\text{DEPT}} \overset{\text{FLOOR}}{(2)}$

The floor '2' is first mapped to the departments located there, and then to the items which they sell. The range of the inner mapping must be compatible with the domain of the outer mapping, but they need not be identical, as illustrated by Q4.

SQL HISTORY



ANSI Standard in 1986. ISO in 1987

→ Structured Query Language

Current standard is **SQL:2023**

→ **SQL:2023** → Property Graph Queries, Muti-Dim. Arrays

→ **SQL:2016** → JSON, Polymorphic tables

→ **SQL:2011** → Temporal DBs, Pipelined DML

→ **SQL:2008** → Truncation, Fancy Sorting

→ **SQL:2003** → XML, Windows, Sequences, Auto-Gen IDs.

→ **SQL:1999** → Regex, Triggers, OO

The minimum language syntax a system needs to say that it supports SQL is **SQL-92**.

SQL HISTORY



Muti-Dim. Arrays

DML

es, Auto-Gen IDs.

The minimum language syntax a system needs to say that it supports SQL is **SQL-92**.

SQL HISTORY



The minimum language
that it supports SQL is

NEWS COMPUTING

The Rise of SQL > It's become the second programming language everyone needs to know

BY RINA DIANE CABALLAR | 23 AUG 2022 | 3 MIN READ |

ISTOCK

SHARE THIS STORY



TAGS

TOP PROGRAMMING LANGUAGES

SQL

SQL dominated the jobs ranking in [IEEE Spectrum's interactive rankings of the top programming languages](#) this year. Normally, the top position is occupied by Python or other mainstays, such as C, C++, Java, and JavaScript, but the sheer number of times employers said they wanted developers with SQL skills, albeit in addition to a more general-purpose language, boosted it to No. 1.

So what's behind SQL's soar to the top? The ever-increasing use of databases, for one. SQL has become the primary query language for accessing and managing data stored in such databases—specifically [relational databases](#), which represent data in table form with rows and columns. Databases serve as the foundation of many enterprise applications and are increasingly found in other places as well, for example taking the place of traditional file systems in smartphones.

"This ubiquity means that every software developer will have to interact with databases no matter the field, and SQL is the de facto standard for interacting with databases," says [Andy Pavlo](#), a professor specializing in database management at the [Carnegie Mellon University \(CMU\) School of Computer Science](#) and a member of the [CMU database group](#).



Jo Kristian Bergum
@jobergum

Tensor and vector da
decade. A disruption
neural representatio

Natural query langu
(SQL).

2:35 AM · Apr 27, 202

39 Retweets 32 Qu

The
that



RELATIONAL LANGUAGES



Data Manipulation Language (DML)

Data Definition Language (DDL)

Data Control Language (DCL)

Also includes:

- View definition
- Integrity & Referential Constraints
- Transactions

Important: SQL is based on **bags** (duplicates) not **sets** (no duplicates).

TODAYS AGENDA



Aggregations + Group By
String / Date / Time Operations
Output Control + Redirection
Nested Queries
Lateral Joins
Common Table Expressions
Window Functions
⚡DB Flash Talk: dbt

EXAMPLE DATABASE



student(sid, name, login, gpa)

sid	name	login	age	gpa
53666	RZA	rza@cs	56	4.0
53688	Taylor	swift@cs	35	3.9
53655	Tupac	shakur@cs	25	3.5

enrolled(sid, cid, grade)

sid	cid	grade
53666	15-445	C
53688	15-721	A
53688	15-826	B
53655	15-445	B
53666	15-721	C

course(cid, name)

cid	name
15-445	Database Systems
15-721	Advanced Database Systems
15-826	Data Mining
15-799	Special Topics in Databases

AGGREGATES

Functions that return a single value from a bag of tuples:

- **AVG(col)** → Return the average col value.
- **MIN(col)** → Return minimum col value.
- **MAX(col)** → Return maximum col value.
- **SUM(col)** → Return sum of values in col.
- **COUNT(col)** → Return # of values for col.

AGGREGATES

Aggregate functions can (almost) only be used in the **SELECT** output list.

Get # of students with a “@cs” login:

```
SELECT COUNT(login) AS cnt  
FROM student WHERE login LIKE '%@cs'
```

AGGREGATES

Aggregate functions can (almost) only be used in the **SELECT** output list.

Get # of students with a “@cs” login:

```
SELECT COUNT(login) AS cnt
```

```
FROM student WHERE login LIKE '@cs'
```

```
SELECT COUNT(*) AS cnt
```

```
FROM student WHERE login LIKE '@cs'
```

AGGREGATES

Aggregate functions can (almost) only be used in the **SELECT** output list.

Get # of students with a “@cs” login:

```
SELECT COUNT(login) AS cnt
```

```
FROM student WHERE login LIKE '%@cs'
```

```
SELECT COUNT(*) AS cnt
```

```
FROM student WHERE login LIKE '%@cs'
```


AGGREGATES

Aggregate functions can (almost) only be used in the **SELECT** output list.

Get # of students with a “@cs” login:

```
SELECT COUNT(login) AS cnt
```

```
SELECT COUNT(*) AS cnt
```

```
SELECT COUNT(1) AS cnt
```

```
SELECT COUNT(1+1+1) AS cnt  
FROM student WHERE login LIKE '%@cs'
```

AGGREGATES

Output of other columns outside of an aggregate is undefined.

Get the average GPA of students enrolled in each course.

```
SELECT AVG(s.gpa), e.cid  
FROM enrolled AS e JOIN student AS s  
ON e.sid = s.sid
```

AVG(s.gpa)	e.cid
3.86	???

AGGREGATES

Output of other columns outside of an aggregate is undefined.

Get the average GPA of students enrolled in each course.



```
SELECT AVG(s.gpa), e.cid
FROM enrolled AS e JOIN student AS s
ON e.sid = s.sid
```

AVG(s.gpa)	e.cid
3.86	???

```
SELECT AVG(s.gpa), ANY_VALUE(e.cid)
FROM enrolled AS e JOIN student AS s
ON e.sid = s.sid
```

AVG(s.gpa)	e.cid
3.86	15-445

GROUP BY

Project tuples into subsets and calculate aggregates against each subset.

```
SELECT AVG(s.gpa), e.cid  
FROM enrolled AS e JOIN student AS s  
ON e.sid = s.sid  
GROUP BY e.cid
```

e.sid	s.sid	s.gpa	e.cid
53435	53435	2.25	15-721
53439	53439	2.70	15-721
56023	56023	2.75	15-826
59439	59439	3.90	15-826
53961	53961	3.50	15-826
58345	58345	1.89	15-445

GROUP BY

Project tuples into subsets and calculate aggregates against each subset.

```
SELECT AVG(s.gpa), e.cid
FROM enrolled AS e JOIN student AS s
ON e.sid = s.sid
GROUP BY e.cid
```

e.sid	s.sid	s.gpa	e.cid
53435	53435	2.25	15-721
53439	53439	2.70	15-721
56023	56023	2.75	15-826
59439	59439	3.90	15-826
53961	53961	3.50	15-826
58345	58345	1.89	15-445



AVG(s.gpa)	e.cid
2.46	15-721
3.39	15-826
1.89	15-445

GROUPING SETS

Specify multiple groupings in a single query instead of using **UNION ALL** to combine the results of several individual **GROUP BY** queries.

```
SELECT c.name AS c_name, e.grade,
       COUNT(*) AS num_students
FROM   enrolled AS e
JOIN   course AS c ON e.cid = c.cid
GROUP BY GROUPING SETS (
    (c.name, e.grade), -- By course and grade
    (c.name),          -- By course only
    ()                 -- Overall total
);
```

GROUPING SETS

Specify multiple groupings in a single query instead of using **UNION ALL** to combine the results of several individual **GROUP BY** queries.

```
SELECT c.name AS c_name, e.grade,
       COUNT(*) AS num_students
  FROM enrolled AS e
  JOIN course AS c ON e.cid = c.cid
  GROUP BY GROUPING SETS (
    (c.name, e.grade), -- By course and grade
    (c.name),          -- By course
    ()                 -- Overall total
  );
```

cid	grade	num_students
<i>null</i>	<i>null</i>	5
15-721	C	1
15-826	B	1
15-445	B	1
15-445	C	1
15-721	A	1
15-445	<i>null</i>	2
15-826	<i>null</i>	1
15-721	<i>null</i>	2

GROUPING SETS

Specify multiple groupings in a single query instead of using **UNION ALL** to combine the results of several individual **GROUP BY** queries.

```
SELECT c.name AS c_name, e.grade,
       COUNT(*) AS num_students
  FROM enrolled AS e
  JOIN course AS c ON e.cid = c.cid
  GROUP BY GROUPING SETS (
    (c.name, e.grade) -- By course and grade
    (c.name),         -- By course
    ()                -- Overall total
  );
```

cid	grade	num_students
<i>null</i>	<i>null</i>	5
15-721	C	1
15-826	B	1
15-445	B	1
15-445	C	1
15-721	A	1
15-445	<i>null</i>	2
15-826	<i>null</i>	1
15-721	<i>null</i>	2

HAVING

Filters results based on aggregation computation.

Like a **WHERE** clause for a **GROUP BY**

```
SELECT AVG(s.gpa) AS avg_gpa, e.cid  
  FROM enrolled AS e, student AS s  
 WHERE e.sid = s.sid  
       AND avg_gpa > 3.9  
 GROUP BY e.cid
```

HAVING

Filters results based on aggregation computation.

Like a **WHERE** clause for a **GROUP BY**

```
SELECT AVG(s.gpa) AS avg_gpa, e.cid  
  FROM enrolled AS e, student AS s  
 WHERE e.sid = s.sid  
    AND avg_gpa > 3.9  
 GROUP BY e.cid
```




HAVING

Filters results based on aggregation computation.

Like a **WHERE** clause for a **GROUP BY**

```
SELECT AVG(s.gpa) AS avg_gpa, e.cid  
  FROM enrolled AS e, student AS s  
 WHERE e.sid = s.sid  
 GROUP BY e.cid  
 HAVING avg_gpa > 3.9;
```



HAVING

Filters results based on aggregation computation.

Like a **WHERE** clause for a **GROUP BY**

```
SELECT AVG(s.gpa) AS avg_gpa, e.cid  
  FROM enrolled AS e, student AS s  
 WHERE e.sid = s.sid  
 GROUP BY e.cid  
HAVING AVG(s.gpa) > 3.9;
```

AVG(s.gpa)	e.cid
3.75	15-415
3.950000	15-721
3.900000	15-826



avg_gpa	e.cid
3.950000	15-721

STRING OPERATIONS

	String Case	String Quotes
SQL-92	Sensitive	Single Only
Postgres	Sensitive	Single Only
MySQL	Insensitive	Single/Double
SQLite	Sensitive	Single/Double
MSSQL	Sensitive	Single Only
Oracle	Sensitive	Single Only

WHERE UPPER(name) = UPPER('TuPaC') **SQL-92**

WHERE name = "TuPaC" **MySQL**

STRING OPERATIONS

LIKE provides string matching with special match operators:

- **'%'** Matches any substring (including empty strings).
- **'_'** Match any one character

SIMILAR TO allows for regular expression matching.

- In the SQL standard but not all systems support it.
- Other systems also support POSIX-style regular expressions.

```
SELECT * FROM enrolled AS e
WHERE e.cid LIKE '15-%';
```

```
SELECT * FROM student AS s
WHERE s.login LIKE '%@c_';
```

```
SELECT * FROM student AS s
WHERE login SIMILAR TO
'[\w]{3}@cs';
```

STRING OPERATIONS

SQL-92 defines string functions.

→ Many DBMSs also have their own unique functions

Can be used in either output and predicates:

```
SELECT SUBSTRING(name,1,5) AS abbrev_name  
FROM student WHERE sid = 53688
```

```
SELECT * FROM student AS s  
WHERE UPPER(s.name) LIKE 'KAN%'
```

STRING OPERATIONS

SQL standard defines the **||** operator for concatenating two or more strings together.

```
SELECT name FROM student
WHERE login = LOWER(name) || '@cs'
```

SQL-92

```
SELECT name FROM student
WHERE login = LOWER(name) + '@cs'
```

MSSQL

```
SELECT name FROM student
WHERE login = CONCAT(LOWER(name), '@cs')
```

MySQL

DATE/TIME OPERATIONS



Operations to manipulate and modify **DATE/TIME** attributes.

Can be used in both output and predicates.

Support/syntax varies wildly...

Demo: Compute the number of days since the beginning of the year.

OUTPUT CONTROL

ORDER BY <column*> [ASC|DESC]

→ Sort tuples by the values in one or more of their columns.

FETCH {FIRST|NEXT} <#> ROWS OFFSET <#> ROWS

→ Limit # of tuples returned in output.
→ Can set an offset to return a “range”

```
SELECT sid, name FROM student
WHERE login LIKE '%@cs'
FETCH FIRST 10 ROWS ONLY;
```

```
SELECT sid, name FROM student
WHERE login LIKE '%@cs'
ORDER BY gpa
OFFSET 5 ROWS
FETCH FIRST 5 ROWS WITH TIES;
```

```
SELECT TOP 10 sid, name MSSQL
FROM student
WHERE login LIKE '%@cs';
```

OUTPUT REDIRECTION

Store query results in another table:

- Table must not already be defined.
- Table will have the same # of columns with the same types as the input.

```
SELECT DISTINCT cid INTO CourseIds SQL-92
FROM enrolled;
```

```
CREATE TABLE CourseIds ( MySQL
  SELECT DISTINCT cid FROM enrolled);
```

OUTPUT REDIRECTION

Store query results in another table:

- Table must not already be defined.
- Table will have the same # of columns with the same types as the input.

```
SELECT DISTINCT cid INTO CourseIds
FROM enrolled;
```

SQL-92

```
SELECT DISTINCT cid
INTO TEMPORARY CourseIds
FROM enrolled;
```

Postgres

```
CREATE TABLE CourseIds (
  SELECT DISTINCT cid FROM enrolled);
```

MySQL

NESTED QUERIES

Invoke a query inside of another query to compose more complex computations.

→ Inner queries can appear (almost) anywhere in query.

```
SELECT name FROM student WHERE  
sid IN (SELECT sid FROM enrolled)
```

NESTED QUERIES

Invoke a query inside of another query to compose more complex computations.

→ Inner queries can appear (almost) anywhere in query.

Outer Query → `SELECT name FROM student WHERE
sid IN (SELECT sid FROM enrolled)` ← **Inner Query**

```
SELECT sid,  
       (SELECT name FROM student AS s  
        WHERE s.sid = e.sid) AS name  
FROM enrolled AS e;
```

NESTED QUERIES

Get the names of students in '15-445'

```
SELECT name FROM student  
WHERE ...
```

sid in the set of people that take 15-445

NESTED QUERIES

Get the names of students in '15-445'

```
SELECT name FROM student
WHERE ...
      SELECT sid FROM enrolled
      WHERE cid = '15-445'
```


NESTED QUERIES


Get the names of students in '15-445'

```
SELECT name FROM student
WHERE sid IN (
  SELECT sid FROM enrolled
  WHERE cid = '15-445'
)
```

NESTED QUERIES

Get the names of students in '15-445'

```
SELECT name FROM student
WHERE sid IN (
  SELECT sid FROM enrolled
  WHERE cid = '15-445'
)
```



NESTED QUERIES

ALL → The expression must be true for all rows in the sub-query.

ANY → The expression must be true for at least one row in the sub-query.

IN → Equivalent to '**=ANY()**' .

EXISTS → At least one row is returned without comparing it to an attribute in outer query.

NESTED QUERIES

Find student record with the highest id that is enrolled in at least one course.

```
SELECT sid, name FROM student  
WHERE ...
```

"Is the highest enrolled sid"

NESTED QUERIES

Find student record with the highest id that is enrolled in at least one course.

```
SELECT sid, name FROM student
WHERE sid =
    SELECT MAX(sid) FROM enrolled
```

NESTED QUERIES

Find student record with the highest id that is enrolled in at least one course.

```
SELECT sid, name FROM student
WHERE sid IN (
    SELECT MAX(sid) FROM enrolled
);
```

sid	name
53688	Bieber

NESTED QUERIES

Find student record with the highest id that is enrolled in at least one course.

```
SELECT sid, name FROM student
WHERE sid IN (
    SELECT sid FROM enrolled
    ORDER BY sid DESC FETCH FIRST 1 ROW ONLY
);
```

NESTED QUERIES

Find student record with the highest id that is enrolled in at least one course.

```
SELECT sid, name FROM student
```

```
WHERE (SELECT sid, name FROM student
```

```
WHERE sid >= (
```

```
);
```

```
SELECT student.sid, name  
FROM student
```

```
);
```

```
JOIN (SELECT MAX(sid) AS sid  
      FROM enrolled) AS max_e  
ON student.sid = max_e.sid;
```


NESTED QUERIES

Find all courses that have no students enrolled in it.

```
SELECT * FROM course
WHERE ...
```

“with no tuples in the enrolled table”

cid	name
15-445	Database Systems
15-721	Advanced Database Systems
15-826	Data Mining
15-799	Special Topics in Databases

sid	cid	grade
53666	15-445	C
53688	15-721	A
53688	15-826	B
53655	15-445	B
53666	15-721	C

NESTED QUERIES

Find all courses that have no students enrolled in it.

```
SELECT * FROM course
WHERE NOT EXISTS(
    tuples in the enrolled table
);
```

NESTED QUERIES

Find all courses that have no students enrolled in it.

```
SELECT * FROM course
WHERE NOT EXISTS(
  SELECT * FROM enrolled
  WHERE course.cid = enrolled.cid
);
```

cid	name
15-799	Special Topics in Databases

NESTED QUERIES

Find all courses that have no students enrolled in it.

```
SELECT * FROM course
WHERE NOT EXISTS(
  SELECT * FROM enrolled
  WHERE course.cid = enrolled.cid
);
```

cid	name
15-799	Special Topics in Databases

LATERAL JOINS

The **LATERAL** operator allows a nested query to reference attributes in other nested queries that precede it (according to position in the query).

→ You can think of it like a **for** loop that allows you to invoke another query for each tuple in a table.

```
SELECT * FROM  
  (SELECT 1 AS x) AS t1,  
  LATERAL (SELECT t1.x+1 AS y) AS t2;
```

t1.x	t2.y
1	2

```
for x in [1]:  
    for y in [x+1]:  
        print(x,y)
```

LATERAL JOIN

Calculate the number of students enrolled in each course and the average GPA. Sort output by the courses' enrollment count in ascending order.

```
SELECT * FROM course AS c,
```

For each course:

→ Compute the # of enrolled students

For each course:

→ Compute the average gpa of enrolled students

LATERAL JOIN

Calculate the number of students enrolled in each course and the average GPA. Sort output by the courses' enrollment count in ascending order.

```
SELECT * FROM course AS c,  
  LATERAL (SELECT COUNT(*) AS cnt FROM enrolled  
            WHERE enrolled.cid = c.cid) AS t1,  
  LATERAL (SELECT AVG(gpa) AS avg FROM student AS s  
            JOIN enrolled AS e ON s.sid = e.sid  
            WHERE e.cid = c.cid) AS t2  
ORDER BY cnt ASC;
```

LATERAL JOIN


Calculate the number of students enrolled in each course and the average GPA. Sort output by the courses' enrollment count in ascending order.

```
SELECT * FROM course AS c,  
  LATERAL (SELECT COUNT(*) AS cnt FROM enrolled  
            WHERE enrolled.cid = c.cid) AS t1,  
  LATERAL (SELECT AVG(gpa) AS avg FROM student AS s  
            JOIN enrolled AS e ON s.sid = e.sid  
            WHERE e.cid = c.cid) AS t2  
ORDER BY cnt ASC;
```


LATERAL JOIN

Calculate the number of students enrolled in each course and the average GPA. Sort output by the courses' enrollment count in ascending order.

```
SELECT * FROM course AS c,  
  LATERAL (SELECT COUNT(*) AS cnt FROM enrolled  
            WHERE enrolled.cid = c.cid) AS t1,  
  LATERAL (SELECT AVG(gpa) AS avg FROM student AS s  
            JOIN enrolled AS e ON s.sid = e.sid  
            WHERE e.cid = c.cid) AS t2  
ORDER BY cnt ASC;
```



LATERAL JOIN


Calculate the number of students enrolled in each course and the average GPA. Sort output by the courses' enrollment count in ascending order.

```
SELECT * FROM course AS c,  
  LATERAL (SELECT COUNT(*) AS cnt FROM enrolled  
            WHERE enrolled.cid = c.cid) AS t1,  
  LATERAL (SELECT AVG(gpa) AS avg FROM student AS s  
            JOIN enrolled AS e ON s.sid = e.sid  
            WHERE e.cid = c.cid) AS t2  
ORDER BY cnt ASC;
```

LATERAL JOIN

Calculate the number of students enrolled in each course and the average GPA. Sort output by the courses' enrollment count in ascending order.

```
SELECT * FROM course AS c,
  LATERAL (SELECT COUNT(*)
    WHERE enrolled.cid = c.cid) AS t1,
  LATERAL (SELECT AVG(gpa) AS avg FROM student AS s
    JOIN enrolled AS e ON s.sid = e.sid
    WHERE e.cid = c.cid) AS t2
ORDER BY cnt ASC;
```



cid	name	cnt	avg
15-799	Special Topics in Databases	0	null
15-826	Data Mining	1	3.9
15-445	Database Systems	2	3.75
15-721	Advanced Database Systems	2	3.95

COMMON TABLE EXPRESSIONS

Specify a temporary result set that can then be referenced by another part of that query.

→ Bind/alias output columns to names before the **AS** keyword.

Alternative to nested queries, views, and explicit temp tables.

```
WITH cteName (col1, col2) AS (  
    SELECT 1, 2  
)  
SELECT col1 + col2 FROM cteName
```

COMMON TABLE EXPRESSIONS

Specify a temporary result set that can then be referenced by another part of that query.

→ Bind/alias output columns to names before the **AS** keyword.

Alternative to nested queries, views, and explicit temp tables.

```
WITH cteName (col1, col2) AS (  
    SELECT 1, 2  
)  
SELECT col1 + col2 FROM cteName
```

COMMON TABLE EXPRESSIONS

Find student record with the highest id that is enrolled in at least one course.

```
WITH maxCTE (maxId) AS (  
    SELECT MAX(sid) FROM enrolled  
)  
SELECT name FROM student AS s  
JOIN maxCTE ON s.sid = maxCTE.maxId;
```

COMMON TABLE EXPRESSIONS

Find student record with the highest id that is enrolled in at least one course.

```
WITH maxCTE (maxId) AS (  
    SELECT MAX(sid) FROM enrolled  
)  
SELECT name FROM student AS s  
JOIN maxCTE ON s.sid = maxCTE.maxId;
```

WINDOW FUNCTIONS

Performs a calculation across a set of tuples that are related to the current tuple, without collapsing them into a single output tuple, to support running totals, ranks, and moving averages.

→ Like an aggregation but tuples are not grouped into a single output tuples.

```
SELECT FUNC-NAME(...) OVER (...)  
FROM tableName;
```

*How to "slice" up data
Can also sort tuples*

*Aggregation Functions
Special Functions*

WINDOW FUNCTIONS

Aggregation functions:

→ Anything that we discussed earlier

Special window functions:

→ **ROW_NUMBER()** → # of the current row

→ **RANK()** → Order position of the current row.

sid	cid	grade	row_num
53666	15-445	C	1
53688	15-721	A	2
53688	15-826	B	3
53655	15-445	B	4
53666	15-721	C	5

```
SELECT *, ROW_NUMBER() OVER () AS row_num  
FROM enrolled;
```

WINDOW FUNCTIONS

Aggregation functions:

→ Anything that we discussed earlier

Special window functions:

→ **ROW_NUMBER()** → # of the current row

→ **RANK()** → Order position of the current row.

sid	cid	grade	row_num
53666	15-445	C	1
53688	15-721	A	2
53688	15-826	B	3
53655	15-445	B	4
53666	15-721	C	5

```
SELECT *, ROW_NUMBER() OVER () AS row_num  
FROM enrolled;
```

WINDOW FUNCTIONS

The **OVER** keyword specifies how to group together tuples when computing the window function.

Use **PARTITION BY** to specify group.

```
SELECT cid, sid,  
       ROW_NUMBER() OVER (PARTITION BY cid)  
FROM enrolled  
ORDER BY cid;
```

WINDOW FUNCTIONS

The **OVER** keyword specifies how to group together tuples when computing the window function.

Use **PARTITION BY** to specify group.

cid	sid	row_number
15-445	53666	1
15-445	53655	2
15-721	53688	1
15-721	53666	2
15-826	53688	1

```
SELECT cid, sid,  
       ROW_NUMBER() OVER (PARTITION BY cid)  
FROM enrolled  
ORDER BY cid;
```

WINDOW FUNCTIONS

You can also include an **ORDER BY** in the window grouping to sort entries in each group.

```
SELECT *,  
       ROW_NUMBER() OVER (ORDER BY cid)  
FROM enrolled  
ORDER BY cid;
```

WINDOW FUNCTIONS

Find the student with second highest grade for each course.

*Group tuples by cid
Then sort by grade*


```
SELECT * FROM (  
  SELECT *, RANK() OVER (PARTITION BY cid  
    ORDER BY grade ASC) AS rank  
  FROM enrolled) AS ranking  
WHERE ranking.rank = 2
```

CONCLUSION

SQL is a hot language.

→ Lots of NL2SQL tools, but writing SQL is not going away.

You should (almost) always strive to compute your answer as a single SQL statement.



<https://spectrum.ieee.org/top-programming-languages-2024>

HOMEWORK #1



Write SQL queries to perform basic data analysis.

- Write the queries locally using DuckDB.
- Submit them to Gradescope
- You can submit multiple times and use your best score.

Due: Sunday Sept 7th @ 11:59pm

<https://15445.courses.cs.cmu.edu/fall2025/homework1>

NEXT CLASS

We will begin our journey to understanding the internals of database systems starting with Storage!

No In-Class Lecture!