DialCore Installer — Support Guide

Installing, resuming, upgrading, rolling back and removing DialCore on a customer server · Version 1.9.63

1. What the installer does

One installer sets up a complete DialCore server: PostgreSQL, .NET 10, Asterisk 20, Kamailio, nginx, the TLS certificate, the DialCore API and web app, the firewall and fail2ban. Every change it makes is recorded, so an installation that stops can be **resumed**, and a finished or failed one can be **rolled back** or **uninstalled**. A later version is installed with **upgrade**, which keeps all settings.

Action	When to use it	Online	Offline
Install	A new server	yes	yes
Resume	An installation stopped with an error or was interrupted	yes	yes
Upgrade	DialCore is installed; put a newer version on it	yes	yes
Rollback	Undo the installation, completely or back to a step	yes	yes
Uninstall	Remove DialCore from the server	yes	yes
Check · Summary · Repair DB	See what is there · show addresses and passwords · fix database tables and access	yes	yes

2. Before you start

Item	Requirement
Server	Ubuntu **24.04** or **26.04** (also 20.04/22.04 and Debian 11/12 online), x86_64; 4 GB RAM or more; 20 GB free disk or more; ideally a fresh server
Access	SSH to the server and `sudo` (or root)
Web address	A domain name pointing at the server (for a free certificate), or the server's IP address for a LAN/test install (self-signed certificate)
E-mail	For certificate expiry notices
Licence	The customer's DialCore licence file (uploaded in the web app after installation)
Ports	80, 443 (web), 5060 (Asterisk SIP), 5090 (Kamailio SIP), 4443 (WebRTC), 10000–20000/UDP (call audio) reachable as needed

Which Ubuntu is the server running?

```
grep VERSION_ID /etc/os-release
```

The offline bundle must match it exactly. The installer refuses a bundle built for another release.

Online or offline?

- **Online:** the server can reach the internet. Use the one-command script (section 3.1) or the normal bundle.
- **Offline:** no internet on the server. Use the offline bundle for its Ubuntu release (section 3.2). It carries every package, so nothing is downloaded.

3. Getting the installer onto the server

All files are on the GitHub release page of the backend repository (`Releases → v1.9.63`):

File	Use
`get-dialcore.sh`	One-command online install / actions
`dialcore-installer-1.9.63.tar.gz` + `.sha256`	Online bundle (any supported Ubuntu/Debian)
`dialcore-installer-1.9.63-offline-ubuntu24.04.tar.gz` + `.sha256`	Offline bundle, Ubuntu 24.04
`dialcore-installer-1.9.63-offline-ubuntu26.04.tar.gz` + `.sha256`	Offline bundle, Ubuntu 26.04

3.1 Online, one command

```
curl -fsSL https://github.com/ascentictechnologies-
pvt/dialercore/releases/latest/download/get-dialcore.sh | sudo bash
```

It asks for the domain (or server IP), e-mail and time zone, checks the domain points at the server, downloads the latest bundle, verifies it and installs. For the other actions, add the action name:

```
curl -fsSL https://github.com/ascentictechnologies-
pvt/dialercore/releases/latest/download/get-dialcore.sh | sudo bash -s -- upgrade
#  … | sudo bash -s -- resume | rollback | uninstall | check | summary | menu
```

3.2 With a bundle (offline, or online by hand)

1. Copy the bundle and its `.sha256` file to the server (USB disk, or from a computer on the same network):

   ```
   scp dialcore-installer-1.9.63-offline-ubuntu26.04.tar.gz* <user>@<server>:~
   ```

2. On the server, check and unpack it in a new folder:

```
sudo -i
mkdir -p /root/dialcore-1.9.63 && cd /root/dialcore-1.9.63
mv ~<user>/dialcore-installer-1.9.63-offline-ubuntu26.04.tar.gz* .
sha256sum -c dialcore-installer-1.9.63-offline-ubuntu26.04.tar.gz.sha256   # → OK
tar -xzf dialcore-installer-1.9.63-offline-ubuntu26.04.tar.gz
cd dialcore-installer-1.9.63
```

3. Start the installer. With no command it shows the menu:

```
./dialcore-install.sh
```

4. The menu

```
DialCore installer 1.9.63
-------------------------
  Packages: offline bundle, ubuntu 26.04 amd64 (no internet needed)
  This server: DialCore not installed

   1) Install       new server: asks domain and e-mail, then installs everything
   2) Resume        continue an installation that stopped
   3) Upgrade       this bundle's API and web app on an installed server; settings kept
   4) Rollback      undo the installation (all of it, or the steps after one)
   5) Uninstall     remove DialCore; shared software stays if others use it
   6) Check         what is installed and what is missing (changes nothing)
   7) Summary       addresses, ports, users and passwords of this installation
   8) Repair DB     missing Kamailio tables, database access for Asterisk and Kamailio
   q) Quit
  Choose:
```

Every menu choice is also a command, e.g. `./dialcore-install.sh upgrade`. The commands are listed in section 10.

5. Install (new server)

1. **Look first** (changes nothing): menu **6 Check**. Free any busy port it lists if it is not an older DialCore.
2. Menu **1 Install**. Answer:
   - **Domain**: e.g. `dialcore.customer.com`, or the server IP for a LAN/test server.
   - **E-mail**: for certificate notices.
   - **Time zone**: the customer's business time zone (Enter = the server's).
   - **Change advanced settings?** Press Enter (No). Everything else is detected, generated or standard.
3. Check the summary and confirm. The installation takes 20–45 minutes (Asterisk is compiled).
4. At the end it prints every address, port, user and password. **Save it securely.** It can be shown again with menu **7 Summary**.
5. Open `https://<domain or IP>`, sign in as the platform administrator and upload the licence.

> **Keep an offline copy of `KEK`** from `/var/lib/dialcore-installer/answers.env`. Data encrypted at rest cannot be read without it. Never send this file by e-mail or chat.

> With a server IP or an offline install the certificate is self-signed: browsers warn until it is accepted. Agents must open the site once and accept it.

6. Resume (an installation stopped)

When a step fails the installer shows the step name and the log file:

```
✗ Step "Base packages" failed (exit 100).
  Details: /var/log/dialcore-installer.log
  Fix the problem, then:  ./dialcore-install.sh install --resume
```

1. Read the end of the log: `tail -40 /var/log/dialcore-installer.log`
2. Fix the cause (section 9 lists the known ones).
3. Menu **2 Resume** (or `./dialcore-install.sh install --resume`). Finished steps are skipped; nothing is asked again.

> Resume is always safe to run again. The answers given the first time are reused.

7. Upgrade (installed server, newer version)

Use the **new version's** bundle (unpacked in a new folder, section 3.2), or online: `… get-dialcore.sh | sudo bash -s -- upgrade`.

1. Tell the customer: the web app is unavailable for about 1–2 minutes; agents sign in again afterwards.
2. Menu **3 Upgrade** (or `./dialcore-install.sh upgrade`) and confirm. It:
    1. backs up the database to `/opt/Ascentic/Dialer/BackEnd/backups/` (if the backup fails, nothing changes);
    2. lets the API write in the call recordings folder (`/var/spool/asterisk/recording`, for the MP3 copy of each recording);
    3. installs the new API beside the running one and switches to it; **if the new API does not start, the previous one is put back automatically**;
    4. replaces the web app (the old one is kept as `/opt/Ascentic/Dialer/Frontend.previous`);
    5. repairs the database (missing Kamailio tables, database access for Asterisk and Kamailio).
3. Sign in to the web app and check the dashboard loads, then make a test call.

> **Not changed by an upgrade:** `dialcore.env` (keys, passwords, settings), nginx, Asterisk, Kamailio, certificates and the saved answers.

Going back: the end of the upgrade prints the exact commands. In short:

```
systemctl stop dialcore-api
ln -sfn <previous API folder printed by the upgrade>
/opt/Ascentic/Dialer/BackEnd/current
systemctl start dialcore-api
rm -rf /opt/Ascentic/Dialer/Frontend && mv /opt/Ascentic/Dialer/Frontend.previous
/opt/Ascentic/Dialer/Frontend
```

Restore the database backup only if engineering asks for it.

8. Rollback and Uninstall

Rollback

Menu **4 Rollback**. It lists the steps and asks which to keep:

- **Enter**: undo everything the installer did, newest first.
- **A step name** (e.g. `database`): keep that step and the ones before it, undo the later ones; then **2 Resume** redoes them.

Steps, in order: `preflight questions base tuning postgres dotnet asterisk kamailio certs database app dbgrants asterisk_cfg kamailio_cfg nginx firewall verify`

Uninstall

Menu **5 Uninstall** (or `./dialcore-uninstall.sh`; add `--dry-run` to only see what would be removed).

- It asks for confirmation, then asks separately before deleting the database. A backup is always made first and kept in `/var/backups/dialcore`.
- PostgreSQL, nginx, .NET, Asterisk, fail2ban and ufw are removed **only if nothing else on the server uses them**; the report at the end lists what was removed and what was kept, with the reason.

> Uninstall deletes the DialCore application, its settings and service accounts. Confirm with the customer and make sure the database backup is wanted before answering **y** to deleting the database.

9. Troubleshooting

What you see	What to do
this offline bundle is for ubuntu 24.04 amd64; this server is ubuntu 26.04 amd64	Use the offline bundle for the server's Ubuntu release (section 2).
Step **Base packages** fails, apt says *unmet dependencies*	Wrong offline bundle for this Ubuntu release, or packages from another source on the server. Check `grep VERSION_ID /etc/os-release` and use the matching bundle.
DNS … points at …, not at this server (online script)	Add or fix the DNS A record and wait a few minutes, or use `--cert selfsigned` for a test server.
Step **TLS certificates** fails (Let's Encrypt)	Port 80 must be reachable from the internet. Open it on every firewall in front of the server, then Resume.
Step **Asterisk** fails during the build	Send the last 60 lines of the log to engineering. Resume afterwards: when asked, keep an Asterisk that is already installed.
useradd: group asterisk exists	Fixed in 1.9.63. On an older bundle: `groupdel asterisk`, then Resume.
Kamailio does not register phones; PostgreSQL log shows missing tables (`subscriber`, `location`)	Menu **8 Repair DB**.
PostgreSQL log: *permission denied for table ps_…* (user `asterisk_rt`) or (`kamailio_rw`)	Menu **8 Repair DB**.
Web app: `ENCRYPTION_REQUIRED` or pages without data	The server and web app versions differ or are older than 1.9.63: run **3 Upgrade**. Open the site with `https://`, never `http://`.
Login says the web app version is different (`VERSION_MISMATCH`)	Browser has an old copy: hard refresh (Ctrl+Shift+R). If it stays, run **3 Upgrade** with the right bundle.
Recordings stay `.wav`; API threads log: *Error opening output … .mp3: Permission denied*	Run **3 Upgrade** (1.9.76 or later), or once: `sudo apt-get install -y acl && sudo setfacl -R -m u:dialcore:rwX -m d:u:dialcore:rwX /var/spool/asterisk/recording`. No Asterisk restart is needed.
No audio on calls	Public IP in the summary must be right; UDP 10000–20000 must be open on every firewall in front of the server.
API not running	`systemctl status dialcore-api` and `journalctl -u dialcore-api -n 100 --no-pager`

Where to look

What	Where
Installer log	`/var/log/dialcore-installer.log` (add `--verbose` to see everything on screen)
Installer progress	`./dialcore-install.sh status`
API logs	`/opt/Ascentic/Dialer/BackEnd/logs/` and `journalctl -u dialcore-api`
Services	`systemctl status dialcore-api asterisk kamailio nginx postgresql`
Database backups	`/opt/Ascentic/Dialer/BackEnd/backups/` (upgrade) · `/var/backups/dialcore` (uninstall)

What to send to engineering

- The bundle file name and the action you ran.
- `tail -80 /var/log/dialcore-installer.log` and the output of `./dialcore-install.sh status`.
- For an API problem: `journalctl -u dialcore-api -n 100 --no-pager`.

> **Never send** `answers.env`, `dialcore.env`, `install-summary.txt` or screenshots of passwords. They contain the keys and passwords of the customer's server.

10. Command reference

Command (from the bundle folder, as root)	Does
`./dialcore-install.sh`	Menu
`./dialcore-install.sh check`	What is installed / missing (changes nothing)
`./dialcore-install.sh install`	Install (resumes automatically if one was started)
`./dialcore-install.sh install --resume`	Resume
`./dialcore-install.sh upgrade`	Upgrade, settings kept
`./dialcore-install.sh status`	Which steps are done
`./dialcore-install.sh summary`	Addresses, ports, users and passwords
`./dialcore-install.sh db-repair`	Missing Kamailio tables, database access for Asterisk/Kamailio
`./dialcore-install.sh rollback` · `rollback --to <step>`	Undo everything · undo the steps after <step>
`./dialcore-install.sh uninstall` · `./dialcore-uninstall.sh`	Remove DialCore
Options: `--dry-run` · `--verbose` · `--yes`	Show only, change nothing · show every command · accept defaults (unattended)