

FncyChap V1.34

Ulf A. Lindgren

Contents

1	Package description	2
1.1	Basic use and requirements	2
2	Commands provided	3
2.1	Toward customization of the chapter head	3
3	An overview of the chapter styles	4
3.1	The chapter Sonny	4
3.2	The chapter Lenny	5
3.3	The chapter Glenn	5
3.4	The chapter Conny	6
3.5	The chapter Rejne	6
3.6	The chapter Bjarne	7
3.7	The chapter Bjornstrup	7
4	A simple example	8
5	Revision details	10

Chapter 1

Package description

THE PACKAGE *fncychap* has been written such that chapter level headings can be altered fast and for me to learn more about L^AT_EX and T_EX. I have no idea if this package is written in a good way. Thus, if anyone reads and tries *FncyChap* I would appreciate any feedback. This will help me gain insight in writing macros.

In any publication it is important to remember that consistency plays an important role. That is, with this package one can change the appearance of each chapter in the publication. However, this is not desirable so don't forget modesty and consistency.

1.1 Basic use and requirements

The package is invoked by writing the following in the preamble of your document

```
\usepackage[style]{fncychap}
```

If the option, *style*, is omitted then the default definition of chapter is used. Originally, there were six predefined chapter styles, namely *Sonny*, *Lenny*, *Glenn*, *Conny*, *Rejne* and *Bjarne*. The names corresponds to Swedish given names, almost surely (a.s.) like IKEA¹. Each such style has a default configuration and if that configuration is sufficient, then this is all that is needed.

In the present release of *fncychap* two additional chapter definitions have been included. The first of these is named *PetersLenny*, after the author Peter Osborn. This chapter definition is based on *Lenny*, Peter has carefully tweaked the measures of the lines, individually, for each chapter number (up to 20) and each appendix (up to Z). The second chapter head is a new one defined by Jean-Marc Francois and he named it *Bjornstrup*.

Originally, *fncychap* did not rely on any other package. However, for the style *Lenny* a postscript font is default, but this font can easily be changed. I encourage the use of the default postscript font since it is scalable in a truly huge manner, which makes *Lenny* nice. In the current release and with the use of Jean-Marcs *Bjornstrup* the color package from the base distribution will be invoked.

¹reg. trademark of Ingvar Kamprad Emtaryd Agunnaryd

Chapter 2

Commands provided

A PART FROM THE CHAPTER STYLES, some additional commands are provided in order to create user defined chapter heads. The commands will in the sequel be described. Each command is boxed and placed on a separate line. Lets begin the descriptions of the commands.

`\mghrulefill{width}`

The above command is a more general version of the command `\hrulefill` in the sense that the width of the ruler can be specified. This command is provided in order to decorate the chapter headers. The chapter heading are divided into two parts. The first part defines the so called `\chapapp` and `\thechapter` which holds information of the text “Chapter” and the current chapter number respectively. The second part is the chapter title provided by the user. From now on, the `\chapapp` and `\thechapter` will be referred to as chapter name and chapter number respectively. The user defined title is referred to as the chapter title.

2.1 Toward customization of the chapter head

The chapter name, number and title can be changed easy, first lets introduce the following two commands

`\ChNameUpperCase`

and

`\ChNameLowerCase`

these commands will change the chapter name into either upper or lower case. One additional case command is provided for the chapter name, namely

`\ChNameAsIs`

which result in the default case. Three similar commands for the chapter title are defined by the commands

`\ChTitleUpperCase`, `\ChTitleLowerCase` and `\ChTitleAsIs`

The rule width of the predefined chapter styles can be controlled by the command

`\ChRuleWidth{width}`

just remember that the *width* must have a unit, for instance *pt*, *mm*, *etc.* The font related matters such as size, type and face can be sent using the commands

`\ChNameVar{stuff}`, `\ChNumVar{stuff}` and `\ChTitleVar{stuff}`

related to the chapter name number and title respectively. The argument, *stuff*, to these functions can be for example `\ChNameVar{\huge\rmfamily\centering}`.

Chapter 3

An overview of the chapter styles

THE CHAPTER STYLES have default settings for all of the functions described in section 2.1. However, it can be changed using the commands. Note that if `\centering`, etc is used to format the text part of the chapter style then the result can be ugly. The chapter style *Bjarne* contains one additional command

`\TheAlphaChapter`

This command will write the chapter number using the corresponding word. `\TheAlphaChapter` have a capability of writing the words *ZERO* to *NINETYNINE*.

In the following sections the pre-defined styles are shown along with the default settings. Both the `\chapter` and `\chapter*` are given.

3.1 The chapter Sonny

The following settings have been used as default parameters

```
\ChNameVar{\Large\sffamily} \ChTitleVar{\Large\sffamily}
\ChNumVar{\Huge} \ChRuleWidth{0.5pt} \ChNameUpperCase
```

Contents	
1 Package description	2
2 Commands provided	3
2.1 Toward customization of the chapter head	3
3 An overview of the chapter styles	5
3.1 The chapter Sonny	5
3.2 The chapter Lemmy	5
3.3 The chapter Glen	5
3.4 The chapter Lemmy	6
3.5 The chapter Bjarne	6
3.6 The chapter Bjarne	7
3.7 The chapter Bjarne	7
4 A simple example	10
5 Revision details	12

Figure 3.1: The stored chapter style Sonny

CHAPTER 1	
Package description	
THE PACKAGE <i>forchaps</i> has been written such that chapter level headings can be altered fast and for me to learn more about <i>forchaps</i> and <i>forchaps</i> , there are no other if the package is written in a good way. This, if anyone wants and forchaps will appreciate any feedback. This will help me gain insight in writing more.	
In any publication it is important to remember that consistency plays an important role. That is, with this package one can change the appearance of sub-chapter in the publication. However, this is not desirable as it may affect readability and consistency.	
1.1 Basic use and requirements	
The package is intended by writing the following in the preamble of your document	
<code>\usepackage{forchaps}</code>	
If the option <i>style</i> is omitted then the default definition of chapter is used. Originally, there were six predefined chapter styles, namely <i>Sonny</i> , <i>Lemmy</i> , <i>Glen</i> , <i>Leung</i> , <i>Bjarne</i> and <i>Bjarne</i> . The names corresponds to Swedish given names, almost every local, the <i>forchaps</i> . Each such style has a default configuration and if that configuration is sufficient, then this is all that is needed. In the present release of <i>forchaps</i> additional chapter definitions have been included. The first of these is named <i>forchaps</i> , after the author Peter Johansson. This chapter definition is based on <i>Lemmy</i> . Peter has carefully tweaked the measures of the lines, individually for each chapter number, up to 20 and each applicable up to 20. The second chapter head is now one defined by Jean-Marc Frenais and he named it <i>Bjarne</i> .	
Originally, <i>forchaps</i> did not rely on any other package. However, for the style <i>Lemmy</i> postscript font is default, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a truly large measure, which makes <i>Lemmy</i> more. In the current release and with the use of Jean-Marc Frenais up to the entire package from the base distribution will be included.	
The following is a list of the package's dependencies	

Figure 3.2: The chapter style Sonny

3.2 The chapter Lenny

The following settings have been used as default parameters

```
\ChNameVar{\fontsize{14}{16}\usefont{OT1}{phv}{m}{n}\selectfont}
\ChNumVar{\fontsize{60}{62}\usefont{OT1}{ptm}{m}{n}\selectfont}
\ChTitleVar{\Huge\bfseries\rmfamily} \ChRuleWidth{1pt}
```

Contents

1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Toward customization of the chapter head	3
3 An overview of the chapter styles	4
3.1 The chapter Lenny	4
3.2 The chapter Glenn	5
3.3 The chapter Camp	6
3.4 The chapter Björn	7
3.5 The chapter Björn	7
3.6 The chapter Björn	7
3.7 The chapter Björn	7
4 A simple example	8
5 Revision details	10

Chapter 1

Package description

THE PACKAGE *ch4p* has been written such that chapter level headings can be altered fast and for me to learn more about *TeX* and *LaTeX*. I have no idea if this package is written in a good way. Thus, if anyone is able and *TeX* *LaTeX* up I would appreciate any feedback. This will help me gain insight in writing macros.

In any publication it is important to remember that consistency plays an important role. That is, with this package one can change the appearance of each chapter in the publication. However, this is not desirable, so don't forget modularity and consistency.

1.1 Basic use and requirements

The package is invoked by writing the following in the preamble of your document

```
\usepackage{ch4p}[package]
```

If the option, *style*, is omitted then the default definition of chapter is used. Originally, there were six predefined chapter styles, namely *Swamp*, *Lenny*, *Glenn*, *Camp*, *Björn* and *Björn*. The names corresponds to Swedish given names, almost surely (s.e.) the *WREA*. Each such style has a default configuration and if that configuration is sufficient, then this is all that is needed.

In the present release of *ch4p* two additional chapter definitions have been included. The first of these is named *Peter* (after the author Peter Petersen). This chapter definition is based on *Lenny*. Peter has carefully worked the measures of the lines, individually, for each chapter number (up to 28) and each appendix (up to 2). The second chapter head is a new one defined by Jean-Marie Francoise and he named it *Björn*.

Originally, *ch4p* did not rely on any other package. However, for the style *Lenny* a postscript font is defined, but this font can easily be changed. To encourage the use of the default postscript font, there is available in a truly huge manner, which makes *Lenny* more. In the current release and with the use of *fontsource* *Björn* up the color package from the base distribution will be invoked.

TeX, TeXmacs, LaTeX, and LaTeX2ε are trademarks of TeX Systems, Inc.

Figure 3.3: The stored chapter style Lenny

Figure 3.4: The chapter style Lenny

Note: An alternative version of this chapter head exist entitled *PetersLenny*.

3.3 The chapter Glenn

The following settings have been used as default parameters

```
\ChNameVar{\bfseries\Large\sffamily} \ChNameUpperCase
\ChTitleVar{\bfseries\Large\rmfamily} \ChTitleUpperCase
\ChNumVar{\Huge} \ChRuleWidth{1pt}
```

CONTENTS

1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Toward customization of the chapter head	3
3 An overview of the chapter styles	5
3.1 The chapter Lenny	5
3.2 The chapter Glenn	6
3.3 The chapter Camp	6
3.4 The chapter Björn	7
3.5 The chapter Björn	7
3.6 The chapter Björn	8
3.7 The chapter Björn	8
4 A simple example	9
5 Revision details	11

CHAPTER 1

PACKAGE DESCRIPTION

THE PACKAGE *ch4p* has been written such that chapter level headings can be altered fast and for me to learn more about *TeX* and *LaTeX*. I have no idea if this package is written in a good way. Thus, if anyone is able and *TeX* *LaTeX* up I would appreciate any feedback. This will help me gain insight in writing macros.

In any publication it is important to remember that consistency plays an important role. That is, with this package one can change the appearance of each chapter in the publication. However, this is not desirable, so don't forget modularity and consistency.

1.1 Basic use and requirements

The package is invoked by writing the following in the preamble of your document

```
\usepackage{ch4p}[package]
```

If the option, *style*, is omitted then the default definition of chapter is used. Originally, there were six predefined chapter styles, namely *Swamp*, *Lenny*, *Glenn*, *Camp*, *Björn* and *Björn*. The names corresponds to Swedish given names, almost surely (s.e.) the *WREA*. Each such style has a default configuration and if that configuration is sufficient, then this is all that is needed.

In the present release of *ch4p* two additional chapter definitions have been included. The first of these is named *Peter* (after the author Peter Petersen). This chapter definition is based on *Lenny*. Peter has carefully worked the measures of the lines, individually, for each chapter number (up to 28) and each appendix (up to 2). The second chapter head is a new one defined by Jean-Marie Francoise and he named it *Björn*.

Originally, *ch4p* did not rely on any other package. However, for the style *Lenny* a postscript font is defined, but this font can easily be changed. To encourage the use of the default postscript font, there is available in a truly huge manner, which makes *Lenny* more. In the current release and with the use of *fontsource* *Björn* up the color package from the base distribution will be invoked.

TeX, TeXmacs, LaTeX, and LaTeX2ε are trademarks of TeX Systems, Inc.

Figure 3.5: The stored chapter style Glenn

Figure 3.6: The chapter style Glenn

3.4 The chapter Conny

The following settings have been used as default parameters

```
\ChNameUpperCase \ChNameVar{\centering\Huge\rmfamily\bfseries}
\ChTitleUpperCase \ChTitleVar{\centering\Huge\rmfamily}
\ChNumVar{\Huge} \ChRuleWidth{2pt}
```

CONTENTS	
1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Toward customization of the chapter head	3
3 An overview of the chapter styles	5
3.1 The chapter Sonny	5
3.2 The chapter Lemmy	5
3.3 The chapter Glom	5
3.4 The chapter Conny	5
3.5 The chapter Rjane	6
3.6 The chapter Bjane	7
3.7 The chapter Bjernestep	7
4 A simple example	10
5 Revision details	12

Figure 3.7: The stored chapter style Conny

CHAPTER 1	
PACKAGE DESCRIPTION	
<p>THE PACKAGE <code>forchapg</code> has been written such that chapter level headings can be altered fast and for free. It is not more about PDFX and TEX. I have no idea if this package is written in a good way. Then, if anyone reads and still <code>forchapg</code> I would appreciate any feedback. This will help me gain insight in writing more.</p> <p>In any publication it is important to remember that consistency plays an important role. That is, with this package one can change the appearance of each chapter in the publication. However, this is not desirable so don't forget <i>moderately</i> and <i>consistently</i>.</p> <p>1.1 Basic use and requirements</p> <p>The package is invoked by writing the following in the preamble of your document</p> <pre>\usepackage[style]{forchapg}</pre> <p>If the option, <code>style</code>, is omitted then the default definition of chapter is used. Originally, there were six predefined chapter styles, namely <code>Sonny</code>, <code>Lemmy</code>, <code>Glom</code>, <code>Conny</code>, <code>Rjane</code> and <code>Bjane</code>. The names corresponds to Swedish given names, almost surely (s.e.) like INEA. Each such style has a default configuration and if this configuration is sufficient, that's all that is needed.</p> <p>In the present release of <code>forchapg</code> two additional chapter definitions have been included. The first of them is named <code>Peterforchapg</code>, after the author Peter Olausson. This chapter definition is based on <code>Lemmy</code>. Peter has carefully checked the measures of the lines, individually for each chapter number (up to 20) and each appearance (up to 2). The second chapter head is a new one defined by Jean-Marie Francis and he named it <code>Bjernestep</code>.</p> <p>Originally, <code>forchapg</code> did not rely on any other package. However, for the style <code>Lemmy</code> a postscript font is needed, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a really huge manner, which makes <code>forchapg</code>. In the current release and with the use of <code>Jean-Marie Francis</code> the color package from the base distribution will be invoked.</p>	
<p>forchapg is part of the <code>forchapg</code> package</p>	

Figure 3.8: The chapter style Conny

3.5 The chapter Rejne

The following settings have been used as default parameters

```
\ChNameUpperCase \ChNameVar{\centering\Huge\rmfamily\bfseries}
\ChTitleUpperCase \ChTitleVar{\centering\Huge\rmfamily}
\ChNumVar{\Huge} \ChRuleWidth{1pt}
```

CONTENTS	
1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Toward customization of the chapter head	3
3 An overview of the chapter styles	5
3.1 The chapter Sonny	5
3.2 The chapter Lemmy	5
3.3 The chapter Glom	5
3.4 The chapter Conny	5
3.5 The chapter Rjane	6
3.6 The chapter Bjane	7
3.7 The chapter Bjernestep	7
4 A simple example	10
5 Revision details	12

Figure 3.9: The stored chapter style Rejne

CHAPTER 1	
1	
PACKAGE DESCRIPTION	
<p>THE PACKAGE <code>forchapg</code> has been written such that chapter level headings can be altered fast and for free. It is not more about PDFX and TEX. I have no idea if this package is written in a good way. Then, if anyone reads and still <code>forchapg</code> I would appreciate any feedback. This will help me gain insight in writing more.</p> <p>In any publication it is important to remember that consistency plays an important role. That is, with this package one can change the appearance of each chapter in the publication. However, this is not desirable so don't forget <i>moderately</i> and <i>consistently</i>.</p> <p>1.1 Basic use and requirements</p> <p>The package is invoked by writing the following in the preamble of your document</p> <pre>\usepackage[style]{forchapg}</pre> <p>If the option, <code>style</code>, is omitted then the default definition of chapter is used. Originally, there were six predefined chapter styles, namely <code>Sonny</code>, <code>Lemmy</code>, <code>Glom</code>, <code>Conny</code>, <code>Rjane</code> and <code>Bjane</code>. The names corresponds to Swedish given names, almost surely (s.e.) like INEA. Each such style has a default configuration and if this configuration is sufficient, that's all that is needed.</p> <p>In the present release of <code>forchapg</code> two additional chapter definitions have been included. The first of them is named <code>Peterforchapg</code>, after the author Peter Olausson. This chapter definition is based on <code>Lemmy</code>. Peter has carefully checked the measures of the lines, individually for each chapter number (up to 20) and each appearance (up to 2). The second chapter head is a new one defined by Jean-Marie Francis and he named it <code>Bjernestep</code>.</p> <p>Originally, <code>forchapg</code> did not rely on any other package. However, for the style <code>Lemmy</code> a postscript font is needed, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a really huge manner, which makes <code>forchapg</code>. In the current release and with the use of <code>Jean-Marie Francis</code> the color package from the base distribution will be invoked.</p>	
<p>forchapg is part of the <code>forchapg</code> package</p>	

Figure 3.10: The chapter style Rejne

3.6 The chapter Bjarne

The following settings have been used as default parameters

```
\ChNameUpperCase \ChNameVar{\raggedleft\normalsize\rmfamily}  
\ChTitleUpperCase \ChTitleVar{\raggedleft\Large\rmfamily}  
\ChRuleWidth{1pt} \ChNumVar{\raggedleft\bfseries\Large}
```

CONTENTS	
1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Forward recommendation of the chapter head	3
3 An overview of the chapter styles	4
3.1 The chapter Bjarne	4
3.2 The chapter Lenny	4
3.3 The chapter Gino	4
3.4 The chapter Gino	4
3.5 The chapter Bjarne	4
3.6 The chapter Bjarne	4
3.7 The chapter Bjarne	4
4 A simple example	8
5 Revision details	10

Figure 3.11: The stored chapter style Bjarne

CHAPTER ONE	
PACKAGE DESCRIPTION	
<p>THE PACKAGE <i>bcyrchap</i> has been written such that chapter level headings can be altered fast and for me to learn more about <i>PDFX</i> and <i>TeX</i>. I have no idea if this package is written in a good way. Thus, if anyone reads and likes <i>bcyrchap</i> to add appropriate new features. This will help me gain insight in writing macros.</p> <p>In any publication it is important to remember that consistency plays an important role. That is, with this package one can change the appearance of a sub chapter in the publication. However, this is not desirable so don't forget consistency and consistency.</p>	
1.1 Basic use and requirements	
<p>The package is invoked by writing the following in the preamble of your document</p> <pre>\usepackage{bjarne}</pre> <p>If the option <i>style</i> is omitted then the default definition of chapter is used. Originally, there were no predefined chapter styles, namely <i>Bjarne</i>, <i>Lenny</i>, <i>Gino</i>, <i>Crang</i>, <i>Reino</i> and <i>Bjarne</i>. The names corresponds to Swedish given names, almost surely (sax) like <i>IKRA</i>. Each such style has a default configuration and if that configuration is sufficient, then this is all that is needed.</p> <p>In the present release of <i>bcyrchap</i> two additional chapter definitions have been included. The first of these is named <i>Peter</i> and the second <i>Peter</i> and <i>Peter</i>. This chapter definition is based on <i>Lenny</i>. Peter has carefully tweaked the measures of the lines, individually, for each chapter number (up to 20 and not up to 20). The second chapter head is a new one defined by <i>Don-Mike</i> and is named <i>Bjarne</i>.</p> <p>Originally, <i>bcyrchap</i> did not rely on any other packages. However, for the style <i>Lenny</i> a postscript font is needed, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a truly large manner, which makes <i>Lenny</i> a better choice. In the current release and with the use of <i>Don-Mike</i> <i>Bjarne</i> is the only package from the base distribution will be needed.</p>	
<p>File: bjarne.sty, of the bcyrchap distribution</p>	

Figure 3.12: The chapter style Bjarne

3.7 The chapter Bjornstrup

The following settings have been used as default parameters

```
\ChNumVar{\fontsize{76}{80}\usefont{OT1}{pzc}{m}{n}\selectfont}  
\ChTitleVar{\raggedleft\Large\sffamily\bfseries}
```

Contents	
1 Package description	2
1.1 Basic use and requirements	2
2 Commands provided	3
2.1 Forward recommendation of the chapter head	3
3 An overview of the chapter styles	4
3.1 The chapter Bjarne	4
3.2 The chapter Lenny	4
3.3 The chapter Gino	4
3.4 The chapter Gino	4
3.5 The chapter Bjarne	4
3.6 The chapter Bjarne	4
3.7 The chapter Bjarne	4
4 A simple example	8
5 Revision details	10

Figure 3.13: The stored chapter style Bjornstrup

1	
Package description	
<p>THE PACKAGE <i>bcyrchap</i> has been written such that chapter level headings can be altered fast and for me to learn more about <i>PDFX</i> and <i>TeX</i>. I have no idea if this package is written in a good way. Thus, if anyone reads and likes <i>bcyrchap</i> to add appropriate new features. This will help me gain insight in writing macros.</p> <p>In any publication it is important to remember that consistency plays an important role. That is, with this package one can change the appearance of a sub chapter in the publication. However, this is not desirable so don't forget consistency and consistency.</p>	
1.1 Basic use and requirements	
<p>The package is invoked by writing the following in the preamble of your document</p> <pre>\usepackage{bjarne}</pre> <p>If the option <i>style</i> is omitted then the default definition of chapter is used. Originally, there were no predefined chapter styles, namely <i>Bjarne</i>, <i>Lenny</i>, <i>Gino</i>, <i>Crang</i>, <i>Reino</i> and <i>Bjarne</i>. The names corresponds to Swedish given names, almost surely (sax) like <i>IKRA</i>. Each such style has a default configuration and if that configuration is sufficient, then this is all that is needed.</p> <p>In the present release of <i>bcyrchap</i> two additional chapter definitions have been included. The first of these is named <i>Peter</i> and the second <i>Peter</i> and <i>Peter</i>. This chapter definition is based on <i>Lenny</i>. Peter has carefully tweaked the measures of the lines, individually, for each chapter number (up to 20 and not up to 20). The second chapter head is a new one defined by <i>Don-Mike</i> and is named <i>Bjarne</i>.</p> <p>Originally, <i>bcyrchap</i> did not rely on any other packages. However, for the style <i>Lenny</i> a postscript font is needed, but this font can easily be changed. I encourage the use of the default postscript font since it is available in a truly large manner, which makes <i>Lenny</i> a better choice. In the current release and with the use of <i>Don-Mike</i> <i>Bjarne</i> is the only package from the base distribution will be needed.</p>	
<p>File: bjarne.sty, of the bcyrchap distribution</p>	

Figure 3.14: The chapter style Bjornstrup

Note: It appears as if the rendering in YAP (dvi previewer in MikTeX) differs from dvips in that the gray box become foreground. Thus, the chapter number is partly hidden.

Chapter 4

A simple example

IF THE PRE-DEFINED STYLES do not fulfill your needs then you can modify the forming routines. The formatting is controlled by three commands. One might as well redefine the original chapter definitions using the `\secdef` and `\renewcommand`, see The L^AT_EX companion. However, at the time of creating this package I decided that this was easier. The command

```
\DOCH
```

formats the chapter name and number. The commands

```
\DOTI{#1}
```

and

```
\DOTIS{#1}
```

formats the chapter title for `\chapter` and `\chapter*` respectively. In order to modify these you will have to use the preamble along with the commands `\makeatletter` and `\makeatother`. The in addition some predefined parameters can be used. The predefined length variables are

```
\mylen, \myhi, \px, \py, \pxx, \pyy and \RW
```

note that `\RW` is special, since it is set by `\ChRuleWidth`. The formatting controlled by `\ChNameVar`, `\ChNumVar` and `\ChTitleVar` store their values in `\CNV`, `\CNoV` and `\CTV` respectively. Finally, the functions `\FmN{ }` and `\FmTi{ }` acts accordingly to `\Ch***AsIs`, `\Ch***UpperCase` and `\Ch***LowerCase`. Note that the stars indicate appropriate substitution of text, see section 2.1.

To illustrate this lets define a new chapter style in which the Chapter name and number in a `\fbox` and the chapter title centered. The `\fboxrule` is linked to the predefined length `\RW` so that it can be controlled by the command `\ChRuleWidth`. Try this example at a computer near you.

```
\makeatletter
\ChNameVar{\Large\rmfamily} % sets the style for name
\ChNumVar{\Huge} % sets the style for digit
\ChTitleVar{\Large\rmfamily\centering} % sets the style for title
\ChRuleWidth{4pt} % Set RW=4pt
\ChNameUpperCase % Make name uppercase
\renewcommand{\DOCH}{%
  \setlength{\fboxrule}{\RW} % Let fbox lines be controlled by
  % \ChRuleWidth

  \fbox{\CNV\FmN{\@chapapp}\space \CNoV\thechapter}\par\nobreak
  \vskip 40\p@}
```

```

\renewcommand{\DOTI}[1]{%
  \CTV\FmTi{#1}\par\nobreak
  \vskip 40\p@}
\renewcommand{\DOTIS}[1]{%
  \CTV\FmTi{#1}\par\nobreak
  \vskip 40\p@}
\makeatother

```

That is all there is to it. Note that the commands `\DOTI` and `\DOTIS` can be redefined anywhere in the document, but that is not a good idea. Suppose that you want to use the `\TheAlphaChapter`. This can be done by initially chose the style *Bjarne* and then redefine `\DOCH`, `\DOTI` and `\DOTIS`.

Revision details

THIS IS VERSION 1.34, some minor problems have been addressed and two new predefined chapter heads have been incorporated. The upper case and lower case handling have been corrected. A bad behavior in changes between `\frontmatter`, `\mainmatter` and `\backmatter`, have been fixed.

In version 1.33 Rejne definition stretched text caused ugly gaps in the vrule aligned with the title text. A compatibility problem with the KOMA class `'scrbook.cls'` the remedy is a redefinition of `'\@schapter'` in line with that used in KOMA. This might not be good since it differs from the base definition. A spell error was corrected.

In version 1.3, a problem with appendices in the Bjarne style was corrected. Wrong behavior, for the commands `\frontmatter`, `\mainmatter` and `\backmatter` was dealt with.

In the release 1.11 of the current package. A bug fix of the Lenny option was included. The problem, reported by Diab Jerius, occurred (underfull vbox) when the option Lenny was used in conjunction with `\section`-command such that the section is typeset at the next page. This caused one line to be misplaced. The remedy was to box the chapter title.

In the release (1.1) of the current package. A modification was made such that it will work with the book class. The problem occurred when the fncychap styles Conny, Rejne, Bjarne or Glenn were used in conjunction with the \LaTeX command `\tableofcontents`. The exact reason for the error is not yet found. The problem was reported by Olivier Guibe.

In the prior release there were no major improvements of the package. However, the package name was changed in order to conform with the (DOS) requirement of eight characters. I also received some feedback, informing me that the \LaTeX base have to be post 1994/12/01. This information has been included in the package such that if an old base is used a warning will be written into the `log`.

Release history:

Release 1 1996/12/13 FancyChapters 1.0b

Release 2 1997/01/08 FncyChap 1.0 (Name change, base date option)

Release 3 1997/01/22 FncyChap 1.1 (Bug fix)

Release 4 1997/04/06 FncyChap 1.11 (Bug fix)

Release 5 2004/09/20 FncyChap 1.3 (Bug fix)

Release 6 2005/08/09 FncyChap 1.33 (Bug fix)

Release 7 2007/07/31 FncyChap 1.34 (Bug fix)