

Scan Report

May 27, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “DC01 Scan”. The scan started at Wed May 27 17:40:02 2026 UTC and ended at Wed May 27 18:07:39 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
2	Results per Host	2
2.1	192.168.10.100	2
2.1.1	Medium 135/tcp	2
2.1.2	Medium 53/udp	6
2.1.3	Low general/tcp	8

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
192.168.10.100 DC01	0	0	2	1	0	0
Total: 1	0	0	2	1	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 3 results selected by the filtering described above. Before filtering there were 45 results.

2 Results per Host

2.1 192.168.10.100

Host scan start Wed May 27 17:41:22 2026 UTC

Host scan end Wed May 27 18:07:34 2026 UTC

Service (Port)	Threat Level
135/tcp	Medium
53/udp	Medium
general/tcp	Low

2.1.1 Medium 135/tcp

Medium (CVSS: 5.0)

NVT: DCE/RPC and MSRPC Services Enumeration Reporting

Summary

Distributed Computing Environment / Remote Procedure Calls (DCE/RPC) or MSRPC based service enumeration reporting.

... continues on next page ...

...continued from previous page...

Quality of Detection (QoD): 80%**Vulnerability Detection Result**

Here is the list of DCE/RPC or MSRPC services running on this host via the TCP protocol:

Port: 49664/tcp

UUID: 0b1c2170-5732-4e0e-8cd3-d9b16f3b84d7, version 0

Endpoint: ncacn_ip_tcp:192.168.10.100[49664]

Annotation: RemoteAccessCheck

UUID: 12345678-1234-abcd-ef00-01234567cffb, version 1

Endpoint: ncacn_ip_tcp:192.168.10.100[49664]

Named pipe : lsass

Win32 service or process : Netlogon

Description : Net Logon service

UUID: 12345778-1234-abcd-ef00-0123456789ab, version 0

Endpoint: ncacn_ip_tcp:192.168.10.100[49664]

Named pipe : lsass

Win32 service or process : lsass.exe

Description : LSA access

UUID: 12345778-1234-abcd-ef00-0123456789ac, version 1

Endpoint: ncacn_ip_tcp:192.168.10.100[49664]

Named pipe : lsass

Win32 service or process : lsass.exe

Description : SAM access

UUID: 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1

Endpoint: ncacn_ip_tcp:192.168.10.100[49664]

Annotation: Ngc Pop Key Service

UUID: 8fb74744-b2ff-4c00-be0d-9ef9a191fe1b, version 1

Endpoint: ncacn_ip_tcp:192.168.10.100[49664]

Annotation: Ngc Pop Key Service

UUID: b25a52bf-e5dd-4f4a-aea6-8ca7272a0e86, version 2

Endpoint: ncacn_ip_tcp:192.168.10.100[49664]

Annotation: KeyIso

UUID: c9ac6db5-82b7-4e55-ae8a-e464ed7b4277, version 1

Endpoint: ncacn_ip_tcp:192.168.10.100[49664]

Annotation: Impl friendly name

UUID: e3514235-4b06-11d1-ab04-00c04fc2dcd2, version 4

Endpoint: ncacn_ip_tcp:192.168.10.100[49664]

Annotation: MS NT Directory DRS Interface

Port: 49665/tcp

UUID: d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1

Endpoint: ncacn_ip_tcp:192.168.10.100[49665]

Port: 49666/tcp

UUID: f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1

Endpoint: ncacn_ip_tcp:192.168.10.100[49666]

Annotation: Event log TCPIP

...continues on next page...

...continued from previous page...

Port: 49667/tcp
 UUID: 3a9ef155-691d-4449-8d05-09ad57031823, version 1
 Endpoint: ncacn_ip_tcp:192.168.10.100[49667]
 UUID: 86d35949-83c9-4044-b424-db363231fd0c, version 1
 Endpoint: ncacn_ip_tcp:192.168.10.100[49667]

Port: 49668/tcp
 UUID: 0b1c2170-5732-4e0e-8cd3-d9b16f3b84d7, version 0
 Endpoint: ncacn_ip_tcp:192.168.10.100[49668]
 Annotation: RemoteAccessCheck
 UUID: 12345678-1234-abcd-ef00-01234567cffb, version 1
 Endpoint: ncacn_ip_tcp:192.168.10.100[49668]
 Named pipe : lsass
 Win32 service or process : Netlogon
 Description : Net Logon service
 UUID: 12345778-1234-abcd-ef00-0123456789ab, version 0
 Endpoint: ncacn_ip_tcp:192.168.10.100[49668]
 Named pipe : lsass
 Win32 service or process : lsass.exe
 Description : LSA access
 UUID: 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1
 Endpoint: ncacn_ip_tcp:192.168.10.100[49668]
 Annotation: Ngc Pop Key Service
 UUID: 8fb74744-b2ff-4c00-be0d-9ef9a191fe1b, version 1
 Endpoint: ncacn_ip_tcp:192.168.10.100[49668]
 Annotation: Ngc Pop Key Service
 UUID: b25a52bf-e5dd-4f4a-aea6-8ca7272a0e86, version 2
 Endpoint: ncacn_ip_tcp:192.168.10.100[49668]
 Annotation: KeyIso
 UUID: c9ac6db5-82b7-4e55-ae8a-e464ed7b4277, version 1
 Endpoint: ncacn_ip_tcp:192.168.10.100[49668]
 Annotation: Impl friendly name
 UUID: e3514235-4b06-11d1-ab04-00c04fc2dcd2, version 4
 Endpoint: ncacn_ip_tcp:192.168.10.100[49668]
 Annotation: MS NT Directory DRS Interface

Port: 57020/tcp
 UUID: 0b1c2170-5732-4e0e-8cd3-d9b16f3b84d7, version 0
 Endpoint: ncacn_http:192.168.10.100[57020]
 Annotation: RemoteAccessCheck
 UUID: 12345678-1234-abcd-ef00-01234567cffb, version 1
 Endpoint: ncacn_http:192.168.10.100[57020]
 Named pipe : lsass
 Win32 service or process : Netlogon
 Description : Net Logon service
 UUID: 12345778-1234-abcd-ef00-0123456789ab, version 0
 Endpoint: ncacn_http:192.168.10.100[57020]
 Named pipe : lsass
 Win32 service or process : lsass.exe

...continues on next page...

...continued from previous page ...	
Description : LSA access	
UUID: 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1	
Endpoint: ncacn_http:192.168.10.100[57020]	
Annotation: Ngc Pop Key Service	
UUID: 8fb74744-b2ff-4c00-be0d-9ef9a191fe1b, version 1	
Endpoint: ncacn_http:192.168.10.100[57020]	
Annotation: Ngc Pop Key Service	
UUID: b25a52bf-e5dd-4f4a-aea6-8ca7272a0e86, version 2	
Endpoint: ncacn_http:192.168.10.100[57020]	
Annotation: KeyIso	
UUID: e3514235-4b06-11d1-ab04-00c04fc2dcd2, version 4	
Endpoint: ncacn_http:192.168.10.100[57020]	
Annotation: MS NT Directory DRS Interface	
Port: 57021/tcp	
UUID: 0b6edbf-a4a24-4fc6-8a23-942b1eca65d1, version 1	
Endpoint: ncacn_ip_tcp:192.168.10.100[57021]	
UUID: 12345678-1234-abcd-ef00-0123456789ab, version 1	
Endpoint: ncacn_ip_tcp:192.168.10.100[57021]	
Named pipe : spoolss	
Win32 service or process : spoolsv.exe	
Description : Spooler service	
UUID: 4a452661-8290-4b36-8fbe-7f4093a94978, version 1	
Endpoint: ncacn_ip_tcp:192.168.10.100[57021]	
UUID: 76f03f96-cdfd-44fc-a22c-64950a001209, version 1	
Endpoint: ncacn_ip_tcp:192.168.10.100[57021]	
UUID: ae33069b-a2a8-46ee-a235-ddfd339be281, version 1	
Endpoint: ncacn_ip_tcp:192.168.10.100[57021]	
Port: 57027/tcp	
UUID: 12345678-1234-abcd-ef00-01234567cffb, version 1	
Endpoint: ncacn_ip_tcp:192.168.10.100[57027]	
Named pipe : lsass	
Win32 service or process : Netlogon	
Description : Net Logon service	
UUID: 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1	
Endpoint: ncacn_ip_tcp:192.168.10.100[57027]	
Annotation: Ngc Pop Key Service	
UUID: 8fb74744-b2ff-4c00-be0d-9ef9a191fe1b, version 1	
Endpoint: ncacn_ip_tcp:192.168.10.100[57027]	
Annotation: Ngc Pop Key Service	
UUID: b25a52bf-e5dd-4f4a-aea6-8ca7272a0e86, version 2	
Endpoint: ncacn_ip_tcp:192.168.10.100[57027]	
Annotation: KeyIso	
Port: 57028/tcp	
UUID: 367abb81-9844-35f1-ad32-98f038001003, version 2	
Endpoint: ncacn_ip_tcp:192.168.10.100[57028]	
Port: 57032/tcp	
UUID: 50abc2a4-574d-40b3-9d66-ee4fd5fba076, version 5	
...continues on next page ...	

...continued from previous page...	
Endpoint: ncacn_ip_tcp:192.168.10.100[57032] Named pipe : dnsserver Win32 service or process : dns.exe Description : DNS Server Port: 57041/tcp UUID: 897e2e5f-93f3-4376-9c9c-fd2277495c27, version 1 Endpoint: ncacn_ip_tcp:192.168.10.100[57041] Annotation: Frs2 Service Note: DCE/RPC or MSRPC services running on this host locally were identified. Reporting this list is not enabled by default due to the possible large size of this list. See the script preferences to enable this reporting.	
Impact An attacker may use this information to gain more knowledge about the remote host and to conduct further attacks based on it.	
Solution: Solution type: Mitigation Filter incoming traffic to this ports.	
Affected Software/OS All systems exposing / disclosing information via DCE/RPC or MSRPC services.	
Vulnerability Insight DCE/RPC or MSRPC services running on the remote host can be enumerated by connecting on port 135 and doing the appropriate queries.	
Vulnerability Detection Method Reports previously collected (via 'DCE/RPC and MSRPC Services Enumeration' OID: 1.3.6.1.4.1.25623.1.0.108044) DCE/RPC or MSRPC services. This VT is reporting a severity by default. If the scanned network is e.g. a private LAN / private WAN which contains systems not accessible to the public (access restricted) and it is accepted that the service is disclosing information to this network please set the 'Network type' configuration of the following VT to e.g. 'Private LAN' or 'Private WAN': Global variable settings (OID: 1.3.6.1.4.1.25623.1.0.12288) In this case a 'Log' level result is used instead. Details: DCE/RPC and MSRPC Services Enumeration Reporting OID:1.3.6.1.4.1.25623.1.0.10736 Version used: 2025-11-26T05:40:08Z	

[\[return to 192.168.10.100 \]](#)

2.1.2 Medium 53/udp

Medium (CVSS: 5.0)
NVT: DNS Cache Snooping Vulnerability (UDP) - Active Check
Summary The DNS server is prone to a cache snooping vulnerability.
Quality of Detection (QoD): 70%
Vulnerability Detection Result Received (an) answer(s) for a non-recursive query for "example.com". Result: 172.66.147.243
Impact Attackers might gain information about cached DNS records which might lead to further attacks. Note: This finding might be an acceptable risk if you: - trust all clients which can reach the server - do not allow recursive queries from outside your trusted client network.
Solution: Solution type: Mitigation There are multiple possible mitigation steps depending on location and functionality needed by the DNS server: - Disable recursion - Don't allow public access to DNS Servers doing recursion - Leave recursion enabled if the DNS Server stays on a corporate network that cannot be reached by untrusted clients - If the risk is accepted either create an override for this result or configure the 'Private LAN' setting mentioned earlier
Vulnerability Insight DNS cache snooping is when someone queries a DNS server in order to find out (snoop) if the DNS server has a specific DNS record cached, and thereby deduce if the DNS server's owner (or its users) have recently visited a specific site. This may reveal information about the DNS server's owner, such as what vendor, bank, service provider, etc. they use. Especially if this is confirmed (snooped) multiple times over a period. This method could even be used to gather statistical information - for example at what time does the DNS server's owner typically access his net bank etc. The cached DNS record's remaining TTL value can provide very accurate data for this. DNS cache snooping is possible even if the DNS server is not configured to resolve recursively for 3rd parties, as long as it provides records from the cache also to 3rd parties (a.k.a. 'lame requests').
Vulnerability Detection Method Sends a crafted DNS query and checks the response.
... continues on next page ...

...continued from previous page ...
Notes: - No scan result is expected if localhost (127.0.0.1) was scanned (self scanning) - If the scanned network is e.g. a private LAN / private WAN which contains systems not accessible to the public (access restricted) and it is accepted that the service is disclosing information to this network please set the 'Network type' configuration of the following VT to e.g. 'Private LAN' or 'Private WAN': Global variable settings (OID: 1.3.6.1.4.1.25623.1.0.12288) Details: DNS Cache Snooping Vulnerability (UDP) - Active Check OID:1.3.6.1.4.1.25623.1.0.146591 Version used: 2025-11-25T05:40:35Z
References url: https://www.cs.unc.edu/~fabian/course_papers/cache_snooping.pdf url: https://docs.microsoft.com/en-us/troubleshoot/windows-server/networking/dns-cs-server-cache-snooping-attacks url: https://kb.isc.org/docs/aa-00509 url: https://kb.isc.org/docs/aa-00482

[[return to 192.168.10.100](#)]

2.1.3 Low general/tcp

Low (CVSS: 2.6)
NVT: TCP Timestamps Information Disclosure
Summary The remote host implements TCP timestamps and therefore allows to compute the uptime.
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was detected that the host implements RFC1323/RFC7323. The following timestamps were retrieved with a delay of 1 seconds in-between: Packet 1: 1192352 Packet 2: 1193377
Impact A side effect of this feature is that the uptime of the remote host can sometimes be computed.
Solution: Solution type: Mitigation To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime. To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled'
... continues on next page ...

...continued from previous page ...
Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled. The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
Vulnerability Detection Method Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z
References url: https://datatracker.ietf.org/doc/html/rfc1323 url: https://datatracker.ietf.org/doc/html/rfc7323 url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152 url: https://www.fortiguard.com/psirt/FG-IR-16-090

[[return to 192.168.10.100](#)]