

Scan Report

May 27, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “Win11 Scan”. The scan started at Wed May 27 19:20:03 2026 UTC and ended at Wed May 27 19:46:05 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
2	Results per Host	2
2.1	192.168.10.54	2
2.1.1	Medium 135/tcp	2
2.1.2	Low general/icmp	5
2.1.3	Low general/tcp	6

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
192.168.10.54 win11.lab.internal	0	0	1	2	0	0
Total: 1	0	0	1	2	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 3 results selected by the filtering described above. Before filtering there were 26 results.

2 Results per Host

2.1 192.168.10.54

Host scan start Wed May 27 19:20:36 2026 UTC

Host scan end Wed May 27 19:46:01 2026 UTC

Service (Port)	Threat Level
135/tcp	Medium
general/icmp	Low
general/tcp	Low

2.1.1 Medium 135/tcp

Medium (CVSS: 5.0)

NVT: DCE/RPC and MSRPC Services Enumeration Reporting

Summary

Distributed Computing Environment / Remote Procedure Calls (DCE/RPC) or MSRPC based service enumeration reporting.

... continues on next page ...

...continued from previous page...

Quality of Detection (QoD): 80%**Vulnerability Detection Result**

Here is the list of DCE/RPC or MSRPC services running on this host via the TCP protocol:

Port: 49664/tcp

UUID: 0b1c2170-5732-4e0e-8cd3-d9b16f3b84d7, version 0

Endpoint: ncacn_ip_tcp:192.168.10.54[49664]

Annotation: RemoteAccessCheck

UUID: 12345778-1234-abcd-ef00-0123456789ac, version 1

Endpoint: ncacn_ip_tcp:192.168.10.54[49664]

Named pipe : lsass

Win32 service or process : lsass.exe

Description : SAM access

UUID: 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1

Endpoint: ncacn_ip_tcp:192.168.10.54[49664]

Annotation: Ngc Pop Key Service

UUID: 8fb74744-b2ff-4c00-be0d-9ef9a191fe1b, version 1

Endpoint: ncacn_ip_tcp:192.168.10.54[49664]

Annotation: Ngc Pop Key Service

UUID: b25a52bf-e5dd-4f4a-aea6-8ca7272a0e86, version 2

Endpoint: ncacn_ip_tcp:192.168.10.54[49664]

Annotation: KeyIso

Port: 49665/tcp

UUID: d95afe70-a6d5-4259-822e-2c84da1ddb0d, version 1

Endpoint: ncacn_ip_tcp:192.168.10.54[49665]

Port: 49666/tcp

UUID: f6beaff7-1e19-4fbb-9f8f-b89e2018337c, version 1

Endpoint: ncacn_ip_tcp:192.168.10.54[49666]

Annotation: Windows Event Log

Port: 49667/tcp

UUID: 3a9ef155-691d-4449-8d05-09ad57031823, version 1

Endpoint: ncacn_ip_tcp:192.168.10.54[49667]

UUID: 86d35949-83c9-4044-b424-db363231fd0c, version 1

Endpoint: ncacn_ip_tcp:192.168.10.54[49667]

Port: 49668/tcp

UUID: 0b6edbfa-4a24-4fc6-8a23-942b1eca65d1, version 1

Endpoint: ncacn_ip_tcp:192.168.10.54[49668]

UUID: 12345678-1234-abcd-ef00-0123456789ab, version 1

Endpoint: ncacn_ip_tcp:192.168.10.54[49668]

Named pipe : spoolss

Win32 service or process : spoolsv.exe

Description : Spooler service

UUID: 4a452661-8290-4b36-8f8e-7f4093a94978, version 1

Endpoint: ncacn_ip_tcp:192.168.10.54[49668]

UUID: 76f03f96-cdfd-44fc-a22c-64950a001209, version 1

...continues on next page...

...continued from previous page ... Endpoint: ncacn_ip_tcp:192.168.10.54[49668] UUID: ae33069b-a2a8-46ee-a235-ddfd339be281, version 1 Endpoint: ncacn_ip_tcp:192.168.10.54[49668] Port: 49669/tcp UUID: 0b1c2170-5732-4e0e-8cd3-d9b16f3b84d7, version 0 Endpoint: ncacn_ip_tcp:192.168.10.54[49669] Annotation: RemoteAccessCheck UUID: 51a227ae-825b-41f2-b4a9-1ac9557a1018, version 1 Endpoint: ncacn_ip_tcp:192.168.10.54[49669] Annotation: Ngc Pop Key Service UUID: 8fb74744-b2ff-4c00-be0d-9ef9a191fe1b, version 1 Endpoint: ncacn_ip_tcp:192.168.10.54[49669] Annotation: Ngc Pop Key Service UUID: b25a52bf-e5dd-4f4a-aea6-8ca7272a0e86, version 2 Endpoint: ncacn_ip_tcp:192.168.10.54[49669] Annotation: KeyIso Port: 49673/tcp UUID: 367abb81-9844-35f1-ad32-98f038001003, version 2 Endpoint: ncacn_ip_tcp:192.168.10.54[49673] Port: 61801/tcp UUID: 6b5bdd1e-528c-422c-af8c-a4079be4fe48, version 1 Endpoint: ncacn_ip_tcp:192.168.10.54[61801] Annotation: Remote Fw APIs Note: DCE/RPC or MSRPC services running on this host locally were identified. Reporting this list is not enabled by default due to the possible large size of this list. See the script preferences to enable this reporting.
Impact An attacker may use this information to gain more knowledge about the remote host and to conduct further attacks based on it.
Solution: Solution type: Mitigation Filter incoming traffic to this ports.
Affected Software/OS All systems exposing / disclosing information via DCE/RPC or MSRPC services.
Vulnerability Insight DCE/RPC or MSRPC services running on the remote host can be enumerated by connecting on port 135 and doing the appropriate queries.
Vulnerability Detection Method Reports previously collected (via 'DCE/RPC and MSRPC Services Enumeration' OID: 1.3.6.1.4.1.25623.1.0.108044) DCE/RPC or MSRPC services.
... continues on next page ...

...continued from previous page ...

This VT is reporting a severity by default. If the scanned network is e.g. a private LAN / private WAN which contains systems not accessible to the public (access restricted) and it is accepted that the service is disclosing information to this network please set the 'Network type' configuration of the following VT to e.g. 'Private LAN' or 'Private WAN':

Global variable settings (OID: 1.3.6.1.4.1.25623.1.0.12288)

In this case a 'Log' level result is used instead.

Details: DCE/RPC and MSRPC Services Enumeration Reporting

OID:1.3.6.1.4.1.25623.1.0.10736

Version used: 2025-11-26T05:40:08Z

[\[return to 192.168.10.54 \]](#)

2.1.2 Low general/icmp

Low (CVSS: 2.1)

NVT: ICMP Timestamp Reply Information Disclosure

Summary

The remote host responded to an ICMP timestamp request.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

The following response / ICMP packet has been received:

- ICMP Type: 14
- ICMP Code: 0

Impact

This information could theoretically be used to exploit weak time-based random number generators in other services.

Solution:

Solution type: Mitigation

Various mitigations are possible:

- Disable the support for ICMP timestamp on the remote host completely
- Protect the remote host by a firewall, and block ICMP packets passing through the firewall in either direction (either completely or only for untrusted networks)

Vulnerability Insight

The Timestamp Reply is an ICMP message which replies to a Timestamp message. It consists of the originating timestamp sent by the sender of the Timestamp as well as a receive timestamp and a transmit timestamp.

... continues on next page ...

...continued from previous page ...

Vulnerability Detection Method

Sends an ICMP Timestamp (Type 13) request and checks if a Timestamp Reply (Type 14) is received.

Details: ICMP Timestamp Reply Information Disclosure

OID:1.3.6.1.4.1.25623.1.0.103190

Version used: 2025-01-21T05:37:33Z

References

cve: CVE-1999-0524

url: <https://datatracker.ietf.org/doc/html/rfc792>

url: <https://datatracker.ietf.org/doc/html/rfc2780>

cert-bund: CB-K15/1514

cert-bund: CB-K14/0632

dfn-cert: DFN-CERT-2014-0658

[\[return to 192.168.10.54 \]](#)

2.1.3 Low general/tcp

Low (CVSS: 2.6)

NVT: TCP Timestamps Information Disclosure

Summary

The remote host implements TCP timestamps and therefore allows to compute the uptime.

Quality of Detection (QoD): 80%

Vulnerability Detection Result

It was detected that the host implements RFC1323/RFC7323.

The following timestamps were retrieved with a delay of 1 seconds in-between:

Packet 1: 4009698

Packet 2: 4010721

Impact

A side effect of this feature is that the uptime of the remote host can sometimes be computed.

Solution:

Solution type: Mitigation

To disable TCP timestamps on linux add the line 'net.ipv4.tcp_timestamps = 0' to /etc/sysctl.conf. Execute 'sysctl -p' to apply the settings at runtime.

To disable TCP timestamps on Windows execute 'netsh int tcp set global timestamps=disabled' Starting with Windows Server 2008 and Vista, the timestamp can not be completely disabled.

... continues on next page ...

...continued from previous page ...
The default behavior of the TCP/IP stack on this Systems is to not use the Timestamp options when initiating TCP connections, but use them if the TCP peer that is initiating communication includes them in their synchronize (SYN) segment. See the references for more information.
Affected Software/OS TCP implementations that implement RFC1323/RFC7323.
Vulnerability Insight The remote host implements TCP timestamps, as defined by RFC1323/RFC7323.
Vulnerability Detection Method Special IP packets are forged and sent with a little delay in between to the target IP. The responses are searched for a timestamps. If found, the timestamps are reported. Details: TCP Timestamps Information Disclosure OID:1.3.6.1.4.1.25623.1.0.80091 Version used: 2023-12-15T16:10:08Z
References url: https://datatracker.ietf.org/doc/html/rfc1323 url: https://datatracker.ietf.org/doc/html/rfc7323 url: https://web.archive.org/web/20151213072445/http://www.microsoft.com/en-us/download/details.aspx?id=9152 url: https://www.fortiguard.com/psirt/FG-IR-16-090

[[return to 192.168.10.54](#)]