

FEM1 Assignment 4, Resonance frequency

Paul Kulyk

Oleksiy Khoma

April 24, 2017

Theoretical resonance frequency

According to the assignment, we had to define first resonance frequency for our beam. Thus, we had to consider coefficient $\alpha_0 = 1.875$. And according to the formula for a resonance frequency we calculated:

$$\frac{1}{2\pi\sqrt{12}}\alpha_0^2\sqrt{\frac{E}{\rho}}\frac{h}{L^2} \approx 21.4507...$$

Frequency mode

For our frequency mode simulation we created three models with different size of meshes:




Figure 1: Robust mesh, approximal size of seed 0.005

Also, for this mode we tried different types of integration: linear full and reduced, as well as quadratic full and reduced. By this we wanted to see the influence of mesh AND type of integration. For this mode, our results could be organised like this:

Type of integration:	Linear reduced	Linear full	Quadratic reduced	Quadratic full
Size of mesh:				
* Robsut	-	-	21.463	21.472
* Medium	-	22.361	21.455	21.455
* Fine	21.020	21.661	21.453	21.453




Figure 2: Medium mesh, approximal size of seed 0.001




Figure 3: Medium mesh, approximal size of seed 0.001

From this, it can clearly be seen that generally, we get quite close results. For this mode, making the size of mesh smaller, does not really influence the final result. However, the method of integration definitely changes it. Nevertheless, we would choose quadratic method without doubt and reduced integration to reduce time needed for simulation.

Impulse based analysis

To have a clear comparison of different modes, we decided to use the same three meshes as for frequency mode. The obvious disadvantage of this method which we expectedly faced, is the time of simulation. For the fine mesh, simulation takes approximately 5 minutes, which is absolutely unexepable for this type of problems.

Robust mesh, approximal size of seed 0.005 Spectrum for robust mesh

Medium mesh, approximal size of seed 0.001 Spectrum for medium mesh

Fine mesh, approximal size of seed 0.001 Spectrum for fine mesh

Size of mesh:	Robsut	Medium	Fine
	19	19	21

The other disadvantage is that we get quite unprecise results. This conclusion could be explained by two effects, which basicaly are connected with each other. First of all, we use quite a finite time step, for our simulation, which creates step like oscilation graph. The other thing is that we are using MATLAB function `fft()` which represents Fast Fourier Transform. One can find that this is very efficient type to compute discrete fourier transform. However, this type of fourier transform of course produces rounding errors, which also influences results heavily.

Conclusions

For finding the eigenfrequency of simple beams, we can clearly say, that Abaqus frequency mode is definitely preferred. It is faster, it gives better results, and it is not so mesh depended as explicit method. To achieve results as close as possible to theoretically calculated, of course finer meshes are preferred. However, in case of problems which might consume more time with fine meshes, more robust could be used.