

Cisco № 16

```
Switch>en
Switch#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#hostname law
law(config)#

law(config)#int vlan 1
law(config-if)#no sh

law(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

law(config-if)#ip address 192.168.0.2 255.255.255.0
law(config-if)#exit
law(config)#
```

2sw

```
Switch>en
Switch#conf t
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#hostname 2sw
2sw(config)#int vlan 1
2sw(config-if)#no sh

2sw(config-if)#
%LINK-5-CHANGED: Interface Vlan1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface Vlan1, changed state to up

2sw(config-if)#ip address 192.168.0.2 255.255.255.0
2sw(config-if)#exit
2sw(config)#
```

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ping 192.168.0.2

Pinging 192.168.0.2 with 32 bytes of data:

Request timed out.
Reply from 192.168.0.2: bytes=32 time<1ms TTL=255
Reply from 192.168.0.2: bytes=32 time<1ms TTL=255
Reply from 192.168.0.2: bytes=32 time<1ms TTL=255

Ping statistics for 192.168.0.2:
    Packets: Sent = 4, Received = 3, Lost = 1 (25% loss),
    Approximate round trip times in milli-seconds:
law(config)#line vty 0 4
law(config-line)#pass 111
law(config-line)#enable secret 123
law(config)#
```

```
2sw(config)#line vty 0 4
2sw(config-line)#pass 111
2sw(config-line)#enable secret 123
2sw(config)#
```
