



Hyperparameter tuning, Batch Normalization, Programming Frameworks

Quiz, 10 questions

10/10 points
(100%)

✓ **Congratulations! You passed!**

Next Item



1 / 1
points

1.

If searching among a large number of hyperparameters, you should try values in a grid rather than random values, so that you can carry out the search more systematically and not rely on chance. True or False?



True



False



Correct



1 / 1
points

2.

Every hyperparameter, if set poorly, can have a huge negative impact on training, and so all hyperparameters are about equally important to tune well. True or False?



True



False



Correct

Yes. We've seen in lecture that some hyperparameters, such as the learning rate, are more critical than others.



1 / 1
points

3.

During hyperparameter search, whether you try to babysit one model ("Panda" strategy) or train a lot of models in parallel ("Caviar") is largely determined by:



Whether you use batch or mini-batch optimization



Correct



The presence of local minima (and saddle points) in your neural network



The amount of computational power you can access

Hyperparameter tuning, Batch Normalization, Programming Frameworks

10/10 points

(100%)

Quiz, 10 questions

1 / 1
points

4.

If you think β (hyperparameter for momentum) is between on 0.9 and 0.99, which of the following is the recommended way to sample a value for beta?



```
1 r = np.random.rand()
2 beta = r*0.09 + 0.9
```



```
1 r = np.random.rand()
2 beta = 1-10**(- r - 1)
```



Correct



```
1 r = np.random.rand()
2 beta = 1-10**(- r + 1)
```



```
1 r = np.random.rand()
2 beta = r*0.9 + 0.09
```

1 / 1
points

5.

Finding good hyperparameter values is very time-consuming. So typically you should do it once at the start of the project, and try to find very good hyperparameters so that you don't ever have to revisit tuning them again. True or false?



True



False



Correct

1 / 1
points

6.

In batch normalization as presented in the videos, if you apply it on the l th layer of your neural network, what are you normalizing?

 $z^{[l]}$ 

Hyperparameter tuning, Batch Normalization, Programming Frameworks

Quiz, 10 questions

10/10 points
(100%)

☐ $a^{[l]}$

☐ $b^{[l]}$



1 / 1
points

7.

In the normalization formula $z_{norm}^{(i)} = \frac{z^{(i)} - \mu}{\sqrt{\sigma^2 + \epsilon}}$, why do we use epsilon?

☐ To have a more accurate normalization

☒ To avoid division by zero



Correct

☐ In case μ is too small

☐ To speed up convergence



1 / 1
points

8.

Which of the following statements about γ and β in Batch Norm are true?

☒ They can be learned using Adam, Gradient descent with momentum, or RMSprop, not just with gradient descent.



Correct

☐ β and γ are hyperparameters of the algorithm, which we tune via random sampling.



Un-selected is correct

☒ They set the mean and variance of the linear variable $z^{[l]}$ of a given layer.



Correct

☐ There is one global value of $\gamma \in \mathbb{R}$ and one global value of $\beta \in \mathbb{R}$ for each layer, and applies to all the hidden units in that layer.



Un-selected is correct

Hyperparameter tuning, Batch Normalization, Programming Frameworks

Quiz, 10 questions, 10 questions selected is correct

10/10 points
(100%)



1 / 1
points

9.

After training a neural network with Batch Norm, at test time, to evaluate the neural network on a new example you should:



Use the most recent mini-batch's value of μ and σ^2 to perform the needed normalizations.



Correct



If you implemented Batch Norm on mini-batches of (say) 256 examples, then to evaluate on one test example, duplicate that example 256 times so that you're working with a mini-batch the same size as during training.



Un-selected is correct



Perform the needed normalizations, use μ and σ^2 estimated using an exponentially weighted average across mini-batches seen during training.



Un-selected is correct



Skip the step where you normalize using μ and σ^2 since a single test example cannot be normalized.



Un-selected is correct



1 / 1
points

10.

Which of these statements about deep learning programming frameworks are true? (Check all that apply)



Even if a project is currently open source, good governance of the project helps ensure that it remains open even in the long term, rather than become closed or modified to benefit only one company.



Correct



A programming framework allows you to code up deep learning algorithms with typically fewer lines of code than a lower-level language such as Python.



Correct

