

Signal Green Final Report

Waqar Aziz, James Kerr, Adeela Saalim, Andrea Senf, Yoann Strigini

March 25, 2015

List of Tables

1 INTRODUCTION

This work was first and foremost an opportunity for working in a group. Employers want engineers who are not only skilled in their craft, but also persons who are able to collaborate, work well as part of a team, and invest in project aims and those working to achieve them. Our team was able to develop a simulation that involved each member in the process. In spite of differing abilities and communication styles, each person was able to contribute in important ways.

The software engineering part of this project focused on creating a traffic simulation software where we can test various traffic management strategies. We wanted to create a simulation that would be visually interesting with user modifiable variables, and that would have potential for further expansion and use.

We were able to create a simulation that is interesting, flexible, and allows different layouts and road policies to be tested and visually represented. Any geographic information system (GIS) map shapefile representing road networks can be loaded into our simulator and could easily be extended to take into account any other relevant attributes.

Our team further gained a more practical understanding of agent based modelling (ABM) through using Repast Symphony, and gained experience with version control through using GitHub.

2 BACKGROUND

2.1 TRAFFIC FLOW FORECASTS

Analysis of complex urban networks and traffic flow models is the groundwork for reliable traffic flow forecasts, which are widely used to avoid traffic congestion and maximise road network capability in metropolitan areas.[11k] Predictions of traffic growth published by the UK Department of Transport in 2013 show that despite a slowdown in the past decade mainly due to economic recession and high oil prices, traffic on all roads in England are expected to grow by about 45% by 2040 [?].

Consequently, causes and effects of traffic congestion have been studied extensively in order to face the increasing road network saturation. Several factors that have significant impact on traffic flow have been identified, including the following:

- Road/Traffic policy approaches
- Timing/Cost of journeys




Figure 1: England traffic, actual and predicted

- Types of vehicles and speed
- Junctions and bottlenecks
- Lane splitting and joining
- High occupancy vehicle lanes
- Driver's behaviour
- Rush hours
- Occasional factors such as car accidents, road works or bad weather

The model we implemented has been designed with acceptable trade-off between accuracy and computational complexity. We have therefore selected the following set of urban traffic factors:

- Different types of vehicles, e.g. trucks are slower than cars and are less likely to overtake
- Driver's behaviour, e.g. reckless drivers do not stop at amber signal
- Journey of vehicles is based on best route according to roads'length and speed limit
- Roads can have multiple lanes, fast vehicles try to overtake slow ones
- Different traffic management policies, including traffic lights and/or give way signs

The ultimate goal of traffic simulation is to create space for people to move along their journeys in a safe manner with consistent progress.

Data extracted from simulations will be evaluated at the end of this report, in order to analyse different traffic policies highlighting their pros and cons.

Our team began by researching various traffic simulation models and code available online. Some of the more significant included.

[?] gave us a picture of what an interesting simulation and its code might look like. [?] offered a good description of what coding with cellular automata involves for those on the team unfamiliar with the concept. In the early stages of the project we thought coding

using cellular automata might be an approach we would utilize; this was later decided against in favour of ABM. [?] show one way to conceptualize moving cars along a road from origin to destination. [?] Detailed example of an agent-based traffic simulation; referenced for approach and features often considered when creating an agent based model. Well written and fairly comprehensive. [?] argues that “only agent-based models can explicitly incorporate the complexity arising from individual behaviors and interactions that exist in the real-world. ”[5e 1458] Shows the wide uses of Repast in various fields [?] [1457 Table 1]. The article notes that agent modelling using desktop environments like Repast Symphony is a good way to explore the potential of ABM in a brief space of time and with minimal training investment [?][1464] and this is a benefit our team hoped to gain through this project. [?] provided many ideas regarding behaviour rules that was useful, as was the brief but descriptive discussion of modelling. [?] The entire team went through a very good tutorial to learn Symphony basics. This tutorial was an excellent introduction to Symphony and had clear parallels to our simulation. [?] used as reference for coding lane changing and gap acceptance logic.

Selected Bibliography [do not renumber, these are throughout the paper]:

3 REQUIREMENTS AND DESIGN

Our traffic simulator is an agent-based, non-deterministic, discrete-time simulator for microscopic traffic modelling which allows different traffic policies on user-defined Geographic Information System (GIS) maps to be tested.

An Agent-Based modelling (ABM) simulation seemed most appropriate for a traffic simulation [?] [see 1465]. ABM uses entities (agents) to embed certain behaviours and they exist in a certain environment. Agents are autonomous, have objectives and goals, and can interact with other agents. ABM is particularly suitable for traffic simulation because agents, such as vehicles and traffic lights, can adapt to the evolving environment and accommodate changes, e.g. a vehicle needs to accelerate when a traffic light turns green.

The system is non-deterministic, with future states of traffic flow depending on unpredictable events, just as real-life traffic phenomena always have a degree of unpredictability. Randomness is added by the use of a random seed which changes during each run: with same input, output is always different.

A discrete time model, given its iterative nature, is convenient for traffic simulations. Every tick the current state of the agents is evaluated, algorithms are recomputed, and the overall state of the system is updated. For example, traffic lights change light every n ticks, and each vehicle’s velocity is updated accordingly. Our simulation updates state every tick of the clock.

Microscopic traffic models typically simulate the behaviour of single vehicles using microscopic properties such as the vehicle’s position and velocity. Our simulation uses the following common decision models [?]: Car-following model, Lane-selection model, and Gap-acceptance model.

Lastly, GIS integration allows real maps to be loaded into the system. GIS is the de-facto standard for most professional traffic simulators, and governments regularly publish GIS maps about road networks, which are freely available for download. Virtually any GIS map can be loaded into our system.

3.1 Milestones

For the purposes of planning, our team set Milestones to measure what we wanted to accomplish. This is our plan as it stood at the beginning of February:

Milestone 1:

- deadline: 23 February
- code compiles and runs simple simulation
- vehicles run on a map
- variable number of vehicles
- vehicles make decisions to reach a goal

Milestone 2:

- deadline: 8 March
- implement basic vehicle type: car
- traffic flows bi-directionally
- junctions
- signals, give way, roundabouts
- multiple maps in GIS standard
- cars have different behaviours: timid, aggressive, patient
- multiple lanes on some roads

Milestone 3:

- deadline: 16 March
- vehicles appear visually different by some criteria (type/behaviour, speed, congestion)
- speed limits on roads
- implement vehicle types: lorry, emergency, motorcycles
- vehicles exhibit passing behaviours

Possible Traffic Policy Implementations:

- all light junctions
- all roundabout/give way junctions
- mix lights/roundabout junctions
- variable speed limits
- same junction policy with varying levels of congestion

3.2 Language and Framework

The team began by choosing a programming language for development. We quickly settled on Java as our language, as everyone on the team was familiar with it and Java is commonly used in industry. Java is fast enough to simulate hundreds of agents, is entirely object oriented which makes it ideal for an agent paradigm, and currently the most popular Agent Based Modelling framework is in Java. C++ was considered, but the team preferred Java for its ease of coding. A scripting language like python would have enabled fast development, but team members were unfamiliar with it, it is computationally slow, and so not a good choice for modelling with many objects.

For a framework we considered several options. We could code an entire agent based traffic simulation ourselves; this was not selected due to the enormous coding task this would involve, and we were concerned we would not meet all the requirements for the assignment in the time allocated. We considered NetLogo, but decided it did too much work for us; we would do almost no coding ourselves, and very little logic to create. We wanted to show our own ability to code and create our own logic.

3.3 Repast Symphony

We settled on Repast Symphony, a general application programming interface (API) providing us tools, libraries, and plug-ins to create a simulation while allowing us to code and implement appropriate logic for the desired simulation. Repast comes with a BSD software license and is widely used in many fields of academia. [?] [table 1, 1457] Repast Symphony provided the following benefits that made it a good fit for our group project:

- As a framework for Java, it is fully object oriented and everything is created as a Plain Old Java Object. It includes Java libraries and .jar utilities, and all objects are rewritable.
- It provides an ABM environment with a practical skeleton of agents and their contexts, and includes features such as behaviour activation, a discrete event scheduler and Watcher component, and space and grid management.
- It provides a flexible plug-in framework, allowing the developers to use, modify, or write plug-ins. It provides the ability to integrate advanced elements into our code such as importing GIS maps, multi-threading, XML configuration files, and other advanced features.
- It includes charting and data collection functions, so we can focus on deciding on traffic policies and changing these parameters rather than spending time finding ways to display and record the results. The probe function is particularly useful for ABM testing.
- It provides an attractive display graphical user interface (GUI) we can modify to suit our needs and make a more interesting simulation, including user defined options at runtime and 2D and 3D visualisation and GIS plugins. One can create new or rewrite existing plug-ins if one wishes.

The benefits of Symphony come at the flipside cost of there being more opportunities for our team to display skill in modelling concepts and logic rather than a mastery of

Java programming skill. When our team chose ABM as our design platform this meant behaviour and goals became more central than designing passive functions [?], and we trust our ability to create an interesting system shows in our project and does credit to our ability. The team spent some time learning the framework, but this was considered a good investment for the benefits.

4 IMPLEMENTATION

4.1 Symphony and Our Code

The integrated development environment (IDE) for Symphony is a preconfigured Eclipse IDE. Eclipse Symphony varies from the normal Eclipse IDE in that it contains custom views, run configurations, and it adds three .jar files to the buildpath: JOGL (Java bindings for openGL), Java3D, and JAI (Java Advanced Imaging). These .jar files are used to create graphical representation of objects. Symphony also requires a ContextBuilder to initialize and drive the simulation, replacing the Java Main() run method; in our code class SignalGreenBuilder.java implements the ContextBuilder for the program.

While Symphony provided a very useful API, our team determined how each agent and behaviour should be modelled and the logic used to describe each object. For example, Symphony had no effect on how we modelled traffic signals. There is no agent superclass, no inheritance interfaces, no exposed code provided. The actual creation of agents and the method of that creation is the work of the programmers.

Symphony provided nice helper features and many tools to increase the speed at which we could code. Our code uses its background foundation required for ABM, including multi-threading, the Clock/Watcher, having objects automatically drawn on the screen, and agents being aware of their environment. While our team wanted to especially take advantage of Symphony's visualisation benefits, our core requirements are based around the logic of the agents, not their appearance.

4.2 Agents and Environment

The architecture for our simulation engine is a hierarchy of Java classes, where each class is either an agent or an environment. Agents are objects that exhibit behaviours and can either be of fixed geography (eg: junction, road) or they can move on the GIS projection (eg: vehicles and their subclasses). Agent behaviour can be embedded through the agents reacting to the environment themselves, by using the watcher component which listens for events and triggers actions, or by globally scheduling events to happen.

An environment forms a container for agents and includes the Road Network Topology (the network), and GIS Geography (the geography). These are loaded from standard GIS shapefiles (.shp extension). The environment is coded in continuous space with (X,Y) co-ordinates on a directed graph network, with the Network being the topological relationship between each road segment. At any time each agent knows its position on the Geography; vehicle agents can ask the Network for their route and then follow this course along each road segment. Continuous space also allows the user interface to display agents in detail during the simulation.

Repast offers a ContextBuilder component containing a framework for creating agents and environments. The team used the framework to model entities and features including (but not limited to): vehicles, roads, junctions, road network topology, and GIS geography. We also coded all behaviour logic (direction, volition, velocity, etc) for the agents.

We used Styled Layer Descriptor (SDL) files to create the presentation; SDL is an extension of OpenGIS which is open source and provides the benefit of XML format.

4.2.1 The SignalGreenBuilder Class

Class `SignalGreenBuilder.java` builds the road network and the GIS geography for our simulation and initialises the agents. It is the only `ContextBuilder` class for the program. At the highest level of abstraction, the program `Context` contains a graph (Road Network) of vertices (Junctions) connected by paths (edges). The Road Network is a directed graph representing the road topology, and the GIS geography is used to display the simulation.

Repast has built-in GIS integration, so reading in spatial data is done by iterating over each `Feature` object of the `ShapefileDataStore` file (shapefile). Every feature of type “MultiLaneString” represents a road object with its spatial location and other attributes. Creating a road network is achieved by linking edges together, and the road network topology is built with pairs of connecting junctions.

Any GIS map shapefile (.shp) representing road networks can be loaded into our simulator. The simulator uses some GIS attributes for modelling vehicle’s behaviour (ex. road type, max speed, etc.) and could easily be extended to take into account any other relevant attribute. GIS maps were simplified by removing the road coordinates between the Junctions to make it more efficient; creating road agents with only the endpoint coordinates specified prevents very complex urban street maps from becoming too computationally expensive.[see figure XXX]




Figure 2: creating road segments from shapefile

Each Road agent is added to both the `Context` and the GIS geography, along with two Lane agents for each side of the Road (used only for displaying vehicle graphics on the UI). A Repast edge is then added to the road network, and the Repast edges are then linked together to create the road network topology. This is done by keeping a cache of all previously created Junctions, so every time a new Road agent is created the cache is checked to see if there already exists Junctions for its end point coordinates. If there is, then we know all roads linked to those Junctions are also linked to the Road agent being created, and we do not need to create any more new Junctions. see [?] for more detail.




Figure 3: How to create new roads

As an example, consider figure [concrete example].

Before R3 is added: Cache of Junctions = (J1, J2, J3) Road network = (R1, R2) Road network topology = (<J1, J2>, <J2, J3>)

After R3 is added: Cache of Junctions = (J1, J2, J3, J4) Road network = (R1, R2, R3) Road network topology = (<J1, J2>, <J2, J3>, <J2, J4>)

Once the whole shapefile has been read, the GIS geography is displayed on the UI, as shown on [figure Display Manhattan]. In this example we have loaded a map of the main avenues of New York City and clicked on a Road agent to show its attributes: name = Madison Av, speedLimit = 65 Km/h, length = 4,805 meters. Virtually any urban street map can be loaded into Signal Green.




Figure 4: Manhattan!!

4.3 The Vehicle Class

Class `Vehicle.java` is a very important class which initializes vehicles, assigns vehicles their individual behaviour, type, source, and interactions, and contains the generic vehicle constructor. Classes `CarVehicle.java` and `TruckVehicle.java` extend the `Vehicle.java` class and override the constructor to create three new types of vehicles: slow cars, fast cars, and trucks. Each type has its own adjusted `maxVelocity` and visual icon.

Method `initVehicle()` creates a type of vehicle agent and assigns it a random source and destination junction that includes the vehicle's route to that destination. For performance reasons we did not find it feasible to calculate the best path at each vertex; instead the entire path is chosen at initialisation using the highly optimised shortest path algorithm provided by Repast Symphony. The path is shortened as each junction is reached on the way to the destination. When the destination is reached, new random values are chosen and the process repeats.

Method `computeDisplacement()` is used to determine exactly how far in metres the vehicle should travel based on the vehicle's attributes.

4.3.1 Method `Step()`

A vehicle's vision is the distance around which a vehicle is aware of its environment and is calculated based on constant values `DIST_VEHICLES` and `DIST_VEHICLES_STOPPED`. Method `step()` determines individual vehicle behaviours, including interaction with junctions and other vehicles, increasing/decreasing speed, changing lanes, and moving the vehicle along the map.

The vehicle checks the speed and distance of any vehicles in its path, slowing if needed to an optimal velocity. If a vehicle observes a slower moving vehicle in its path, it makes a decision whether or not to change lanes. The vehicle also checks for approaching junctions, decelerating to a stopped position before the light if a red light is in view. If no other vehicles or junctions are in its vision it will accelerate to its `maxVelocity`.

The method `step()` works as follows. (See Figure .) Assume the current vehicle V is heading towards a junction $J[i]$. $J[i]$ is the next node on its route, $J[1..n]$, where n is the number of nodes, $J[1]$ and $J[n]$ are V 's origin and destination.

V needs to first decide which lane it wants to go to (lane selection decision model, step 1.2) and check that the road is clear (gap acceptance decision model, step 2).

In steps 3 and 4, V tries to either accelerate or slow down, depending on the outcome of the previous steps.

Next, if V is close enough to $J[i]$, traffic management policies are evaluated (step 8): for example, if $J[i]$ uses traffic jams, then V asks $J[i]$ if it has to wait (Light.RED signal detected, step 8.1.1). Finally, displacement is executed, meaning V 's position is updated both in the road network topology and in the GIS projection (step 9).

V checks what is the $J[i]$ on the route $J[n]$. It knows which vehicles are approaching because it holds a priority queue of incoming Vehicles for each road segment, where weights are the distance from V to $J[i]$. This is an efficient solution as insertion is done in $O(\log n)$, while removal is done in constant time.




Figure 5: Sequence diagram




Figure 6: Faster vehicle overtakes slower truck and merges back on the outer lane.

From Repast's point of view, Step() method is executed every iteration of the simulation, using the Java annotation: @ScheduledMethod(start = 1, interval = 1) meaning that it starts from tick one, and gets executed every tick.

4.3.2 Simulation Calibration

Manual testing of SG was fundamental for proper calibration of simulation parameters. Improper calibration leads to invalid output, thus special care must be taken when adjusting values to make the simulation visually realistic. The Constant class holds all arbitrary calibration parameters.

Simulation parameters and relevant measures are summarised as follows:

- 1 simulation tick = 1 second
- GIS projection distances reflect real distances, and are measured in meters
- Minimum distance between vehicles to avoid collisions = 1.8 meters
- Arbitrary acceleration factor of vehicles = 1.6
- Real vehicle displacement in meters = displacement * 70
- Displacement equation: $x = v_0 * t + \frac{1}{2} a * t^2$, where x is the displacement, v_0 the initial velocity, a the acceleration, t the time which is arbitrarily set to 4.
- Truck maximum speed = 80 Km/h

4.3.3 Moving on GIS Geography

The vehicle.java class determines the behaviour of vehicles so they follow roads. This required special coding, as GIS images point true north and use azimuth coordinates for its 3D mapping, while the UI points to grid north and uses simple (X,Y) coordinates for the grid.

Azimuth coordinates allow one to measure distances and plot locations in a spherical coordinate system, and our code utilized this form of measurement in moving the vehicles along the maps. We referenced [?] to see how one could compute the correct angle for displaying graphics on the UI.

This further required the use of kinematics equations for plotting the direction of vehicles in several methods. Kinematics is the study of objects moving through space. Because we used GIS maps, all calculations along the map involve real distances.




Figure 7: Vehicle V moving on its planned route.

For example, consider Figure . The following are the main steps:

1. V is heading towards J3 so it needs to compute the distance to it.
2. V computes its current displacement. Displacement is computed using a standard kinematics equation which takes into account velocity and acceleration.
3. There can now be two cases:
 - If V cannot make it all the way to J3, V just moves towards it by the whole displacement in meters.
 - If V is close enough to J3, meaning that current displacement $>$ distance to next junction, V first moves to J3, updates its route (i.e. a pointer to the next junction) and then performs the remaining displacement towards the new next junction.

4.3.4 Junction Classes

Class `Junction.java` creates junction objects that are nodes on the road network. These objects contain references to road segments (including adjacent junctions and roads) and queues (containing vehicles) associated with it. It is used throughout the program to determine where vehicles are, and so is fundamental to vehicle behaviour.

Class `TrafficLight.java` extends `Junction.java` and schedules traffic light management. It has its own step method to iterate through lights, using class `Light.java` which encapsulates and toggles between the three light states.

In order to implement traffic management policies, some junctions need to embed special behaviour. Signal Green supports traffic light logic or give way signs, however the model can easily be expanded by extending the `Junction` class. We assume that junctions with more than two road segments need some traffic management logic, so they will be either instances of `TrafficLight` or `GiveWaySign`.

Traffic lights have one instance of `Light` for each road adjacent to that junction, each light has a signal attribute which can be either RED, GREEN or AMBER. Lights change their state every 25 ticks, at any time only one `Light` for that junction can be in GREEN

state. Vehicles that are exiting a road segment check if the Junction is an instance of TrafficLight, in which case they inspect the signal to know if they must stop.




Figure 8: Junction of type TrafficLight.

In proximity of give way intersections, on the other hand, vehicles check for each road segment which vehicle is closest to that intersection, to know who has precedence. (See Figure .)




Figure 9: Junction of type GiveWaySign.

4.4 External libraries and tools

Most external libraries used are part of the Repast Simphony ABM toolkit. The following list summarises the third party libraries used, some of which come with the installation of SG.

- Repast Simphony, free open source agent-based modelling platform.
<http://repast.sourceforge.net/>
- GeoTools, The Open Source Java GIS Toolkit, to read in GIS shapefiles.
<http://www.geotools.org/>
- OpenGIS Styled Layer Descriptor, free and publicly available, for rendering maps and vehicles.
<http://www.opengeospatial.org/standards/sld>
- JTS Topology Suite from Vividsolutions, an API of 2D spatial functions, open source, LGPL license.
<http://www.vividsolutions.com/jts/JTSHome.htm>
- GIS maps downloaded from the US Dept. of Transportation, freely available for download.
<http://www.fhwa.dot.gov/planning/processes/tools/nhpn/2011/>

- PriorityBlockingDeque, a doubly linked priority queue implementation by Aviad Ben Dov, based on `java.util.concurrent.LinkedBlockingDeque`.
- IzPack java installer generator, for final project package.
<http://izpack.org/>

4.5 Other Work

The only class which is not our team's work is class `PriorityBlockingDeque.java`. This class is copyrighted by Aviad Ben Dov, and it implements a rather complicated data structure holding vehicles in a queue at junctions. We used his work because the code was complex enough that it would take a great deal of time to write ourselves, and we thought it prudent to use his code with attribution instead of risking not completing the junction code satisfactorily in time or relying too heavily on his work.

5 TESTING

5.1 Introduction

This test plan has been created to check if our system conforms to all functional requirements and also to specify the types of testing which will be used to validate the functional requirements, action required on failed tests and time line to perform testing of the system. Exhaustive testing of the system is naturally not realistically possible in the time given but we will use a diverse range of tests to find bugs and errors in the system including unit, functional, error and system testing. System is implemented using java therefore cross platform testing will be performed too. Automation testing will not be possible due to the nature of agent-based modelling simulations. Agents are non-deterministic and there is no set predictability of where objects will be at a given time. There is not a set result that can be expected for each vehicle, so automated testing for agents is not generally possible.

ABM testing will be done by running the simulation, observing the agents' behaviour and comparing it with expected behaviour. We will test our code at three different levels of functionality: This will include testing of agents interaction with other components of environment (roads, traffic lights) when programme will be executed at run time.

5.2 Objectives and Tasks

5.2.1 Objectives

The objective of testing our system is to provide adequate testing of functional requirements, validation and behaviour of system under simulated condition. Testing will be done by running the simulation, observing the agents' behaviour and comparing it with expected behaviour. Debug methods are written to eliminate bugs in the code and exceptions are handled to avoid the crashes. Simulation is run at least more than 3 times in order to test the expected behaviour of agents during simulation run.

5.2.2 Tasks

- Identifying functional requirements and writing the tests cases.
- Executing tests.
- Record the failed test cases and reporting them to team.
- Performing the re-test on failed test cases one bugs are fixed.

5.3 Scope

In context to our system, which is implemented using agent-based model it will be tested at three different levels of functionality.

- **Agents' behaviour**
Verified by checking the changing environment variables around agents. This tests functional requirements of the system as well.
- **Runtime Parameters**
Elements and data which load at runtime will be tested using valid and invalid inputs and checking for correct results.
- **Overall behaviour of system**
Checks that all agents of the system produce expected results for a given scenario.

5.3.1 Levels of Functionalities

- **Agents' behaviour:**
Can be checked by changing environment variables around agents. These behaviours of agents also forms the functional requirements of the system as well. We have two agents in our system.
 1. **Vehicles**
step() method of Vehicle class is the entry point of control into simulation. All methods related to vehicle behaviour are invoked inside this method.
 - **Test Case1:** Vehicle Impasse
Expected Output: This "if condition" in step() method should not be true i.e. no Vehicle should be stuck in impasse.
Actual Output: Console output does not print the statement "Vehicle is stuck in impasse. Cannot move...". "if condition" remains false.
Result: Passed
 - **Test Case 2:** moveTowards()
Input: Coordinate and displacement
Expected Output: Every vehicle on the network should move to a new coordinate and exception should not be thrown printing on console "Could not move vehicle for some reason."
Actual Output: Vehicle moved. No exception thrown.
Result: Passed
 - **Test Case 3:** Accelerate() Every vehicle must accelerate in order to move.
input: Takes ACCELERATION and time t to calculate velocity.
Expected Output: Vehicles should be moving not more than maximum velocity.
Actual Output: No vehicle colliding and no vehicle static if car ahead is not stopping.
Result: Passed

- **Test Case 4:** slowDown() Every vehicle must slow down in order to stop.
Input: Takes ACCELERATION and $t*2$ to calculate velocity.
Expected Output: If velocity is less than zero then vehicles must stop.
Actual Output: Vehicles stopped when velocity is less than zero.
Result: Passed

2. Traffic Lights

- **Test Case 5:** Traffic Light Green
Expected Output: Cars should keep moving if traffic light is green.
Actual Output: Cars did not stop.
Result: Passed.
- **Test Case 6:** Traffic Light Red
Expected Output: Cars should stop if traffic light is red.
Actual Output: Cars stops when traffic light is red.
Result: Passed
- **Test Case 7:** Traffic Lights On More Than 2 Roads Junction
Traffic lights should only be displayed on junctions that contain more than two roads.
Expected Output: Only junctions with more than two roads display traffic lights.
Actual Output: Traffic lights are displayed only on more than two road junctions.
Result: Passed



Figure 10: Network with traffic lights.

• Runtime Parameters:

Elements and data which loads at run time will form part of runtime testing. It will be tested, giving all valid and invalid inputs and check results. Following elements will be tested at run time:

- **Test Case 8:** SignalGreenBuilder Implements ContextBuilder
This class contains methods to build the context and initialise all variables required during the simulation execution.
Input: Run signalGreen Model, to load user GUI which contains GIS map, Vehicle agents and TrafficLight Agents.
Expected Output: Map should be loaded and displayed along with three different types of vehicles and traffic lights on all junctions that have more than two edges.
Actual Output: Map loaded with 100 vehicles which is default value and traffic

lights on junctions with more than two edges only.

Result: Passed

– **Test Case 9:** Number of vehicles

Input: Enter a number in "Number of vehicles" field on parameters tab.

4, 0, -1 and a character given as input.

Expected Output: Only entered number of vehicles should appear on road network. No vehicles should appear for negative numbers and characters.

Actual Output: Vehicles are equal to number entered. No vehicles for negative and character input.

Result: Passed




Figure 11: Number of cars

– **Test Case 10:** No Traffic Lights

"Traffic Lights" on parameters tab, if unchecked traffic lights should not appear on display and cars should not consider traffic lights.

Expected Output: Cars should travel on road without stopping at traffic lights as there are none.

Actual Output: No traffic lights are displayed and cars carry on moving on roads.

Result: Passed.

– **Test Case 11:** Multiple Maps

Input: In parameters tab, user should be able to select different maps. Manhattan and New York maps given as input.

Expected Output: Maps should be loaded at run time and simulation should run.

Actual Output: Two different maps loaded and simulation executed successfully.

Result: Passed

• **Overall behaviour of system:**

Checks that all agents of the system produce expected results in a given scenario.




Figure 12: Map of Manhattan


This will include testing of agents interaction with other components of environment (roads, traffic lights) when programme will be executed at run time.

- **Test Case 12:** Every junction holds a queue of vehicles running on a particular outward road.

Expected Output of `next.printVehiclesQueue(origin):[signalGreen.Vehicle@54008645, signalGreen.Vehicle@1a43b86b]` Peek vehicle: `signalGreen.Vehicle@54008645`

Actual Output: Using probe tool, selecting the area which we want to inspect:

There are indeed two vehicles running on W 34th St, and their object ID match.



Result: Passed

5.4 Conclusion

This test plan covers all major requirements of traffic simulation we have developed which verifies the functional requirements established at the beginning of the project. Test cases were developed to test the expected behaviour of the system using different parameters at run time.

6 TEAM WORK

Our approach to the project was to set down ideas, goals, and tools in the first two weeks, then jump into the coding and get as far along as we could until the initial report came due. This worked well in many ways. Important decisions about implementation were decided very quickly so coding was able to start in January. The milestones were itemized early in the project, with Milestone 1 set early and items assigned to Milestones 2 and 3 differentiated closer to the deadline of the Initial Report.

6.1 Roles and Task Division

Yoann Strigini: Design Architect, Developer One Design SignalGreen model, integration with GIS, develop Vehicle class, presentation layer, documentation (architecture and technical details) Adeela Saalim: Testing Specialist Develop test cases, run test cases, document testing James Kerr: Documentation Specialist Two, LaTeX Specialist Writing technical documentation for report Waqar Aziz: Developer Two, Head Policy Comparison and Reporting Develop reporting functionality; primary traffic policy testing and reporting Andrea Senf: Team Coordinator, Tech Doc Specialist Coordinate team activities, Scrum Master, Lead documentation and reporting

6.2 Tools

- GitHub. GitHub was used for creating the code, providing version control and easy sharing of code. Initial and final reports were also kept there. Andrea held the main code repository, and the team branched off that code.
- Communication. For communication outside coding, the most used tool by far was WhatsApp; this was practical for team chat, answering basic questions, and coordinating meetings. Longer reports for the group were written on asana or sent by email. Asana was used consistently by team members and was helpful for the documentation of the final report and for automatically generated Gantt charts through Instagantt.
- Meetings. When one or more group members believed a whole group meeting was needed to further the project, this was communicated on WhatsApp and a time and place of meeting was arranged using input from all members. These meetings were in person. Other times two or three members met together using Skype or in person as needed to work on parts of the project pertaining only to them.

6.3 Development and Reporting

The team set out to utilize an Agile method of development with SCRUM reports once a week, either in person (if we had a meeting) or written if we did not gather. Group SCRUM did not pan out exactly as anticipated, as early meetings had absences which made SCRUM impractical as we waited for other members arrived (which they occasionally did not). We then decided to transition completely to written reports.

Approximately every week the group coordinator would remind the team to post WhatsApp/asana updates so everyone was aware of what the others were doing and to help the team to continually progress. Team members were to request help as needed and there was always a visible 'next task' waiting when one's current task had been completed, so while SCRUM was not overtly performed the goals behind the method did remain.

6.4 Team Challenges

Our team faced several challenges in working together and with our chosen tools. [Note: all members are here referred to as 'he'.]

- Our team struggled to coordinate regarding GitHub the first part of the project, as several members focused on coding on their own machines rather than branching from GitHub in the weeks prior to the initial report date. Initial code was uploaded to GitHub the day before the initial report was due. The members leading in coding later created a full GitHub project for everyone to access.
- A member missed two meetings where decisions were made, so his preferences were not implemented. As he had strong feelings about these decisions it was difficult for the person to accept and caused some friction.
- A member found he did not have the ability to run Symphony and so did not have a way to code his part of the project; the group was notified of this after the initial report presentation. He found a way to partially resolve this so he could code from the last week of February, although still without full Eclipse functionality.
- A member had difficulty prioritizing his code at the end, putting off resolving a key issue for several days. This resulted in our final Milestone deadline being pushed back almost a week and added stress to other team members.
- After difficulty getting team members to follow through with attending agreed meetings, we voted to modify our practice so that absence to agreed full group meetings would result in a point for that person being deducted.

7 EVALUATION

7.1 Group Project

University group projects can be tricky to make work well; professional teams generally have the benefits of prior working relationships and clearly understood authority and accountability structures. SignalGreen team members were generally unfamiliar with each other before forming the group; four of our team formed based on where we were sitting in the introductory lecture, and the fifth was a person who we heard was looking for a group.

Distributing points is generally difficult to manage well, as giving too much power to democratic vote can be seen as unfair and hurtful by some members, and not allowing enough flexibility can result in members not feeling impressed to participate or work in a timely fashion.

In general, as masters students we are committed to doing good work, as our work for the project is part of our training for our careers. On this basis our team decided to share points evenly, and points lost due to agreed criteria would be distributed by vote. Some




Figure 13: Gantt Chart from 8 Feb

members did more work than our points can reflect, and we trust their hard work will pay off in personal dividends in the future.

Ultimately, the goal of the team was for everyone to get through the module with a pass (preferably much better). To this end, we are not group critiquing each other, nor are we calculating what we ourselves did for comparison to others. As we believe our team has been successful in the project we feel it would be better to end with a feeling of satisfaction for having completed a quality project.

7.2 Milestone Results

All objectives set for Milestone 1 were completed in its entirety by the deadline set by the team. At that time we extended the deadlines of the Milestones to have all coding finished by 16 March, and then turn to cleaning the code and final commenting while testing was finishing and traffic policies were compared during the week of 16 March.

We completed tasks very much on schedule with what we planned at the beginning. In the interest of better code, we extended the Milestone 2 deadline to March 16; this




Figure 14: Gantt Chart from 26 March

allowed some desired behaviours to be completed. All coding was originally scheduled to stop 16 March to leave time for continued testing, commenting and code cleaning, and documentation.

One member had issues with his code that put the team a week behind at the end. This was disappointing, but team members pulled together to complete the rest of the tasks on schedule and bring out our traffic simulation by the deadline.

7.3 Functional Requirements

Final Characteristics - vehicles run on a map - multiple maps in GIS standard - variable number of vehicles - vehicles make decisions to reach a goal - vehicles exhibit passing behaviours - implement basic vehicle types: car, lorry - cars have different behaviours: aggressive, patient - vehicles appear visually different by type - traffic flows bi-directionally - junctions, signals, give way - multiple lanes on some/all roads - speed limits on roads

Functional Requirements

- Maps Multiple maps can be used Use GIS standard
- Roads Can have multiple lanes Traffic flows bi-directionally Vehicles appear to run along roads
- Vehicles Variable number of vehicles Accelerate and decelerate Appear visually different by type Type car with unique behaviour Type truck with unique behaviour Exhibit passing behaviours Journey calculated by road length and speed limit
- Junctions Connect roads Type give way Type signal Signals change between red, amber, green Vehicles stop at red and go at green Source at junctions Stop/wait before junctions
- Simulation User controlled variables Runs on different machines

7.4 Repast Symphony

Overall we think our use of Repast Symphony was successful for our project. It provided a foundation API and Eclipse configuration that was not directly involved with agents or behaviours. It allowed us to create attractive visuals in the simulation and analysis graphing. We spent little time debugging, and were able to focus on simulating traffic. Symphony provided many extras (XML persistent storage, installers, etc) that we did not use due to lack of need or lack of implementation time.

An unforeseen disadvantage of Symphony arose in that it cannot be installed or used on KCL lab computers. One member of our group did not have access to Symphony at home or on campus (the group did not know this until after the initial presentation), and he was not able to find a way to use Symphony until almost March, and then not effectively. This greatly reduced his ability to be useful to the team in coding and held up work on a major segment of the code.

Originally we considered using a belief-desire-intention (BDI) model to code the agents' behaviour, but as the member intending to code this was unable to use Symphony, behaviours were instead coded into the agents themselves.

We originally intended to implement both signal and roundabout junctions, but the code for the signals and give way took much more work than anticipated, and so we decided not to implement roundabouts in this version of our code.

7.5 Further Work

“Validation data is usually macroscopic statistics such as flow rate, speeds and queue time, which can easily be compared with data from real traffic experiments. ” [?]

- If we had more time we would have liked to download a road map from a town in England where we know road data/statistics and compare our model to the actual traffic flow for the same road. This would be a big step in validating our logic and making the code useful to others wishing to model traffic.
- Creating roundabouts was the next goal for our code, and this would make the code work for modelling most UK towns and cities. (Roundabouts are not generally used in the USA.)
- Further development can be done in displaying road closures for modelling construction or traffic accidents. This would make the model more realistic and useful in determining maintenance disruption.
- Implement source/sinks for allowing traffic to come on/off the map in a more natural location than at junctions; perhaps from the edges of the map would be more optimal visually. This would allow traffic congestion to increase as more cars are fed into the simulation than are going out (and vice versa), and would allow modelling of road conditions created by end of workday, post-sport competition, etc.
- We did not make progress on the BDI as planned, so this was left out of the code. The code could be restructured to more neatly implement this if desired.
- Adding other vehicle types such as motorbikes or road features such as pedestrian crossings or high occupancy vehicle (HOV) lanes to model their effect on congestion and traffic flow.

8 PEER ASSESSMENT

Waqar: 20

James: 18.5

Adeela: 20

Andrea: 20

Yoann: 21.5