

Accelerator Design Educational Primer – Conceptualizing and Optimizing the Hybrid LHeC-like Electron-Ion Collider Design

Initial internal version – A.Seryi, July 14, 2025. March 2026 – being updated for IPAC26.

March 19, 2026

1 Abstract

Note that the latest version being prepared for IPAC26 by the team of authors is in Overleaf – view the draft here: <https://www.overleaf.com/read/xfsncsysmktg#9f81ed>

The Electron-Ion Collider (EIC) Mission Need requires $\sqrt{s} = 20\text{-}100$ GeV (upgradable to 140 GeV) and luminosity $10^{33}\text{-}10^{34}$ $\text{cm}^{-2} \text{ s}^{-1}$. The current ring-ring baseline achieves the full scope, including $\sim 10^{34}$ $\text{cm}^{-2} \text{ s}^{-1}$ across all energies. However, when the design is re-optimized for the lower boundary – accepting $\sim 10^{33}$ $\text{cm}^{-2} \text{ s}^{-1}$ and prioritizing cost – an alternative configuration emerges as more advantageous: a hybrid LHeC-like electron accelerator using multi-pass energy recovery linacs (ERL). This solution reduces electron-beam power by roughly an order of magnitude, yielding nearly a factor of two reduction in total project cost compared with the present baseline while still satisfying the minimum physics requirements. The study performs parametric cost and performance modeling, augmented by AI-driven optimization, to explore this design space. Serving primarily as an educational exercise for the next generation of accelerator physicists and engineers, the paper demonstrates modern design methods: rapid parametric scans, cost-driven optimization, and integration of AI tools. It examines technical feasibility, identifies critical R&D (high-current ERL operation, beam-beam effects, synchronization, etc.), and discusses how such re-optimization studies can be used to train designers in an era when artificial intelligence dramatically expands exploration of complex accelerator parameter spaces.

2 Introduction

The Electron-Ion Collider (EIC) is a proposed facility to probe the structure of nucleons and nuclei at high energies. The standard EIC design aims for a luminosity in the range of 10^{33} $\text{cm}^{-2} \text{ s}^{-1}$ to 10^{34} $\text{cm}^{-2} \text{ s}^{-1}$ (average luminosity), as defined in the CD0 mission need statement. The EIC is designed as a classical ring-ring collider, with electron and proton storage rings, providing collisions.

However, to reduce costs, a hybrid approach combining EIC proton beam parameters with LHeC-like electron beam parameters can be explored, while still giving the luminosity from the CD0 mission need statement range. The idea to explore this approach was prompted by discussion of the LHeC project at the Open Symposium for the European Strategy for Particle Physics, where during the discussion (see link in the references) it was claimed that inserting a new electron ring into the LHC tunnel would be cost prohibitive and would also limit LHeC luminosity.

The hybrid design that we will discuss below could potentially use a linac for electrons, working in an energy-recovery mode, reducing the need for an electron ring, and therefore providing significant reduction of cost, albeit with the need for some additional R&D.

This note presents parameter tables as well as brief description for:

- Standard EIC with 1×10^{34} $\text{cm}^{-2} \text{ s}^{-1}$ luminosity (project baseline).
- Hybrid EIC-LHeC with $\sim 2 \times 10^{33}$ $\text{cm}^{-2} \text{ s}^{-1}$ (using EIC proton emittances).

- Optimized hybrid EIC-LHeC with $1 \times 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$.

Cost estimates for the hybrid electron complex are also provided, including a conversion to USA DOE accounting for the lower-cost recirculating version. A discussion on the crab waist scheme for further luminosity optimization is also included.

3 AI models and prompts

Describe here AI models used and prompts

4 Baseline EIC Parameters (1E34 Luminosity)

The standard EIC baseline for 10 GeV electron and 275 GeV proton achieve peak $1 \times 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$ luminosity with the following set of parameters.

Table 1: Baseline EIC Parameters (1E34 Peak Luminosity)

Parameter	Value	Unit
Ring circumference	3834.00	m
Revolution frequency	78229.77	Hz
Number of bunches	1160	
Electron rest mass energy	0.000511	GeV
Proton rest mass energy	0.938	GeV
Electron gamma	19569.47	
Proton gamma	293.14	
Electron energy	10.0	GeV
Electron bunch population	1.72e+11	particles
Electron normalized horiz emittance	391.0	μm
Electron normalized vert emittance	26.0	μm
Electron geometric horiz emittance	20.0	nm
Electron geometric vert emittance	1.3	nm
Electron β_{a_x} at IP	0.45	m
Electron β_{a_y} at IP	0.06	m
Electron bunch length (RMS)	0.007	m
Electron horizontal beam size at IP	94.8	μm
Electron vertical beam size at IP	8.6	μm
Electron horizontal beam-beam xi	0.072	
Electron vertical beam-beam xi	0.100	
Electron horizontal RMS beam angle	210.7	μrad
Electron vertical RMS beam angle	154.0	μrad
Electron beam current	1554.99	mA
Proton energy	275.0	GeV
Proton bunch population	6.9e+10	particles
Proton normalized horiz emittance	3.3	μm
Proton normalized vert emittance	0.3	μm
Proton geometric horiz emittance	11.3	nm
Proton geometric vert emittance	1.0	nm
Proton β_{a_x} at IP	0.80	m
Proton β_{a_y} at IP	0.07	m
Proton bunch length (RMS)	0.060	m
Proton horizontal beam size at IP	94.9	μm
Proton vertical beam size at IP	8.6	μm
Proton horizontal beam-beam xi	0.012	

Proton vertical beam-beam xi	0.012	
Proton horizontal RMS beam angle	118.6	μrad
Proton vertical RMS beam angle	119.2	μrad
Proton beam current	1.00	A
Effective horizontal beam size	134.1	μm
Effective vertical beam size	12.2	μm
Collision frequency	9.1e+07	Hz
Luminosity	1.05e+34	$\text{cm}^{-2} \text{s}^{-1}$

5 Standard LHeC Parameters

The standard LHeC set of parameters is also shown here for reference and comparison. We use parameters of the first stage LHeC with reduced electron beam energy (to 20 GeV, in comparison with 50 GeV in the full project) as presented to ESPP.

Table 2: LHeC Parameters (20 GeV Electron, 7 TeV Proton)

Parameter	Value	Unit
Ring circumference	26659.00	m
Revolution frequency	11245.91	Hz
Number of bunches	2808	
Electron rest mass energy	0.000511	GeV
Proton rest mass energy	0.938	GeV
Electron gamma	39138.94	
Proton gamma	7462.69	
Electron energy	20.0	GeV
Electron bunch population	1.19e+10	particles
Electron normalized horiz emittance	22.0	μm
Electron normalized vert emittance	22.0	μm
Electron geometric horiz emittance	0.6	nm
Electron geometric vert emittance	0.6	nm
Electron β_{a_x} at IP	0.20	m
Electron β_{a_y} at IP	0.20	m
Electron bunch length (RMS)	0.003	m
Electron horizontal beam size at IP	10.6	μm
Electron vertical beam size at IP	10.6	μm
Electron horizontal beam-beam xi	2.185	
Electron vertical beam-beam xi	2.185	
Electron horizontal RMS beam angle	53.0	μrad
Electron vertical RMS beam angle	53.0	μrad
Electron beam current	60.1	mA
Proton energy	7000.0	GeV
Proton bunch population	2.2e+11	particles
Proton normalized horiz emittance	2.5	μm
Proton normalized vert emittance	2.5	μm
Proton geometric horiz emittance	0.3	nm
Proton geometric vert emittance	0.3	nm
Proton β_{a_x} at IP	0.35	m
Proton β_{a_y} at IP	0.35	m
Proton bunch length (RMS)	0.075	m
Proton horizontal beam size at IP	10.7	μm
Proton vertical beam size at IP	10.7	μm
Proton horizontal beam-beam xi	0.001	

Proton vertical beam-beam xi	0.001	
Proton horizontal RMS beam angle	30.7	μrad
Proton vertical RMS beam angle	30.7	μrad
Proton beam current	1.11	A
Effective horizontal beam size	15.1	μm
Effective vertical beam size	15.1	μm
Collision frequency	3.2e+07	Hz
Luminosity	5.78e+33	$\text{cm}^{-2} \text{s}^{-1}$

6 Hybrid EIC-LHeC Parameters (2E33 Luminosity)

For the hybrid with $\sim 2\text{E33}$ luminosity, proton emittances are kept the same as standard EIC, while the parameters of electron beam (emittances, beam current, bunch repetition rate) are taken from LHeC design. The number of proton bunches is reduced by a factor of three, in comparison with EIC baseline, while keeping the proton beam current constant, in order to match to the electron bunch rate assumed in LHeC.

Table 3: Hybrid EIC-LHeC Parameters (2E33 Luminosity)

Parameter	Value	Unit
Ring circumference	3834.00	m
Revolution frequency	78229.77	Hz
Number of bunches	386	
Electron rest mass energy	0.000511	GeV
Proton rest mass energy	0.938	GeV
Electron gamma	19569.47	
Proton gamma	293.14	
Electron energy	10.0	GeV
Electron bunch population	1.19e+10	particles
Electron normalized horiz emittance	22.0	μm
Electron normalized vert emittance	22.0	μm
Electron geometric horiz emittance	1.1	nm
Electron geometric vert emittance	1.1	nm
Electron β_{a_x} at IP	1.20	m
Electron β_{a_y} at IP	0.05	m
Electron bunch length (RMS)	0.003	m
Electron horizontal beam size at IP	36.7	μm
Electron vertical beam size at IP	7.5	μm
Electron horizontal beam-beam xi	3.474	
Electron vertical beam-beam xi	0.679	
Electron horizontal RMS beam angle	30.6	μrad
Electron vertical RMS beam angle	149.9	μrad
Electron beam current	57.58	mA
Proton energy	275.0	GeV
Proton bunch population	2.1e+11	particles
Proton normalized horiz emittance	3.3	μm
Proton normalized vert emittance	0.3	μm
Proton geometric horiz emittance	11.3	nm
Proton geometric vert emittance	1.0	nm
Proton β_{a_x} at IP	0.12	m
Proton β_{a_y} at IP	0.06	m
Proton bunch length (RMS)	0.070	m
Proton horizontal beam size at IP	36.8	μm
Proton vertical beam size at IP	7.8	μm

Proton horizontal beam-beam xi	0.001	
Proton vertical beam-beam xi	0.002	
Proton horizontal RMS beam angle	306.3	μrad
Proton vertical RMS beam angle	130.6	μrad
Proton beam current	1.00	A
Effective horizontal beam size	52.0	μm
Effective vertical beam size	10.8	μm
Collision frequency	3.0e+07	Hz
Luminosity	2.10e+33	$\text{cm}^{-2} \text{s}^{-1}$

7 Hybrid EIC-LHeC Parameters (1E34 Luminosity)

For the optimized hybrid with 1E34 luminosity, proton emittances are reduced (here we count on eventual development of the on-collision-energy electron cooling). The vertical emittance of electron beam is reduced too, assuming the the beam will be generated in a magnetized electron gun, and then Derbenev's beam transformer will be used to convert magnetized round electron beam into flat beam. We conservatively assumed that the vertical electron emittance can be reduced just by a factor of ten.

Table 4: Hybrid EIC-LHeC Parameters (1E34 Luminosity)

Parameter	Value	Unit
Ring circumference	3834.00	m
Revolution frequency	78229.77	Hz
Number of bunches	386	
Electron rest mass energy	0.000511	GeV
Proton rest mass energy	0.938	GeV
Electron gamma	19569.47	
Proton gamma	293.14	
Electron energy	10.0	GeV
Electron bunch population	1.19e+10	particles
Electron normalized horiz emittance	22.0	μm
Electron normalized vert emittance	2.2	μm
Electron geometric horiz emittance	1.1	nm
Electron geometric vert emittance	0.1	nm
Electron β_{a_x} at IP	0.25	m
Electron β_{a_y} at IP	0.10	m
Electron bunch length (RMS)	0.003	m
Electron horizontal beam size at IP	16.8	μm
Electron vertical beam size at IP	3.4	μm
Electron horizontal beam-beam xi	3.474	
Electron vertical beam-beam xi	6.789	
Electron horizontal RMS beam angle	66.8	μrad
Electron vertical RMS beam angle	32.7	μrad
Electron beam current	58.0	mA
Proton energy	275.0	GeV
Proton bunch population	2.07e+11	particles
Proton normalized horiz emittance	0.9	μm
Proton normalized vert emittance	0.1	μm
Proton geometric horiz emittance	3.1	nm
Proton geometric vert emittance	0.3	nm
Proton β_{a_x} at IP	0.09	m
Proton β_{a_y} at IP	0.05	m
Proton bunch length (RMS)	0.070	m

Proton horizontal beam size at IP	16.8	μm
Proton vertical beam size at IP	3.6	μm
Proton horizontal beam-beam xi	0.003	
Proton vertical beam-beam xi	0.007	
Proton horizontal RMS beam angle	182.4	μrad
Proton vertical RMS beam angle	77.8	μrad
Proton beam current	1.00	A
Effective horizontal beam size	23.8	μm
Effective vertical beam size	5.0	μm
Collision frequency	3.02e+07	Hz
Luminosity	1.00e+34	$\text{cm}^{-2} \text{ s}^{-1}$

We note that the table above is shown quite large beam-beam effects on the electron beam, which will be severely disrupted after collision. Calculations of luminosity need to be done taking beam-beam effects into account, and moreover, feasibility of energy recovery and recirculation of such disrupted beam needs to be studied. Possibly, parameters can be further optimized to reduce disruption of the electron beam.

8 Cost Estimations for Hybrid EIC-LHeC

Cost estimates for the electron complex, IR, and detector are provided, comparing single-pass and recirculating versions. That means, the 10 GeV energy of electron beam is provided by a single pass through the 10 GeV linac in the first case, and by two recirculating passes through 5 GeV linac in the second case. In the table below, PY indicate Person-Year. The cost scaling below was done with help of AI and is not fully checked, although the cost numbers for the IR and detector has been manually increased in comparison with the scaling.

Table 5: Hybrid EIC-LHeC Cost and Manpower Estimate Comparison

Component	Single-Pass Cost (MCHF)	Single-Pass (PY)	Recirc Cost (MCHF)	Recirc (PY)
SRF System (scaled)	134.0	N/A	67.0	N/A
Cryogenic Infrastructure (scaled)	13.8	N/A	6.9	N/A
Civil Engineering (scaled)	96.3	N/A	48.2	N/A
General Infrastructure (scaled)	19.3	N/A	9.7	N/A
SRF R&D and Prototyping	31.0	N/A	31.0	N/A
Injector	40.0	N/A	40.0	N/A
Dump System and Source	5.0	N/A	5.0	N/A
Recirculation Arcs additions	0.0	N/A	70.0	100.0 (est)
Electron Complex Subtotal	339.4	703.0	277.8	451.0
Interaction Region	50.0	50.0	50.0	50.0
Detector (estimate)	250.0	100.0	250.0	100.0
Total Estimated	639.5	853.0	577.8	601.8

The above estimate is highly tentative and needs to be scrutinized. Still, it shows that 5 GeV (or 6 GeV) linac, with two recirculations is a more cost effective approach than a single 10 GeV linac. Since the differences are small, we will assume the the linac is capable of 6 GeV. The maximum electron beam energy of 18 GeV, required for the EIC top of the energy range, could then be achieved with three recirculations.

9 USA DOE Cost Accounting for EIC-LHeC Hybrid

The lower-cost recirculating (6 GeV linac) version is converted to USA DOE accounting: material to USD (1 CHF $\approx$ 1.25 USD), labor at 300k USD/PY (fully loaded), and large 60% contingency, given the very tentative nature of the cost estimation.

Table 6: USA DOE Cost Accounting for EIC-LHeC Hybrid

Item	Value (MUSD)
Material Costs (converted)	722.2
Labor Costs (PY to USD)	180.5
Pre-Contingency Total	902.7
Total with 60% Contingency	1444.3

While the above estimate is highly tentative and need to be scrutinized, its value is about twice lower than the top of the CD0 approved cost range for EIC project, which may justify further evaluation of this hybrid EIC deign option.

10 Discussion on Crab Waist Scheme

The crab waist (CW) scheme has been evaluated for potential luminosity enhancement. In CW, a large crossing angle and Piwinski angle allow squeezing β_y^* to very small values while suppressing beam-beam resonances. Preliminary very tentative calculations show $L \sim 2e32 \text{ cm}^{-2} \text{ s}^{-1}$ with standard parameters, but with aggressive β^* reduction and electron vertical emittance reduction, L might reach $\sim 1e34$. CW may enable achieving higher L while controlling beam-beam effects on the beams, allowing additional flexibility. Studies should continue with parameter optimization and detailed tracking simulations.

11 Discussion of the challenges and R&D needed for EIC-LHeC hybrid

The issues in the EIC-LHeC hybrid ERL approach are the following

1. Feasibility of $1E-4$ energy recovery efficiency that would require R&D and demonstration. However, ERL demonstration at around 10 GeV can be done at CEBAF at low beam current, and at PERLE for lower energy but higher electron beam current.
2. The value of 60 mA polarized electron beam current is beyond the present state of the art. However, it is synergistic with the efforts at JLAB for creation of 10 mA polarized electron beam, as a driver for polarized positron production. Once 10 mA is achieved, multiplexing several electron sources with RF mergers may be possible.
3. Stronger focusing of protons at IP and larger divergence may impact FD apertures, require tighter collimation depth, will impact optics and DA, and may reduce 4pi detector coverage, and needs to be studied.
4. Possibly, lower number of proton bunches and higher charge, assumed in the parameters, will result in increased IBS, reducing the average luminosity. This may be mitigated by adjusting electron beam parameters.
5. There is a question if this hybrid scheme can be implemented without major changes to ePIC detector. Ideally, it is desired that any changes of accelerator scheme would not impact ongoing design of the detector and its major MDI systems.

The presented hybrid scheme, while it may theoretically prove to be less expensive, requires additional R&D and experimental demonstrations. Given its reduced cost and overall reduced construction efforts, its compatibility with the present project timeline require further careful analysis. It may be worth discussing this option even just to confirm that the present path of the EIC project is optimal.

References

- [1] The European Strategy for Particle Physics (ESPP) Open Symposium, July 2025 <https://agenda.infn.it/event/44943/>
- [2] Presentation of LHeC project at ESPP 2025, questions and answers: <https://youtu.be/NX1eYfo15JI?list=PLbsqUzxZ1cP5p4izedCWb7EOP-ZkSH495&t=2703>
- [3] A sample of EIC project parameters. https://eic.jlab.org/Documents/EIC-General/20250305-EIC_ParameterList.pdf
- [4] Phase-One LHeC submission to ESPP <https://indico.cern.ch/event/1439855/contributions/6461558/attachments/3045931/5381880/backup.pdf>
- [5] Bruning O., 2018 LHeC cost estimate report, CERN Geneva <https://cds.cern.ch/record/2652349/files/CERN-ACC-2018-0061.pdf>
- [6] Tune Shift in Beam-Beam Collisions with a Crossing Angle, P. Raimondi, M. Zobov <https://www.lnf.infn.it/acceleratori/dafne/NOTEDAFNE/G/G-58.pdf>
- [7] Crab Waist collision scheme: a novel approach for particle colliders, M Zobov <https://arxiv.org/pdf/1608.06150>
- [8] Luminosity and Crab Waist Collision Studies, Wanwei Wu and Don Summers <https://arxiv.org/pdf/1505.06482>
- [9] Crab Waist Collision Scheme, Mikhail Zobov <https://da.lnf.infn.it/wp-content/uploads/sites/8/2017/08/CrabWaist.pdf>




Figure 1: Layout of EIC project.




Figure 2: Layout of EIC built as LHeC hybrid with energy recovery. Electron energy of 10 GeV provided by two recirculation through 5 GeV SC RF linac (capable of 6 GeV). The recirculation arc are standard magnets (no FFA). Electron beam parameters are taken from LHeC first stage (optimized for 20 GeV electron beam) and optimized to match IP beam sizes while keeping the limits on electron and proton beam currents. The beam-beam parameters of electrons allowed to exceed one, while for protons kept below 0.01. The average luminosity is around $2E33$, without electron cooling at collision energy, and $1E34$ with electron cooling at collision energy. In case when the second IP will be equipped with a detector, the luminosity will be shared, where the electron bunches will be distributed using RF separators.