

ACCELERATOR DESIGN EDUCATIONAL PRIMER – CONCEPTUALIZING AND OPTIMIZING THE HYBRID LHEC-LIKE ELECTRON-ION COLLIDER DESIGN*

A. Seryi, L. van Riesen-Haupt, Old Dominion University, Norfolk, United States

C. A. Lindstrøm, University of Oslo, Oslo, Norway

T. Pieloni, L. Vanhecke, École Polytechnique Fédérale de Lausanne, Lausanne, Switzerland

Abstract

The Electron-Ion Collider (EIC) Mission Need requires $\sqrt{s} = 20\text{--}100$ GeV (upgradable to 140 GeV) and luminosity $10^{33}\text{--}10^{34}$ cm⁻² s⁻¹. The current ring-ring baseline achieves the full scope, including $\sim 10^{34}$ cm⁻² s⁻¹ across all energies. However, when the design is re-optimized for the lower boundary — accepting 10^{33} cm⁻² s⁻¹ and prioritizing cost — an alternative configuration emerges as more advantageous: a hybrid LHeC-like electron accelerator using multi-pass energy recovery linacs (ERL). This solution reduces electron-beam power by roughly an order of magnitude, yielding nearly a factor of two reduction in total project cost compared with the present baseline while still satisfying the minimum physics requirements. The study performs parametric cost and performance modeling, augmented by AI-driven optimization, to explore this design space. Serving primarily as an educational exercise for the next generation of accelerator physicists and engineers, the paper demonstrates modern design methods: rapid parametric scans, cost-driven optimization, and integration of AI tools. It examines technical feasibility, identifies critical R&D (high-current ERL operation, beam-beam effects, synchronization, etc.), and discusses how such re-optimization studies can be used to train designers in an era when artificial intelligence dramatically expands exploration of complex accelerator parameter spaces.

PREAMBLE – AI AND EDUCATION

Educating future accelerator scientists in the AI era require developing new approaches. This paper is not an ultimate answer, but just a small step, hopefully in the right direction, along the path of finding optimal methodology of transferring knowledge to the new generation in the new world of unprecedented acceleration of analysis, simulations, and coding, due to proliferation of AI.

The emergence of AI-assisted coding presents both unique challenges and unprecedented opportunities for accelerator physics education. Institutions like Fermilab, which hosts the US Particle Accelerator School, and CERN, home to the CERN Accelerator School CAS, need to rapidly adapt their pedagogical approaches to this new reality. Launch of the Genesis program in the US further encourages use of AI for accelerated design of particle accelerators.

In this paper, we will try to mimic what can be done in one-week USPAS course on accelerator design, where students

typically analyze and collectively develop a mini project. Past examples of such USPAS mini-projects are compact LWFA-fed ring light source [USPAS2016] or ERL-based EUV light source [USPAS2023].

Those projects mentioned above were performed without use of AI. For the present paper, we use the same approach of USPAS mini-project, but assume that students will have access to AI tools, and will make most of design steps using AI. The authors of this paper are not students, however, we are trying to imagine what we could do in one week, if we were given the described below mini-project. In a sense, the paper is a rehearsal or a draft script for a future USPAS course, where accelerator mini-projects will be evaluated and conceptualized using AI tools.

EIC-LHEC MINI-PROJECT

Describe EIC-LHeC in style of USPAS one-week class mini-project.

Text

Text

Text

Text

Text

EIC-LHEC PARAMETERS

Describe process and prompts for generation of parameters.

Tables of parameters

Text

Text

Text

Text

Text

BEAM-BEAM EVALUATIONS

Describe process and prompts for generation of beam-beam code and how it can be used for this case.

Text

Text

Include picture of beam-beam collision

Text

Text

Text

* Thanks go here

IR OPTICS EVALUATIONS

Describe process and prompts for generation of IR optics, beam envelopes, estimation of the collimation depth.

Text

Text

Include picture of IR optics

Text

Text

Text

IR MAGNETS EVALUATIONS

Describe process and prompts for evaluation of parameters and technological options for IR magnets, which will be determined need to be SC magnets, including discussion of Nb or Nb₃Sn choices

Text

Text

Text

Text

Text

ENERGY RECOVERY EVALUATIONS

Describe process and prompts for evaluation of the energy recovery

Text

Text

Text

Text

Text

RECIRCULATION EVALUATIONS

Describe process and prompts for evaluation of recirculation

Text

Text

Text

Text

Text

INITIAL COST ESTIMATIONS

Describe process and prompts for initial evaluation of the cost of EIC-LHeC accelerator

Text

Text

Text

Text

Text

ADVANCED COST ESTIMATIONS

Describe process and prompts for advanced evaluation of the cost of EIC-LHeC accelerator

Text

Text

Text

Text

Text

REQUIRED R&D AND NEXT STEPS

Describe process and prompts for determination of the needed R&D and next steps for such EIC-LHeC accelerator

Text

Text

Text

Text

Text

VERIFICATION OF AI RESULTS

Discuss how verification of AI results will be performed, and how it is connected with our believe that students will learn accelerator physics from such educational approach.

Text

Text

Text

Text

Text

CONNECTION TO GENESIS PROGRAM

Discuss connection to Genesis program.

Text

Text

Text

Text

Text

SELF-ASSESSMENT AND NEXT STEPS

Discuss how we feel about the described approach, what is missing, where we are not sure, what are directions of future developments.

Text

Text

Text

Text

Text

CONCLUSION

Write conclusion

OLDER TEXT FROM HERE ON

This and next sections contain older text that will be used, edited or deleted.

DRAFT FROM GITHUB TO MOVE

Some draft text for this paper are at <https://github.com/aseryi/vibe-coding/tree/main/EIC-LHeC>

This text is being moved here. Some formatting (e.g. tables) do not work well yet. It will be fixed parsed appropriately in a few days

(see link in the references) it was claimed that inserting a new electron ring into the LHC tunnel would be cost prohibitive and would also limit LHeC luminosity.

The hybrid design that we will discuss below could potentially use a linac for electrons, working in an energy-recovery mode, reducing the need for an electron ring, and therefore providing significant reduction of cost, albeit with the need for some additional R&D.

This note presents parameter tables as well as brief description for:

- Standard EIC with $1 \times 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$ luminosity (project baseline).
- Hybrid EIC-LHeC with $\sim 2 \times 10^{33} \text{ cm}^{-2} \text{ s}^{-1}$ (using EIC proton emittances).
- Optimized hybrid EIC-LHeC with $1 \times 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$.

Cost estimates for the hybrid electron complex are also provided, including a conversion to USA DOE accounting for the lower-cost recirculating version. A discussion on the crab waist scheme for further luminosity optimization is also included.

AI MODELS AND PROMPTS

Describe here AI models used and prompts

BASLINE EIC PARAMETERS (1E34 LUMINOSITY)

The standard EIC baseline for 10 GeV electron and 275 GeV proton achieve peak $1 \times 10^{34} \text{ cm}^{-2} \text{ s}^{-1}$ luminosity with the following set of parameters.

Table 1: Baseline EIC Parameters (1E34 Peak Luminosity)

Parameter	Value	Unit
Ring circumference	3834.00	m
Revolution frequency	78229.77	Hz
Number of bunches	1160	
Electron rest mass energy	0.000511	GeV
Proton rest mass energy	0.938	GeV
Electron gamma	19569.47	
Proton gamma	293.14	
Electron energy	10.0	GeV
Electron bunch population	1.72e+11	particles
Electron normalized horiz emittance	391.0	μm
Electron normalized vert emittance	26.0	μm
Electron geometric horiz emittance	20.0	nm
Electron geometric vert emittance	1.3	nm
Electron beta _x at IP	0.45	m
Electron beta _y at IP	0.06	m
Electron bunch length (RMS)	0.007	m
Electron horizontal beam size at IP	94.8	μm
Electron vertical beam size at IP	8.6	μm
Electron horizontal beam-beam xi	0.072	
Electron vertical beam-beam xi	0.100	

Electron horizontal RMS beam angle	210.7	μrad
Electron vertical RMS beam angle	154.0	μrad
Electron beam current	1554.99	mA
Proton energy	275.0	GeV
Proton bunch population	6.9e+10	particles
Proton normalized horiz emittance	3.3	μm
Proton normalized vert emittance	0.3	μm
Proton geometric horiz emittance	11.3	nm
Proton geometric vert emittance	1.0	nm
Proton β_{x_0} at IP	0.80	m
Proton β_{y_0} at IP	0.07	m
Proton bunch length (RMS)	0.060	m
Proton horizontal beam size at IP	94.9	μm
Proton vertical beam size at IP	8.6	μm
Proton horizontal beam-beam xi	0.012	
Proton vertical beam-beam xi	0.012	
Proton horizontal RMS beam angle	118.6	μrad
Proton vertical RMS beam angle	119.2	μrad
Proton beam current	1.00	A
Effective horizontal beam size	134.1	μm
Effective vertical beam size	12.2	μm
Collision frequency	9.1e+07	Hz
Luminosity	1.05e+34	$\text{cm}^{-2} \text{s}^{-1}$

STANDARD LHEC PARAMETERS

The standard LHeC set of parameters is also shown here for reference and comparison. We use parameters of the first stage LHeC with reduced electron beam energy (to 20 GeV, in comparison with 50 GeV in the full project) as presented to ESPP.

Table 2: LHeC Parameters (20 GeV Electron, 7 TeV Proton)

Parameter	Value	Unit
Ring circumference	26659.00	m
Revolution frequency	11245.91	Hz
Number of bunches	2808	
Electron rest mass energy	0.000511	GeV
Proton rest mass energy	0.938	GeV
Electron gamma	39138.94	
Proton gamma	7462.69	
Electron energy	20.0	GeV
Electron bunch population	1.19e+10	particles
Electron normalized horiz emittance	22.0	μm
Electron normalized vert emittance	22.0	μm
Electron geometric horiz emittance	0.6	nm
Electron geometric vert emittance	0.6	nm
Electron β_{x_0} at IP	0.20	m
Electron β_{y_0} at IP	0.20	m
Electron bunch length (RMS)	0.003	m
Electron horizontal beam size at IP	10.6	μm
Electron vertical beam size at IP	10.6	μm
Electron horizontal beam-beam xi	2.185	
Electron vertical beam-beam xi	2.185	
Electron horizontal RMS beam angle	53.0	μrad
Electron vertical RMS beam angle	53.0	μrad

Electron beam current	60.1	mA
Proton energy	7000.0	GeV
Proton bunch population	2.2e+11	particles
Proton normalized horiz emittance	2.5	μm
Proton normalized vert emittance	2.5	μm
Proton geometric horiz emittance	0.3	nm
Proton geometric vert emittance	0.3	nm
Proton β_{x_0} at IP	0.35	m
Proton β_{y_0} at IP	0.35	m
Proton bunch length (RMS)	0.075	m
Proton horizontal beam size at IP	10.7	μm
Proton vertical beam size at IP	10.7	μm
Proton horizontal beam-beam xi	0.001	
Proton vertical beam-beam xi	0.001	
Proton horizontal RMS beam angle	30.7	μrad
Proton vertical RMS beam angle	30.7	μrad
Proton beam current	1.11	A
Effective horizontal beam size	15.1	μm
Effective vertical beam size	15.1	μm
Collision frequency	3.2e+07	Hz
Luminosity	5.78e+33	$\text{cm}^{-2} \text{s}^{-1}$

HYBRID EIC-LHEC PARAMETERS (2E33 LUMINOSITY)

For the hybrid with $\sim 2\text{E}33$ luminosity, proton emittances are kept the same as standard EIC, while the parameters of electron beam (emittances, beam current, bunch repetition rate) are taken from LHeC design. The number of proton bunches is reduced by a factor of three, in comparison with EIC baseline, while keeping the proton beam current constant, in order to match to the electron bunch rate assumed in LHeC.

Table 3: Hybrid EIC-LHeC Parameters (2E33 Luminosity)

Parameter	Value	Unit
Ring circumference	3834.00	m
Revolution frequency	78229.77	Hz
Number of bunches	386	
Electron rest mass energy	0.000511	GeV
Proton rest mass energy	0.938	GeV
Electron gamma	19569.47	
Proton gamma	293.14	
Electron energy	10.0	GeV
Electron bunch population	1.19e+10	particles
Electron normalized horiz emittance	22.0	μm
Electron normalized vert emittance	22.0	μm
Electron geometric horiz emittance	1.1	nm
Electron geometric vert emittance	1.1	nm
Electron β_{x_0} at IP	1.20	m
Electron β_{y_0} at IP	0.05	m
Electron bunch length (RMS)	0.003	m
Electron horizontal beam size at IP	36.7	μm
Electron vertical beam size at IP	7.5	μm
Electron horizontal beam-beam xi	3.474	

Electron vertical beam-beam xi	0.679	
Electron horizontal RMS beam angle	30.6	μrad
Electron vertical RMS beam angle	149.9	μrad
Electron beam current	57.58	mA
Proton energy	275.0	GeV
Proton bunch population	2.1e+11	particles
Proton normalized horiz emittance	3.3	μm
Proton normalized vert emittance	0.3	μm
Proton geometric horiz emittance	11.3	nm
Proton geometric vert emittance	1.0	nm
Proton β_{x_0} at IP	0.12	m
Proton β_{y_0} at IP	0.06	m
Proton bunch length (RMS)	0.070	m
Proton horizontal beam size at IP	36.8	μm
Proton vertical beam size at IP	7.8	μm
Proton horizontal beam-beam xi	0.001	
Proton vertical beam-beam xi	0.002	
Proton horizontal RMS beam angle	306.3	μrad
Proton vertical RMS beam angle	130.6	μrad
Proton beam current	1.00	A
Effective horizontal beam size	52.0	μm
Effective vertical beam size	10.8	μm
Collision frequency	3.0e+07	Hz
Luminosity	2.10e+33	$\text{cm}^{-2} \text{s}^{-1}$

HYBRID EIC-LHEC PARAMETERS (1E34 LUMINOSITY)

For the optimized hybrid with 1E34 luminosity, proton emittances are reduced (here we count on eventual development of the on-collision-energy electron cooling). The vertical emittance of electron beam is reduced too, assuming the the beam will be generated in a magnetized electron gun, and then Derbenev's beam transformer will be used to convert magnetized round electron beam into flat beam. We conservatively assumed that the vertical electron emittance can be reduced just by a factor of ten.

Table 4: Hybrid EIC-LHeC Parameters (1E34 Luminosity)

Parameter	Value	Unit
Ring circumference	3834.00	m
Revolution frequency	78229.77	Hz
Number of bunches	386	
Electron rest mass energy	0.000511	GeV
Proton rest mass energy	0.938	GeV
Electron gamma	19569.47	
Proton gamma	293.14	
Electron energy	10.0	GeV
Electron bunch population	1.19e+10	particles
Electron normalized horiz emittance	22.0	μm
Electron normalized vert emittance	2.2	μm
Electron geometric horiz emittance	1.1	nm
Electron geometric vert emittance	0.1	nm
Electron β_{x_0} at IP	0.25	m
Electron β_{y_0} at IP	0.10	m

Electron bunch length (RMS)	0.003	m
Electron horizontal beam size at IP	16.8	μm
Electron vertical beam size at IP	3.4	μm
Electron horizontal beam-beam xi	3.474	
Electron vertical beam-beam xi	6.789	
Electron horizontal RMS beam angle	66.8	μrad
Electron vertical RMS beam angle	32.7	μrad
Electron beam current	58.0	mA
Proton energy	275.0	GeV
Proton bunch population	2.07e+11	particles
Proton normalized horiz emittance	0.9	μm
Proton normalized vert emittance	0.1	μm
Proton geometric horiz emittance	3.1	nm
Proton geometric vert emittance	0.3	nm
Proton β_{x_0} at IP	0.09	m
Proton β_{y_0} at IP	0.05	m
Proton bunch length (RMS)	0.070	m
Proton horizontal beam size at IP	16.8	μm
Proton vertical beam size at IP	3.6	μm
Proton horizontal beam-beam xi	0.003	
Proton vertical beam-beam xi	0.007	
Proton horizontal RMS beam angle	182.4	μrad
Proton vertical RMS beam angle	77.8	μrad
Proton beam current	1.00	A
Effective horizontal beam size	23.8	μm
Effective vertical beam size	5.0	μm
Collision frequency	3.02e+07	Hz
Luminosity	1.00e+34	$\text{cm}^{-2} \text{s}^{-1}$

We note that the table above is shown quite large beam-beam effects on the electron beam, which will be severely disrupted after collision. Calculations of luminosity need to be done taking beam-beam effects into account, and moreover, feasibility of energy recovery and recirculation of such disrupted beam needs to be studied. Possibly, parameters can be further optimized to reduce disruption of the electron beam.

COST ESTIMATIONS FOR HYBRID EIC-LHEC

Cost estimates for the electron complex, IR, and detector are provided, comparing single-pass and recirculating versions. That means, the 10 GeV energy of electron beam is provided by a single pass through the 10 GeV linac in the first case, and by two recirculating passes through 5 GeV linac in the second case. In the table below, PY indicate Person-Year. The cost scaling below was done with help of AI and is not fully checked, although the cost numbers for the IR and detector has been manually increased in comparison with the scaling.

Table 5: Hybrid EIC-LHeC Cost and Manpower Estimate Comparison

Component	Single-Pass Cost (MCHF)	Single-Pass (PY)	Recirc Cost (MCHF)	Recirc (PY)
-----------	----------------------------	---------------------	-----------------------	----------------

PREAMBLE

EDIT OR MOVE TEXT BELOW (This is my LinkedIn post)

Educating Future Accelerator Scientists in the AI Era

The emergence of AI-assisted coding presents both unique challenges and unprecedented opportunities for accelerator physics education. Institutions like Fermilab, which hosts the US Particle Accelerator School , and CERN, home to the CERN Accelerator School CAS, need to rapidly adapt their pedagogical approaches to this new reality.

The animation below demonstrates what's now possible: using Claude Code AI, we created a simulation of electron-positron beam collisions in just minutes, from a paragraph-long prompt. You can explore the full example at <https://lnkd.in/ep2pxya8>

This capability suggests a transformative shift in how students learn. Rather than passively attending lectures or running decades-old legacy codes, students could actively create simplified simulation codes, then iteratively refine them through AI-assisted modifications to explore different physics phenomena. For instance, with the beam-beam collision example, students could progressively enhance their understanding by:

Converting to physical units

Implementing realistic beam distributions with emittance and beta-functions

Adding luminosity calculations

Investigating how luminosity depends on disruption parameters and beam offsets

Critically, students would develop diagnostic tests to verify that physics principles are correctly implemented – learning to validate AI-generated code against their understanding of the underlying physics.

This approach ensures that as we leverage AI tools, we continue developing human experts capable of designing and building the accelerators and colliders of tomorrow. The goal isn't to replace human expertise, but to accelerate its development while maintaining rigor and deep understanding.

INTRODUCTION

EDIT TEXT BELOW

The Electron-Ion Collider (EIC) is a proposed facility to probe the structure of nucleons and nuclei at high energies. The standard EIC design aims for a luminosity in the range of $10^{33} \text{ cm}^{-2} \text{ s}^{-1}$ to $10^{34} \text{ cm}^{-2} \text{ s}^{-1}$ (average luminosity), as defined in the CD0 mission need statement. The EIC is designed as a classical ring-ring collider, with electron and proton storage rings, providing collisions.

However, to reduce costs, a hybrid approach combining EIC proton beam parameters with LHeC-like electron beam parameters can be explored, while still giving the luminosity from the CD0 mission need statement range. The idea to explore this approach was prompted by discussion of of LHeC project at the Open Symposium for the European Strategy for Particle Physics, where during the discussion

SRF System (scaled)	134.0	N/A
Cryogenic Infrastructure (scaled)	13.8	N/A
Civil Engineering (scaled)	96.3	N/A
General Infrastructure (scaled)	19.3	N/A
SRF R&D and Prototyping	31.0	N/A
Injector	40.0	N/A
Dump System and Source	5.0	N/A
Recirculation Arcs additions	0.0	N/A
Electron Complex Subtotal	339.4	703.0
Interaction Region	50.0	50.0
Detector (estimate)	250.0	100.0
Total Estimated	639.5	853.0

The above estimate is highly tentative and needs to be scrutinized. Still, it shows that 5 GeV (or 6 GeV) linac, with two recirculations is a more cost effective approach than a single 10 GeV linac. Since the differences are small, we will assume the the linac is capable of 6 GeV. The maximum electron beam energy of 18 GeV, required for the EIC top of the energy range, could then be achieved with three recirculations.

USA DOE COST ACCOUNTING FOR EIC-LHEC HYBRID

The lower-cost recirculating (6 GeV linac) version is converted to USA DOE accounting: material to USD (1 CHF $\approx$ 1.25 USD), labor at 300k USD/PY (fully loaded), and large 60% contingency, given the very tentative nature of the cost estimation.

Table 6: USA DOE Cost Accounting for EIC-LHeC Hybrid

Item	Value (MUSD)
Material Costs (converted)	722.2
Labor Costs (PY to USD)	180.5
Pre-Contingency Total	902.7
Total with 60% Contingency	1444.3

While the above estimate is highly tentative and need to be scrutinized, its value is about twice lower than the top of the CD0 approved cost range for EIC project, which may justify further evaluation of this hybrid EIC deign option.

DISCUSSION ON CRAB WAIST SCHEME

The crab waist (CW) scheme has been evaluated for potential luminosity enhancement. In CW, a large crossing angle and Piwinski angle allow squeezing β_y^* to very small values while suppressing beam-beam resonances. Preliminary very tentative calculations show $L \sim 2e32 \text{ cm}^{-2} \text{ s}^{-1}$ with standard parameters, but with aggressive β^* reduction and electron vertical emittance reduction, L might reach $\sim 1e34$. CW may enable achieving higher L while controlling beam-beam effects on the beams, allowing additional flexibility. Studies should continue with parameter optimization and detailed tracking simulations.

DISCUSSION OF THE CHALLENGES AND R&D NEEDED FOR EIC-LHEC HYBRID

The issues in the EIC-LHeC hybrid ERL approach are the following

1. Feasibility of $1\text{E-}4$ energy recovery efficiency that would require R&D and demonstration. However, ERL demonstration at around 10 GeV can be done at CEBAF at low beam current, and at PERLE for lower energy but higher electron beam current.
2. The value of 60 mA polarized electron beam current is beyond the present state of the art. However, it is synergistic with the efforts at JLAB for creation of 10 mA polarized electron beam, as a driver for polarized positron production. Once 10 mA is achieved, multiplexing several electron sources with RF mergers may be possible.
3. Stronger focusing of protons at IP and larger divergence may impact FD apertures, require tighter collimation depth, will impact optics and DA, and may reduce 4pi detector coverage, and needs to be studied.
4. Possibly, lower number of proton bunches and higher charge, assumed in the parameters, will result in increased IBS, reducing the average luminosity. This may be mitigated by adjusting electron beam parameters.
5. There is a question if this hybrid scheme can be implemented without major changes to ePIC detector. Ideally, it is desired that any changes of accelerator scheme would not impact ongoing design of the detector and its major MDI systems.

The presented hybrid scheme, while it may theoretically prove to be less expensive, requires additional R&D and experimental demonstrations. Given its reduced cost and overall reduced construction efforts, its compatibility with the present project timeline require further careful analysis. It may be worth discussing this option even just to confirm that the present path of the EIC project is optimal.

MANUSCRIPTS

This short document demonstrates the use of the JACoW formatting style in $\text{\LaTeX}$, highlighting the template's key features. It is intended to help authors quickly create a correctly formatted JACoW manuscript in $\text{\LaTeX}$. Authors are expected to be familiar with the contents of the "JACoW Style Guide" document (`jacow_latex_style_guide`), which is available on the JACoW website.

Headings

Title and section headings are automatically converted to uppercase, therefore the author must ensure that all units and acronyms with mixed case writings (keV, MeV, GHz, μs , SwissFEL, SuperKEKB, FCC-hh) are correctly typeset (see

use of macro `\NoCaseChange{text}` in above title). The plural of proper nouns and acronyms in uppercase has to be a LOWERCASE "s" (e. g. LINACs, PLMs).

Figures and Tables

Figures and tables should be placed as close as possible to where they are mentioned. Each figure and table must be numbered in ascending order (1, 2, 3, etc.) throughout the paper. The lettering in figures and tables must be large enough to be reproduced clearly.

Figure 1: Example of figure inclusion. The caption should have a period "." at the end.

When referring to a figure from within the text, the convention is to use the abbreviated form (e. g., Fig. 1) *unless* the reference is at the start of the sentence. Reference to a table, however, is never abbreviated (e. g., Table 7). As a matter of style, authors are advised not to begin any sentence with an abbreviation or a number.

Table captions are typically composed as a heading, with the initial letters of principal words capitalized and without a period at the end. A description of the table contents should be confined to the text of the paper and not in the table caption.

Table 7: Table Heading

Column 1	Column 2 [mm]	Column 3 [GeV]
Attribute A	100.2	20.3
Attribute B	137.0	~ 9.1

Equations

Equations with numbers do not need to be referenced (the number can be suppressed using `\nonumber`):

$$C_B = \frac{q^3}{3\epsilon_0 mc} = 3.54 \mu\text{eV/T} . \quad (1)$$

Units

Units should be written using `\qty{value}{unit}` or `\num{value}` of the "siunitx" package as shown in Eq. (1). Some examples are: 3 keV, 100 kW, 7 μm .

References

In the interest of promoting complete and uniform citations, the IEEE Editorial Style for Transactions and Journals has been adopted. References [**ref:jacow-paper**, **ref:journal-paper**] exemplify this style. When citing a periodical, use the ISO 4 standard for abbreviating journal names. Please refer to Annex C of the "Style Guide for JACoW Conference Papers" for examples. Authors are responsible for paying attention to the details of the style to ensure their references are accurate, and properly formatted. Each paper published in recent JACoW proceedings has been assigned a digital object identifier (DOI). Including

a DOI in a reference facilitates importing references into bibliographic databases and is strongly recommended. Furthermore, hyperlinks to DOIs are required, while links to non-DOI URLs are prohibited. JACoW conferences that stipulate a page limit typically exempt the reference section from this requirement.

CONCLUSION

This short document illustrates the use of the JACoW format style, which is described in detail in the Style Guide.

REFERENCES

- [1] COMPACT RING-BASED X-RAY SOURCE WITH ON-ORBIT AND ON-ENERGY LASER-PLASMA INJECTION, TUA3CO03, NAPAC-2016, USPAS 2016 mini project.
- [2] EUV FEL LIGHT SOURCE BASED ON ENERGY RECOVERY LINAC WITH ON-ORBIT LASER PLASMA INJECTION, USPAS 2023 mini project, MOPG66, IPAC 2024
- [3] The European Strategy for Particle Physics (ESPP) Open Symposium, July 2025 <https://agenda.infn.it/event/44943/>
- [4] Presentation of LHeC project at ESPP 2025, questions and answers: [https://youtu.be/NX1eYfo15JI?](https://youtu.be/NX1eYfo15JI?list=PLbsqUzxZ1cP5p4izedCWb7EOP-ZkSH495&t=2703)
- [5] A sample of EIC project parameters. https://eic.jlab.org/Documents/EIC-General/20250305-EIC_ParameterList.pdf
- [6] Phase-One LHeC submission to ESPP <https://indico.cern.ch/event/1439855/contributions/6461558/attachments/3045931/5381880/backup.pdf>
- [7] Bruning O., 2018 LHeC cost estimate report, CERN Geneva <https://cds.cern.ch/record/2652349/files/CERN-ACC-2018-0061.pdf>
- [8] Tune Shift in Beam-Beam Collisions with a Crossing Angle, P. Raimondi, M. Zobov <https://www.lnf.infn.it/acceleratori/dafne/NOTEDAFNE/G/G-58.pdf>
- [9] Crab Waist collision scheme: a novel approach for particle colliders, M Zobov <https://arxiv.org/pdf/1608.06150>
- [10] Luminosity and Crab Waist Collision Studies, Wanwei Wu and Don Summers <https://arxiv.org/pdf/1505.06482>
- [11] Crab Waist Collision Scheme, Mikhail Zobov <https://da.lnf.infn.it/wp-content/uploads/sites/8/2017/08/CrabWaist.pdf>